


# ***DENSO***



**VM-D/G Series  
Cleanroom Type Robot  
(Class 100)**

## ***DENSO ROBOT***

**Vertical articulated**

**VM-6083D/G-P100, VM-60B1D/G-P100**

**OWNER'S MANUAL  
(SUPPLEMENT)**

# Preface

This robot unit (except the controller) is the cleanroom type (class 100).

This manual describes about the cleanroom type robot for VM-6083D/G and VM-60B1D/G series.

This book is a supplement to the “VM-D or VM-G SERIES MANUALS”. Use this supplement together with the “VM-D or VM-G SERIES MANUALS”.

Before use, read this manual carefully together with related manuals to safely get the maximum benefit from your robot in your assembling operations.

## Robot models covered by this manual

---


Medium-sized, vertical articulated VM-D or VM-G series (Class 100 for cleanroom type)

VM-6083D/G-P100

VM-60B1D/G-P100

---

Coding of the set model:



# Contents

1	Robot Unit Specifications.....	1
	(1) VM-6083D-P100 .....	1
	(2) VM-60B1D-P100.....	2
2	Outer Dimensions and Workable Space of the Robot Unit .....	3
	(1) VM-6083D-P100 .....	3
	(2) VM-60B1D-P100.....	4
3	Air Piping and Signal Wiring .....	5
4	Notes when Handling the Cleanroom Type .....	6

# 1 Robot Unit Specifications

Reference manual [VM-D or VM-G series, GENERAL INFORMATION ABOUT ROBOT, Chapter 3]

Following tables list the robot unit specifications of the VM-6083D/G-P100 and VM-60B1D/G-P100.

## (1) VM-6083D/G-P100

VM-6083D/G-P100, specifications

Item		Specifications
Model name of robot set ( <b>Note 1</b> )		VM-6083D/G-P100
Model name of robot unit		VM-6083D/GM-P100
Overall arm length		385 (first arm) + 445 (second arm) = 830 mm
Arm offset		J1 (swing): 180 mm, J3 (front arm): 100 mm
Maximum motion area		R = 1111 mm (end-effector mounting face) R = 1021 mm (Point P: J4, J5, J6 center)
Motion range		J1 : $\pm 170^\circ$ , J2 : $+135^\circ, -90^\circ$ , J3 : $+165^\circ, -80^\circ$ J4 : $\pm 185^\circ$ , J5 : $\pm 120^\circ$ , J6 : $\pm 360^\circ$
Maximum payload		10 kg
Maximum composite speed		8300 mm/s (at the center of an end-effector mounting face)
Position repeatability ( <b>Note 2</b> )		In each of X, Y and Z directions: $\pm 0.05$ mm
Maximum allowable inertia moment		Around J4 and J5: $0.36 \text{ kgm}^2$ Around J6: $0.064 \text{ kgm}^2$
Position detection		Absolute encoder
Drive motor and brake		AC servomotors for all joints, Brakes for joints J2 to J6
User air piping ( <b>Note 3</b> )		6 systems ( $\phi 4 \times 6$ ), 3 solenoid valves (2-position, double solenoid) contained.
User signal line		10 (for proximity sensor signals, etc.)
Air source	Operating pressure	$1.0 \times 10^5 \text{ Pa}$ to $3.9 \times 10^5 \text{ Pa}$
	Maximum allowable pressure	$4.9 \times 10^5 \text{ Pa}$
Weight		Approx. 78 kg
Clean class for cleanroom type		Class 100 ( $0.3 \mu$ ) at use points
<b>Note 1: The model name of robot set refers to the model name of a complete set including a robot unit and robot controller.</b>		
<b>Note 2: Position repeatability is the value at constant ambient temperature.</b>		

## (2) VM-60B1D/G-P100

### VM-60B1D/G-P100, specifications



Item		Specifications
Model name of robot set ( <b>Note 1</b> )		VM-60B1D/G-P100
Model name of robot unit		VM-60B1D/GM-P100
Overall arm length		520 (first arm) + 590 (second arm) = 1110 mm
Arm offset		J1 (swing): 180 mm, J3 (front arm): 100 mm
Maximum motion area		R = 1388 mm (end-effector mounting face) R = 1298 mm (Point P: J4, J5, J6 center)
Motion range		J1 : $\pm 170^\circ$ , J2 : $+135^\circ, -90^\circ$ , J3 : $+168^\circ, -80^\circ$ J4 : $\pm 185^\circ$ , J5 : $\pm 120^\circ$ , J6 : $\pm 360^\circ$
Maximum payload		10 kg
Maximum composite speed		8300 mm/s (at the center of an end-effector mounting face)
Position repeatability ( <b>Note 2</b> )		In each of X, Y and Z directions: $\pm 0.07$ mm
Maximum allowable inertia moment		Around J4 and J5: $0.36 \text{ kgm}^2$ Around J6: $0.064 \text{ kgm}^2$
Position detection		Absolute encoder
Drive motor and brake		AC servomotors for all joints, Brakes for joints J2 to J6
User air piping ( <b>Note 3</b> )		6 systems ( $\phi 4 \times 6$ ), 3 solenoid valves (2-position, double solenoid) contained.
User signal line		10 (for proximity sensor signals, etc.)
Air source	Operating pressure	$1.0 \times 10^5 \text{ Pa}$ to $3.9 \times 10^5 \text{ Pa}$
	Maximum allowable pressure	$4.9 \times 10^5 \text{ Pa}$
Weight		Approx. 80 kg
Clean class for cleanroom type		Class 100 ( $0.3 \mu$ ) at use points
<b>Note 1: The model name of robot set refers to the model name of a complete set including a robot unit and robot controller.</b>		
<b>Note 2: Position repeatability is the value at constant ambient temperature.</b>		

## 2 Outer Dimensions and Workable Space of the Robot Unit

Reference manual [VM-D or VM-G series, GENERAL INFORMATION ABOUT ROBOT, Chapter 3]

Following figures show the outer dimensions and workable space of the robot.

### (1) VM-6083D/G-P100



Outer dimensions and workable space (VM-6083D/G-P100)


[illegible]

4

### 3 Air Piping and Signal Wiring

Reference manual [VM-D or VM-G series, GENERAL INFORMATION ABOUT ROBOT, Chapter 3]

The VM-6083D/G-P100 & VM-60B1D/G-P100 are equipped with 6 air pipes for air chuck, 10 signal lines, and 3 solenoid valves in it. The air piping and signal wiring is shown in Figure below. The specifications of the solenoid valves are common to the VM-D/G series.



**Air Piping and Signal Wiring [VM-6083D/G-P100 & VM-60B1D/G-P100]**

## 4 Notes when Handling the Cleanroom Type

The cleanroom type of the VM-6083D/G-P100 & VM-60BD/G-P100 robot satisfies Clean Class 100 (0.3  $\mu$ ); however, the robot controller does not.

When carrying out installation, maintenance or inspection jobs of the cleanroom type robot in your clean room, be sure to follow your dust-proof job rules. If you remove the covers from the robot controller or robot unit, even the cleanroom type may scatter worn belt dust, piping grease, dust or dirt accumulating inside.

### Jobs requiring special care

- CALSET
- Cleaning of cooling fan filters in the robot controller
- Replacement of encoder backup batteries
- Replacement of controller memory backup batteries
- Inspection of timing belts
- Replacement of controller fuses
- Replacement of controller output ICs



**VM-6083D/G-P100 & VM-60B1D/G-P100  
Cleanroom Type Robot (Class 100)**

---

**OWNER'S MANUAL  
(SUPPLEMENT)**

First Edition      December 2002  
Second Edition   September 2005

DENSO WAVE INCORPORATED  
Factory Automation Division

9G

---

The purpose of this manual is to provide accurate information in the handling and operating of the robot. Please feel free to send your comments regarding any errors or omissions you may have found, or any suggestions you may have for generally improving the manual.

In no event will DENSO WAVE INCORPORATED be liable for any direct or indirect damages resulting from the application of the information in this manual.

**DENSO WAVE INCORPORATED**

**Factory Automation Division**

**410002-6570-R2**