


# Carbon Film Resistors

## MCF 0.25W Series



### Features:

- Automatically insertable
- High quality performance
- Non-flame type available
- Cost effective and commonly used
- Too low or too high values can be supplied on a case to case basis

### Performance Specifications:

Temperature Coefficient	: $\pm 350$ PPM / °C for $\leq 10 \Omega$ : $\pm 450$ PPM / °C for $11 \Omega - 99 \text{ K}\Omega$ : 0 to $-700$ PPM / °C for $100 \text{ K}\Omega$ to $1 \text{ M}\Omega$ : 0 to $-1,500$ PPM / °C for $1.1 \text{ M}\Omega$ to $10 \text{ M}\Omega$
Short-Time Overload	: $\Delta R / R \leq \pm(1\% + 0.05 \Omega)$ , with no evidence of mechanical damage
Minimum Insulation Resistance	: $10,000 \text{ M}\Omega$
Dielectric Withstanding Voltage	: No evidence of flashover, mechanical damage, arcing or insulation breakdown
Terminal Strength	: No evidence of mechanical damage
Resistance to Soldering Heat	: $\Delta R / R \leq \pm(1\% + 0.05 \Omega)$ , with no evidence of mechanical damage
Minimum Solderability	: 95% coverage
Resistance to Solvent	: No deterioration of protective coating and markings
Temperature Cycling	: $\Delta R / R \leq \pm(1\% + 0.05 \Omega)$ , with no evidence of mechanical damage
Load Life in Humidity	: Normal type : $\Delta R / R \pm 3\%$ for $< 100 \text{ K}\Omega$ , $\pm 5\%$ for $\geq 100 \text{ K}\Omega$ : Non-flame type : $\Delta R / R \pm 5\%$ for $< 100 \text{ K}\Omega$ , $\pm 10\%$ for $\geq 100 \text{ K}\Omega$
Load Life	: Normal type : $\Delta R / R \pm 2\%$ for $< 56 \text{ K}\Omega$ , $\pm 3\%$ for $\geq 56 \text{ K}\Omega$ : Non-flame type : $\Delta R / R \pm 5\%$ for $< 100 \text{ K}\Omega$ , $\pm 10\%$ for $\geq 100 \text{ K}\Omega$
Operating Temperature	: $-55^\circ\text{C}$ to $+155^\circ\text{C}$

### Specification Table

Series	Power Rating at 70°C (W)	Dimension				Maximum Working Voltage (V)	Maximum Overload Voltage (V)	Dielectric Withstanding Voltage (V)	Resistance Range
		Maximum Diameter (D)	Maximum Length (L)	Height (H $\pm 3$ )	Lead Diameter (d $\pm 0.05$ )				
MCF 0.25W	1/4 (0.25)	2.5	6.8	28	0.54	250	500	500	1 $\Omega$ to 10 $\text{M}\Omega$

**Note** : Standard E-24 series values in  $\pm 5\%$  tolerance


Dimensions : Millimetres

# Carbon Film Resistors


## MCF 0.25W Series




Derating Curve



Current Noise



Temperature Coefficient



# Carbon Film Resistors

## MCF 0.25W Series



### Resistance Preferred Value Range

E6	E12	E24	E96	E6	E12	E24	E96	E6	E12	E24	E96
10	10	10	10				21.5				46.4
			10.2	22	22	22	22.1	47	47	47	47.5
			10.5				22.6				48.7
			10.7				23.2				49.9
		11	11				23.7			51	51.1
			11.3			24	24.3				52.3
			11.5				24.9				53.6
			11.8				25.5				54.9
	12	12	12.1				26.1	56	56	56	56.2
			12.4				27.7				57.6
			12.7	27	27	27	27.4				59
		13	13				28				60.4
			13.3				28.7			62	61.9
			13.7				29.4				63.4
			14			30	30.1				64.9
			14.3				30.9				66.5
			14.7				31.6	68	68	68	68.1
15	15	15	15				32.4				69.8
			15.4	33	33	33	33.2				71.5
			15.8				34				73.2
		16	16.2				34.8			75	75
			16.5				35.7				76.8
			16.9			36	36.5				78.7
			17.4				37.4				80.6
			17.8				38.3	82	82	82	82.5
	18	18	18.2	39	39	39	39.2				84.5
			18.7				40.2				86.6
			19.1				41.2				88.7
			19.6				42.2			91	90.9
		20	20			43	43.2				93.1
			20.5				44.2				95.3
			21				45.3				97.6

Above values in accordance with IEC Publication 63 (1963) and BS2488

### Part Number Explanation:

**MCF**

**0.25W**

**10R**

Power Rating

Resistance

### Stocked Values

Tolerance	Wattage (W)	Preferred Value Range	Range Value
5%	0.5	E24	1R - 10M

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.