

[illegible][illegible]

UEXT

B-V-10-LF(GBH254SMT-10)

[illegible][illegible]

USB-Host (Keyboard)

USB1

Pin	Label
1	VBUS
2	D-
3	D+
4	GND
5	Shield

+5V_USB

USB_D-
USB_D+

GND

USB-SRWH-6A-LF(USB-A)

The diagram shows the USB-C connector pins and their connections to the USB-PWR module. The pins are labeled as follows:

- VBUS**: Connected to **A4**, **B9**, **B4**, and **A9**.
- DN1**: Connected to **A7** and **D_N**.
- DP1**: Connected to **A6** and **D_P**.
- CC1**: Connected to **A5**.
- CC2**: Connected to **B5**.
- SBU1**: Connected to **AB**.
- SBU2**: Connected to **BB**.
- GND**: Connected to **A1**, **B12**, **B1**, and **A12**.
- SHELL**: Connected to **0**.

The USB-PWR module has the following connections:

- +5V_USB**: Connected to the **VBUS** pins.
- D_N**: Connected to the **DN1** pin.
- D_P**: Connected to the **DP1** pin.
- R10**: A 5.11/700402 resistor connected between the **CC1** and **CC2** pins.
- R12**: A 5.11/700402 resistor connected between the **CC1** and **CC2** pins.
- PWR_FLAG**: Connected to the **SHELL** pin.
- GND**: Connected to the **GND** pins.

The diagram illustrates a power supply circuit. It features two input sources, both labeled +5V_USB. The first input is connected to a red LED (LED/RED/6603) through a resistor R1 (2.2k/Ω/0402) and a PWR_LED1 indicator. The second input is connected to a PWR_FLAG indicator. The circuit includes a DC-DC converter U3 (SY80894AAC(S0123-5)) with a feedback network consisting of resistors R15 (220k/Ω/0402) and R16 (49.9k/1%Ω/0402). A capacitor C1 (22μF/4.3V/200V/50μm/0603) is connected to the input. The output of the converter is connected to a PWR_FLAG indicator and a load resistor R2 (22k/Ω/300V/50μm/0603). The output voltage is labeled Vout = 0.6 * (1 + Ra/Rb). The circuit also includes a capacitor C2 (22μF/4.3V/200V/50μm/0603) and a resistor R3 (2.2k/Ω/0402) connected to a +3.3V input.

Mounting Holes

MH1

Mounting_Hole_NPTH

MH2

Mounting_Hole_NPTH

MH3

Mounting_Hole_NPTH

MH4

Mounting_Hole_NPTH

Fiducials

 FID1 Fiducial	 FID3 Fiducial	 FID5 Fiducial
 FID2 Fiducial	 FID4 Fiducial	 FID6 Fiducial

RP2040 PGM/DBG



The diagram shows a red rectangular pin header with four pins. The pins are numbered 1, 2, 3, and 4 from top to bottom. Pin 1 is labeled SWD1, pin 2 is labeled SWCLK, pin 3 is labeled SWDIO, and pin 4 is labeled GND. The labels SWD1, SWCLK, and SWDIO are in green text, while GND is in red text. The pin numbers 1, 2, 3, and 4 are in red text. The entire diagram is enclosed in a red rectangular border.

SWD1
4
2
3
SWCLK
SWDIO
GND
NA(HN1x3)



Rev: A

KiCad E.D.A. eeschema 7.0.6