

[illegible][illegible]

UEXT

B-V-10-LF(GBH254SMT-10)

[illegible]

6502 MCU

Pin Connections:

- Power:** VDD (3) to +3.3V; VSS (17, 18, 39) to GND.
- Reset:** RES (38) to +3.3V via 10k/R0402.
- Clock:** PHI2 (35) to 100nF/C20; PHI10 (42) to 10k/R0402.
- Data Bus:** A0-A15 (4, 5, 8, 9, 10, 11, 12, 13, 14, 15) and D0-D7 (30, 31, 32, 33, 34, 35, 36, 37) to data bus.
- Control Bus:** RDY (41), BE (34), SYNC (2), VPB (40), MLB (44), SOB (33) to control bus.
- Other:** R14 (10k/R0402) connected to GND.

W65C0256TQG-14 (TQFP44)

Legend:

- RDY:** R17 10k/R0402 → +3.3V
- IRQB:** R18 10k/R0402 → +3.3V
- NMIB:** R19 10k/R0402 → +3.3V
- BE:** R20 10k/R0402 → +3.3V
- SOB:** R21 10k/R0402 → +3.3V

[illegible]

USB-Host (Keyboard)

USB1

+5V_USB

USB_D-
USB_D+

VBUS 1
D- 2
D+ 3
GND 4
SHIELD 5

USB-SRWH-6A-LF(USB-A)

GND

USB-C-1

USB-PWR

+5V_USB

VBUS A4
VBUS B9
VBUS B4
VBUS A9

DM1 A7 D_N
DM2 B7

DP1 A6 D_P
DP2 B6

CC1 A5
CC2 B5

SBUS1 A8
SBUS2 B8

GND A1
GND B12
GND B1
GND A12

SHELL 0

PWR_FLAG

5.1k/20k

5.1k/20k

GND

Mounting Holes

MH1
Mounting_Hole_NPTH

MH2
Mounting_Hole_NPTH


MH3
Mounting_Hole_NPTH

MH4
Mounting_Hole_NPTH

Fiducials

 FID01 Fiducial	 FID03 Fiducial	 FID05 Fiducial
 FID02 Fiducial	 FID04 Fiducial	 FID06 Fiducial

RP2040 PGM/DBG



The diagram shows a 4-pin connector with pins 1, 2, and 3 highlighted in red. Pin 1 is labeled SWD1, pin 2 is labeled SWCLK, and pin 3 is labeled SWDIO. A ground symbol is shown next to pin 3. Below the connector, the text NA(HN1x3) is written.



Rev: A

Id: 1/1