Microstrip Calculation:
Copper Thickness (1oz): 1.4mil/0.035mm
Board thickness: 1.6mm
Dielectric thickness (layer 1 to 2): 0.2mm
Er: 4.6
Polygon Isolation: 8mil/0.2032mm
RF Trace Width: 13.8mil/0.35mm
https://chemandy.com/calculators/coplanar-waveguide-with-ground-calculator.htm

Ublox ZED-F9P

Cut jumper to remove I2C pullups from bus

Close jumper to enable SPI

7-bit unshifted I2C address: 0x42

RTC Backup

Stat LEDs

Cut jumper to disable LED

USB / Power

Connections

Qwiic Right Angle

Qwiic Right Angle

PTH

J6

Radio

Special Instructions
No clean process

sparkfun

open hardware

Released under the Creative Commons
Attribution Share-Alike 4.0 License
https://creativecommons.org/licenses/by-sa/4.0/

TITLE: ${PROJECTNAME}

Design by: ${DESIGNER}

REV: ${REV}

Sheet: /

File: ${FILENAME}

Date: ${CURRENT_DATE}

Sheet: ${#}/${##}

Title:

Size: User | Date: | Rev:

KiCad E.D.A. eeschema 7.0.6 | Id: 1/1