

The schematic diagram illustrates the SAMD21 microcontroller board. The central component is the SAMD21 microcontroller, which is connected to various external components. The power supply section includes a 3.3V rail and a GND rail. A reset button (S8) is connected to the RESET pin. A crystal oscillator (Y1) is connected to the PA00 and PA01 pins. A USB connector is shown on the right side, with pins for D+, D-, GND, and VCC. The diagram also shows the internal structure of the microcontroller, including the SAMD21 core and the SAMD21 peripheral controller.

3.3V

1 VCC SWDIO/TMS 2 SWDIO
3 GND 3 SWCLK/TCK 4 SWCLK
5 GND 5 SWO/TDO 6
7 KEY NC/TDI 8
9 GND RESET 10

GND

Test Points



The diagram shows four test points for an AVR microcontroller, labeled AREF, SWDIO, SWCLK, and RESET. Each label is positioned to the left of a horizontal line. The line is green for the first three points (AREF, SWDIO, SWCLK) and red for the fourth point (RESET). At the right end of each line is a semi-circular connection point.

LEDS

Released under the Creative Commons
Attribution Share-Alike 4.0 License
<https://creativecommons.org/licenses/by-sa/4.0/>

TITLE: \${PROJECTNAME}

Design by:	Alex Wende	REV: v10
------------	------------	-------------

REV:
V10

Sheet: /	
Date: \${CURRENT_DATE}	Sheet: \${#}/

Size: User	Date:	Rev:
KiCad E.D.A.	eeschema 7.0.6	Id: 1

Rev:
Id: 1/1