


V_USB – 6V MAX
V_BATT – Single Cell (4.2V MAX)

[illegible]

The diagram illustrates the pin connections for the Raspberry Pi 4B. It features three main connectors: J1 (GPIO), J2 (USB), and J3 (I2C).

- J1 (GPIO):** Pins 1 through 12 are connected to various power and data lines. Pin 1 is connected to V_BATT, pin 2 to EN, pin 3 to D17, pin 4 to D7, pin 5 to D8, pin 6 to D9, pin 7 to D10, pin 8 to D12, pin 9 to D19, pin 10 to D1, and pin 11 to D11. Pin 12 is connected to GND.
- J2 (USB):** Pins 1 through 16 are connected to various power and data lines. Pin 1 is connected to 3.3V, pin 2 to RST, pin 3 to A0, pin 4 to A2, pin 5 to A3, pin 6 to D4, pin 7 to D5, pin 8 to D6, pin 9 to SCK, pin 10 to MOSI, pin 11 to MISO, pin 12 to D14, pin 13 to D13, and pin 14 to GND.
- J3 (I2C):** Pins 4, 3, 2, and 1 are connected to various power and data lines. Pin 4 is connected to D1, pin 3 to D11, pin 2 to VCC, and pin 1 to GND.

[illegible]

VCC: 2.1–3.6V

3.3V

3.3V

R5

10kOhm

U1

VCC

RST

D10/PWM0/RSSI

D11/PWM1/SDA

D1/A1/SCL

D14/DIN

D13/DOUT

D7/CTS

D6/RTS

D8/DTR/SLP_RQ

D0/A0

D2/A2

D3/A3

D5/ASSOCIATE

D9/ON/SLP

D12

D17/SS

D4

D5

D9

D12

D19/ATNN/BT_MODE

GND

XBEE3

C1

-10%

GND



REV: \$100

Sheet: $\$ \{ \# \} / \$ \{ \#\# \}$

Rev:
Id: 1/1