


THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION. ANY REPRODUCTION IN PART OR WHOLE IS STRICTLY PROHIBITED WITHOUT WRITTEN PERMISSION!


PROPRIETARY

3.3V Buck Converter

SJ1 Select buck or displayport for 3V3



20V Boost Converter




Use high quality caps, ex.: CL21A475KBQNNNE

VIN = 12V
LEDs/string = 7
Vf = 2.75V - 3V (guesstimate)
ILED = 18.5mA
fOSC = ~850kHz
VOUT = 20.25V


Inductor Value (L1) = 23.03uH
Current Sense Resistor (R13) <= 58.3 mOhm (70% cutoff)

RT = 47K (850 KHz fOSC)
RISET = 15K (~18.5mA LEDs)
OVPSet = 47K + 20K (0.44V out)


On/Off Switch




Backlight Control



Power Indicator




Retina Display and DisplayPort Connector



Note: Sink side pinout used
Lanes are targetted at 85 Ohm differential (+/-15%)
Avoid discontinuities in the reference plane
DP_PWR normally not connected

MCU (for Backlight Control)



ISSUE	\$[COMPANY]		© 2013
DRAWN	TITLE		REV
\$(DRAWN)			\$(REV)
CHECKED	DATE	DRG No	\$(DRGNO)
\$(CHECKED)	\$(CURRENT_DATE)		
DATE	FILE:	PROJECTNAME	PAGE: \$[#]/\$[##]
\$(DATE)			

DisplayPort Layout Notes:
http://www.nxp.com/documents/application_note/AN10798.pdf