

Photodiodes with TO-18 footprint:

Pinout:  
1 Anode  
2 Cathode  
3 Case

Fermionics FD80FC  
<https://www.fermionics.com/High-Speed-Devices.html>

Hamamatsu G9801-32  
<https://www.hamamatsu.com/eu/en/product/type/G9801-32/index.html>

Fermionics FD80FC  
typ. 0.4 pF at  $V_r = 5\text{ V}$

TIASim predictions (<https://github.com/aeWallin/TIASim>)

Fast detector:  
Diode FDS015, RF 1.2 kOhm, CF 0.6 pF gives BW-3dB: 452 MHz

Slow detector:  
Diode S5973, RF 1 MOhm, CF None, BW-3db: 3.5 MHz

Copyright Anders E E Wallin, 2020.  
This documentation describes Open Hardware and is licensed under the CERN OHL v. 1.2.  
You may redistribute and modify this documentation under the terms of the CERN OHL v.1.2. (<http://ohwr.org/cernohl>). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. Please see the CERN OHL v.1.2 for applicable conditions

