# Chapter 1

# Example problem: Steady flow in a curved tube

The problem of steady flow in a curved tube is considered with a prescribed Poiseuille flow at the inlet and a traction-free outlet condition. It is not clear that the latter is appropriate, but the main aim of this example is to check that the `TubeMesh` works correctly.

A detailed comparison between the flow field and the Dean solution should be performed for validation purposes, but the qualitative features seem reasonable.





**Figure 1.1 Sketch of the problem with pressure contours.**




**Figure 1.2 Contours of axial velocity and secondary streamlines.**

Detailed documentation to be written. Here's the driver code...

```
//LIC// ====================================================================
//LIC// This file forms part of oomph-lib, the object-oriented,
//LIC// multi-physics finite-element library, available
//LIC// at http://www.oomph-lib.org.
//LIC//
//LIC// Copyright (C) 2006-2026 Matthias Heil and Andrew Hazel
//LIC//
//LIC// This library is free software; you can redistribute it and/or
//LIC// modify it under the terms of the GNU Lesser General Public
//LIC// License as published by the Free Software Foundation; either
//LIC// version 2.1 of the License, or (at your option) any later version.
//LIC//
//LIC// This library is distributed in the hope that it will be useful,
//LIC// but WITHOUT ANY WARRANTY; without even the implied warranty of
//LIC// MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
//LIC// Lesser General Public License for more details.
//LIC//
//LIC// You should have received a copy of the GNU Lesser General Public
//LIC// License along with this library; if not, write to the Free Software
//LIC// Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
//LIC// 02110-1301  USA.
//LIC//
//LIC// The authors may be contacted at oomph-lib@maths.man.ac.uk.
//LIC//
//LIC//====================================================================
/// Driver for a 3D navier stokes steady entry flow problem in a
/// uniformly curved tube

//Generic routines
#include "generic.h"
#include "navier_stokes.h"

// The mesh
```

```
#include "meshes/tube_mesh.h"

using namespace std;

using namespace oomph;


//=start_of_MyCurvedCylinder=====================================
//A geometric object that represents the geometry of the domain
//================================================================
class MyCurvedCylinder : public GeomObject
{
public:

 /// Constructor that takes the radius and curvature of the tube
 /// as its arguments
 MyCurvedCylinder(const double &radius, const double &delta) :
  GeomObject(3,3), Radius(radius), Delta(delta) { }

/// Destructor
virtual~MyCurvedCylinder(){}

/// Lagrangian coordinate xi
void position (const Vector<double>& xi, Vector<double>& r) const
{
 r[0] = (1.0/Delta)*cos(xi[0]) + xi[2]*Radius*cos(xi[0])*cos(xi[1]);
 r[1] = (1.0/Delta)*sin(xi[0]) + xi[2]*Radius*sin(xi[0])*cos(xi[1]);
 r[2] = -xi[2]*Radius*sin(xi[1]);
}


/// Return the position of the tube as a function of time
/// (doesn't move as a function of time)
void position(const unsigned& t,
              const Vector<double>& xi, Vector<double>& r) const
  {
   position(xi,r);
  }

private:

 /// Storage for the radius of the tube
 double Radius;

 //Storage for the curvature of the tube
 double Delta;
};

//=start_of_namespace============================================
/// Namespace for physical parameters
//================================================================
namespace Global_Physical_Variables
{
 /// Reynolds number
 double Re=50;

 /// The desired curvature of the pipe
 double Delta=0.1;
} // end_of_namespace


//=start_of_problem_class========================================
/// Entry flow problem in tapered tube domain
//================================================================
template<class ELEMENT>
class SteadyCurvedTubeProblem : public Problem
{

public:

 /// Constructor: Pass DocInfo object and target errors
 SteadyCurvedTubeProblem(DocInfo& doc_info, const double& min_error_target,
                  const double& max_error_target);

 /// Destructor (empty)
 ~SteadyCurvedTubeProblem() {}

 /// Update the problem specs before solve
 void actions_before_newton_solve();

 /// After adaptation: Pin redudant pressure dofs.
 void actions_after_adapt()
  {
   // Pin redudant pressure dofs
   RefineableNavierStokesEquations<3>::
    pin_redundant_nodal_pressures(mesh_pt()->element_pt());
  }
```

```
 /// Doc the solution
 void doc_solution();

 /// Overload generic access function by one that returns
 /// a pointer to the specific  mesh
 RefineableTubeMesh<ELEMENT>* mesh_pt()
  {
   return dynamic_cast<RefineableTubeMesh<ELEMENT>*>(Problem::mesh_pt());
  }

private:

 /// Doc info object
 DocInfo Doc_info;

 /// Pointer to GeomObject that specifies the domain volume
 GeomObject *Volume_pt;

}; // end_of_problem_class



//=start_of_constructor=============================================
/// Constructor: Pass DocInfo object and error targets
//==================================================================
template<class ELEMENT>
SteadyCurvedTubeProblem<ELEMENT>::SteadyCurvedTubeProblem(DocInfo& doc_info,
                                          const double& min_error_target,
                                          const double& max_error_target)
 : Doc_info(doc_info)
{

 // Setup mesh:
 //------------

 // Create GeomObject that specifies the domain geometry
 //The radius of the tube is one and the curvature is specified by
 //the global variable Delta.
 Volume_pt=new MyCurvedCylinder(1.0,Global_Physical_Variables::Delta);
 //Define pi
 const double pi = MathematicalConstants::Pi;
 //Set the centerline coordinates spanning the mesh
 Vector<double> centreline_limits(2);
 centreline_limits[0] = 0.0;
 centreline_limits[1] = pi;

 //Set the positions of the angles that divide the outer ring
 //These must be in the range -pi,pi, ordered from smallest to
 //largest
 Vector<double> theta_positions(4);
 theta_positions[0] = -0.75*pi;
 theta_positions[1] = -0.25*pi;
 theta_positions[2] = 0.25*pi;
 theta_positions[3] = 0.75*pi;

 //Define the radial fraction of the central box (always halfway
 //along the radius)
 Vector<double> radial_frac(4,0.5);
 // Number of layers in the initial mesh
 unsigned nlayer=6;

 // Build and assign mesh
 Problem::mesh_pt()= new RefineableTubeMesh<ELEMENT>(Volume_pt,
                                                     centreline_limits,
                                                     theta_positions,
                                                     radial_frac,
                                                     nlayer);
 // Set error estimator
 Z2ErrorEstimator* error_estimator_pt=new Z2ErrorEstimator;
 mesh_pt()->spatial_error_estimator_pt()=error_estimator_pt;
 // Error targets for adaptive refinement
 mesh_pt()->max_permitted_error()=max_error_target;
 mesh_pt()->min_permitted_error()=min_error_target;
 // Set the boundary conditions for this problem: All nodal values are
 // free by default -- just pin the ones that have Dirichlet conditions
 // here.
 //Choose the conventional form by setting gamma to zero
 //The boundary conditions will be pseudo-traction free (d/dn = 0)
 ELEMENT::Gamma[0] = 0.0;
 ELEMENT::Gamma[1] = 0.0;
 ELEMENT::Gamma[2] = 0.0;

 //Loop over the boundaries
 unsigned num_bound = mesh_pt()->nboundary();
 for(unsigned ibound=0;ibound<num_bound;ibound++)
```

```
  {
   unsigned num_nod= mesh_pt()->nboundary_node(ibound);
   for (unsigned inod=0;inod<num_nod;inod++)
    {
     // Boundary 0 is the inlet symmetry boundary:
     // Boundary 1 is the tube wall
     // Pin all values
     if((ibound==0) || (ibound==1))
      {
       mesh_pt()->boundary_node_pt(ibound,inod)->pin(0);
       mesh_pt()->boundary_node_pt(ibound,inod)->pin(1);
       mesh_pt()->boundary_node_pt(ibound,inod)->pin(2);
      }
    }
  } // end loop over boundaries

 // Loop over the elements to set up element-specific
 // things that cannot be handled by constructor
 unsigned n_element = mesh_pt()->nelement();
 for(unsigned i=0;i<n_element;i++)
  {
   // Upcast from GeneralisedElement to the present element
   ELEMENT* el_pt = dynamic_cast<ELEMENT*>(mesh_pt()->element_pt(i));

   //Set the Reynolds number, etc
   el_pt->re_pt() = &Global_Physical_Variables::Re;
  }

 // Pin redudant pressure dofs
 RefineableNavierStokesEquations<3>::
  pin_redundant_nodal_pressures(mesh_pt()->element_pt());

 //Attach the boundary conditions to the mesh
 cout <<"Number of equations: " << assign_eqn_numbers() << std::endl;

} // end_of_constructor


//=start_of_actions_before_newton_solve==================================
/// Set the inflow boundary conditions
//========================================================================
template<class ELEMENT>
void SteadyCurvedTubeProblem<ELEMENT>::actions_before_newton_solve()
{

 // (Re-)assign velocity profile at inflow values
 //----------------------------------------------
 unsigned ibound=0;
 unsigned num_nod= mesh_pt()->nboundary_node(ibound);
 for (unsigned inod=0;inod<num_nod;inod++)
  {
   // Recover coordinates of tube relative to centre position
   double x=mesh_pt()->boundary_node_pt(ibound,inod)->x(0) -
    1.0/Global_Physical_Variables::Delta;
   double z=mesh_pt()->boundary_node_pt(ibound,inod)->x(2);
   //Calculate the radius
   double r=sqrt(x*x+z*z);

   // Poiseuille-type profile for axial velocity (component 1 at the inlet)
   mesh_pt()->boundary_node_pt(ibound,inod)->
    set_value(1,(1.0-pow(r,2.0)));
  }

} // end_of_actions_before_newton_solve


//=start_of_doc_solution=================================================
/// Doc the solution
//========================================================================
template<class ELEMENT>
void SteadyCurvedTubeProblem<ELEMENT>::doc_solution()
{
 //Output file stream
 ofstream some_file;
 char filename[100];

 // Number of plot points
 unsigned npts;
 npts=5;

 //Need high precision for large radii of curvature
 //some_file.precision(10);
 // Output solution labelled by the Reynolds number
 snprintf(filename, sizeof(filename), "%s/soln_Re%g.dat",Doc_info.directory().c_str(),
         Global_Physical_Variables::Re);
 some_file.open(filename);
 mesh_pt()->output(some_file,npts);
```

```
 some_file.close();

} // end_of_doc_solution



////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////


//=start_of_main=======================================================
/// Driver for 3D entry flow into a curved tube. If there are
/// any command line arguments, we regard this as a validation run
/// and perform only a single adaptation
//======================================================================
int main(int argc, char* argv[])
{

 // Store command line arguments
 CommandLineArgs::setup(argc,argv);

 // Allow (up to) two rounds of fully automatic adapation in response to
 //-------------------------------------------------------------------------
 // error estimate
 //---------------
 unsigned max_adapt;
 double max_error_target,min_error_target;

 // Set max number of adaptations in black-box Newton solver and
 // error targets for adaptation
 if (CommandLineArgs::Argc==1)
  {
   // Up to two adaptations
   max_adapt=2;

   // Error targets for adaptive refinement
   max_error_target=0.001;
   min_error_target=0.00001;
  }
 // Validation run: Only one adaptation. Relax error targets
 // for faster solution
 else
  {
   // Validation run: Just one round of adaptation
   max_adapt=1;

   // Error targets for adaptive refinement
   max_error_target=0.02;
   min_error_target=0.002;
  }
 // end max_adapt setup

 // Set up doc info
 DocInfo doc_info;
 // Do Taylor-Hood elements
 //------------------------
 {
  // Set output directory
  doc_info.set_directory("RESLT_TH");

  // Step number
  doc_info.number()=0;

  // Build problem
  SteadyCurvedTubeProblem<RefineableQTaylorHoodElement<3> >
   problem(doc_info,min_error_target,max_error_target);

  cout « " Doing Taylor-Hood elements " « std::endl;

  // Solve the problem
  problem.newton_solve(max_adapt);
  // Doc solution after solving
  problem.doc_solution();
 }

 // Do Crouzeix-Raviart elements
 //-------------------------
 {
  // Set output directory
  doc_info.set_directory("RESLT_CR");

  // Step number
  doc_info.number()=0;

  // Build problem
  SteadyCurvedTubeProblem<RefineableQCrouzeixRaviartElement<3> >
```

```
   problem(doc_info,min_error_target,max_error_target);

  cout « " Doing Crouzeix-Raviart elements " « std::endl;

  // Solve the problem
  problem.newton_solve(max_adapt);
  // Doc solution after solving
  problem.doc_solution();
 }

} // end_of_main
```

## 1.1 PDF file

A pdf version of this document is available. \