Images in the Frequency Domain

Topic 8

Week 8 – Mar. 6th, 2019

Topic 8: Images in the Frequency Domain

- **Fourier Series/Transform**
- Images in Frequency Domain
- The Convolution Theorem
- High-Pass, Low-Pass and Band-Pass Filters

A Different type of Basis

- Last week we learned how to represent images using a different basis
- This week we are going to learn how to represent images using a very different and perhaps counter-intuitive basis – the *Fourier basis*
- This basis gives us a representation of our images in *frequency space*

Representing a Function with Sine Functions

$$f(x) = \begin{cases} -1 & \text{if } x < 0 \\ 1 & \text{otherwise} \end{cases}$$

- Let's try to approximate the above function with only a sine wave
- We are going to use the basic "building block" of a general sine wave:

$$A \sin(\omega x + \phi)$$

Quick Review: Sinusoid

$$y(x) = A\sin(\omega x + \phi)$$

A is the wave's amplitude

Quick Review: Sinusoid

$$y(x) = A\sin(\omega x + \phi)$$

ω is the **angular** frequency

$$\omega = 2\pi f$$

where f is the frequency of the wave

Quick Review: Sinusoid

$$y(x) = A\sin(\omega x + \phi)$$

ϕ is the phase

Representing a Function with Sine Functions

- First attempt – represent using single sine wave:

$$f(x) \approx \sin(x)$$

Representing a Function with Sine Functions

- First attempt – represent using single sine wave:

$$f(x) \approx \frac{4}{\pi}\sin(x)$$

Representing a Function with Sine Functions

- Second attempt – represent using two sine waves of **different frequency**:

$$f(x) \approx \frac{4}{\pi}\sin(x) + \frac{4}{3\pi}\sin(3x)$$

Fourier Series

N=3

N=10

- It turns out we can represent our step function exactly as the infinite sum of the sine waves:

$$F(x) = \sum_{n=1}^{N=\infty} \frac{4}{(2n-1)\pi} \sin\big((2n-1)x\big)$$

(**Note: Don't memorize this!** We will learn how to calculate these coefficients….)

Fourier Series

N=3

N=10

- **Discontinuities are difficult** – they require more higher frequency terms to represent
- The representation error for finite terms gives a “ringing” effect – name will make more sense in 2D, but the cause of is more intuitive in 1D

Fourier Transform

- In general we can represent a function $f(x)$ by the sum of an infinite series of sine waves
- The way we do this is called the ***Fourier transform,*** and is usually defined with the **complex** exponential:

$$F(\omega) = \int_{-\infty}^{\infty} f(x)\, e^{-i\omega x}\, dx$$

- $f(x)$ is the function we want to transform to the frequency domain
- $\mathrm{F}(\omega)$ is the function in the frequency domain, where $\omega = 2\pi f$

Fourier Transform

- ***Fourier transform***:

$$F(\omega) = \int_{-\infty}^{\infty} f(x)\, e^{-i\omega x}\, dx$$

  - $f(x)$ is the function we want to transform to the frequency domain
  - $\mathrm{F}(\omega)$ is the function in the frequency domain, where $\omega = 2\pi f$

- Often this is defined instead with spatial frequency f:

$$F(f) = \int_{-\infty}^{\infty} f(x)\, e^{-i2\pi f x}\, dx$$

Inverse Fourier Transform

- We can also go back to the original spatial signal with the inverse transform!
- ***Inverse Fourier transform***:

$$f(x) = \frac{1}{2\pi} \int_{-\infty}^{\infty} F(\omega)\, e^{i\omega x}\, d\omega$$

  - $F(\omega)$is the function we want to transform to the spatial domain
  - $f(x)$ is the function in the spatial domain

Fourier Transform

- ***Fourier transform***:

$$F(\omega) = \int_{-\infty}^{\infty} f(x)\, e^{-i\omega x}\, dx$$

- Wait, what happened to the sine?
- Still there, just hidden behind the complex exponential function:

$$e^{i\omega x} = \cos \omega x + i \sin \omega x$$

(real) (complex)

Fourier Transform

- Behind the complex exponential:

$$e^{i\omega x} = \cos \omega x + i \sin \omega x$$

(Euler's formula)

(Note: $e^{-i\omega x} = \cos -\omega x + i \sin -\omega x$)

- This cos/sin pair can encode the **phase** of the sinusoid (i.e. direction of vector on unit circle):

$$u \cos \omega x + v \sin \omega x = A \sin(\omega x + \phi)$$

where,

$$A = \pm\sqrt{u^2 + v^2}, \qquad \phi = \arctan \frac{u}{v}$$

(image from Wikipedia)

Note: It is not important to understand the complex exponential function, it is just a more compact way of encoding the frequency/phase

Fourier Transform as a Change in Basis

- ***Fourier transform***:

$$F(\omega) = \int_{-\infty}^{\infty} f(x)\, i \sin \omega x + f(x) \cos \omega x \, dx$$

- The sine and cosine functions are an **orthogonal basis**
- The Fourier transform decomposes the function $f(x)$ into a **weighted sum of basis functions** (i.e. sin/cos) in the complex space
- This is similar to the change of basis we saw before, where we defined a vector based on two basis vectors, e.g. $\mathbf{v} = v_0 \boldsymbol{i} + v_1 \boldsymbol{j}$

Frequency Spectrum

- A sine curve is transformed to a **single point** in the Frequency domain
- This is because it is a single frequency (i.e. **one term** in the Fourier series)

Frequency Spectrum

- More complex functions are transformed into **many points** in the frequency domain
- They are composed of many frequencies (i.e. **many terms** in the Fourier series)

Fourier Series is Just Another Basis!

https://en.wikipedia.org/wiki/Fourier_series

Topic 8: Images in the Frequency Domain

- Fourier Series/Transform
- **Images in Frequency Domain**
- The Convolution Theorem
- High-Pass, Low-Pass and Band-Pass Filters

Fourier Transform of Images

- The continuous 2D Fourier transform is defined:

$$F(u,v) = \iint_{-\infty}^{\infty} f(x,y)\, e^{-i(ux+vy)}\, dx\, dy$$

- The discrete 2D Fourier transform is defined:

$$F(u,v) = \sum_{x} \sum_{y} f(x,y)\, e^{-i(ux+vy)}$$

- Images are just a discrete 2D function, so we can also represent them in the frequency domain

Simple Fourier Examples

$f(x, y)$

$F(u, v)$

Fourier is parameterized by u, v: frequency components in the x and y directions)

Simple Fourier Examples

$f(x, y)$

$F(u, v)$

Fourier is parameterized by u, v: frequency components in the x and y directions)

Simple Fourier Examples

$f(x, y)$

$F(u, v)$

Fourier is parameterized by u, v: frequency components in the x and y directions)

Fourier Transform of Images

- As we said of the 1D Fourier transform, it can be thought of as a change of basis, where the basis functions are sinusoids of different frequencies
- Each of the images we just saw is a actually a Fourier **basis function**

Fourier Transform of Images

$$F(u,v) = \sum_x \sum_y f(x,y)\, e^{-i(u\,x+v\,y)}$$

- **With the 2D Fourier transform we can visualize these basis functions as images!**

- Above right, we show the 2D basis function, below right, the coordinates of that function in the 2D Frequency domain

(©Bill Freeman, MIT)

Fourier Transform of Images

- Vector form may be more intuitive:

$$F(\boldsymbol{\omega}) = f(x, y)\, e^{-i\boldsymbol{\omega}\boldsymbol{x}}$$

where $\boldsymbol{\omega} = (u, v), \boldsymbol{x} = (x, y)$

- Direction of the basis function (sinusoid) is direction of the vector $\boldsymbol{\omega}$=(u, v)
- Frequency is determined by the magnitude of the vector $\boldsymbol{\omega}$=(u, v)

(©Bill Freeman, MIT)

Fourier Transform of Images

- Above we show the 2D basis function, below the coordinates of that function in the 2D Frequency domain

- Direction of the basis function (sinusoid) is direction of the vector $\boldsymbol{\omega}$=(u, v)
- Frequency is determined by the magnitude of the vector $\boldsymbol{\omega}$=(u, v)

(©Bill Freeman, MIT)

Fourier Transform of Images

- Above we show the 2D basis function, below the coordinates of that function in the 2D Frequency domain

- Direction of the basis function (sinusoid) is direction of the vector $\boldsymbol{\omega}$=(u, v)
- Frequency is determined by the magnitude of the vector $\boldsymbol{\omega}$=(u, v)

(©Bill Freeman, MIT)

Images and the Fourier Transform

- We have a set of basis 2D sinusoids (let's say images)
- Images can be decomposed into a **weighted** linear combination of sinusoids of different frequencies
- It is these **weights** that are the values in the Fourier "image" – and they are complex numbers

$= w_0 \cdot$ $+ w_1 \cdot$ $+ w_2 \cdot$ $\cdots$

Increasing frequency →

Fourier Transform as a Basis

$$exp[\, j\, 2\pi\, (ux + vy)\,] =$$
$$cos[2\pi(ux + vy)] + j\, sin[2\pi(ux + vy)]$$

Intermission

Fourier Transformed Image

Error

This is a complex valued function!
Can't just display the values as image

$$f(x,y) \xrightarrow[\text{Transform}]{\text{Fourier}} F(u,v)$$

Fourier Transformed Image

$f(x, y)$ → $F(u, v)$

Fourier Transform

$|F(u, v)|$

Fourier Transformed Image

$f(x, y)$ → $F(u, v)$

Fourier Transform

$|F(u, v)|$

Fourier Transformed Image

$f(x, y)$ → $F(u, v)$ $\log|F(u, v)|$

Fourier Transform

DC Component

- F(0,0) is called the DC component
- What is this bright F(0,0) component?

$$F(0,0) = \sum_x \sum_y f(x,y)\, e^{i(0x+0y)}$$

- In the Fourier domain, it's equal to the sum of all image pixels
- In the spatial domain, it's the image's **mean brightness/intensity**
- This is the information in the image that does not change with spatial location

$\log |F(u,v)|$

Frequency/Phase in Fourier

$f(x, y)$ → $F(u, v)$

Fourier Transform

Frequency/Phase in Fourier

- The Fourier transform of an image gives us an "image" $F(u, v)$ where each pixel is a **complex number** representing the components in the Fourier basis

- If we express these complex numbers instead in **polar coordinates**:
  - **magnitude/radius = frequency component**
  - **angle = phase component**

- Remember we are decomposing our function into sinusoids which have both **frequency** and **phase**, i.e.

$$y(x) = A \sin 2\pi f x + \phi$$

amplitude

phase

Images and the Fourier Transform

- In image processing we will be focusing on the **frequency**
- However, without the phase component we can't reconstruct a spatial image!

$f(x, y)$

Fourier Transform

$\log |F(u, v)|$

Topic 8: Images in the Frequency Domain

- Fourier Series/Transform
- **Images in Frequency Domain**
- The Convolution Theorem

Images and the Fourier Transform

- Let's look at what some of these frequency components look like in the spatial domain

$f(x, y)$

Fourier Transform

$\log |F(u, v)|$

Images and the Fourier Transform

- Let's zero out the low frequency Fourier components
- We are left with **high frequency components** – i.e. **edges**!

$f(x, y)$

Inverse Fourier Transform

$\log |F(u, v)|$

Images and the Fourier Transform

- Let's zero out the high frequency Fourier components
- We are left with **low frequency components** – the image looks **blurred**

$f(x, y)$

Inverse Fourier Transform

$\log |F(u, v)|$

Images and the Fourier Transform

- Let's zero out the high frequency Fourier components
- We are left with low frequency components – looks blurred

$f(x, y)$

Inverse Fourier Transform

Notice the "ringing" effect we saw in 1D!

Flashback to 1D

N=3

N=10

- The representation error for finite terms gives a “ringing” effect – name will make more sense in 2D, but the cause of is more intuitive in 1D

Gaussians and Fourier Transform

- This ringing is because a box filter in the spatial domain is mapped to a sinc function in the frequency domain (and vice versa):

$$\mathrm{sinc}(x) = \frac{\sin(x)}{x}$$

- However, **Guassians in spatial domain are also Gaussians in frequency domain**

Gaussian Filters in Frequency Domain

- Instead of using a box, let's try a Gaussian instead

$f(x, y)$

Inverse Fourier Transform

$\log |F(u, v)|$

Gaussian Filters in Frequency Domain

- This is a smoothed image!
- Same result as if we convolved image with Gaussian filter
- But all we did here was multiply our Fourier transformed image by a Gaussian…
- How did we get the same result as convolution (many multiplications per pixel) with only one per pixel?

Gaussian Filters in Frequency Domain

- Taking it even further…

$f(x, y)$

Inverse Fourier Transform

$\log |F(u, v)|$

Topic 8: Images in the Frequency Domain

- Fourier Series/Transform
- Images in Frequency Domain
- **The Convolution Theorem**
- High-Pass, Low-Pass and Band-Pass Filters

The Convolution Theorem

- Let $f(x, y), h(x, y)$ be 2D spatial functions, $F(u, v), H(u, v)$ be their corresponding Fourier transforms, $\mathcal{F}^{-1}$ be the inverse Fourier transform, and $*$ is the convolution operator, then:

$$f(x) * h(x) = \mathcal{F}^{-1}(F(u, v)H(u, v))$$

- **Convolution** in the **spatial domain** is the same as **multiplication** in the **frequency domain**
- Why does this matter?
- Because image filtering operations in the spatial domain can be implemented by a simple convolution in the frequency domain!

Image Filtering in Frequency Domain

$f(x, y)$

Fourier Transform

$F(u, v)$

Multiply
In Fourier

$F(u, v)\ H(u, v)$

Inverse Fourier Transform

$h(x, y)$

$H(u, v)$

filtered image: $f'(x, y)$

When is Fourier Used for Image Filtering?

- So why don't we always do image filtering in the frequency domain?
- Because **the Fourier transform/inverse Fourier transform steps** give us significant overhead, it may not be more efficient than spatial convolution, depending on the filter size
- **Usually image filtering is only done in frequency domain for large image filters**

- It turns out there is a much more efficient implementation of the Discrete Fourier Transform (DFT) called the Fast Fourier Transform (FFT)
- For a 1D signal with N data points, DFT is $O(N^2)$, FFT is $O(N \log N)$

Topic 8: Images in the Frequency Domain

- Fourier Series/Transform
- Images in Frequency Domain
- The Convolution Theorem
- **High-Pass, Low-Pass and Band-Pass Filters**

Signal Processing Loan-Words

- There are a number of terms we use in visual computing that are borrowed from signal processing, and the frequency domain
- These are important to understand, and you will hear them used quite a bit
- You've already seen one: *the DC component!* This actually stands for direct current, which doesn't make much sense with images

Low-Pass Filters

- These are examples of "**low pass**" and "**high pass**" filters – a term common in signal processing
- **Low-pass filter**, we let low-frequencies "pass" through and "block" high frequencies

$f(x, y)$

Inverse Fourier Transform

$|H(u, v)|$

High-Pass Filters

- These are examples of “**low pass**” and “**high pass**” filters – a term common in signal processing
- **High-pass filter**, we let high-frequencies “pass” through and “block” low frequencies

Inverse Fourier Transform

$f(x, y)$ $F(u, v) * H(u, v)$ $|H(u, v)|$

Band-Pass Filters

- A band-pass filter only allows through a range of frequencies, i.e. a frequency “band” – here effected by the difference of two gaussian filters

$f(x, y)$

Inverse Fourier Transform

$|H(u, v)|$

End of Topic 8