

Saliency Maps

Paul Bienkowski

Seminar “Brain Modelling”

2014-07-14

Outline

1 Introduction

- Motivation and Definitions

2 Prequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Introduction

1 Introduction

- Motivation and Definitions

2 Prerequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix


Introduction



Introduction



Introduction



Introduction

Definition

salient

most noticeable or important

Introduction

Definition

salient

most noticeable or important

Definition

map

topographically arranged representation of information in a multidimensional space

Introduction

Definition

salient

most noticeable or important

Definition

map

topographically arranged representation of information in a multidimensional space

Definition

saliency map

A 2D map representing visual saliency of a corresponding visual scene.

Motivation

Biological

- plan eye movement
- see things “from the corner of the eye”

Technical

- pre-select important areas from images for image processing
- performance gain in computer vision applications
- object detection (computer graphics application)

Example Maps



Prequisites

1 Introduction

- Motivation and Definitions

2 Prequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Contrast

- *Color intensity contrast* is the difference in color perception
- distance within *Lab color space*
 - models perception better than RGB
- requires reference color
 - global average → global contrast
 - local average function → spatial contrast

Contrast

- *Color intensity contrast* is the difference in color perception
 - distance within *Lab color space*
 - models perception better than RGB
 - requires reference color
 - global average → global contrast
 - local average function → spatial contrast

Types of contrast

- color
 - intensity
 - motion
 - orientation
 - depth

} differences

Ventral/dorsal pathway




Figure: Ventral and dorsal stream

What?	Where?
Object recognition / identification Temporal cortex Ventral stream	Spatial processing Parietal cortex Dorsal stream

Models and algorithms

1 Introduction

- Motivation and Definitions

2 Prequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Koch et al. 1987

Shifts in selective visual attention: towards the underlying neural circuitry

- How to handle large amounts of sensory data?
- → only process parts of them: SELECTIVE ATTENTION

Koch et al. 1987

Shifts in selective visual attention: towards the underlying neural circuitry

- How to handle large amounts of sensory data?
- → only process parts of them: SELECTIVE ATTENTION
- decomposition into early representation of basic features
- retinotopical feature maps
- combined into one general saliency map

Koch et al. 1987


Shifts in selective visual attention: towards the underlying neural circuitry

- How to handle large amounts of sensory data?
- → only process parts of them: SELECTIVE ATTENTION
- decomposition into early representation of basic features
- retinotopical feature maps
- combined into one general saliency map

"A 'saliency map', that is, an explicit two-dimensional topographical map that encodes stimulus conspicuity, or saliency, at every location in the visual scene." [2]

Koch et al. 1987

The saliency map



Koch et al. 1987

The saliency map





Figure: Sample Koch/Itti saliency map

Example Maps



Koch et al. 1987

Visual search

To search a visual scene, the saliency map and two mechanisms are required:

Koch et al. 1987

Visual search

To search a visual scene, the saliency map and two mechanisms are required:

Winner-take-all

- maximum value and location are determined
- using complex pyramid-shaped neural network
- directs the next saccade

Koch et al. 1987

Visual search

To search a visual scene, the saliency map and two mechanisms are required:

Winner-take-all

- maximum value and location are determined
- using complex pyramid-shaped neural network
- directs the next saccade

Inhibition of return

- concept to prevent going back to seen locations
- simple to implement using inhibitory synapses

Koch et al. 1987

Visual search

Special task: Search for a person in a group of people

- ventral stream detects faces
- feed face locations into saliency map (dorsal stream)
- search salient (face) locations for matching face

Itti/Koch et al. 2001


Computational Modelling of visual Attention

- Itti refines Koch's model
- describes early stages in detail
- uses simple localized filters
 - center-sourround
 - gabor kernels


Itti/Koch et al. 2001

Computational Modelling of visual Attention

- Itti refines Koch's model
- describes early stages in detail
- uses simple localized filters
 - center-sourround
 - gabor kernels



Center-sourround /
DIFFERENCE OF GAUSSIANS



Gabor kernels

Perazzi et al. 2012

Contrast Based Filtering for Salient Region Detection

- fast and reliable *application-oriented* algorithm
- salient *region* detection
- contour detail stays intact



Perazzi et al. 2012

Contrast Based Filtering for Salient Region Detection

1. segment input image using SLIC

- *Simple Linear Iterative Clustering*
- (edge-preserving) K-means clustering algorithms
- geodesic image distance in Lab color space
- segments are called *elements*

Perazzi et al. 2012

Contrast Based Filtering for Salient Region Detection

1. segment input image using SLIC

- *Simple Linear Iterative Clustering*
- (edge-preserving) K-means clustering algorithms
- geodesic image distance in Lab color space
- segments are called *elements*

2. analyze segment uniqueness

- rarity of the element color
- compared to all other segments
- weighted by the distance between them
- Gaussian weight function for fast localized uniqueness

Perazzi et al. 2012

Contrast Based Filtering for Salient Region Detection


1. segment input image using SLIC
 - *Simple Linear Iterative Clustering*
 - (edge-preserving) K-means clustering algorithms
 - geodesic image distance in Lab color space
 - segments are called *elements*
2. analyze segment uniqueness
 - rarity of the element color
 - compared to all other segments
 - weighted by the distance between them
 - Gaussian weight function for fast localized uniqueness
3. analyze segment distribution
 - occurrence of a color elsewhere in the image
 - low variance → compact object → more salient

Perazzi et al. 2012

Contrast Based Filtering for Salient Region Detection

1. segment input image using SLIC
 - *Simple Linear Iterative Clustering*
 - (edge-preserving) K-means clustering algorithms
 - geodesic image distance in Lab color space
 - segments are called *elements*
2. analyze segment uniqueness
 - rarity of the element color
 - compared to all other segments
 - weighted by the distance between them
 - Gaussian weight function for fast localized uniqueness
3. analyze segment distribution
 - occurrence of a color elsewhere in the image
 - low variance → compact object → more salient
4. combine segment uniqueness and distribution and apply to original pixels

Example Maps



Hou et al. 2007


- in natural scene images, spatial frequency analysis (Fourier transform) yields a typical average pattern
- can be used to determine *untypical* frequencies
→ not average image data but interesting object
- reverse lookup for saliency map generation

Hou et al. 2007

- in natural scene images, spatial frequency analysis (Fourier transform) yields a typical average pattern
- can be used to determine *untypical* frequencies
→ not average image data but interesting object
- reverse lookup for saliency map generation

- independent of low-level features
- filter background noise from data
- flexible system
- *not neuro-biologically plausible*

Example Maps



Algorithm features

- Blurriness
 - caused by center-sourround filters or downsampling for performance
 - no problem in finding single POI¹ (winner-take-all)
 - impedes object detection

¹point of interest

Algorithm features

- Blurriness
 - caused by center-sourround filters or downsampling for performance
 - no problem in finding single POI¹ (winner-take-all)
 - impedes object detection
- sort POI by intensity
 - opposite of boundary detection (binary decision)
 - required for visual search

¹point of interest

Algorithm features

- Blurriness
 - caused by center-sourround filters or downsampling for performance
 - no problem in finding single POI¹ (winner-take-all)
 - impedes object detection
- sort POI by intensity
 - opposite of boundary detection (binary decision)
 - required for visual search
- iterative analysis
 - approximate quickly, refine over time
 - useful in robotics

¹point of interest

Algorithm features

- Blurriness
 - caused by center-sourround filters or downsampling for performance
 - no problem in finding single POI¹ (winner-take-all)
 - impedes object detection
- sort POI by intensity
 - opposite of boundary detection (binary decision)
 - required for visual search
- iterative analysis
 - approximate quickly, refine over time
 - useful in robotics
- spatio-temporal analysis
 - analyze video data, movement detection

¹point of interest

Discussion

1 Introduction

- Motivation and Definitions

2 Prerequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Comparison

Approach	Itti/Koch	Perazzi	Hou
Model type	neural	computational	computational
Object detection	impossible	great (with contours)	good
Sortable by intensity	good / inhibition of return	fair	fair
Iterative analysis	simple	not possible	n/a
Movement detection	use 3-dim. input space	possible	difficult

Table: Comparison between approaches and their features and capabilities

Neuro-biological relevance

- Koch/Itti
 - based on neuro-biological findings
 - easily implementable using feedforward neural networks
 - combinable with winner-take-all/inhibition of return for visual search

Neuro-biological relevance

- Koch/Itti

- based on neuro-biological findings
- easily implementable using feedforward neural networks
- combinable with winner-take-all/inhibition of return for visual search

- Perazzi **and** Hou

- computational models
- no similar findings in biological research
- no obvious neural network implementations
- perform tasks associated with both ventral *and* dorsal stream

Neuro-biological relevance

- Koch/Itti

- based on neuro-biological findings
- easily implementable using feedforward neural networks
- combinable with winner-take-all/inhibition of return for visual search

- Perazzi **and** Hou

- computational models
- no similar findings in biological research
- no obvious neural network implementations
- perform tasks associated with both ventral *and* dorsal stream

Looking for a neuro-biological model of visual attention?

Neuro-biological relevance

■ Koch/Itti

- based on neuro-biological findings
- easily implementable using feedforward neural networks
- combinable with winner-take-all/inhibition of return for visual search

■ Perazzi **and** Hou

- computational models
- no similar findings in biological research
- no obvious neural network implementations
- perform tasks associated with both ventral *and* dorsal stream

Looking for a neuro-biological model of visual attention?

⇒ Koch/Itti!

Conclusion

1 Introduction

- Motivation and Definitions

2 Prequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Conclusion

- many different saliency detection methods (named three)

Conclusion

- many different saliency detection methods (named three)
- either **neural** or **computational** models

Conclusion

- many different saliency detection methods (named three)
 - either **neural** or **computational** models
 - Koch/Itti is state-of-the-art neuro-biological model for saliency

Conclusion

- many different saliency detection methods (named three)
- either **neural** or **computational** models
- Koch/Itti is state-of-the-art neuro-biological model for saliency
- other algorithms include object detection etc, more task specific

Conclusion

- many different saliency detection methods (named three)
 - either **neural** or **computational** models
 - Koch/Itti is state-of-the-art neuro-biological model for saliency
 - other algorithms include object detection etc, more task specific
 - broad area of applications in science and industry

Appendix

1 Introduction

- Motivation and Definitions

2 Prerequisites

- Contrast
- Ventral/dorsal pathway

3 Models and algorithms

- Koch/Itti et al. 1987/2001
- Perazzi et al. 2012
- Hou et al. 2007
- Algorithm features

4 Discussion

- Comparison
- Neuro-biological relevance

5 Conclusion

6 Appendix

Bibliography

-  Xiaodi Hou and Liqing Zhang.
Saliency detection: A spectral residual approach.
In *Computer Vision and Pattern Recognition, 2007. CVPR'07. IEEE Conference on*, pages 1–8. IEEE, 2007.
-  Laurent Itti and Christof Koch.
Computational modelling of visual attention.
Nature reviews neuroscience, 2(3):194–203, 2001.
-  R. M. Klein and J. Ivanoff.
Inhibition of return.
3(10):3650, 2008.
revision #90806.
-  Raymond M Klein.
Inhibition of return.
Trends in cognitive sciences, 4(4):138–147, 2000.
-  Christof Koch and Shimon Ullman.
Shifts in selective visual attention: towards the underlying neural circuitry.
In *Matters of Intelligence*, pages 115–141. Springer, 1987.

Bibliography



Norbert Krüger, Peter Janssen, Sinan Kalkan, Markus Lappe, Ales Leonardis, Justus Piater, Antonio Jose Rodriguez-Sanchez, and Laurenz Wiskott.

Deep hierarchies in the primate visual cortex: What can we learn for computer vision?

Pattern Analysis and Machine Intelligence, IEEE Transactions on,
35(8):1847–1871, 2013.



Federico Perazzi, Philipp Krahenbuhl, Yael Pritch, and Alexander Hornung.

Saliency filters: Contrast based filtering for salient region detection.

In *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, pages 733–740. IEEE, 2012.



Pamela Reinagel and Anthony M Zador.

Natural scene statistics at the centre of gaze.

Network: Computation in Neural Systems, 10(4):341–350, 1999.

Image sources

- 3 <http://www.npebd.com/wp-content/uploads/2014/06/Eiffel-Tower.jpg>
- 1 http://upload.wikimedia.org/wikipedia/commons/thumb/f/fb/Ventral-dorsal_streams.svg/1024px-Ventral-dorsal_streams.svg.png
- 2 <http://cogpsy.info/wp-content/uploads/2012/10/Itti-Koch-2001-Computational-modeling-of-visual-attention.jpg>
- 6 http://opticalengineering.spiedigitallibrary.org/data/Journals/OPTICE/23430/057008_1_9.png
- 3 http://opticalengineering.spiedigitallibrary.org/data/Journals/OPTICE/24206/0E_51_2_026201_f006.png
- 4b <http://www.intechopen.com/source/html/16592/media/image74.png>
- 16 http://stanford.edu/~philkr/imgs/sf_teaser.png

Questions?

Questions?

Thanks for your attention!