

# INDEX

Provisions appear on pages 1–402.

Commentary appears on pages 405–822.

Page numbers followed by *e*, *f*, or *t* indicate equations, figures or tables.

- access floors, seismic design requirements, 127–128, 610
- accidental mass eccentricity, 175, 186, 570, 697–698
- active fault, defined, 77
- additions, 5, 77. *See also* alterations
- adequate structural strength, use of term, 410
- aerodynamic shade, snow drifts and, 59–61, 59*e*, 62*f*, 63*f*, 497–498, 498*f*, 499*f*
- aerodynamic wind loads, on tall buildings, 754
- aeroelastic model (AM), wind tunnel test, 793
- air-permeable cladding, wind loads, 333, 781–783, 782*f*
- air-supported structures, snow loads, 54, 494
- aleatory uncertainty, 35
  - defined, 466
- Alfred P. Murrah Federal Building, 411
- “all heights” method. *See* enclosed, partially enclosed, and open buildings of all heights
- allowable stress design (ASD)
  - defined, 1
  - load combinations, 8–9, 420–421, 421*t*
  - procedures, 2, 405
  - requirement to use, 417
  - seismic design criteria, 525
- along-wind response. *See* gust effects, wind loads
- alterations, 393
  - defined, 77
- amusement structures, 152
- anchorages
  - access floors, 603–605
  - in concrete, 637
  - fall arrest and lifeline, loads and, 16, 436
  - in masonry, 143, 144, 150
  - nonbuilding structures, 150, 155, 155*t*, 637
  - nonstructural components, 125, 603–605, 605*f*
  - structural walls, 4, 108–109, 108*e*
  - tanks and vessels, 644, 644*f*
- appendage, defined, 77
- approval, defined, 77
- approved, defined, 21, 245
- approximate fundamental frequency, 751–753, 752*e*, 752*f*, 753*e*
- approximate fundamental period, 102, 102*e*, 561–562, 561*f*
- arched roofs, wind loads MWFRS directional procedure, 278*f*
- architectural components, seismic design requirements,
  - 125–128, 126*e*, 126*t*, 127*t*, 128*e*, 146, 605–611, 608–609*t*, 611*f*
- ASCE Tsunami Design Geodatabase, 25, 26*f*, 32, 33*f*, 456, 465, 465*f*
- atmospheric icing, 69–76, 517–523
  - definitions, 69, 518–519
  - design procedure, 71
  - design temperatures for freezing rain, 70*f*, 71, 72–73*f*, 522
  - ice loads caused by freezing rain, 70–71, 70*e*, 70*f*, 71*e*, 72–73*f*, 74*f*, 75*f*, 76*f*, 519–521, 520*f*, 521*t*
  - partial loading, 76, 522
  - site-specific studies, 69
  - wind on ice-covered structures, 71, 72–73*f*, 74*f*, 75*f*, 76, 521–522, 522*t*
- attached canopy, defined, 245
  - on buildings, 380
- attachments, defined, 78, 526–527, 527*f*
- attics (uninhabitable), live loads, 18
- balconies and decks, live loads, 433–434
- barrel vault roofs, snow loads, 54, 59, 495, 497
- base
  - defined, 78
  - seismic design criteria, 527–529, 527*f*, 528*f*, 529*f*
- base flood, defined, 21
- base flood elevation (BFE), defined, 21
- base level, defined, 167
- base shear, defined, 78
- base slab averaging
  - defined, 197
  - soil-structure interaction, 201, 201*e*, 707, 707*f*
- basic wind speed, defined, 245
- Bathymetric profile, defined, 25
- bearing walls
  - alternative structural design criteria, 114–119, 114*f*, 115*t*, 116*e*, 118*e*, 119*e*
  - defined, 81
- boilers and pressure vessels, seismic design requirements, 133, 159–160, 616
- boundary elements, defined, 78
- braced frame, defined, 79
- breakaway wall
  - defined, 21
  - flood loads, 21, 440
- building, defined, 1, 78
- building appurtenances and rooftop structures and equipment
  - wind loads, components and cladding, 375–382, 375*e*, 379*f*, 379*t*, 380*e*, 380*f*, 380*t*, 381*f*, 382*t*
  - see also* wind loads on building appurtenances and other structure, MWFRS (directional procedure)
- building envelope products, C&C ratings for, 740
- building frame system, defined, 79
- building structure. *See* seismic design requirements, building structure
- building types, defined
  - enclosed, 245, 732
  - envelope, 246
  - flexible, 246, 732
  - low-rise, 245
  - open, 245, 732
  - partially enclosed, 245, 732
  - partially open, 246, 732
  - regular-shaped, 246, 732
  - rigid, 246, 732
  - simple diaphragm, 246
  - torsionally regular under wind load, 246
- cables
  - material-specific seismic design and detailing requirements, 136, 620
  - wind on ice-covered, 521–522, 522*t*

- camber, 395, 811
- cantilevered column system, defined, 78
- cantilevered storage racks, seismic design requirements, 638, 638f
- ceilings, accoustical tile standard, 610
- ceilings, seismic design requirements, 127, 607, 608–609t, 610
- change of use provisions, 393
- channelized scour, defined, 86
- characteristic earthquake, defined, 78
- chimneys and stacks, seismic design requirements, 152, 640
- circular bins, wind loads
  - components and cladding, 382, 382e, 382t, 383f, 384–385f, 385, 386f, 387f, 788–789, 789f
  - MWFRS directional procedure, 322, 326f, 327, 327e, 328f, 329f, 776, 776–777
- circular sector, defined, 743
- classification, of buildings and other structures
  - risk categorization, 4–5, 4t, 5t, 412–414, 413f
  - toxic, highly toxic, and explosive substances, 5, 414–415
- climate data, estimation of basic wind speeds from regional, 249, 740–741
- closure ratio (inundated protected area), defined, 25
- coastal A-zone, defined, 21, 439–440
- coastal high hazard area (V-zone), defined, 21, 439–440
- cold-formed steel light frame construction, seismic design and detailing requirements, 135–136, 619–620
- collapse, of buildings, 410–411
- collapse prevention structural performance level, defined, 25
- collector (drag strut, tie, diaphragm strut), defined, 78
- component importance factor, 121, 595
- component period, 124–125, 124e, 602–603
- components and appurtenances
  - defined, 69, 78, 526–527, 527f
  - see also* building appurtenances and rooftop structures and equipment
- components and cladding (C&C), 731, 740
  - defined, 246, 732
  - see also* wind loads, components and cladding
- composite steel and concrete structures, seismic design and detailing requirements, 142, 627–628
- concentrated live loads, 13, 435
- centrically braced frame (CBF), defined, 79
- concrete
  - anchorage in, 150
  - chimneys and stacks, 152, 640
  - definitions, 78
- concrete, seismic design and detailing requirements
  - composite steel and concrete structures, 142, 627–628
  - diaphragms, 139–142, 141f, 142f, 622–627, 622f, 623f, 624f, 625f, 626f, 627f
  - foundations, 136, 621
  - piles, 137–139, 137e, 138–139e, 621–622
  - precast structural walls, 136, 621
  - shear walls, 136–137, 621
- conduits and cable distributions systems, seismic design requirements, 131
- connection, defined, 136
- connector, defined, 136, 621
- construction documents, defined, 78
- containment systems (secondary), seismic design requirements, 153, 640–641
- continuous beam systems, snow loads, 54, 57
- controlled drainage, defined, 65
- cool roof slope factor, snow loads and, 54, 59f
- counteracting structural actions, basic requirements, 3
- coupling beams, 143–144
  - defined, 78
- crane loads, 17–18, 437
- critical action, defined, 78
- critical equipment/critical systems, defined, 25
- critical facility, defined, 25
- curved roofs, snow loads and, 54, 58–59, 60f, 495, 497
- damping device, defined, 181
- damping system, defined, 181
- damping systems, seismic design requirements
  - alternative procedures and acceptance criteria, 189–196, 189e, 190e, 191e, 191t, 192e, 193e, 194e, 195e, 195t, 196e, 699–701, 699f, 700e, 700f, 700t
  - damping systems distinguished from seismic force-resisting systems, 693, 694f
  - design review, 187, 698
  - general design requirements, 183–185, 183e, 185e, 693–697, 696f
  - nonlinear response history, 186–187, 697–698, 697t
  - testing, 187–189, 698–699
- data-base assisted design, wind tunnel procedure, 794
- dead loads, 11–12, 425, 426–427t
- deadweight tonnage (DWT), defined, 25
- debris impact loads. *See* impact loads
- deformability, elements defined, 78
- deformation, types defined, 78
- deformation-controlled actions
  - defined, 78
  - global acceptance criteria, 166, 166t, 670–671, 670t
- design earthquake, types defined, 78
- design earthquake ground motion, defined, 78
- design flood, defined, 21
- design flood elevation (DFE), defined, 21
- design force, defined, 246
- design pressure, defined, 246
- design professional, defined, 80
- design strength, defined, 1, 27, 80
- design tsunami parameters, defined, 27
- design wind speeds, ASCE 7-93 to 7-10, 740t
- designated seismic systems
  - certification required, 597–598
  - defined, 78
  - design requirements, 122
- detailed plain concrete structural wall, defined, 136
- deterministic seismic hazard analysis (DSHA), 711, 713, 723
- diaphragm boundary, defined, 78
- diaphragm chord, defined, 78
- diaphragm flexibility, seismic design requirements, 95t, 96–98, 96e, 96f, 97t, 98f, 98t
- diaphragms
  - buildings exempted from torsional wind load cases, 397–399, 398f, 399f
  - concrete, seismic design and detailing requirements, 139–142, 141f, 142f, 622–627, 622f, 623f, 624f, 625f, 626f, 627f
  - defined, 246, 732
  - steel, seismic design and detailing requirements, 136, 620
  - types, defined, 78
- diaphragms, chords, and collectors, seismic design, building structures, 90–92t, 95t, 106–108, 106e, 106f, 107e, 107f, 108t
- directional procedure
  - defined, 246
  - see also* wind loads on buildings, MWFRS directional procedure; wind loads on building appurtenances and other structures, MWFRS directional procedure

displacement restraint system, defined, 167

displacement-dependent damping device, defined, 181

displacements, seismic demands on nonstructural components, 124, 124*e*

distribution systems

- defined, 78
- seismic design criteria, 529–530
- seismic design requirements, 131–133, 614

domed roofs

- snow loads, 59, 497
- wind loads, components and cladding, 350*f*
- wind loads, MWFRS directional procedure, 277*f*, 767–768

drainage systems. *See* rain loads

drift, defined, 51

drift and deformation, seismic design requirements, 109–110, 109*t*

drifts on lower roofs (aerodynamic shade), snow and, 59–61, 59*e*, 62*f*, 63*f*, 497–498, 498*f*, 499*f*

dual structural system, defined, 79

duct systems, seismic design requirements, 131–132, 614

ductility-governed action, defined, 27

durability, serviceability considerations, 395, 803

dynamic analysis

- isolated structures, 175–176, 176*e*, 687–689, 688*t*
- nonstructural components, 123–124, 123*e*, 601–602, 602*f*
- see also* linear dynamic analysis

earthquakes

- characteristic earthquake, defined, 78
- design, defined, 78
- design earthquake ground motion, defined, 78
- load combinations for, 420–421
- nature of “loads,” 525
- performance-based procedures, 407–408
- risk categorization of buildings, 5*t*

earth-retaining structures, seismic design requirements, 152, 640

eave height, defined, 246

eccentrically braced frame (EBF), defined, 79

effective damping, defined, 167

effective stiffness, defined, 167

effective wind area, defined, 246–247, 732–733.

- See also* wind loads, components and cladding

electric power-generating facilities, seismic design requirements, 151, 639

electrical systems, seismic design requirements, 121, 130

element actions, defined, 78–79

elevators and escalators

- impact loads, 16
- seismic design requirements, 133, 616

embedment, soil-structure interaction, 201–202, 201*e*, 707–708

enclosed, partially enclosed, and open buildings of all heights, MWFRS directional procedure, 273–274, 273*t*, 274*e*, 275–276*f*, 277*f*, 278*f*, 279*f*, 280*f*, 281*f*, 282*f*, 283*f*, 767–769, 768*f*

enclosed and partially enclosed low-rise buildings, MWFRS envelope procedure, 311, 311*e*, 311*t*, 312–314*f*, 771–773, 772*f*, 773*f*

enclosed building, defined, 245

enclosed simple diaphragm buildings with height <160 ft, wind loads MWFRS directional procedure, 273, 284–285, 284*t*, 285*f*, 286*f*, 288–290*t*, 291–310*t*, 769–770

enclosed simple diaphragm low-rise buildings, MWFRS envelope procedure, 315, 315*e*, 315*t*, 316–320*f*, 773–774

enclosure, defined, 79

enclosure classification, wind loads, 270–271, 754–756

enclosure fire, 818

Energy Grade Line Analysis, tsunamis, 458–459, 459*t*, 461–462, 463*f*, 464*f*, 467, 469, 470–471

envelope procedure

- defined, 247
- see also* wind loads on buildings, MWFRS envelope procedure

epistemic uncertainty, defined, 466

equipment and equipment platforms, snow loads on, 64

equipment support, defined, 79

equivalent lateral force (ELF) procedure

- building structures, 101–104, 101*e*, 102*e*, 102*t*, 103*e*, 103*f*, 104*e*, 560–567, 560*f*, 561*f*, 562*f*, 564*f*, 565*e*, 565*f*, 566*e*, 567*e*
- damping systems, 184
- isolated structures, 172–175, 173*e*, 174*e*, 682–687, 683*f*, 684*f*, 685*t*, 686*t*, 687*f*
- soil-structure interaction, 198, 198*e*

erosion and scour, flood loads, 21, 440

escalators. *See* elevators and escalators

escarpments

- defined, 247
- topographic effects on wind speed, 266, 267*f*, 268, 268*e*

essential facilities, defined, 1

evacuation, tsunamis and, 48–50, 50*f*, 447–449, 458, 468–469, 472, 483, 484

expansion and contraction, serviceability considerations, 395, 803

exposure, wind load general requirements, 266, 741–744, 741*f*, 742*t*, 743*e*, 744*f*, 745*f*, 746*f*, 747*f*, 748*f*

exposure factor, snow loads, 52, 58*t*, 493–494

extraordinary events

- basic requirements, 4
- load combinations for, 9, 421–423, 422*e*

fall arrest and lifeline anchorage, live loads, 16, 436

fasteners, power-actuated, 125, 605

file cabinets, 433

fire, defined, 401

fire effects, performance-based design procedures for

- definitions, 401, 815–816
- general requirements, 401, 816
- performance objectives, 401–402, 816–817
- performance-based structural fire design, 815–816
- structural analysis of fire effects, 402, 819–821
- thermal analysis of fire effects, 402, 817–819

fire exposure, defined, 401

fire resistance

- basic requirements, 3, 410
- defined, 401

fixed ladders

- defined, 13
- live loads and, 16, 435

fixed service equipment, weight of, 11, 425

flat roof snow loads, 51, 51*e*, 53*e*, 54, 58*f*, 493–495

- defined, 51
- examples of establishing, 501–502, 501*e*, 502*e*

flexible building or structure, defined, 246, 732

flexible component, defined, 78

flexible connections, defined, 79

flexible diaphragm, defined, 246

flexure-controlled diaphragm, 530

- defined, 78

flood hazard area, defined, 21

flood hazard map, defined, 21

- flood insurance rate map (FIRM), defined, 21
- flood loads, 21–23, 22*e*, 22*t*, 23*e*, 23*f*, 439–445, 441*e*, 442*e*, 442*f*, 442*t*, 443*f*, 443*t*, 444*e*
  - definitions, 21, 439–440
- floods
  - load combinations for, 7, 8, 418, 421
  - performance-based procedures, 406
  - risk categorization of buildings, 5*t*
- floor responses, seismic design requirements, 123–124, 124*e*, 601–602, 602*f*
- floors and foundations, weight of, 12, 431
- force-controlled actions
  - defined, 78
  - global acceptance criteria, 165, 165*e*, 165*t*, 667–670, 667*e*, 668*f*, 668*t*, 669*f*
- force-controlled elements, defined, 181
- force-sustained action, defined, 27
- foundation geotechnical capacity, defined, 79
- foundation input motion, defined, 197
- foundation structural capacity, defined, 79
- foundations
  - building structures, 110–114, 111*t*, 112*t*, 113*t*, 587*f*, 588*f*
  - concrete, 136, 621
  - nonbuilding structures, 150
  - soil-structure interaction and damping effects, 199–201, 199*e*, 200*e*, 200*t*, 201*e*, 705–706, 706*f*
  - tsunami loads and effects, 46–49, 47*e*, 47*f*, 47*t*, 48*f*, 480–484, 481*e*, 481*f*, 482*e*, 482*f*, 483*f*
- frames
  - alternative structural design criteria, 114–119, 114*f*, 115*t*, 116*e*, 118*e*, 119*e*
  - drift of, serviceability considerations, 395, 802, 802*e*, 804–805*f*, 806–807*f*, 808–809*f*, 810–811*f*
  - types, defined, 79
- free roof, defined, 247
- freeboard, seismic design requirements, 153, 153*e*, 641
- free-field, use of term, 703
- free-field motion, defined, 197
- freezer building, defined, 51
- freezing rain
  - defined, 69, 518
  - design temperatures for, 70*f*, 71, 72–73*f*, 522
  - ice loads caused by, 70–71, 70*e*, 70*f*, 71*e*, 72–73*f*, 74*f*, 75*f*, 76*f*, 519–521, 520*f*, 521*t*
- friction clips, 125, 605, 605*f*
  - defined, 79
- Froude number, defined, 27
- fuel load
  - defined, 401
  - performance-based procedures for fire effects, 402, 818
- functionality requirements, performance-based procedures, 409–410
- gable/hip roofs
  - defined, 336*f*
  - snow loads, 57–58, 61*f*, 496–497
  - wind loads, components and cladding, 337*f*, 338*f*, 339*f*, 340*f*, 341*f*, 342*f*, 343*f*, 344*f*, 351–362*f*, 783*t*, 784*t*, 785*t*
  - wind loads, MWFRS directional procedure, 275–276*f*
- garage loads
  - passenger vehicles, 17, 18, 437
  - trucks and buses, 18
- gas spheres, seismic design, 160–161, 648
- geological hazards and geotechnical investigation, seismic design criteria, 86, 86*e*, 86*t*, 537–539, 537*e*
- glass, seismic design requirements, 126, 127*t*, 128, 128*e*, 607, 610–611
- glaze, defined, 69
- glazed curtain wall, defined, 79
- glazed openings, wind loads, 270–271
- glazed storefront, defined, 79
- glazing
  - definitions, 247, 755
  - tornado damage and, 763
- global acceptance criteria, nonlinear response history analysis
  - deformation-controlled actions, 166, 166*t*, 670–671, 670*t*
  - element-level acceptance criteria, 165, 667
  - elements of gravity force-resisting system, 166, 671
  - force-controlled actions, 165, 165*e*, 165*t*, 667–670, 667*e*, 668*f*, 668*t*, 669*f*
  - story drift, 165, 666–667
  - unacceptable response, 165, 664–666, 665*f*, 665*t*, 666*t*
- grab bar systems
  - defined, 13
  - live loads and, 16, 435
- grade plane, defined, 27, 79
- granular material storage tanks, seismic design requirements, 158–159, 647–648, 647*e*, 647*f*, 648*f*
- gross frontal area, defined, 743
- ground motions, nonlinear response history analysis
  - amplitude scaling, 164, 661–662, 661*f*
  - application to structural model, 164, 662
  - ground motion modification, 164, 660–661
  - ground motion selection, 164, 659–660
  - period range for scaling/matching, 164, 661
  - spectral matching, 164, 662
  - target response spectrum, 163–164, 658–659, 658*f*
- ground snow loads, 51, 52–53*f*, 55*t*, 56*t*, 57*t*, 58*t*, 489, 490–491*t*, 491–493, 492*t*, 493*t*
- ground-supported cantilever walls or fences, seismic design requirements, 641–642, 641*f*, 642*f*
- gust effects, wind loads, 269–270, 269*e*, 269*t*, 270*e*, 750–754, 751*e*, 751*t*, 752*e*, 752*f*, 752*t*, 753*e*, 754*e*, 755*t*
- guys and cables. *See* cables
- handrail and guardrail systems
  - defined, 13
  - live loads and, 13, 16, 435
- hazard-consistent tsunami scenario, defined, 27
- heat transfer
  - defined, 401
  - thermal analysis of fire effects, 402, 818–819
- heating, ventilating, air-conditioning, and refrigeration (HVACR)
  - defined, 79
  - seismic design requirements, 130
- helipad loads
  - helipad defined, 13
  - live loads, 18, 437–438
- high-deformability element, defined, 78
- hills
  - defined, 247
  - topographic effects on wind speed, 266, 267*f*, 268, 268*e*
- hip and gable roofs. *See* gable/hip roofs
- hoarfrost
  - defined, 69
  - formation of, 518
- hoists, 16, 435–436
- hurricane wind speeds, 735, 735*e*
- hurricane-prone areas

- basic wind speeds at selected, 736*t*, 737*t*, 738*t*, 739*t*  
defined, 247
- hydraulic structures, seismic design requirements, 153, 640, 640*f*
- hydrodynamic loads  
defined, 27  
during flooding, 22, 22*e*, 440–441, 441*e*  
tsunami loads and effects, 42–44, 42*e*, 42*t*, 43*e*, 473–477, 473*e*, 474*e*, 475*f*, 476*f*, 477*f*
- hydrostatic loads  
defined, 27  
during flooding, 21–22, 440  
tsunami loads and effects, 41–42, 41*e*, 42*e*, 473
- hydrostatic pressure, soil loads, 12, 425, 430–431*t*, 431
- ice dams and icicles, snow loads, 54, 494, 495, 496*f*
- ice loads  
load combinations for, 7, 8–9, 418–419, 421  
risk categorization of buildings, 5*t*  
*see also* atmospheric icing
- ice-sensitive structures, defined, 69, 518
- immediate occupancy structural performance level, defined, 27
- impact loads  
defined, 27  
flooding, 23, 441–444, 442*e*, 442*f*, 442*t*, 443*f*, 443*t*, 444*e*  
live loads, 16, 435–436  
tsunamis, 44–46, 44*e*, 44*t*, 45*f*, 46*e*, 46*t*, 477–480, 477*t*, 478*t*, 479*e*
- impact-protective system, 247, 755
- impact-resistant glazing, 247, 755
- importance factor  
defined, 1  
seismic design criteria, 85, 535, 535*f*  
snow loads and, 52, 493, 494–495
- in-cloud icing, defined, 69, 518–519, 519*f*
- inspection, special defined, 79
- inspector, special defined, 79
- internal pressure coefficients, wind loads, 271, 271*e*, 271*t*, 756
- inundation depth, defined, 27
- inundation depth and flow velocity, tsunamis  
analysis of design, 30–31, 30*e*, 458–461, 459*t*, 460*e*, 460*f*  
based on runup, 31–32, 31*e*, 31*f*, 32*t*, 461–462, 462*e*, 463*f*, 464*f*  
based on site-specific probabilistic hazard analysis, 32–38, 32*e*, 33*f*, 34*f*, 35*f*, 35*t*, 37*f*, 38*f*, 462, 465–467, 465*f*, 467*f*
- inundation elevation, defined, 27
- inundation limit, defined, 27
- inverted pendulum-type structures, defined, 79
- isolated structures. *See* seismically isolated structures, seismic design requirements
- isolation interface, defined, 167
- isolation system, defined, 167
- isolator unit, defined, 167
- joint, defined, 79
- kinematic soil-structure interactions, 201–202, 201*e*, 703, 704, 707–708, 707*f*  
defined, 197
- ladders, fixed, live loads, 435
- lateral forces, basic requirements, 4
- lateral pressures  
crane loads, 18  
soil loads, 12, 431
- leeward snowdrifts, 61, 497–498, 498*f*
- library stack rooms, live loads, 18, 433, 438
- life safety structural performance level, defined, 27
- lifeline anchorages. *See* fall arrest and lifeline anchorage
- light frame wall, defined, 81
- light frame wood shear wall, defined, 81
- light-frame construction, defined, 79
- limit deformation, defined, 78
- limit state, defined, 1
- limited-deformability element, defined, 78
- linear analysis  
damping systems, seismic design requirements, 699–700, 700*f*  
as precondition to nonlinear response history analysis, 163, 657
- linear dynamic analysis  
seismic design, building structures, 104–106, 105*e*, 567–571  
soil-structure interaction, 198
- liquefaction evaluation requirements, seismic design criteria, 538–539
- liquefaction scour, defined, 27
- liquefiable sites, seismic design requirements, 150, 637
- liquids, tanks and vessels for, 155–161, 155–156*e*, 156*t*, 157*e*, 157*t*, 160, 631*f*, 644–648, 647*f*, 648*f*, 649–652*f*, 653–654*f*
- live loads, 13–19, 14–16*t*, 433–439  
concentrated, 13, 16, 435  
crane loads, 17–18, 437  
definitions, 14–16*t*  
garage loads, 17, 18, 437  
handrail and guardrail systems, 13, 16, 435  
helipad loads, 18, 437–438  
impact loads, 16, 435–436  
library stack rooms, 18, 433, 438  
live load defined, 13  
roof load reduction, 17, 17*e*, 437  
seating for assembly use, 18–19, 438  
sidewalks, driveways, yards subject to trucking, 19  
solar panels, 19, 438  
stair treads, 19  
uniform load reduction, 16–17, 16*e*, 436–437, 436*f*  
uniformly distributed loads, 433–435, 434*t*  
uninhabitable attics, 18  
unspecified loads, 13
- “lives at risk,” 413
- load and resistance factor (LRFD), 417, 521, 587
- load combinations, 7–9, 417–423  
for allowable stress design, 8–9, 420–421, 421*t*  
for extraordinary events, 9, 421–423, 422*e*  
for strength design, 7–8, 417–420, 418*t*, 419*e*  
for structural integrity loads, 9
- load effects, defined, 1
- load factor, defined, 1
- load path connections, basic requirements, 4
- load tests, generally, 5, 415
- loads, defined, 1
- local coseismic tsunamis, defined, 27
- local scour, defined, 27
- longitudinal forces, crane loads, 18
- longitudinal reinforcement ratio, defined, 79
- long-period transition. *See* seismic ground motion, long period transition, and risk coefficient maps
- long-term deflection, serviceability considerations, 395, 803
- low-deformability element, defined, 78

- low-rise buildings
  - defined, 245
  - wind loads, components and cladding, 333–334, 334*e*, 335*f*, 337*f*, 338*f*, 339*f*, 340*f*, 341*f*, 342*f*, 343*f*, 344*f*, 345*f*, 346*f*, 347*f*, 348*f*, 349*f*, 350*f*, 786
  - wind loads, components and cladding, simplified, 334, 334*e*, 350*t*, 351–362*f*
  - see also* enclosed and partially enclosed low-rise buildings
- low-sloped roofs, snow loads and, 52–53, 495
- machinery, impact loads, 16
- main wind force resisting system (MWFRS)
  - buildings exempted from torsional wind load cases, 397–399, 398*f*, 399*f*
  - defined, 245, 247, 733
  - procedure to determine, 245
  - wind tunnel procedure, 793–794
- main wind force resisting system (MWFRS) directional
  - procedure, wind loads on building appurtenances and other structures, 321–333, 775–780
  - design wind loads, other structures, 322, 322*e*, 325*f*, 326*f*, 327, 328*f*, 329*f*, 330–331*f*, 331, 776–778, 777*f*
  - design wind loads, solid freestanding walls and solid signs, 322, 322*e*, 323–324*f*, 775–776
  - general requirements, 322
  - scope, 321, 321*t*
- main wind force resisting system (MWFRS), directional
  - procedure, wind loads on buildings, 273–310, 767–774
  - enclosed, partially enclosed, and open buildings of all heights, 273–274, 273*t*, 274*e*, 275–276*f*, 277*f*, 278*f*, 279*f*, 280*f*, 281*f*, 282*f*, 283*f*, 288–290*t*, 767–769, 768*f*, 773
  - enclosed simple diaphragm buildings with height <160 ft, 273, 284–285, 284*t*, 285*f*, 286*f*, 291–310*t*, 769–770
- main wind force resisting system (MWFRS), envelope
  - procedure, wind loads on buildings, 311–320, 767, 771–774
- main wind force resisting system (MWFRS), with pitched roofs, 773
  - enclosed and partially enclosed low-rise buildings, 311, 311*e*, 311*t*, 312–314*f*, 771–773, 772*f*, 773*f*
  - enclosed simple diaphragm low-rise buildings, 315, 315*e*, 315*t*, 316–320*f*, 773–774
  - scope, 311, 771
- mapped risk coefficient spectral response periods. *See* seismic ground motion, long period transition, and risk coefficient maps
- marquee, 433
- masonry
  - anchorage in, 143, 144, 150
  - seismic design and detailing requirements, 142–144, 628
- materials and constructions, weight of, 11, 425, 426–427*t*, 428–430*t*
- material-specific seismic design and detailing requirements, 135–144, 619–629
  - composite steel and concrete, 142, 627–628
  - concrete, 136–142, 137*e*, 138–139*e*, 139*f*, 141*f*, 142*f*, 620–627, 622*f*, 623*f*, 624*f*, 625*f*, 626*f*, 627*f*
  - masonry, 142–144, 628
  - steel, 135–136, 619–620
  - wood, 144, 628
- maximum considered earthquake, geometric mean peak ground acceleration, 41, 79, 206–207, 220–221*f*, 222–223*f*, 224–225*f*, 537, 714, 723
  - defined, 79
- maximum considered tsunami, defined, 27, 456
- maximum displacement, defined, 167
- mean recurrence intervals of load effects, wind tunnel procedure, 389, 794
- mean roof height, defined, 247
- means of egress, use of term, 593
- mechanical and electrical components, seismic design
  - nonbuilding structures, 146
  - nonstructural components, 129–134, 129*t*, 593, 596, 596*f*, 611–617, 613*f*, 614*f*
  - premanufactured, 121, 596, 596*f*
- mechanically anchored tanks or vessels, defined, 80
- minimum snow load, defined, 51
- modeling criteria, seismic design, 100–101
- moment frames
  - defined, 79
  - seismic design, 94–96
- momentum flux, defined, 27
- monoslope roofs, wind loads
  - components and cladding, 347*f*, 348*f*
  - MWFRS directional procedure, 274, 274*e*, 279*f*, 280*f*, 281*f*, 282*f*, 768
- Monte Carlo analysis, 407, 460–461, 469, 735
- multiple folded plate roofs, snow loads, 54, 495, 497
- multispan gable roofs, wind loads, components and cladding, 346*f*
- nearshore profile, defined, 27
- nearshore tsunami amplitude, defined, 27
- nominal loads, defined, 1
- nominal strength, defined, 1, 80
- nonbuilding critical facility structure, defined, 27
- nonbuilding structures
  - defined, 27, 80
  - wind loads, components and cladding, 382, 382*e*, 382*t*, 383*f*, 384–385*f*, 385, 386*f*, 387*t*, 788–789, 789*f*
  - see also* seismic design requirements, nonbuilding structures
- noncritical actions, defined, 79
- nonhurricane wind speeds, 734–735, 735*e*
- nonlinear response history analysis, 163–166, 657–671
  - damping systems, 186–187, 697–698, 697*t*
  - global acceptance criteria, 165–166, 165*e*, 165*t*, 166*t*, 664–671, 665*f*, 665*t*, 666*t*, 667*e*, 668*f*, 668*t*, 669*f*, 670*t*
  - ground motions, 163–164, 658–662, 658*f*, 661*f*
  - linear analysis, 163, 657
  - modeling and analysis, 164–165, 662–664, 664*f*
  - soil-structure interaction, 199
  - vertical response analysis, 163, 658
- nonspecified load combinations, 8, 419–420, 419*e*, 420*e*
- nonstructural components and systems
  - defined, 1, 27, 78
  - see also* seismic design requirements, nonstructural components
- occupancy, defined, 1
- occupant protections, tornadoes and, 756–759
- offshore tsunami amplitude, 30–32, 35–36, 449, 456, 458–460, 465, 465*f*, 466
  - defined, 28
- one- and two-story buildings, exempted from torsional load cases, 397
- one-way slabs, live loads, 17, 437
- open buildings
  - defined, 245
  - wind loads, components and cladding, 375, 375*e*, 376*f*, 377*f*, 378*f*, 788
- open structure, defined, 28

open-frame equipment structures, snow loads, 63–64, 63*f*, 64*f*, 501  
 openings, defined, 247  
 open-top tank, defined, 80  
 ordinary action, defined, 79  
 ordinary precast structural wall, defined, 136  
 orthogonal, defined, 80  
 other structures, defined, 1  
 out-of-plane bending, seismic design requirements, 126–127, 607  
 owner, defined, 80

parapets  
   snow load, 61, 61*f*, 498–500  
   wind loads, components and cladding, 364, 374*f*, 375, 375*e*, 379*f*, 379*t*, 788  
   wind loads, MWFRS directional procedure, 274, 274*e*, 284–285, 286*f*, 331–332, 769, 778–779, 779*f*  
   wind loads, MWFRS envelope procedure, 314, 314*e*

partial loading, 13, 435  
   atmospheric icing, 76, 522  
   snow loads, 54, 57, 61*f*, 495–496

partially enclosed building, defined, 245  
 partially open building, defined, 246

partitions  
   defined, 80  
   live loads and, 13, 435  
   seismic design requirements, 128, 610

passenger vehicles  
   garage loads, 437  
   live loads, 17

P-Delta effect, 104, 104*e*, 105, 150, 159, 165, 565–566, 569–570, 663  
   defined, 1, 80

peaks-over-thresholds (POT) model, 520, 735

performance-based procedures  
   defined, 1  
   earthquakes, 407–408  
   floods, 406  
   functionality requirements, 409–410  
   strength and stiffness requirements, 2, 405–409, 407*f*, 407*t*  
   *see also* fire effects, performance-based design procedures for

petrochemical tanks, seismic design requirements, 158, 646

piers and wharves, seismic design requirements, 152, 639–640

pile cap, defined, 80

pile scour, defined, 28

piles  
   composite steel and concrete structures, 142  
   concrete, 137–139, 137*e*, 138–139*e*, 621–622  
   defined, 80

pipe racks, seismic design requirements, 150, 150*e*, 638, 638*t*

pipes and cable trays, snow loads, 64, 64*f*

piping and tubing systems, 132, 614–615, 644

pitched roofs  
   wind loads, MWFRS directional procedure, 274, 274*e*, 279*f*, 280*f*, 281*f*, 282*f*, 768  
   wind loads, MWFRS envelope procedure, 314–315, 314*e*

plain concrete, defined, 78

plunging scour, defined, 28

ponding, defined, 51, 65

ponding instability and ponding load  
   defined, 51, 65  
   rain loads, 65, 512, 512*e*, 512*f*  
   snow loads, 62, 489, 501

pore pressure softening, defined, 28

power failures, risk categorization, 413

power-actuated fasteners, 125, 605

precast concrete diaphragm design options, defined, 136

precast structural walls, seismic design and detailing requirements, 136, 621

premanufactured mechanical and electric components  
   defined, 80  
   seismic design requirements, 121, 596, 596*f*

pressure model (PM), wind tunnel test, 793

primary drainage system, defined, 65

primary members, defined, 65

primary structural component, defined, 28

probabilistic seismic hazard analysis (PSHA), tsunami inundation depth and flow velocity based on, 32–38, 32*e*, 33*f*, 34*f*, 35*f*, 35*t*, 37*f*, 38*f*, 462, 465–467, 465*f*, 467*f*

projections and parapets. *See* parapets

quality assurance, seismic design criteria, 526

raceway, defined, 614

radiation damping  
   defined, 197  
   soil-structure interaction, 199–201, 199*e*, 200*e*, 200*t*, 201*e*, 705–706, 706*f*

rain loads, 65, 65*e*, 507–513  
   controlled drainage, 65, 512–513, 513*e*, 513*f*  
   design rain loads, 65, 507–511, 508*e*, 508*f*, 509*e*, 509*t*, 510*f*, 510*t*, 511*t*  
   ponding instability and ponding load, 65, 512, 512*e*, 512*f*  
   roof drainage, 65, 507

rain-on snow surcharge, 62, 500–501  
   examples of establishing, 502–504, 502*e*, 503*e*, 504*e*

reasonable probability, use of term, 410

recognized literature, defined, 28, 247

reference sea level, defined, 28

refrigerated gas liquid storage tanks and vessels, 160–161

regional climatic data, estimation of basic wind speeds from, 249, 740–741

registered design professional, defined, 80

reinforced concrete, defined, 78

relative sea level change, defined, 28

reliability analysis, 406–409, 422, 467

required live loads, 13

required strength, defined, 80

resistance factor, defined, 1

ridges  
   defined, 247  
   topographic effects on wind speed, 266, 267*f*, 268, 268*e*

rigid building or structure, defined, 246

rigid component, defined, 78

rigid diaphragm, defined, 246

rigid high-frequency base balance model (H-FBBM), wind tunnel test, 793

rigid pressure model (PM), wind tunnel test, 793

rime, defined, 69

rime ice, 519*f*

risk categorization, building classification and, 84, 412–414, 413*f*

risk category  
   defined, 1  
   *see also* wind hazard maps

risk-targeted maximum considered earthquake (MCER)  
   damping systems, 184–186  
   definitions, 79–80  
   ground motion hazard analysis, 205–206  
   ground motion parameters, 209, 210–211*f*, 212–213*f*, 214*f*, 215*f*, 216, 217*f*, 218*f*, 219*f*, 717–722, 719*t*, 720*t*, 721*t*, 722–723, 722*t*

- response spectrum, 85, 171–172
- seismic ground motion values, 84, 84*e*, 84*t*
- see also* seismic ground motion, long period transition, and risk coefficient maps
- Ronan point disaster, 411
- roof live loads
  - defined, 13
  - reduction in, 17, 17*e*, 437
  - solar panels and, 19
- roof overhangs
  - components and cladding, 364, 374*f*, 380*t*, 788
  - enclosed simple diaphragm buildings with Height <160 ft, MWFRS, 287*f*, 287*t*, 773
  - MWFRS directional procedure, 274, 275–276*f*, 285, 770
  - MWFRS envelope procedure, 312–314*f*, 314
- roofs
  - open buildings with monoslope, pitched, or troughed free, 274, 274*e*, 279*f*, 280*f*, 281*f*, 282*f*
  - pressures, 774
  - rain loads and drainage, 65, 507
  - snow loads, 54, 58–63, 59*e*, 60*f*, 62*f*, 63*f*, 495, 497–501, 498*f*, 499*f*, 501*f*
  - vegetative roofs, 11, 425, 434, 783
  - wind loads MWFRS directional procedure, 291–310*t*, 322, 322*e*, 776
  - see also* solar panels, rooftop; wall and roof surfaces
- rugged component, defined, 78
- runup elevation
  - defined, 28
  - inundation depth and flow velocity, tsunamis, 31–32, 31*e*, 31*f*, 32*t*, 461–462, 462*e*, 463*f*, 464*f*
- R-value
  - defined, 51
  - snow loads, 54
- Saffir-Simpson Hurricane Wind Scale, 735–736, 735*t*, 736*t*
- sawtooth roofs
  - snow loads, 54, 59, 495, 497
  - wind loads, 349*f*
- scragging, defined, 167
- screen enclosure, defined, 13
- scupper, defined, 65
- sea level, wind loads and ground elevation above, 268, 268*t*, 748, 748*e*
- seating for assembly use, live loads, 18–19, 438
- secondary drainage system, defined, 65
- secondary member, defined, 65
- secondary structural component, defined, 28
- seismic design category, 85–86, 85*t*, 535–537
  - category A, design requirements, 86, 537
  - defined, 80
- seismic design criteria, 77–87, 525–541
  - allowable stress standards, 525
  - alternative materials and methods, 77, 526
  - applicability, 77, 526
  - definitions, 77–81, 526–530, 527*f*, 528*f*, 529*f*
  - earthquake “loads” nature, 525
  - federal government construction, 525
  - geological hazards and investigation, 86, 86*e*, 86*t*, 537–539, 537*e*
  - importance factor and risk category, 85, 535, 535*f*
  - quality assurance, 77, 526
  - seismic design category, 80, 85–86, 85*t*, 535–537
  - seismic ground motion values, 83–85, 84*e*, 84*f*, 84*t*, 85*e*, 530–535, 531*f*, 532*e*, 532*f*, 533*f*, 534*f*, 539–540, 540*f*
  - vertical ground motion for, 87, 87*e*, 87*t*, 539–540, 540*f*
- seismic design requirements, building structures, 89–119, 543–591
  - analysis procedure selection, 100, 100*t*, 557–558, 558*t*
  - diaphragm flexibility, configuration, irregularities, redundancy, 95*t*, 96–98, 96*e*, 96*f*, 97*t*, 98*f*, 98*t*, 550–552, 552*f*, 553*f*, 554, 554*f*, 555*f*
  - diaphragms, chords, and collectors, 90–92*t*, 95*t*, 106–108, 106*e*, 106*f*, 107*e*, 107*f*, 108*t*, 571–579, 572*f*, 573*f*, 574*f*, 575*f*, 576*f*, 578*f*, 578*t*, 579*e*, 579*f*, 579*t*
  - direction of loading, 99–100, 557
  - drift and deformation, 109–110, 109*t*, 581–583
  - equivalent lateral force (ELF) procedure, 101–104, 101*e*, 102*e*, 102*t*, 103*e*, 103*f*, 104*e*, 560–567, 560*f*, 561*f*, 562*f*, 564*f*, 565*e*, 565*f*, 566*e*, 567*e*
  - foundation design, 110–114, 111*t*, 112*t*, 113*t*, 587*f*, 588*f*
  - linear dynamic analysis, 104–106, 105*e*, 567–571, 571*f*
  - modeling criteria, 100–101, 558–560, 559*f*
  - seismic load effects and combinations, 98–99, 98*e*, 99*e*, 555–556
  - simplified alternative criteria for simple bearing wall or frame system, 114–119, 114*f*, 115*t*, 116*e*, 118*e*, 119*e*, 588–589, 589*f*
  - structural design basis, 89, 543–546, 544*f*, 545*f*
  - structural system selection, 89–96, 90–92*t*, 95*t*, 546–550, 550*t*
  - structural walls and anchorages, 108–109, 108*e*, 580–581, 580*f*, 581*f*
- seismic design requirements, nonbuilding structures, 145–161, 631–656
  - analysis procedure selection, 145, 147*t*, 631–634, 632*f*, 633*f*, 634*f*, 635*f*
  - design, 145
  - design basis, 631
  - structural design requirements, 146–147, 147*e*, 148*t*, 149–150, 149*e*, 636–637
  - structures not similar to buildings, 152–153, 640–642, 640*f*, 641*f*, 642*f*
  - structures similar to buildings, 150–152, 638–640
  - supported by other structures, 146, 634–635
  - tanks and vessels, 153–161, 153–154*e*, 154*t*, 155*e*, 155*t*, 156*e*, 156*t*, 157*e*, 157*t*, 642–655, 642*e*, 643*e*, 644*f*, 647*f*, 648*f*, 649–652*f*, 653–654*f*
- seismic design requirements, nonstructural components, 121–134, 593–618, 594*f*
  - anchorages, 125, 603–605, 605*f*
  - applied to nonbuilding structures, 596
  - architectural components, 125–128, 126*e*, 126*t*, 127*t*, 128*e*, 593, 594*f*, 605–611, 608–609*t*, 611*f*
  - component importance factor, 121, 595
  - exemptions, 595–596
  - general design requirements, 122–123, 122*t*, 597–600
  - mechanical and electrical components, 129–134, 129*t*, 593, 596, 596*f*, 611–617, 613*f*, 614*f*
  - seismic demands and, 123–125, 123*e*, 124*e*, 124*f*, 600–603, 600*f*, 601*f*, 602*f*, 603*f*
- seismic force-resisting system, defined, 80
- seismic forces, defined, 80
- seismic ground motion, long period transition, and risk coefficient maps, 209–236, 717–724, 719*t*, 720*t*, 721*t*, 722–723, 722*t*
- Alaska, 214*f*, 215*f*, 222*f*, 227*f*, 232*f*, 235*f*
- American Samoa, 209, 219*f*, 231*f*, 234*f*
- conterminous US, 210–211*f*, 212–213*f*, 220–221*f*, 225–226*f*, 230*f*, 233*f*



ground motion web tool, 724  
 Guam and Northern Mariana Islands, 209, 218*f*, 224*f*, 231*f*, 234*f*  
 Hawaii, 216*f*, 222*f*, 228*f*, 232*f*, 235*f*  
 Puerto Rico and US Virgin Islands, 217*f*, 223*f*, 229*f*, 232*f*, 235*f*  
 updates, 723  
 seismic ground motion values, 83–85, 84*e*, 84*t*, 85*e*, 530–535, 531*f*, 532*e*, 532*f*, 533*f*, 534*f*, 539–540, 540*f*  
 seismic load effects and combinations, 8, 9, 98–99, 98*e*, 99*e*, 420  
 seismic loading, buildings controlled by, 397  
 seismic loading direction, 99–100  
 seismically isolated structures, seismic design requirements, 167–179, 673–692, 673*f*  
     analysis procedure selection, 172, 682  
     design review, 176, 689  
     dynamic analysis procedures, 175–176, 176*e*, 687–689, 688*t*  
     equivalent lateral force (ELF) procedure, 172–175, 173*e*, 174*e*, 682–687, 683*f*, 684*f*, 685*t*, 686*t*, 687*f*  
     general design requirements, 168–171, 170–171*e*, 674–682, 674*t*, 677*e*, 677*f*, 677*t*, 678*f*, 678*t*, 680*t*, 681*f*  
     seismic ground motion criteria, 171–172, 682  
     testing, 176–179, 178*e*, 178*f*, 689–692  
 self-anchored tanks or vessels, defined, 80  
 self-straining forces and effects  
     basic requirements, 3, 410  
     load combinations for, 7–8, 9, 419, 421  
 service loads, defined, 1–2  
 serviceability considerations  
     camber, 395, 811  
     deflection, vibration, and drift, 395, 801–803, 804–805*f*, 806–807*f*, 808–809*f*, 810–811*f*  
     performance-based procedures, 409  
 serviceability design, wind speeds for, 740, 740*e*, 740*t*  
 shear keys, material-specific seismic design and detailing requirements, 144  
 shear panel, defined, 80  
 shear wall-frame interactive system, defined, 79  
 shear walls (concrete), seismic design and detailing requirements, 136–137, 621  
 shear-controlled diaphragm, defined, 78, 530  
 shielding, 273, 311, 321, 333, 732  
 shipping, tsunami debris impact and, 478–479  
 shoaling, defined, 28  
 short hangers, bracing exemptions for, 596  
 sidewalks, driveways, and yards subject to trucking, live loads, 19  
 signs, wind loads and  
     solid attached, 322, 776  
     solid freestanding, 322, 322*e*, 324–325*f*, 775  
 silos  
     components and cladding, 382, 382*e*, 382*t*, 383*f*, 384–385*f*, 385, 788–789, 789*f*  
     MWFRS directional procedure, 322, 326*f*, 327, 328*f*, 329*f*, 776, 776–777  
 simple diaphragm building, defined, 246  
 site class, defined, 80  
 site classification procedure  
     definitions, 203, 709–710  
     generally, 203, 204*t*, 709  
     parameters, 204, 204*e*, 710  
 site-specific ground motion procedures, for seismic design, 205–207, 711–715  
     design acceleration parameters, 206, 713–714  
     design response spectrum, 206, 206*e*, 713  
     maximum considered earthquake, geometric mean peak ground acceleration, 206–207, 714  
     maximum considered earthquake, ground motion hazard analysis, 205–206, 206*f*, 712–713  
     site response analysis, 205, 711–712  
 site-specific probabilistic hazard analysis, tsunami inundation depth and flow velocity, 32–38, 32*e*, 33*f*, 34*f*, 35*f*, 35*t*, 37*f*, 38*f*, 462, 465–467, 465*f*  
 sliding snow, 61–62, 500, 500*f*, 502, 502*e*  
 slippery surface, defined, 51  
 sloped roofs, snow loads, 51, 54, 54*e*, 58*f*, 59*f*, 60*f*, 495, 502, 502*e*  
 snow, defined, 69  
 snow loads, 51–76, 489–505  
     caused by freezing rain, 519, 519*f*  
     definitions, 51  
     drifts on lower roofs (aerodynamic shade), 59–61, 59*e*, 62*f*, 63*f*, 497–498, 498*f*, 499*f*  
     on equipment and equipment platforms, 64  
     examples of establishing, 501–504, 501*e*, 502*e*, 502*f*, 503*e*, 503*f*, 504*e*  
     in excess of design value, 489  
     on existing roofs, 62–63, 501, 501*f*  
     on flat roofs, 51, 51*e*, 53*e*, 54, 58*t*, 493–495  
     on ground, 51, 52–53*f*, 55*t*, 56*t*, 57*t*, 58*t*, 489, 490–491*t*, 491–493, 492*t*, 493*t*  
     on open-frame equipment structures, 63–64, 63*f*, 64*f*  
     partial loading, 54, 57, 61*f*, 495–496  
     ponding instability and, 62, 501  
     on projections and parapets, 61, 61*f*, 498–500  
     rain-on snow surcharge, 62, 500–501  
     sliding snow, 61–62, 500, 500*f*, 502, 502*e*  
     on sloped roofs, 51, 54, 54*e*, 58*f*, 59*f*, 60*f*, 495, 502, 502*e*  
     unbalanced loads, 57–59, 61*f*, 496–497  
 soil damping, defined, 197  
 soil hysteretic damping, 199–201, 199*e*, 200*e*, 200*t*, 201*e*  
     soil-structure interaction, 705–706  
 soil loads, 11*t*, 12  
 soil loads and hydrostatic pressure, 425, 430–431*t*, 431  
 soil-structure interaction (SSI), 197–202, 703–708  
     ELF procedure, 198, 198*e*  
     foundation damping effects, 199–201, 199*e*, 200*e*, 200*t*, 201*e*, 705–706, 706*f*  
     kinematic SSI effects, 201–202, 201*e*, 703, 704, 707–708, 707*f*  
     SSI adjusted structural demands, 198–199, 198*e*, 704–705  
 solar array, defined, 247  
 solar panels, rooftop  
     defined, 247  
     live loads, 19, 438  
     MWFRS directional procedure, 327, 327*e*, 330–331, 330–331*f*, 331*f*, 777–778, 777*f*  
     seismic design requirements, 133–134, 133*e*, 595, 616–617 for slopes < 7 degrees, 389–390, 794–795  
     weight of, 12, 425  
     wind loads, components and cladding, 385  
 soliton fission, 36, 462  
     defined, 28  
 space frame system, defined, 79  
 special flood hazard area, defined, 21  
 special inspections, defined, 79  
 special wind regions, 249, 740  
 sprinkler systems, seismic design requirements, 132–133, 616  
 stairs and ramps  
     live loads, 19  
     seismic design requirements, 128, 611, 611*f*  
 standard fire resistance design, defined, 401, 815  
 steel

- cables, 136, 620
- chimneys and stacks, 152, 640
- composite steel and concrete structures, 142, 627–628
- seismic design and detailing requirements, 135–136, 619–620
- storage racks, 150–151, 638–639, 638*f*
- tubular support structures, for wind turbines, 153, 641
- stepped roofs, wind loads, components and cladding, 345*f*
- stiffness. *See* strength and stiffness requirements
- storage racks
  - defined, 80
  - seismic design requirements, 150–151, 638–639, 638*f*
- story, defined, 80
- story above grade plane, defined, 80, 530, 530*f*
- story drift, defined, 80
- story drift ratio, defined, 80
- story shear, defined, 80
- strength, types defined, 80
- strength and stiffness requirements, 2–3, 2*t*, 3*t*, 405
  - performance-based procedures, 2, 405–409, 407*f*, 407*t*
- strength design
  - defined, 2
  - load combinations for, 7–8, 417–420, 418*t*, 419*e*
  - procedures, 405
- structural analysis, of fire effects, 402, 819–821
- structural component, defined, 28
- structural damping, gust effects, 753
- structural design fire, 402, 818
  - defined, 401
- structural design procedures, tsunami loads and effects, 38–41, 38*e*, 39*f*, 39*t*, 40*e*, 41*t*, 467–473, 468*t*, 470*f*, 471*f*, 472*f*
- structural height, defined, 80
- structural integrity requirements, 3–4, 410–412
  - accidents, misuse, sabotage and, 410
  - collapse and, 410–411
  - design alternatives, 411
  - guidelines for, 411–412
  - load combinations for, 9
  - performance objectives, fire effects, 401, 817
- structural observations, defined, 80
- structural systems
  - defined, 79
  - seismic design requirements, 89–96, 90–92*t*, 95*t*
- structural wall, defined, 28, 81
- structure, defined, 80
- subdiaphragm, defined, 80
- supports, defined, 80, 526–527, 527*f*
- surface roughness, 58*t*, 266, 268, 493, 741–744, 741*f*, 745*f*
- surge, defined, 28
- susceptible bay, defined, 65
- sustained flow scour, defined, 28
- tall buildings, aerodynamic wind loads on, 754
- tanks
  - with height <120*ft*, wind loads, components and cladding, 382, 382*e*, 382*t*, 383*f*
  - wind loads, MWFRS directional procedure, 322, 326*f*, 327, 327*e*, 328*f*, 329*f*, 776, 776–777
- tanks and vessels, seismic design requirements, 151–152, 153, 639, 639*f*, 642
  - anchorage, 644, 644*f*
  - boilers and pressure vessels, 648
  - design basis, 153–154, 153–154*e*, 642–643, 642*e*, 643*e*
  - elevated, for liquids and granular materials, 631*f*, 647–648, 647*f*, 648*f*
  - flexibility of piping attachment, 154–155, 155*e*, 155*t*, 644
  - ground-supported tanks for granular materials, 158–159, 647, 647*e*
  - ground-supported tanks for liquids, 155–156*e*, 155–157, 156*t*, 157*e*, 157*t*, 644–646
  - horizontal, saddle-supported vessels for liquid and vapor, 648, 655
  - petrochemical tanks, 158, 646
  - strength and ductility, 154, 643–644
  - structural towers for, 151–152
  - water storage and treatment tanks, 158, 646
- telecommunication towers
  - seismic design requirements, 153, 641
  - tornadoes and, 763–764
- telecommunications failures, risk categorization, 413
- temporary facilities, defined, 2
- testing agency, defined, 81
- thermal analysis, of fire effects, 402, 817–819
- thermal boundary condition, defined, 401
- thermal factor, snow loads, 52, 54, 58*t*, 63, 494
- thermal insulation, defined, 401
- thermal response, defined, 401
- thermal restraint, defined, 401
- topographic effects, wind loads general requirements, 266, 267*f*, 268, 268*e*, 744–748
- topographic transect, defined, 28
- tornado limitation, wind loads general requirements, 270, 271, 756–764, 757*t*, 758*f*, 759*f*, 759*t*, 760*e*, 761*t*, 762*t*, 763*t*, 764*t*
- torsional wind load cases, buildings exempted from, 397–399, 398*f*, 399*f*, 804*f*, 816
- torsionally regular building under wind load, defined, 246
- total maximum displacement, defined, 167
- toxic, highly toxic, and explosive substances, building classification and, 5, 414–415
- toxic substances, defined, 2
- transfer forces, diaphragm, defined, 78, 530
- traveling fire, 818
- troughed free roofs, wind loads MWFRS directional procedure, 274, 274*e*, 279*f*, 280*f*, 281*f*, 282*f*
- truck and bus garages, live loads, 18
- trussed communication towers, tornadoes and, 763–764
- tsunami, defined, 28
- tsunami amplitude, defined, 28
- tsunami bore, defined, 28
- tsunami bore height, defined, 28
- tsunami breakaway wall, defined, 28
- tsunami design zone, defined, 28
- tsunami design zone map, defined, 28
- tsunami evacuation map, defined, 28
- tsunami loads and effects, 25–50, 447–488
  - debris impact loads, 44–46, 44*e*, 44*t*, 45*f*, 46*e*, 46*t*, 477–480, 477*t*, 478*t*, 479*e*
  - definitions, 25–29, 456
  - foundation design, 46–49, 47*e*, 47*f*, 47*t*, 48*f*, 480–484, 481*e*, 481*f*, 482*e*, 482*f*, 483*f*
  - hydrodynamic loads, 42–44, 42*e*, 42*t*, 43*e*, 473–477, 473*e*, 474*e*, 475*f*, 476*f*, 477*f*
  - hydrostatic loads, 41–42, 41*e*, 42*e*, 473
  - inundation depth and flow velocity, analysis of design, 30–31, 30*e*, 458–461, 459*t*, 460*e*, 460*f*
  - inundation depth and flow velocity, based on runup, 31–32, 31*e*, 31*f*, 32*t*, 461–462, 462*e*, 463*f*, 464*f*
  - inundation depth and flow velocity, based on site-specific probabilistic hazard analysis, 31*e*, 32–38, 32*e*, 33*f*, 34*f*, 35*f*, 35*t*, 37*f*, 38*f*, 462, 465–467, 465*f*

- nonstructural components and systems, 50, 485
- risk categories, 30, 457–458
- scope and exceptions, 25, 26*f*, 27*f*, 28*f*, 447–449, 456, 457*f*
- structural countermeasures for, 49, 484
- structural design procedures for, 28, 38–41, 38*e*, 39*f*, 39*t*, 40*e*, 41*t*, 467–473, 468*t*, 470*f*, 471*f*, 472*f*
- vertical evacuation refuge strategies and structures, 49, 49*f*, 449, 458, 468, 469, 472, 484–485
- Western state hazard exposure, 448*t*, 449*f*, 450*f*, 451*f*, 452*f*, 453*f*, 454*f*, 455*f*, 484–485
- tsunami risk category, defined, 28
- tsunami-prone region, defined, 28
- tubular support structures, wind turbines, 641
- ultimate deformation, defined, 78
- unbalanced roof loads, 57–59, 61*f*, 496–497, 502, 502*e*
- uniform live loads, reduction in, 16–17, 16*e*, 436–437, 436*f*
- uniformly distributed loads, 13, 433–435, 434*t*
- utility lines, seismic design requirements, 133, 616
- vegetative and landscaped roofs, 11, 425, 434, 738
- vehicle barrier systems
  - defined, 13
  - live loads and, 16, 435
- velocity pressure, wind loads general requirements, 268–269, 268*e*, 268*t*, 748–750, 748*e*, 749*e*, 749*f*, 750*e*, 750*f*, 750*t*
- velocity-dependent damping device, defined, 181
- veneers, defined, 81
- ventilated roof, defined, 51
- vertical deflections, serviceability considerations, 208*f*, 395, 801–802
- vertical evacuation refuge strategies, tsunamis and, 49, 49*f*
- vertical front area, defined, 743
- vertical ground motions, 87, 87*e*, 87*t*, 145–146, 539–540, 540*f*, 634
- vertical response analysis, 163, 658
- vertical response spectrum, seismic design criteria, 86
- vibrations, serviceability considerations, 395, 802–803, 803*e*
- wall and roof surfaces, wind loads MWFRS directional procedure, 284, 769
- walls
  - cantilevered ground-supported, 153
  - components and cladding, wind loads, 335*f*
  - drift of, serviceability considerations, 395, 802, 802*e*, 804–805*f*, 806–807*f*, 808–809*f*, 810–811*f*
  - solid freestanding, wind loads, 322, 322*e*, 324–325*f*, 775
  - types defined, 81
  - wave loads on vertical, 441, 442*t*
  - wind loads MWFRS directional procedure, 287*f*, 291–292*t*  
*see also* bearing walls; wall and roof surfaces
- warm roof slope factor, snow loads and, 54
- water storage and treatment tanks, seismic design requirements, 158, 646
- water-and sewage-treatment facilities, failure of, 413
- wave loads, during flooding, 22–23, 22*e*, 22*t*, 23*e*, 23*f*, 441, 442*t*
- wheel loads, cranes and, 17–18
- wind, generally
  - on ice-covered structures, 71, 72–73*f*, 74*f*, 75*f*, 521–522, 522*t*
  - load combinations for, 420–421
  - risk categorization of buildings, 5*t*
- wind directionality
  - wind loads, general requirements, 266, 266*t*, 741
  - wind tunnel procedure, 389, 794
  - wind hazard maps, 740
  - basic wind speed, 249, 734
  - component and cladding ratings for building envelope products, 740
  - design wind speeds ASCE 7-93 to 7-10, 740*t*
  - estimation of basic wind speeds from regional climatic data, 249, 740–741
  - hurricane wind speeds, 735, 735*e*
  - nonhurricane wind speeds, 734–735, 735*e*
  - return periods, 734
  - Risk Category I, basic wind speeds, 250–251*f*, 258–259*f*
  - Risk Category II, basic wind speeds, 252–253*f*, 260–261*f*, 737*t*
  - Risk Category III, basic wind speeds, 254–255*f*, 262–263*f*, 738*t*
  - Risk Category IV, basic wind speeds, 256–257*f*, 264–265*f*, 739*t*
  - Saffir-Simpson Hurricane Wind Scale, 735–736, 735*t*, 736*t*, 740
  - special wind regions, 249, 740
  - wind speeds, for serviceability design, 740, 740*e*, 740*t*
  - wind speeds, selected coastal locations, 736*t*
- wind loads, components and cladding, 245, 333–387, 781–791
  - building appurtenances and rooftop structures and equipment, 375–382, 375*e*, 379*f*, 379*t*, 380*e*, 380*f*, 380*t*, 381*f*, 382*t*
  - building types, 783–786, 783*t*, 784*t*, 785*t*, 786*f*, 787*f*
  - buildings with height <60*ft*, 364, 364*e*, 364*t*, 365–373*t*, 375, 783*t*, 787–788
  - buildings with height >60*ft*, 350, 350*e*, 362–363*t*, 363, 786–787
  - low-rise buildings, 333–334, 334*e*, 335*f*, 337*f*, 338*f*, 339*f*, 340*f*, 341*f*, 342*f*, 343*f*, 344*f*, 345*f*, 346*f*, 347*f*, 348*f*, 349*f*, 350*f*, 786
  - low-rise buildings, simplified, 334, 334*e*, 350*t*, 351–362*f*, 787–788
  - nonbuilding structures, 382, 382*e*, 382*t*, 383*f*, 384–385*f*, 385, 386*f*, 387*f*, 788–789, 789*f*
  - open buildings, 375, 375*e*, 376*f*, 377*f*, 378*f*, 788
  - rooftop solar panels, 385
  - rooftop structures and, 380
- wind loads, general requirements, 245–271, 731–766
  - alternate procedure to calculate, 753
  - critical load condition, 249
  - definitions, 245–247, 732–733
  - enclosure classification, 270–271, 754–756
  - exposure, 266, 741–744, 741*f*, 742*t*, 743*e*, 744*f*, 745*f*, 746*f*, 747*f*, 748*f*
  - ground elevation above sea level, 268, 268*t*, 748, 748*e*
  - gust effects, 269–270, 269*e*, 269*t*, 270*e*, 750–754, 751*e*, 751*t*, 752*e*, 752*f*, 752*t*, 753*e*, 754*e*, 755*t*
  - internal pressure coefficients, 271, 271*e*, 271*t*, 756
  - limitations, 731–732
  - procedures, 245, 246*f*, 731
  - sign convention, 249
  - topographic effects, 266, 267*f*, 268, 268*e*, 744–748
  - tornado limitation, 271, 756–764, 757*t*, 758*f*, 759*f*, 759*t*, 760*e*, 761*t*, 762*t*, 763*t*, 764*t*
  - velocity pressure, 268–269, 268*e*, 268*t*, 748–750, 748*e*, 749*e*, 749*f*, 750*e*, 750*f*, 750*t*
  - wind directionality, 266, 266*t*, 741
  - wind pressures acting on opposite faces of each building surface, 249, 734
  - see also* wind hazard maps

- wind loads on building appurtenances and other structures,
  - MWFRS directional procedure, 321–333, 775–780
  - design wind loads, other structures, 322, 322*e*, 325*f*, 326*f*, 327, 328*f*, 329*f*, 330–331*f*, 331, 776–778, 777*f*
  - design wind loads, solid freestanding walls and solid signs, 322, 322*e*, 323–324*f*, 775–776
- wind loads on buildings, MWFRS directional procedure, 273–310, 767–774
  - enclosed, partially enclosed, and open buildings of all heights, 273–274, 273*t*, 274*e*, 275–276*f*, 277*f*, 278*f*, 279*f*, 280*f*, 281*f*, 282*f*, 283*f*, 767–769, 768*f*
  - enclosed simple diaphragm buildings with height <160 ft, 273, 284–285, 284*t*, 285*f*, 286*f*, 291–310*t*, 769–770
- wind loads on buildings, MWFRS envelope procedure, 311–320, 767, 771–774
  - enclosed and partially enclosed low-rise buildings, 311, 311*e*, 311*t*, 312–314*f*, 771–773, 772*f*, 773*f*
  - enclosed simple diaphragm low-rise buildings, 315, 315*e*, 315*t*, 316–320*f*, 773–774
- wind pressure calculations, tornadoes, 760–763, 760*e*, 761*e*, 762*t*, 763*t*
- wind tunnel procedure, 389–390, 781, 793–795
  - defined, 247
  - design data and, 793–794
  - dynamic response, 389
  - load effects, 389, 794
  - minimum reductions permitted, 793–794
  - roof-mounted solar collectors for slopes <7 degrees, 389–390, 794–795
  - test conditions, 389
  - test types, 793
  - wind-borne debris, 389
- wind turbine generators, seismic design requirements, 153, 641
- wind-borne debris
  - enclosure classification, 755–756
  - wind tunnel procedure, 389
- wind-borne debris regions, 270, 733, 755
  - defined, 247, 733
- wind-restraint system, defined, 167
- windstorms, tornadoes versus, 757–758, 759*f*
- windward snow drifts, 61, 497–498, 498*f*
- wood, seismic design and detailing requirements, 144, 628
- wood structure panel, defined, 81