

An urban corridor that gives AI a green light

Autonomous delivery, low-speed shuttles, inspection and guide robots, mobile clinics, mobile classrooms, rehabilitation aids — all stuck at one bottleneck: no street is willing, or ready, to let them out. This proposal turns the 9.72 km continuous green corridor of the Jing-Zhang Heritage Park into an urban channel where AI scenarios can take to the street legally, slowly, under supervision and with a way out, assembling the seven sets of facilities and rules that street entry requires.

Design area	Trunk length	Grade A	Grade B	Grade C	Bottleneck	Green ratio	300 m coverage
11.41 sq km	9.72 km	5.30 km	3.31 km	1.11 km	11.4%	24.7%	56.0%

GREEN LIGHT — An Urban Corridor That Gives AI Scenarios a Green Light

GREEN LIGHT — An Urban Corridor That Gives AI Scenarios a Green Light

GREEN LIGHT — An Urban Corridor That Gives AI Scenarios a Green Light

GREEN-LIGHT — An Urban Corridor That Gives AI Scenarios a Green Light

The core move: grade the trunk into A/B/C right-of-way by cross-section

5.30 km of Grade A with full-time physical separation; 3.31 km of Grade B demoted to the edge at peak, 1.11 km of Grade C barred at peak and rerouted. Grade A is 54.5% of the trunk, so more than half needs no time-slicing rule at all. The grading rests on inferred widths; what the proposal asserts is the method, to be recomputed once survey data arrives.

Five layers of coexistence: time slicing is only the fourth

Physical separation (separate wherever width allows) → speed and size (harm scales with speed squared) → the yielding covenant (vehicles always yield and must visibly signal awareness; predictability over avoidance rate) → time slicing (Grade B and C at peak only) → fail-safe and exit (auto-clear above thresholds, a stop button anyone can press, attributable events, rollback on failure). It does not promise zero conflict; it promises conflicts can be detected, attributed and exited from.

Three landmarks, three kinds of invisibility

Point Zero makes results visible including failures, the Right-of-Way Clock makes rules visible, the Service Ring makes facilities and labour visible — trust, governance and respect. All make functional facilities visible rather than building scenery.

Phasing as a risk-graded opening sequence

Phase 1 closed pilot 257.3 ha at Xiaoyuehe, Phase 2 guided 271.3 ha at Origin Station with marshals, Phase 3 open 612.8 ha across the north and south segments. Each carries quantified gates and rollback conditions; Phase 1 avoids the densest segment deliberately.

A shortcoming reported on our own initiative

Tr-to-door points within 300 m cover only 56.0% of residential land. The 81.7% at 500 m looks better, but the corridor is only about 1.3 km wide so that measure approaches saturation. Points must be densified outward per the 300 m gap. The proposal keeps the shortcoming and states its basis rather than covering it with a more flattering measure.

GREEN LIGHT — An Urban Corridor That Gives AI Scenarios a Green Light

Computed From Geometry		Opening Data	
Each curve is formula, source file and a confidence level, independently recomputable for the geometry		Each curve is formula, source file and a confidence level, independently recomputable for the geometry	
Design area	114.13 sq.km	5	FAS test
Partition area	114.13 sq.km	5	Building height limit
Frank length	97.22 km	5	Building coverage ratio limit
Grid A length	5.26 km	5	Setback requirement
Grid B length	3.31 km	5	Setback requirement
Grid C length	1.11 km	5	The FAS and building coverage ratio reported are the computed values for the FAS test, based on the building coverage ratio limit and the setback requirement. The building coverage ratio limit is the building coverage ratio limit for the building coverage ratio limit.
Barren share	11.4%	5	
Urban share	24.7%	5	
Public space share	2.2%	5	
Road land share	12.5%	5	
Building coverage ratio (scheme estimate)	19.5%	5	
FAS (scheme estimate)	1.26	5	
Total floor area (estimate)	14.42 M sq.m	5	
Traffic points	30	5	
Coverage of housing, 300 m	56.0%	5	
Coverage of housing, 500 m	81.7%	5	
Mean station spacing	3.89 km	5	
Key areas total	369.3 ha	5	
Phase 1 closed plot	257.3 ha	5	
Phase 2 graded	271.3 ha	5	
Phase 3 open	612.8 ha	5	
		Local residential status	
		Land use classification	No gaps, no overlaps
		Metabolic scheme	Valid
		Area self-proof	Partition total - site area

04 Evidence chain: from geometry to prose, recomputable at every step



Every spatial suggestion is a conceptual proposal, a reference scheme, or material for professional teams to develop further. None of it replaces formal planning or constitutes an approved conclusion, statutory approval, investment commitment, feasibility conclusion or parcel-level verdict. All geometry derives from the provisional rough boundary registered in the site package, about 0.11% from the announced area, and cannot serve as a statutory redline or precise-area basis; official FAR, height, density, green ratio and setback controls are all recorded as missing and are not assumed. Safety thresholds are advisory, pending professional review. The final judgement rests with people and professional teams.