CMF





Chip NTC Thermistors

CMF




Application

- Temperature compensation of IC, LCD
- Transistor
- Crystal oscillator of mobile communications equipments
- Temperature sensor for rechargeable batteries
- Temperature sensor for CPU
- Temperature compensation of several kinds of circuits

Characteristics

- Miniature size
- No lead
- Ideal for high density SMT installation
- Superior solderability and resistance to soldering heat
- · Ideal for wave or reflow soldering

Dimensions (mm)



Size	L	W	T	M
	(Length)	(Width)	(Thickness)	(Width of termination Point)
0402	.04± .006	.02± .004	.024 max	0.004 min
(1005)	(1.0± 0.15)	(0.5± 0.10)	(0.60 max)	(0.10 min)
0603	.063± .006	.031± .006	.037 max	.004 max
(1608)	(1.6± 0.15)	(0.8± 0.15)	(0.95 max)	(0.10 max)
0805	.08± .008	.05± .008	.05 max	.006 max
(2012)	(2.0± 0.20)	(1.25± 0.2)	(1.25 max)	(0.15 max)
1206	.126± .008	.063± .008	.063 max	.008 max
(3216)	(3.2± 0.20)	(1.6± 0.20)	(1.6 max)	(0.20 max)

CMF	Е	3	39)Z	10	03	,	J	1	N	7	Г
Chip NTC thermistor	Size	Code	B-va (25/8	alue 85°C)		stance °C (Ω)	Toler	ance	Termi	nation	Pack	aging
	Code	Inches	Z	00	103	10x10 ³	F	±1%	Р	Pd	В	Bulk
	С	1206	F	50	104	10x10 ⁴	G	±2%	N	Nickel Barrier	Т	Tape & Reel
	В	0805	G	35			Н	±3%				
	Α	0603	Н	70			J	±4%				
	Х	0402					K	±10%				

0402 Series					
Part No.	Resistance at 25°C (KΩ)	B-Constant (25/85°C (K)			
CMFX39F103_	10	3950			
CMFX40F473_	47	4050			
CMFX40F104_	100	4050			

0603 Series					
Part No.	Resistance at 25°C (KΩ)	B-Constant (25/85°C (K)			
CMFA39F103_	10	3435			
CMFA39H103_	10	3970			
CMFA39Z223_	22	3900			
CMFA39F473_	47	3950			
CMFA39F104_	100	3950			
CMFA39F224_	220	3950			
CMFA35F103_	10	3550			
CMFA39F683_	68	3950			
CMFA41Z564_	560	4100			

0805 Series					
Part No.	Resistance at 25°C (KΩ)	B-Constant (25/85°C (K)			
CMFB34G472_	4.7	3435			
CMFB34G103_	10	3435			
CMFB35F103_	10	3550			
CMFB39Z223_	22	3900			
CMFB40Z473_	47	4000			
CMFB40Z104_	100	4000			
CMFB39H103_	10	3970			
CMFB32Z202_	2	3200			
CMFB36F153_	15	3650			
CMFB40F333_	33	4050			

1206 Series						
Part No.	Resistance at 25°C (KΩ)	B-Constant (25/85°C (K)				
CMFC21Z221_	0.22	3200				
CMFC32Z331_	0.33	3200				
CMFC32F471_	0.47	3250				
CMFC33F102_	1.0	3350				
CMFC34Z222_	2.2	3400				
CMFC34Z332_	3.3	3400				
CMFC34Z472_	4.7	3400				
CMFC34Z682_	6.8	3400				
CMFC35Z103_	10	3500				
CMFC39Z103_	10	3900				
CMFC39Z153_	15	3900				
CMFC39F223_	22	3950				
CMFC40Z333_	33	4000				
CMFC41Z473_	47	4100				
CMFC41Z683_	68	4100				
CMFC42Z104_	100	4200				
CMFC43Z224_	220	4300				



8415 Mountain Sights Avenue • Montreal (Quebec), H4P 2B8, Canada **Tel:** (514) 739-3274 • 1-800-561-7207 • **Fax:** (514) 739-2902 • **E-mail:** sales@cantherm.com