

62 mm C-Series module with CoolSiC™ Trench MOSFET

Features

- Electrical features
 - $V_{DS} = 2000\text{ V}$
 - $I_{DN} = 400\text{ A}$ / $I_{DRM} = 800\text{ A}$
 - Low switching losses
 - High current density
- Mechanical features
 - 4 kV AC 1 min insulation

Potential applications

- UPS systems
- DC/DC converter
- High-frequency switching application
- Solar applications

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

Description




Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	MOSFET, T1 / T2	3
3	Body diode (MOSFET, T1 / T2)	5
4	Characteristics diagrams	7
5	Circuit diagram	11
6	Package outlines	12
7	Module label code	13
	Revision history	14
	Disclaimer	15

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	RMS, $f = 50 \text{ Hz}$, $t = 1 \text{ min}$	4.0	kV
Material of module baseplate			Cu	
Internal isolation		basic insulation (class 1, IEC 61140)	Al_2O_3	
Creepage distance	d_{Creep}	terminal to heatsink	29.0	mm
Creepage distance	d_{Creep}	terminal to terminal	23.0	mm
Clearance	d_{Clear}	terminal to heatsink	23.0	mm
Clearance	d_{Clear}	terminal to terminal	11.0	mm
Comparative tracking index	CTI		> 400	
Relative thermal index (electrical)	RTI	housing	140	°C

Table 2 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	L_{sCE}			20		nH
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_C = 25 \text{ °C}$, per switch		0.465		mΩ
Storage temperature	T_{stg}		-40		125	°C
Mounting torque for module mounting	M	- Mounting according to valid application note	M6, Screw	3	6	Nm
Terminal connection torque	M	- Mounting according to valid application note	M6, Screw	2.5	5	Nm
Weight	G			340		g

2 MOSFET, T1 / T2

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Drain-source voltage	V_{DSS}	$T_{vj} = 25 \text{ °C}$	2000	V
Implemented drain current	I_{DN}		400	A
Continuous DC drain current	I_{DDC}	$T_{vj} = 175 \text{ °C}$, $V_{GS} = 18 \text{ V}$ $T_C = 25 \text{ °C}$	375	A
Repetitive peak drain current	I_{DRM}	verified by design, t_p limited by T_{vjmax}	800	A

(table continues...)

Table 3 (continued) Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Gate-source voltage, max. transient voltage	V_{GS}	$D < 0.01$	-10/23	V
Gate-source voltage, max. static voltage	V_{GS}		-7/20	V

Table 4 Recommended values

Parameter	Symbol	Note or test condition	Values	Unit
On-state gate voltage	$V_{GS(on)}$		18	V
Off-state gate voltage	$V_{GS(off)}$		-3	V

Table 5 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Drain-source on-resistance	$R_{DS(on)}$	$I_D = 400\text{ A}$		2.6	4	mΩ
Gate threshold voltage	$V_{GS(th)}$	$I_D = 224\text{ mA}$, $V_{DS} = V_{GS}$, $T_{vj} = 25\text{ °C}$, (tested after 1ms pulse at $V_{GS} = +20\text{ V}$)	3.45	4.3	5.15	V
Total gate charge	Q_G	$V_{DD} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$		1.56		μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\text{ °C}$		0.9		Ω
Input capacitance	C_{ISS}	$f = 100\text{ kHz}$, $V_{DS} = 1200\text{ V}$, $V_{GS} = 0\text{ V}$, $T_{vj} = 25\text{ °C}$		48.2		nF
Output capacitance	C_{OSS}	$f = 100\text{ kHz}$, $V_{DS} = 1200\text{ V}$, $V_{GS} = 0\text{ V}$, $T_{vj} = 25\text{ °C}$		1.13		nF
Reverse transfer capacitance	C_{rss}	$f = 100\text{ kHz}$, $V_{DS} = 1200\text{ V}$, $V_{GS} = 0\text{ V}$, $T_{vj} = 25\text{ °C}$		0.08		nF
C_{OSS} stored energy	E_{OSS}	$V_{DS} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$, $T_{vj} = 25\text{ °C}$		2030		μJ
Drain-source leakage current	I_{DSS}	$V_{DS} = 2000\text{ V}$, $V_{GS} = -3\text{ V}$, $T_{vj} = 25\text{ °C}$		0.08	660	μA
Gate-source leakage current	I_{GSS}	$V_{DS} = 0\text{ V}$, $T_{vj} = 25\text{ °C}$			400	nA
Turn-on delay time (inductive load)	$t_{d on}$	$I_D = 400\text{ A}$, $R_{Gon} = 8.2\text{ Ω}$, $V_{DD} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$	286		ns
			$T_{vj} = 125\text{ °C}$	258		
			$T_{vj} = 175\text{ °C}$	248		

(table continues...)

Table 5 (continued) **Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rise time (inductive load)	t_r	$I_D = 400\text{ A}$, $R_{Gon} = 8.2\ \Omega$, $V_{DD} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$	266		ns
			$T_{vj} = 125\text{ °C}$	252		
			$T_{vj} = 175\text{ °C}$	239		
Turn-off delay time (inductive load)	$t_{d\ off}$	$I_D = 400\text{ A}$, $R_{Goff} = 2.2\ \Omega$, $V_{DD} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$	226		ns
			$T_{vj} = 150\text{ °C}$	244		
			$T_{vj} = 175\text{ °C}$	255		
Fall time (inductive load)	t_f	$I_D = 400\text{ A}$, $R_{Goff} = 2.2\ \Omega$, $V_{DD} = 1200\text{ V}$, $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$	57.5		ns
			$T_{vj} = 150\text{ °C}$	57.7		
			$T_{vj} = 175\text{ °C}$	60.5		
Turn-on energy loss per pulse	E_{on}	$I_D = 400\text{ A}$, $V_{DD} = 1200\text{ V}$, $L_\sigma = 25\text{ nH}$, $V_{GS} = -3/18\text{ V}$, $R_{Gon} = 8.2\ \Omega$, $di/dt = 3.2\text{ kA}/\mu\text{s}$ ($T_{vj} = 175\text{ °C}$)	$T_{vj} = 25\text{ °C}$	75.3		mJ
			$T_{vj} = 125\text{ °C}$	75.8		
			$T_{vj} = 175\text{ °C}$	79.8		
Turn-off energy loss per pulse	E_{off}	$I_D = 400\text{ A}$, $V_{DD} = 1200\text{ V}$, $L_\sigma = 25\text{ nH}$, $V_{GS} = -3/18\text{ V}$, $R_{Goff} = 2.2\ \Omega$, $dv/dt = 15.9\text{ kV}/\mu\text{s}$ ($T_{vj} = 175\text{ °C}$)	$T_{vj} = 25\text{ °C}$	24.3		mJ
			$T_{vj} = 125\text{ °C}$	25.5		
			$T_{vj} = 175\text{ °C}$	26.7		
Thermal resistance, junction to case	R_{thJC}	per MOSFET			0.0880	K/W
Thermal resistance, case to heat sink	R_{thCH}	per MOSFET, $\lambda_{grease} = 1\text{ W}/(\text{m}^2\text{K})$, $\lambda_{grease} = 1\text{ W}/(\text{m}^2\text{K})$		0.0330		K/W
Temperature under switching conditions	$T_{vj\ op}$		-40		175	°C

Note: The selection of positive and negative gate-source voltages impacts losses and the long-term behavior of the MOSFET and body diode. The design guidelines described in Application Notes AN 2018-09 and AN 2021-13 must be considered to ensure sound operation of the device over the planned lifetime.

$T_{vj,op} > 150\text{ °C}$ is allowed for operation at overload conditions for MOSFET and body diode. For detailed specifications, please refer to AN 2021-13.

3 Body diode (MOSFET, T1 / T2)

Table 6 **Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit
DC body diode forward current	I_{SD}	$T_{vj} = 175\text{ °C}$, $V_{GS} = -3\text{ V}$ $T_C = 25\text{ °C}$	315	A

Table 7 **Characteristic values**


Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Forward voltage	V_{SD}	$I_{SD} = 400 \text{ A}$, $V_{GS} = -3 \text{ V}$	$T_{vj} = 25 \text{ °C}$		4.6	6.15	V
			$T_{vj} = 125 \text{ °C}$		4.15		
			$T_{vj} = 175 \text{ °C}$		4		

4 Characteristics diagrams

Output characteristic (typical), MOSFET, T1 / T2

$$I_D = f(V_{DS})$$


$$V_{GS} = 18 \text{ V}$$



Output characteristic field (typical), MOSFET, T1 / T2

$$I_D = f(V_{DS})$$


$$T_{vj} = 175 \text{ °C}$$



Transfer characteristic (typical), MOSFET, T1 / T2

$$I_D = f(V_{GS})$$


$$V_{DS} = 20 \text{ V}$$



Drain source on-resistance (typical), MOSFET, T1 / T2

$$R_{DS(on)} = f(T_{vj})$$

$$V_{GS} = 18 \text{ V}$$




4 Characteristics diagrams

Gate-source threshold voltage (typical), MOSFET, T1 / T2

$$V_{GS(th)} = f(T_{vj})$$


$$V_{GS} = V_{DS}$$



Gate charge characteristic (typical), MOSFET, T1 / T2

$$V_{GS} = f(Q_G)$$


$$I_D = 400$$
 A, $T_{vj} = 25$ °C



Capacity characteristic (typical), MOSFET, T1 / T2

$$C = f(V_{DS})$$


$$f = 100$$
 kHz, $T_{vj} = 125$ °C, $V_{GS} = -3$ V



Forward characteristic body diode (typical), MOSFET, T1 / T2

$$I_{SD} = f(V_{SD})$$

$$T_{vj} = 25$$
 °C




4 Characteristics diagrams

Switching losses (typical), MOSFET, T1 / T2

$$E = f(R_G)$$


$V_{DD} = 1200 \text{ V}$, $I_D = 400 \text{ A}$, $V_{GS} = -3/18 \text{ V}$



Switching losses (typical), MOSFET, T1 / T2

$$E = f(I_D)$$


$R_{Goff} = 2.2 \text{ } \Omega$, $R_{Gon} = 8.2 \text{ } \Omega$, $V_{DD} = 1200 \text{ V}$, $V_{GS} = -3/18 \text{ V}$



Switching times (typical), MOSFET, T1 / T2

$$t = f(R_G)$$


$V_{DD} = 1200 \text{ V}$, $I_D = 400 \text{ A}$, $T_{vj} = 175 \text{ } ^\circ\text{C}$, $V_{GS} = -3/18 \text{ V}$



Switching times (typical), MOSFET, T1 / T2

$$t = f(I_D)$$


$R_{Goff} = 2.2 \text{ } \Omega$, $R_{Gon} = 8.2 \text{ } \Omega$, $V_{DD} = 1200 \text{ V}$, $T_{vj} = 175 \text{ } ^\circ\text{C}$, $V_{GS} = -3/18 \text{ V}$



4 Characteristics diagrams


Reverse bias safe operating area (RBSOA), MOSFET, T1 / T2

$I_D = f(V_{DS})$
 $R_{Goff} = 2.2 \Omega$, $T_{vj} = 175 \text{ }^\circ\text{C}$, $V_{GS} = -3/18 \text{ V}$



Transient thermal impedance , MOSFET, T1 / T2

$Z_{th} = f(t)$



5 Circuit diagram




Figure 1

6 Package outlines




Figure 2

7 Module label code



Module label code			
Code format	Data Matrix		Barcode Code128
Encoding	ASCII text		Code Set A
Symbol size	16x16		23 digits
Standard	IEC24720 and IEC16022		IEC8859-1
Code content	Content	Digit	Example
	Module serial number	1 – 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 – 21	15
	Date code (production week)	22 – 23	30
Example	<div></div> <div>7154914284655054991153071549142846550549911530</div>		

Figure 3

Revision history

Document revision	Date of release	Description of changes
V1.0	2017-12-21	Target datasheet
V1.1	2018-01-19	Target datasheet
V1.2	2018-10-17	Target datasheet
n/a	2020-09-01	Datasheet migrated to a new system with a new layout and new revision number schema: target or preliminary datasheet = 0.xy; final datasheet = 1.xy
0.10	2021-06-28	Target datasheet
0.20	2022-08-09	Target datasheet
0.30	2022-09-27	Target datasheet
1.00	2022-12-22	Final datasheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2022-12-22

Published by

Infineon Technologies AG
81726 Munich, Germany

© 2022 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any
aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-AAX973-007

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.