

## Small-Signal Transistor

### Features



- N-channel
- Depletion mode
- $dv/dt$  rated
- Pb-free lead-plating; RoHS compliant
- Halogen-free according to AEC61249-2-21

### Product validation

Fully qualified according to JEDEC for Industrial Applications

**Table 1** Key performance parameters

Parameter	Value	Unit
$V_{DS}$	100	V
$R_{DS(on),max}$	12	$\Omega$
$I_{DSS,min}$	0.09	A
ESD Sensitivity, JESD22-A114 (HBM)	Class 0 (<250V)	



Part number	Package	Marking	Related links
BSS169I	PG-SOT23-3	Fls	-

Table of contents

Description ..... 1

Maximum ratings ..... 3

Thermal characteristics ..... 3

Electrical characteristics ..... 4

Electrical characteristics diagrams ..... 6

Package outlines ..... 10

Revision history ..... 11

Trademarks ..... 12

Disclaimer ..... 12

## 1 Maximum ratings

at  $T_A=25\text{ °C}$ , unless otherwise specified

**Table 2 Maximum ratings**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Continuous drain current	$I_D$	-	-	0.19	A	$T_A=25\text{ °C}$
				0.15		$T_A=70\text{ °C}$
Pulsed drain current	$I_{D,pulse}$	-	-	0.76	A	$T_A=25\text{ °C}$
Reverse diode $dv/dt$	$dv/dt$	-	-	6	kV / $\mu s$	$I_D=0.19\text{ A}$ , $V_{DS}=20\text{ V}$ , $di/dt=200\text{ A}/\mu s$ , $T_{j,max}=150\text{ °C}$
Gate source voltage	$V_{GS}$	-20	-	20	V	-
Power dissipation	$P_{tot}$	-	-	0.36	W	$T_A=25\text{ °C}$
Operating and storage temperature	$T_j$ , $T_{stg}$	-55	-	150	°C	IEC climatic category; DIN IEC 68-1: 55/150/56

## 2 Thermal characteristics

**Table 3 Thermal characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction - ambient, minimal footprint	$R_{thJA}$	-	-	250	K/W	-

### 3 Electrical characteristics

at  $T_j=25\text{ °C}$ , unless otherwise specified

**Table 4 Static characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	100	-	-	V	$V_{GS}=-10\text{ V}$ , $I_D=250\text{ }\mu\text{A}$
Gate threshold voltage	$V_{GS(th)}$	-2.9	-2.2	-1.8	V	$V_{DS}=3\text{ V}$ , $I_D=50\text{ }\mu\text{A}$
Drain-source cutoff current	$I_{D(off)}$	-	-	0.1	$\mu\text{A}$	$V_{DS}=100\text{ V}$ , $V_{GS}=-10\text{ V}$ , $T_j=25\text{ °C}$
				10		$V_{DS}=100\text{ V}$ , $V_{GS}=-10\text{ V}$ , $T_j=125\text{ °C}$
Gate-source leakage current	$I_{GSS}$	-	-	10	nA	$V_{GS}=20\text{ V}$ , $V_{DS}=0\text{ V}$
On-state drain current	$I_{DSS}$	90	-	-	mA	$V_{GS}=0\text{ V}$ , $V_{DS}=10\text{ V}$
Drain-source on-state resistance	$R_{DS(on)}$	-	5.3	12	$\Omega$	$V_{GS}=0\text{ V}$ , $I_D=0.05\text{ A}$
			2.9	-		$V_{GS}=10\text{ V}$ , $I_D=0.19\text{ A}$
Transconductance	$g_{fs}$	-	0.20	-	S	$ V_{DS} >2 I_D R_{DS(on)max}$ , $I_D=0.15\text{ A}$

**Table 5 Dynamic characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Input capacitance	$C_{iss}$	-	51	-	pF	$V_{GS}=-10\text{ V}$ , $V_{DS}=25\text{ V}$ , $f=1\text{ MHz}$
Output capacitance	$C_{oss}$		9			
Reverse transfer capacitance	$C_{rss}$		4			
Turn-on delay time	$t_{d(on)}$	-	2.9	-	ns	$V_{DD}=50\text{ V}$ , $V_{GS}=-3\text{ to }7\text{ V}$ , $I_D=0.12\text{ A}$ , $R_G=6\text{ }\Omega$
Rise time	$t_r$		2.7			
Turn-off delay time	$t_{d(off)}$		11			
Fall time	$t_f$		27			

**Table 6 Gate charge characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate to source charge	$Q_{gs}$	-	0.12	-	nC	$V_{DD}=80\text{ V}$ , $I_D=0.12\text{ A}$ , $V_{GS}=-3\text{ to }7\text{ V}$
Gate to drain charge	$Q_{gd}$		0.9		nC	
Gate charge total	$Q_g$		2.1		nC	
Gate plateau voltage	$V_{plateau}$		-0.43		V	

**Table 7 Reverse diode**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Diode continuous forward current	$I_S$	-	-	0.19	A	$T_A=25\text{ °C}$
Diode pulse current	$I_{S,pulse}$			0.76		
Diode forward voltage	$V_{SD}$	-	0.82	1.2	V	$V_{GS}=-10\text{ V}$ , $I_F=0.19\text{ A}$ , $T_J=25\text{ °C}$
Reverse recovery time	$t_{rr}$	-	20.5	25.6	ns	$V_R=50\text{ V}$ , $I_F=0.12\text{ A}$ , $di_F/dt=100\text{ A}/\mu\text{s}$
Reverse recovery charge	$Q_{rr}$		9.7	12.1	nC	

## 4 Electrical characteristics diagrams







Diagram 5: Typ. output characteristics




$I_D = f(V_{DS})$ ,  $T_j = 25^\circ\text{C}$ ; parameter:  $V_{GS}$

Diagram 6: Typ. drain-source on resistance




$R_{DS(on)} = f(I_D)$ ,  $T_j = 25^\circ\text{C}$ ; parameter:  $V_{GS}$

Diagram 7: Typ. transfer characteristics




$I_D = f(V_{GS})$ ,  $|V_{DS}| > 2|I_D|R_{DS(on)max}$ ,  $T_j = 25^\circ\text{C}$

Diagram 8: Typ. transconductance




$g_{fs} = f(I_D)$ ,  $V_{DS} = 5\text{ V}$ ,  $T_j = 25^\circ\text{C}$

Diagram 9: Normalized drain-source on resistance




$$R_{DS(on)} = f(T_j), I_D = 0.05 \text{ A}, V_{GS} = 0 \text{ V}$$

Diagram 10: Typ. gate threshold voltage




$$V_{GS(th)} = f(T_j), V_{DS} = 3 \text{ V}, I_D = 50 \mu\text{A}$$

Diagram 11: Typ. capacitances



$$C = f(V_{DS}), V_{GS} = -3 \text{ V}, f = 1 \text{ MHz}$$


Diagram 12: Forward characteristics of reverse diode



$$I_F = f(V_{SD}); \text{parameter: } T_j$$




Diagram 13: Typ. gate charge




$V_{GS}=f(Q_{gate}), I_D=0.12\text{ A pulsed}, T_J=25\text{ }^{\circ}\text{C}$

Diagram 14: Drain-source breakdown voltage




$V_{BR(DSS)}=f(T_J), I_D=250\text{ }\mu\text{A}$

Gate charge waveforms



## 5 Package outlines



PACKAGE - GROUP NUMBER: PG-SOT23-3-U03					
DIMENSIONS	MILLIMETERS		DIMENSIONS	MILLIMETERS	
	MIN.	MAX.		MIN.	MAX.
A	0.88	1.02	e	1.90	
A1	0.01	0.10	e1	0.95	
A2	0.89	1.12	L	0.40	0.60
A3	0.15	0.35	N	3	
A4	0.70		O	3°	8°
b	0.32	0.47	O1	6°	8°
c	0.08	0.18			
D	2.80	3.04			
E	2.40	2.64			
E1	1.32	1.40			

NOTE: ALL DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.

Figure 1 Outline PG-SOT23-3mm

## Revision history

BSS169I

### Revision 2025-03-13, Rev. 2.2

Previous revisions

Revision	Date	Subjects (major changes since last revision)
2.0	2021-01-26	Release of final version
2.1	2021-03-17	Update technology naming
2.2	2025-03-13	Update package outline drawing

#### Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**We Listen to Your Comments** Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: [erratum@infineon.com](mailto:erratum@infineon.com)

#### Published by

Infineon Technologies AG  
81726 München, Germany  
© 2025 Infineon Technologies AG  
All Rights Reserved.

#### Important notice

The products which may also include samples and may be comprised of hardware or software or both ("Product") are sold or provided and delivered by Infineon Technologies AG and its affiliates ("Infineon") subject to the terms and conditions of the frame supply contract or other written agreement(s) executed by a customer and Infineon or, in the absence of the foregoing, the applicable Sales Conditions of Infineon. General terms and conditions of a customer or deviations from applicable Sales Conditions of Infineon shall only be binding for Infineon if and to the extent Infineon has given its express written consent.

For the avoidance of doubt, Infineon disclaims all warranties of non-infringement of third-party rights and implied warranties such as warranties of fitness for a specific use/purpose or merchantability.

Infineon shall not be responsible for any information with respect to samples, the application or customer's specific use of any Product or for any examples or typical values given in this document.

The data contained in this document is exclusively intended for technically qualified and skilled customer representatives. It is the responsibility of the customer to evaluate the suitability of the Product for the intended application and the customer's specific use and to verify all relevant technical data contained in this document in the intended application and the customer's specific use. The customer is responsible for properly designing, programming, and testing the functionality and safety of the intended application, as well as complying with any legal requirements related to its use.

Unless otherwise explicitly approved by Infineon, Products may not be used in any application where a failure of the Product or any consequences of the use thereof can reasonably be expected to result in personal injury. However, the foregoing shall not prevent the customer from using any Product in such fields of use that Infineon has explicitly designed and sold it for, provided that the overall responsibility for the application lies with the customer.

If the Product includes security features:

Because no computing device can be absolutely secure, and despite security measures implemented in the Product, Infineon does not guarantee that the Product will be free from intrusion, data theft or loss, or other breaches ("Security Breaches"), and Infineon shall have no liability arising out of any Security Breaches.

If this document includes or references software:

The software is owned by Infineon under the intellectual property laws and treaties of the United States, Germany, and other countries worldwide. All rights reserved. Therefore, you may use the software only as provided in the software license agreement accompanying the software. If no software license agreement applies, Infineon hereby grants you a personal, non-exclusive, non-transferable license (without the right to sublicense) under its intellectual property rights in the software (a) for software provided in source code form, to modify and reproduce the software solely for use with Infineon hardware products, only internally within your organization, and (b) to distribute the software in binary code form externally to end users, solely for use on Infineon hardware products. Any other use, reproduction, modification, translation, or compilation of the software is prohibited.

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).