N-Channel Power MOSFET

FEATURES

- Excellent FOM
- Ultra low rdson
- 100% UIS & Rg tested
- RoHS compliant
- Halogen-free

KEY PERFORMANCE PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
V_{DS}	100	V
$R_{DS(on)}$ (max)	11	mΩ
$Q_{g,typ}$	21	nC

APPLICATIONS

- Solenoid and motor drivers
- DC-DC converters
- Load Switch
- SMPS

Pb-Free RoHS COMPLIANT HALOGEN FREE

TO-252_A





Note: MSL 3 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	100	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25°C	I_D	47	A
	T_C = 100°C		30	
Pulsed Drain Current (Note 1)		I_{DM}	188	A
Total Power Dissipation	T_C = 25°C	P_D	46	W
	T_C = 100°C		19	
Single Pulse Avalanche Energy (Note 2)		E_{AS}	147	mJ
Single Pulse Avalanche Current (Note 2)		I_{AS}	9.9	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	2.7	°C/W
Junction to Ambient Thermal Resistance (Note 3)	$R_{\Theta JA}$	45	°C/W

Notes:

1. Pulse Width ≤ 100μs.
2. L = 3mH, R_G = 25Ω, Starting T_J = 25°C.
3. Device on a PCB FR4 with 1 in^2 (single layer, 2 oz thickness) copper area for drain connection.

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static (Note 4)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	BV_{DSS}	100	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	$V_{GS(TH)}$	1.2	1.7	2.2	V
Gate Body Leakage	V_{GS} = ±20V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 80V, V_{GS} = 0V	I_{DSS}	--	--	1	μA
Drain-Source On-State Resistance	V_{GS} = 10V, I_D = 20A	$R_{DS(on)}$	--	8.3	11	mΩ
	V_{GS} = 4.5V, I_D = 15A		--	11	14	
Dynamic (Note 5)						
Total Gate Charge	V_{DS} = 50V, I_D = 20A, V_{GS} = 10V	Q_g	--	21	--	nC
Gate-Source Charge		Q_{gs}	--	4.8	--	
Gate-Drain Charge		Q_{gd}	--	3.8	--	
Input Capacitance	V_{DS} = 50V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	1291	--	pF
Output Capacitance		C_{oss}	--	631	--	
Reverse Transfer Capacitance		C_{rss}	--	43	--	
Gate Resistance	f = 1.0MHz	R_g	--	2	--	Ω
Switching (Note 6)						
Turn-On Delay Time	V_{DD} = 50V, R_G = 3Ω, I_D = 30A, V_{GS} = 10V	$t_{d(on)}$	--	8.4	--	ns
Turn-On Rise Time		t_r	--	57	--	
Turn-Off Delay Time		$t_{d(off)}$	--	23	--	
Turn-Off Fall Time		t_f	--	84	--	
Source-Drain Diode						
Forward Voltage (Note 4)	I_S = 20A, V_{GS} = 0V	V_{SD}	--	--	1.2	V
Reverse Recovery Time	I_S = 20A, dI_F/dt = 100A/μs	t_{rr}	--	44	--	ns
Reverse Recovery Charge		Q_{rr}	--	50	--	nC

Notes:

4. Pulse test: Pulse Width ≤ 300μs, duty cycle ≤ 2%.
5. Defined by design. Not subject to production test.
6. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM110NM10LCP ROG	TO-252_A	2,500pcs / 13” Reel

CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature



On-Resistance vs. Gate-Source Voltage



CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Capacitance vs. Drain-Source Voltage



BV_{DSS} vs. Junction Temperature



Maximum Safe Operating Area, Junction-to-Case



Source-Drain Diode Forward Current vs. Voltage



Normalized Thermal Transient Impedance, Junction-to-Case



CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Power Dissipation



Drain Current



Normalized gate threshold voltage vs Temperature



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-252_A





DETAIL A, ROTATED -90°
(SCALE 2:1)



SUGGESTED PAD LAYOUT



MARKING DIAGRAM

110NM10L	= Device marking
Y	= Year Code
WW	= Week Code (01~52)
L	= Lot Code (1~9,A~Z)
F	= Factory Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC TO-252, VARIATION AA, ISSUE F.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSION, OR GATE BURRS.
5. DWG NO. REF: HQ2SD07-TO252_A-144 REV A.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.