

### General Description

The AGM314MD combines advanced trench MOSFET technology with a low resistance package to provide extremely low  $R_{DS(ON)}$ .

This device is ideal for load switch and battery protection applications.

### Features

- Advance high cell density Trench technology
- Low  $R_{DS(ON)}$  to minimize conductive loss
- Low Gate Charge for fast switching
- Low Thermal resistance
- 100% Avalanche tested
- 100% DVDS tested


### Application

- MB/VGA Vcore
- SMPS 2<sup>nd</sup> Synchronous Rectifier
- POL application
- BLDC Motor driver

### Product Summary

BVDSS	RDSON	ID
30V	10mΩ	30A
-30V	21mΩ	-20A

### TO-252-4L Pin Configuration



### Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
AGM314MD	AGM314MD	TO-252-4L	330mm	16mm	2500

**Table 1. Absolute Maximum Ratings (TA=25°C)**

Symbol	Parameter	Rating		Units
		N-Ch	P-Ch	
$V_{DS}$	Drain-Source Voltage ( $V_{GS}=0V$ )	30	-30	V
$V_{GS}$	Gate-Source Voltage ( $V_{DS}=0V$ )	±20	±20	V
$I_D$	Drain Current-Continuous( $TC=25^{\circ}C$ ) (Note 1)	30	-20	A
	Drain Current-Continuous( $TC=100^{\circ}C$ )	21	-14	A
$I_{DM}$ (pluse)	Drain Current-Pulsed (Note 2)	120	-80	A
$P_D$	Total Power Dissipation( $TC=25^{\circ}C$ )	29.7	29.7	W
	Total Power Dissipation( $TC=100^{\circ}C$ )	11.9	11.9	W
EAS	Avalanche energy (Note 3)	81	81	mJ
$T_J, T_{STG}$	Operating Junction and Storage Temperature Range	-55 To 150	-55 To 150	°C

**Table 2. Thermal Characteristic**

Symbol	Parameter	Typ	Max	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient (Steady State) <sup>1</sup>	---	50	°C/W
$R_{\theta JC}$	Thermal Resistance Junction-Case <sup>1</sup>	---	4.2	°C/W

**Table 3. N- Channel Electrical Characteristics (TJ=25℃unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BVDSS	Drain-Source Breakdown Voltage	VGS=0V ID=250μA	30	--	--	V
IDSS	Zero Gate Voltage Drain Current	VDS=30V,VGS=0V	--	--	1	μA
IGSS	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	VDS=VGS,ID=250μA	1.2	1.6	2.2	V
gFS	Forward Transconductance	VDS=5V,ID=5A	--	7	--	S
RDS(on)	Drain-Source On-State Resistance	VGS=10V, ID=10A	--	10	15	mΩ
		VGS=4.5V, ID=5A	--	16	24	mΩ
Dynamic Characteristics						
Ciss	Input Capacitance	VDS=15V,VGS=0V, F=1MHZ	--	618	--	pF
Coss	Output Capacitance		--	99	--	pF
Crss	Reverse Transfer Capacitance		--	88	--	pF
Rg	Gate resistance	VGS=0V, VDS=0V,f=1.0MHz	--	1.8	--	Ω
Switching Times						
td(on)	Turn-on Delay Time	VDS=15V,VGS=10V, RGEN=6.8Ω, RL=3.5Ω	--	12	--	nS
tr	Turn-on Rise Time		--	25	--	nS
td(off)	Turn-Off Delay Time		--	38	--	nS
tf	Turn-Off Fall Time		--	16	--	nS
Qg	Total Gate Charge	VGS=10V, VDS=15V, ID=15A	--	11.7	--	nC
Qgs	Gate-Source Charge		--	3.8	--	nC
Qgd	Gate-Drain Charge		--	2.3	--	nC
Source-Drain Diode Characteristics						
ISD	Source-Drain Current(Body Diode)		--	--	30	A
VSD	Forward on Voltage	VGS=0V,IS=10A	--	--	1.2	V
trr	Reverse Recovery Time	IF=10A , dl/dt=100A/μs , TJ=25℃	--	17	--	ns
Qrr	Reverse Recovery Charge		--	31	--	nc

Notes 1.The maximum current rating is package limited.

Notes 2.Repetitive Rating: Pulse width limited by maximum junction temperature

Notes 3.EAS condition: TJ=25℃, VDD=15V, Vgs=10V, ID=18A, L=0.5mH, RG=25ohm

**Table 3. P-Channel Electrical Characteristics (TJ=25°C unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BVDSS	Drain-Source Breakdown Voltage	VGS=0V ID=-250μA	-30	--	--	V
IDSS	Zero Gate Voltage Drain Current	VDS=-30V,VGS=0V	--	--	-1	μA
IGSS	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	VDS=VGS,ID=-250μA	-1.2	-1.5	-2.2	V
gFS	Forward Transconductance	VDS=-10V,ID=-5A	--	7	--	S
RDS(on)	Drain-Source On-State Resistance	VGS=-10V, ID=-10A	--	21	26	mΩ
		VGS=-4.5V, ID=-5A	--	29	35	mΩ
Dynamic Characteristics						
Ciss	Input Capacitance	VDS=-15V,VGS=0V, F=1MHZ	--	689	--	pF
Coss	Output Capacitance		--	101	--	pF
Crss	Reverse Transfer Capacitance		--	88	--	pF
Rg	Gate resistance	VGS=0V, VDS=0V,f=1.0MHz	--	11.1	--	Ω
Switching Times						
td(on)	Turn-on Delay Time	VGS=-10V,VDS=-15V, RL=1Ω,RGEN=3Ω	--	9	--	nS
tr	Turn-on Rise Time		--	5	--	nS
td(off)	Turn-Off Delay Time		--	21	--	nS
tf	Turn-Off Fall Time		--	3.3	--	nS
Qg	Total Gate Charge	VGS=-10V, VDS=-25V, ID=-5A	--	13.2	--	nC
Qgs	Gate-Source Charge		--	26	--	nC
Qgd	Gate-Drain Charge		--	3.3	--	nC
Source-Drain Diode Characteristics						
ISD	Source-Drain Current(Body Diode)		--	--	-20	A
VSD	Forward on Voltage	VGS=0V,IS=-10A	--	--	-1.2	V
trr	Reverse Recovery Time	IF=-10A , dI/dt=100A/μs , TJ=25℃	--	13	--	ns
Qrr	Reverse Recovery Charge		--	8.5	--	nc

Notes 1.The maximum current rating is package limited.

Notes 2.Repetitive Rating: Pulse width limited by maximum junction temperature

Notes 3.EAS condition: TJ=25°C , VDD=-15V, Vgs=-10V, ID=-18A, L=0.5mH, RG=25ohm

# N-Channel Electrical Characteristics Diagrames







**Figure 1. On-Regin Characteristics**

**Figure 2. Transfer Characteristics**

**Figure 3. On-Resistance vs. Drain Current and Gate Voltage**

**Figure 4. On-Resistance vs. Junction Temperature**

**Figure 5. On-Resistance vs. Gate-Source Voltage**

**Figure 6. Body-Diode Characteristics**


Figure 7. Gate-Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Forward Biased Safe Operating Area




Figure 10. Single Pulse Power Rating Junction-to-Ambient





Figure 11. Normalized Maximum Transient Thermal Impedance



# P-Channel Electrical Characteristics Diagrames







**Figure 1. On-Regin Characteristics**

**Figure 2. Transfer Characteristics**

**Figure 3. On-Resistance vs. Drain Current and Gate Voltage**

**Figure 4. On-Resistance vs. Junction Temperature**

**Figure 5. On-Resistance vs. Gate-Source Voltage**

**Figure 6. Body-Diode Characteristics**


Figure 7. Gate-Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Forward Biased Safe Operating Area




Figure 10. Single Pulse Power Rating Junction-to-Ambient









Figure 11. Normalized Maximum Transient Thermal Impedance



# Dimensions (TO-252-4L)




SYMBOL	MILLIMETER		
	MIN	Typ.	MAX
A	2.200	2.300	2.400
A1	0.000		0.127
b	0.550	0.600	0.650
b1	0.000		0.120
c(电镀后)	0.460	0.520	0.580
D	6.500	6.600	6.700
D1	5.334 REF		
D2	5.346 REF		
D3	4.490 REF		
E	6.000	6.100	6.200
e	1.270 TYP		
e1	2.540 TYP		
h	0.000	0.100	0.200
L	9.900	10.100	10.300
L1	2.988 REF		
L2	1.400	1.550	1.700
L3	1.600 REF		
L4	0.700	0.800	0.900
Φ	1.100	1.200	1.300
θ	0°		8°
θ1	9° TYP		
θ2	9° TYP		



TO-252-4L

Marking Instructions:




Disclaimer:

The information provided in this document is believed to be accurate and reliable. However, Shenzhen Core Control Source Electronics Technology Co., Ltd. does not assume any responsibility for the following consequences. Do not consider the use of such information or use beyond its scope.

The information mentioned in this document may be changed at any time without notice.

The products and information provided in this document do not infringe patents. Shenzhen Core Control Source Electronics Technology Co., Ltd. assumes no responsibility for any infringement of any other rights of third parties. The result of using such products and information.

This document is the third version issued on March 10th, 2024. This document replaces all previously provided information.

 It is a registered trademark of Shenzhen Core Control Source Electronics Technology Co., Ltd.

Copyright © 2017 Shenzhen Core Control Source Electronics Technology Co., Ltd. all rights reserved.