MOSFET

PG-TO247-3

650V CoolMOS™ CM8 Power Transistor

The CoolMOS™ 8th generation platform is a revolutionary technology for high voltage power MOSFETs, designed according to the superjunction (SJ) principle and pioneered by Infineon Technologies. The 650V CoolMOS™ CM8 series is the successor to the 650V CoolMOS™ 7 Family and is enhancing Infineon's WBG offering. It combines the benefits of a fast switching SJ MOSFET with excellent ease of use, e.g low ringing tendency, implemented fast body diode (CFD) for all products with outstanding robustness against hard commutation and excellent ESD capability. Furthermore, extremely low switching and conduction losses of CM8, make switching applications even more efficient.

Tab

Drain
Pin 2, Tab

Gate
Pin 1

Source
*1: Internal body diode   Pin 3

Features

- Best in class 650V SJ MOSFET performance
- Suitable for hard and soft switching topologies thanks to an outstanding commutation ruggedness
- Integrated fast body diode and ESD protection
- .XT interconnection technology for best in class thermal performance

Benefits

- Ease of use and fast design-in through low ringing tendency and usage across PFC and PWM stages
- Simplified thermal management due to our advanced die attach technique
- Increased power density solutions enabled by using products with smaller footprint and higher manufacturing quality due state of the art ESD protection
- Suitable for a wide variety of applications and power ranges

Hal   Pb

RoHS

Potential applications

- Power supplies and converters
- PFC stages & LLC resonant converters
- High efficiency switching applications
- e.g. Datacenter, AI Server, Telecom Power Supply

Product validation

Fully qualified according to JEDEC for Industrial Applications

Please note: For MOSFET paralleling the use of ferrite beads on the gate or separate totem poles is generally recommended.

Table 1   Key performance parameters

Parameter	Value	Unit
V_{DS} @ $T_{j,max}$	700	V
$R_{DS(on),max}$	18	mΩ
$Q_{g,typ}$	173	nC
$I_{D,pulse}$	505	A
E_{oss} @ 400V	19.6	µJ
Body diode di_F/dt	1300	A/µs
ESD class (HBM)	2	

Part number	Package	Marking	Related links
IPW65R018CM8	PG-TO247-3	65R018C8	see Appendix A

Table of contents

1 Maximum ratings

at T_j = 25°C, unless otherwise specified

Table 2   Maximum ratings

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Continuous drain current [1]	I_D	-	-	116	A	T_C=25°C
				73		T_C=100°C
Pulsed drain current [2]	$I_{D,pulse}$	-	-	505	A	T_C=25°C
Avalanche energy, single pulse	E_{AS}	-	-	297	mJ	I_D=6.7A; V_{DD}=50V; see table 10
Avalanche energy, repetitive	E_{AR}			1.48		
Avalanche current, single pulse	I_{AS}	-	-	6.7	A	-
MOSFET dv/dt ruggedness	dv/dt	-	-	120	V/ns	V_{DS}=0...400V
Gate source voltage (static)	V_{GS}	-20	-	20	V	static;
Gate source voltage (dynamic)	V_{GS}	-30	-	30	V	AC (f>1 Hz)
Power dissipation	P_{tot}	-	-	521	W	T_C=25°C
Storage temperature	T_{stg}	-55	-	150	°C	-
Operating junction temperature	T_j					
Extended operating junction temperature	T_j	150	-	175	°C	≤50 h in the application lifetime
Mounting torque	-	-	-	60	Ncm	M3 and M3.5 screws
Continuous diode forward current	I_S	-	-	116	A	T_C=25°C
Diode pulse current [2]	$I_{S,pulse}$			505		
Reverse diode dv/dt [3]	dv/dt	-	-	70	V/ns	V_{DS}=0...400V, I_{SD}≤116A, T_j=25°C see table 8
Maximum diode commutation speed	di_F/dt			1300	A/µs	
Insulation withstand voltage	V_{ISO}	-	-	n.a.	V	V_{rms}, T_C=25°C, t=1min

[1] Limited by $T_{j,max}$

[2] Pulse width t_p limited by $T_{j,max}$

[3] Identical low side and high side switch with identical R_G

2 Thermal characteristics

Table 3 **Thermal characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case	R_{thJC}	-	-	0.24	K/W	-
Thermal resistance, junction - ambient	R_{thJA}	-	-	62	K/W	leaded
Thermal resistance, junction - ambient for SMD version	R_{thJA}	-	-	-	K/W	-
Soldering temperature, wavesoldering only allowed at leads	T_{sold}	-	-	260	°C	1.6mm (0.063 in.) from case for 10s

3 Electrical characteristics

at T_j=25°C, unless otherwise specified

Table 4   Static characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	650	-	-	V	V_{GS}=0V, I_D=1mA
Gate threshold voltage	$V_{(GS)th}$	3.7	4.2	4.7	V	V_{DS}=V_{GS}, I_D=1.48mA
Zero gate voltage drain current	I_{DSS}	-	-	2	μA	V_{DS}=650V, V_{GS}=0V, T_j=25°C
			244	-		V_{DS}=650V, V_{GS}=0V, T_j=150°C
Gate-source leakage current	I_{GSS}	-	-	0.1	μA	V_{GS}=20V, V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$	-	0.015	0.018	Ω	V_{GS}=10V, I_D=55.6A, T_j=25°C
			0.033	-		V_{GS}=10V, I_D=55.6A, T_j=150°C
Gate resistance	R_G	-	1	-	Ω	f=1MHz

Table 5   Dynamic characteristics

| Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Input capacitance	C_{iss}	-	8290	-	pF	V_{GS}=0V, V_{DS}=400V, f=250kHz
Output capacitance	C_{oss}		91			
Effective output capacitance, energy related [4]	$C_{o(er)}$	-	245	-	pF	V_{GS}=0V, V_{DS}=0...400V
Effective output capacitance, time related [5]	$C_{o(tr)}$	-	2702	-	pF	I_D=constant, V_{GS}=0V, V_{DS}=0...400V
Turn-on delay time	$t_{d(on)}$	-	44.5	-	ns	V_{DD}=400V, V_{GS}=13V, I_D=29.7A, R_G=1.8Ω; see table 9
Rise time	t_r		16.1			
Turn-off delay time	$t_{d(off)}$		159.2			
Fall time	t_f		5.1			

[4] $C_{o(er)}$ is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 400V

[5] $C_{o(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 400V

Table 6   Gate charge characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate to source charge	Q_{gs}		48		nC	
Gate to drain charge	Q_{gd}	-	54	-	nC	V_{DD}=400V, I_D=29.7A, V_{GS}=0 to 10V
Gate charge total	Q_g		173		nC	
Gate plateau voltage	$V_{plateau}$		5.8		V	

Table 7   Reverse diode characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Diode forward voltage	V_{SD}	-	0.9	-	V	V_{GS}=0V, I_F=29.7A, T_j=25°C
Reverse recovery time	t_{rr}		180	225	ns	V_R=400V, I_F=29.7A, di_F/dt=100A/µs; see table 8
Reverse recovery charge	Q_{rr}	-	1.54	2.31	µC	
Peak reverse recovery current	I_{rrm}		16.4	-	A	

4 Electrical characteristics diagrams

Diagram 1: Power dissipation

P_{tot}=f(T_C)

Diagram 2: Safe operating area

I_D=f(V_{DS}); T_C=25 °C; D=0; parameter: t_p

Diagram 3: Safe operating area

I_D=f(V_{DS}); T_C=80 °C; D=0; parameter: t_p

Diagram 4: Max. transient thermal impedance

Z_{thJC}=f(t_P); parameter: D=t_p/T

Diagram 5: Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C; parameter: V_{GS}

Diagram 6: Typ. output characteristics

I_D=f(V_{DS}); T_j=125 °C; parameter: V_{GS}

Diagram 7: Typ. drain-source on-state resistance

$R_{DS(on)}$=f(I_D); T_j=125 °C; parameter: V_{GS}

Diagram 8: Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=55.6 A; V_{GS}=10 V

Diagram 9: Typ. transfer characteristics

I_D=f(V_{GS}); V_{DS}=20V; parameter: T_j

Diagram 10: Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=29.7 A pulsed; parameter: V_{DD}

Diagram 11: Forward characteristics of reverse diode

I_F=f(V_{SD}); parameter: T_j

Diagram 12: Avalanche energy

E_{AS}=f(T_j); I_D=6.7 A; V_{DD}=50 V

Diagram 13: Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=10 mA

Diagram 14: Typ. capacitances

C=f(V_{DS}); V_{GS}=0 V; f=250 kHz

Diagram 15: Typ. Coss stored energy

E_{oss}=f(V_{DS})

5 Test circuits

Table 8 Diode characteristics

Test circuit for diode characteristics	Diode recovery waveform

Table 9 Switching times

Switching times test circuit for inductive load	Switching times waveform

Table 10 Unclamped inductive load

Unclamped inductive load test circuit	Unclamped inductive waveform

6 Package outlines

PACKAGE - GROUP NUMBER:	**PG-TO247-3-U06**	
DIMENSIONS	**MILLIMETERS**	
	MIN.	MAX.
A	4.83	5.21
A1	2.27	2.54
A2	1.85	2.16
b	1.07	1.33
b1	1.90	2.41
b2	2.87	3.38
c	0.55	0.68
D	20.80	21.10
D1	16.25	17.65
D2	0.95	1.35
E	15.70	16.13
E1	13.10	14.15
E2	3.68	5.10
E3	1.00	2.60
e	5.44	
N	3	
L	19.80	20.32
L1	3.95	4.47
øP	3.50	3.70
Q	5.49	6.00
S	6.04	6.30

NOTE:
DIMENSIONS DO NOT INCLUDE MOLDFLASH; PROTRUSION OR GATE BURRS

Figure 1   Outline PG-TO247-3, dimensions in mm

7 Appendix A

Table 11   Related links

- IFX CoolMOS CM8 Webpage

- IFX CoolMOS CM8 application note

- IFX CoolMOS CM8 simulation model

- IFX Design tools

Revision history

IPW65R018CM8

Revision 2025-03-07, Rev. 2.1

Previous revisions

Revision	Date	Subjects (major changes since last revision)
2.0	2024-12-19	Release of final version
2.1	2025-03-07	Update of maximum transient thermal impedance and SOA

Trademarks
All referenced product or service names and trademarks are the property of their respective owners.

We Listen to Your Comments Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: erratum@infineon.com