MOSFET – N-Channel, POWERTRENCH®

150 V, 35 A, 42 mΩ

FDP42AN15A0



TO−220
CASE 340AT



Features

- $R_{DS(on)}$ = 36 mΩ (Typ.) @ V_{GS} = 10 V, I_D = 12 A
- $Q_{G(tot)}$ = 33 nC (Typ.) @ V_{GS} = 10 V
- Low Miller Charge
- Low Q_{rr} Body Diode
- UIS Capability (Single Pulse and Repetitive Pulse)
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Consumer Appliances
- Synchronous Rectification
- Uninterruptible Power Supply
- Micro Solar Inverter

MARKING DIAGRAM

&Z = Assembly Code
&3 = Date Code (Year & Week)
&K = Lot Run Traceability Code
FDP42AN15A0 = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 9 of this data sheet.

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	150	V
Gate to Source Voltage	V_{GS}	±20	V
Drain Current – Continuous (V_{GS} = 10 V, T_C = 25°C)	I_D	35	A
Continuous (V_{GS} = 10 V, T_C = 100°C)		24	A
Continuous (T_{amb} = 25°C, V_{GS} = 10 V, with $R_{\theta JA}$ = 43°C/W)		5	A
Pulsed		Figure 4	A
Single Pulse Avalanche Energy	E_{AS}	90	mJ
Power Dissipation	P_D	150	W
Derate above 25°C		1.0	W/°C
Operating and Storage Temperature Range	T_J, T_{STG}	−55 to +175	°C

THERMAL CHARACTERISTICS

Thermal Resistance (Junction to Case)	$R_{\theta JC}$	1.0	°C/W
Maximum Thermal Resistance (Junction to Ambient)	$R_{\theta JA}$	62	°C/W

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
BV_{DSS}	Drain to Source Breakdown Voltage	V_{GS} = 0 V, I_D = 250 μA		150	–	–	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 120 V, V_{GS} = 0 V	T_C = 25°C	–	–	1	μA
			T_C = 150°C	–	–	250	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±20 V		–	–	±100	nA
ON CHARACTERISTICS							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA		2	–	4	V
$R_{DS(on)}$	Drain to Source On Resistance	V_{GS} = 10 V, I_D = 12 A		–	0.036	0.042	Ω
		V_{GS} = 6 V, I_D = 6 A		–	0.040	0.060	Ω
		V_{GS} = 10 V, I_D = 12 A, T_J = 175°C		–	0.090	0.107	Ω
DYNAMIC CHARACTERISTICS							
C_{iss}	Input Capacitance	V_{DS} = 25 V, V_{GS} = 0 V, f = 1 MHz		–	2150	–	pF
C_{oss}	Output Capacitance			–	225	–	pF
C_{rss}	Reverse Transfer Capacitance			–	45	–	pF
$Q_{g(tot)}$	Total Gate Charge at 10 V	V_{DD} = 75 V, I_D = 12 A, I_g = 1.0 mA	V_{GS} = 0 V to 10 V	–	30	39	nC
$Q_{g(th)}$	Threshold Gate Charge		V_{GS} = 0 V to 2 V	–	4.2	5.4	nC
Q_{gs}	Gate to Source Gate Charge	V_{DD} = 75 V, I_D = 12 A, I_g = 1.0 mA		–	9.5	–	nC
Q_{gs2}	Gate Charge Threshold to Plateau			–	5.3	–	nC
Q_{gd}	Gate to Drain “Miller” Charge			–	6.9	–	nC
SWITCHING CHARACTERISTICS (V_{GS} = 10 V)							
t_{on}	Turn-On Time	V_{DD} = 75 V, I_D = 12 A, V_{GS} = 10 V, R_{GS} = 7.5 Ω		–	–	46	ns
$t_{d(on)}$	Turn-On Delay Time			–	11	–	ns
t_r	Rise Time			–	19	–	ns
$t_{d(off)}$	Turn-Off Delay Time			–	27	–	ns
t_f	Fall Time			–	23	–	ns
t_{off}	Turn-Off Time			–	–	74	ns
DRAIN−SOURCE DIODE CHARACTERISTICS							
V_{SD}	Source to Drain Diode Voltage	I_{SD} = 12 A		–	–	1.25	V
		I_{SD} = 6 A		–	–	1.0	V
t_{rr}	Reverse Recovery Time	I_{SD} = 12 A, dI_{SD}/dt = 100 A/μs		–	–	82	ns
Q_{rr}	Reverse Recovery Charge			–	–	204	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Starting T_J = 25°C, L = 0.2 mH, I_{AS} = 30 A.

Typical Characteristics (T_C = 25°C unless otherwise noted)



Figure 1. Normalized Power Dissipation vs. Ambient Temperature



Figure 2. Maximum Continuous Drain Current vs. Case Temperature



Figure 3. Normalized Maximum Transient Thermal Impedance



Figure 4. Peak Current Capability

Typical Characteristics (T_C = 25°C unless otherwise noted)



Figure 5. Forward Bias Safe Operating Area



NOTE: Refer to ON Semiconductor Application Notes AN7514 and AN7515

Figure 6. Unclamped Inductive Switching Capability



Figure 7. Transfer Characteristics



Figure 8. Saturation Characteristics



Figure 9. Drain to Source On Resistance vs. Drain Current



Figure 10. Normalized Drain to Source On Resistance vs. Junction Temperature

Typical Characteristics (T_C = 25°C unless otherwise noted)



Figure 11. Normalized Gate Threshold Voltage vs. Junction Temperature



Figure 12. Normalized Drain to Source Breakdown Voltage vs. Junction Temperature



Figure 13. Capacitance vs. Drain to Source Voltage



Figure 14. Gate Charge Waveforms for Constant Gate Current

Test Circuits and Waveforms



Figure 15. Unclamped Energy Test Circuit



Figure 16. Unclamped Energy Waveforms



Figure 17. Gate Charge Test Circuit



Figure 18. Gate Charge Waveforms



Figure 19. Switching Time Test Circuit



Figure 20. Switching Time Waveforms

PSPICE Electrical Model

```
.SUBCKT FDB42AN15A0  2 1 3 ; rev June 11, 2002
Ca 12 8 6.0e–10
Cb 15 14 8e–10
Cin 6 8 2.1e–9

Dbody 7 5 DbodyMOD
Dbreak 5 11 DbreakMOD
Dplcap 10 5 DplcapMOD

Ebreak 11 7 17 18 159.5
Eds 14 8 5 8 1
Egs 13 8 6 8 1
Esg 6 10 6 8 1
Evthres 6 21 19 8 1
Evtemp 20 6 18 22 1

It 8 17 1

Lgate 1 9 4.81e–9
Ldrain 2 5 1.0e–9
Lsource 3 7 4.63e–9

RLgate 1 9 48.1
RLdrain 2 5 10
RLsource 3 7 46.3

Mmed 16 6 8 8 MmedMOD
Mstro 16 6 8 8 MstroMOD
Mweak 16 21 8 8 MweakMOD

Rbreak 17 18 RbreakMOD 1
Rdrain 50 16 RdrainMOD 14e–3
Rgate 9 20 1.36
RSLC1 5 51 RSLCMOD 1e–6
RSLC2 5 50 1e3
Rsource 8 7 RsourceMOD 20e–3
Rvthres 22 8 RvthresMOD 1
Rvtemp 18 19 RvtempMOD 1
S1a 6 12 13 8 S1AMOD
S1b 13 12 13 8 S1BMOD
S2a 6 15 14 13 S2AMOD
S2b 13 15 14 13 S2BMOD

Vbat 22 19 DC 1

ESLC 51 50  VALUE={(V(5,51)/ABS(V(5,51)))*(PWR(V(5,51)/(1e–6*65),3))}

.MODEL DbodyMOD D (IS=2.4E–11 N=1.08 RS=4.2e–3 TRS1=2.2e–3 TRS2=2.5e–9
+ CJO=1.35e–9 M=6.3e–1 TT=4.8e–8 XTI=3.9)
.MODEL DbreakMOD D (RS=1.5e–1 TRS1=1e–3 TRS2=–8.9e–6)
.MODEL DplcapMOD D (CJO=.43e–9 IS=1e–30 N=10 M=0.66)

.MODEL MmedMOD NMOS (VTO=3.5 KP=4 IS=1e–30 N=10 TOX=1 L=1u W=1u RG=9.3e–1)
.MODEL MstroMOD NMOS (VTO=4.0 KP=70 IS=1e–30 N=10 TOX=1 L=1u W=1u)
.MODEL MweakMOD NMOS (VTO=3.12 KP=0.06 IS=1e–30 N=10 TOX=1 L=1u W=1u RG=9.3e–1 RS=.1)

.MODEL RbreakMOD RES (TC1=1e–3 TC2=–15e–7)
.MODEL RdrainMOD RES (TC1=1.7e–2 TC2=4e–5)
.MODEL RSLCMOD RES (TC1=2.5e–3 TC2=1e–6)
.MODEL RsourceMOD RES (TC1=1e–3 TC2=1e–6)
.MODEL RvthresMOD RES (TC1=–5.3e–3 TC2=–1.5e–5)
.MODEL RvtempMOD RES (TC1=–2.7e–3 TC2=1e–6)

.MODEL S1AMOD VSWITCH (RON=1e–5 ROFF=0.1 VON=–4 VOFF=–1.5)
.MODEL S1BMOD VSWITCH (RON=1e–5 ROFF=0.1 VON=–1.5 VOFF=–4)
.MODEL S2AMOD VSWITCH (RON=1e–5 ROFF=0.1 VON=–1 VOFF=0.5)
.MODEL S2BMOD VSWITCH (RON=1e–5 ROFF=0.1 VON=0.5 VOFF=–1)
.ENDS
```



Note: For further discussion of the PSPICE model, consult **A New PSPICE Sub-Circuit for the Power MOSFET Featuring Global Temperature Options**; IEEE Power Electronics Specialist Conference Records, 1991, written by William J. Hepp and C. Frank Wheatley.

SABER Electrical Model

```
rev June 11, 2002
template FDB42AN15A0 n2,n1,n3
electrical n2,n1,n3
{
var i iscl
dp..model dbodymod =  (isl=2.4e−11,nl=1.08,rs=4.2e−3,trs1=2.2e−3,trs2=2.5e−9,cjo=1.35e−9,m=6.3e−1,tt=4.8e−8,xti=3.9)
dp..model dbreakmod = (rs=1.5e−1,trs1=1e−3,trs2=−8.9e−6)
dp..model dplcapmod =  (cjo=.43e−9,isl=10e−30,nl=10,m=0.66)
m..model mmedmod = (type=_n,vto=3.5,kp=4,is=1e−30, tox=1)
m..model mstrongmod = (type=_n,vto=4.0,kp=70,is=1e−30, tox=1)
m..model mweakmod = (type=_n,vto=3.12,kp=0.06,is=1e−30, tox=1,rs=.1)
sw_vcsp..model s1amod =  (ron=1e−5,roff=0.1,von=−4,voff=−1.5)
sw_vcsp..model s1bmod =  (ron=1e−5,roff=0.1,von=−1.5,voff=−4)
sw_vcsp..model s2amod =  (ron=1e−5,roff=0.1,von=−1,voff=0.5)
sw_vcsp..model s2bmod =  (ron=1e−5,roff=0.1,von=0.5,voff=−1)
c.ca n12 n8 = 6.0e−10
c.cb n15 n14 = 8e−10
c.cin n6 n8 = 2.1e−9

dp.dbody n7 n5 = model=dbodymod
dp.dbreak n5 n11 = model=dbreakmod
dp.dplcap n10 n5 = model=dplcapmod

spe.ebreak n11 n7 n17 n18 = 159.5
spe.eds n14 n8 n5 n8 = 1
spe.egs n13 n8 n6 n8 = 1
spe.esg n6 n10 n6 n8 = 1
spe.evthres n6 n21 n19 n8 = 1
spe.evtemp n20 n6 n18 n22 = 1

i.it n8 n17 = 1

l.lgate n1 n9 = 4.81e−9
l.ldrain n2 n5 = 1.0e−9
l.lsource n3 n7 = 4.63e−9

res.rlgate n1 n9 = 48.1
res.rldrain n2 n5 = 10
res.rlsource n3 n7 = 46.3

m.mmed n16 n6 n8 n8 = model=mmedmod, l=1u, w=1u
m.mstrong n16 n6 n8 n8 = model=mstrongmod, l=1u, w=1u
m.mweak n16 n21 n8 n8 = model=mweakmod, l=1u, w=1u

res.rbreak n17 n18  = 1, tc1=1e−3,tc2=−15e−7
res.rdrain n50 n16  = 14e−3, tc1=1.7e−2,tc2=4e−5
res.rgate n9 n20 = 1.36
res.rslc1 n5 n51  = 1e−6, tc1=2.5e−3,tc2=1e−6
res.rslc2 n5 n50 = 1e3
res.rsource n8 n7  = 20e−3, tc1=1e−3,tc2=1e−6
res.rvthres n22 n8  = 1, tc1=−5.3e−3,tc2=−1.5e−5
res.rvtemp n18 n19  = 1, tc1=−2.7e−3,tc2=1e−6
sw_vcsp.s1a n6 n12 n13 n8 = model=s1amod
sw_vcsp.s1b n13 n12 n13 n8 = model=s1bmod
sw_vcsp.s2a n6 n15 n14 n13 = model=s2amod
sw_vcsp.s2b n13 n15 n14 n13 = model=s2bmod

v.vbat n22 n19 = dc=1
equations {
i (n51−>n50) +=iscl
iscl: v(n51,n50) = ((v(n5,n51)/(1e−9+abs(v(n5,n51))))*((abs(v(n5,n51)*1e6/65))** 3))}
}
```



SPICE Thermal Model

REV 23 June 11, 2002

FDB42AN15A0_Thermal

CTHERM1 TH 6 2e−3
CTHERM2 6 5 4.5e−3
CTHERM3 5 4 7e−3
CTHERM4 4 3 3e−2
CTHERM5 3 2 4e−2
CTHERM6 2 TL 8.5e−1

RTHERM1 TH 6 6.2e−2
RTHERM2 6 5 8.2e−2
RTHERM3 5 4 9.2e−2
RTHERM4 4 3 9.7e−2
RTHERM5 3 2 0.2
RTHERM6 2 TL 0.22

SABER Thermal Model

SABER thermal model FDB42AN15A0_Thermal
template thermal_model th tl
thermal_c th, tl
{
ctherm.ctherm1 th 6 =2e−3
ctherm.ctherm2 6 5 =4.5e−3
ctherm.ctherm3 5 4 =7e−3
ctherm.ctherm4 4 3 =3e−2
ctherm.ctherm5 3 2 =4e−2
ctherm.ctherm6 2 tl =8.5e−1

rtherm.rtherm1 th 6 =6.2e−2
rtherm.rtherm2 6 5 =8.2e−2
rtherm.rtherm3 5 4 =9.2e−2
rtherm.rtherm4 4 3 =9.7e−2
rtherm.rtherm5 3 2 =0.2
rtherm.rtherm6 2 tl =0.22}



PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package	Reel Size	Tape Width	Quantity
FDP42AN15A0	FDP42AN15A0	TO−220	Tube	N/A	800 Units / Tube



TO−220−3LD
CASE 340AT
ISSUE B

DATE 08 AUG 2022

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.00	--	4.70
A1	SEE NOTE "F"		
A2	2.10	--	2.85
b	0.55	--	1.00
b2	1.10	--	1.62
b4	1.42	--	1.62
c	0.36	--	0.60
D	13.90	--	16.30
D1	8.13	--	9.40
D2	11.50	--	14.30
D3	15.42	--	16.51
E	9.65	--	10.67
E1	7.59	--	8.65
e	2.40	--	2.67
H1	6.06	--	6.69
L	12.70	--	14.04
L1	2.70	--	4.10
P	3.50	--	4.00
Q	2.50	--	3.40
z	2.13 REF		
z1	2.06 REF		
Θ	3°	–	5°







GENERIC MARKING DIAGRAM*

XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

NOTES:
A) REFERENCE JEDEC, TO-220, VARIATION AB
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
E) DOES NOT COMPLY JEDEC STANDARD VALUE.
F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
G) PRESENCE IS SUPPLIER DEPENDENT
H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

DOCUMENT NUMBER:	**98AON13818G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−220−3LD**	**PAGE 1 OF 1**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales