IXYS

HiPerFET™ Power MOSFETs

N-Channel Enhancement Mode
High dv/dt, Low t_{rr}, HDMOS™ Family

Obsolete:
IXFM10N100
IXFM12N100

	V_{DSS}	I_{D25}	$R_{DS(on)}$
IXFH/~~IXFM~~ 10 N100	1000 V	10 A	1.20 Ω
IXFH/~~IXFM~~ 12 N100	1000 V	12 A	1.05 Ω

$t_{rr} \leq 250$ ns



TO-247 AD (IXFH)



~~TO-204 AA (IXFM)~~

Package not available



G = Gate, D = Drain,
S = Source, TAB = Drain

Symbol	Test Conditions		Maximum Ratings	
V_{DSS}	T_J = 25°C to 150°C		1000	V
V_{DGR}	T_J = 25°C to 150°C; R_{GS} = 1 MΩ		1000	V
V_{GS}	Continuous		±20	V
V_{GSM}	Transient		±30	V
I_{D25}	T_C = 25°C	10N100	10	A
		12N100	12	A
I_{DM}	T_C = 25°C, pulse width limited by T_{JM}	10N100	40	A
		12N100	48	A
I_{AR}	T_C = 25°C	10N100	10	A
		12N100	12	A
E_{AR}	T_C = 25°C		30	mJ
dv/dt	$I_S \leq I_{DM}$, di/dt ≤ 100 A/µs, $V_{DD} \leq V_{DSS}$, $T_J \leq 150°C$, R_G = 2 Ω		5	V/ns
P_D	T_C = 25°C		300	W
T_J			-55 ... +150	°C
T_{JM}			150	°C
T_{stg}			-55 ... +150	°C
T_L	1.6 mm (0.062 in.) from case for 10 s		300	°C
M_d	Mounting torque		1.13/10	Nm/lb.in.
Weight			TO-204 = 18 g, TO-247 = 6 g	

Symbol	Test Conditions		Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
V_{DSS}	V_{GS} = 0 V, I_D = 3 mA		1000			V
$V_{GS(th)}$	$V_{DS} = V_{GS}$, I_D = 4 mA		2.0		4.5	V
I_{GSS}	V_{GS} = ±20 V_{DC}, V_{DS} = 0				±100	nA
I_{DSS}	V_{DS} = 0.8 • V_{DSS}	T_J = 25°C			250	µA
	V_{GS} = 0 V	T_J = 125°C			1	mA
$R_{DS(on)}$	V_{GS} = 10 V, I_D = 0.5 • I_{D25}	10N100			1.20	Ω
		12N100			1.05	Ω
	Pulse test, t ≤ 300 µs, duty cycle d ≤ 2 %					

Features
- International standard packages
- Low $R_{DS\ (on)}$ HDMOS™ process
- Rugged polysilicon gate cell structure
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
  - easy to drive and to protect
- Fast intrinsic Rectifier

Applications
- DC-DC converters
- Synchronous rectification
- Battery chargers
- Switched-mode and resonant-mode power supplies
- DC choppers
- AC motor control
- Temperature and lighting controls
- Low voltage relays

Advantages
- Easy to mount with 1 screw (TO-247) (isolated mounting screw hole)
- Space savings
- High power density

© 2004 IXYS All rights reserved

Symbol	Test Conditions	Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
g_{fs}	V_{DS} = 10 V; I_D = 0.5 • I_{D25}, pulse test	6	10		S
C_{iss}	V_{GS} = 0 V, V_{DS} = 25 V, f = 1 MHz		4000		pF
C_{oss}			310		pF
C_{rss}			70		pF
$t_{d(on)}$	V_{GS} = 10 V, V_{DS} = 0.5 • V_{DSS}, I_D = 0.5 • I_{D25} R_G = 2 Ω (External),		21	50	ns
t_r			33	50	ns
$t_{d(off)}$			62	100	ns
t_f			32	50	ns
$Q_{g(on)}$	V_{GS} = 10 V, V_{DS} = 0.5 • V_{DSS}, I_D = 0.5 • I_{D25}		122	155	nC
Q_{gs}			30	45	nC
Q_{gd}			50	80	nC
R_{thJC}				0.42	K/W
R_{thCK}			0.25		K/W

Source-Drain Diode

Symbol	Test Conditions		Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
I_S	V_{GS} = 0 V	10N100			10	A
		12N100			12	A
		13N100			12.5	A
I_{SM}	Repetitive; pulse width limited by T_{JM}	10N100			40	A
		12N100			48	A
		13N100			50	A
V_{SD}	I_F = I_S, V_{GS} = 0 V, Pulse test, t ≤ 300 µs, duty cycle d ≤ 2 %				1.5	V
t_{rr}	I_F = I_S -di/dt = 100 A/µs, V_R = 100 V	T_J = 25°C			250	ns
		T_J = 125°C			400	ns
Q_{RM}		T_J = 25°C		1		µC
		T_J = 125°C		2		µC
I_{RM}		T_J = 25°C		10		A
		T_J = 125°C		15		A

TO-247 AD (IXFH) Outline



Terminals: 1 - Gate 2 - Drain
3 - Source Tab - Drain

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	4.7	5.3	.185	.209
A_1	2.2	2.54	.087	.102
A_2	2.2	2.6	.059	.098
b	1.0	1.4	.040	.055
b_1	1.65	2.13	.065	.084
b_2	2.87	3.12	.113	.123
C	.4	.8	.016	.031
D	20.80	21.46	.819	.845
E	15.75	16.26	.610	.640
e	5.20	5.72	0.205	0.225
L	19.81	20.32	.780	.800
L1		4.50		.177
∅P	3.55	3.65	.140	.144
Q	5.89	6.40	0.232	0.252
R	4.32	5.49	.170	.216
S	6.15 BSC		242 BSC	

TO-204 AA (IXFM) Outline



Pins 1 - Gate 2 - Source
Case - Drain

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	6.4	11.4	.250	.450
A1		3.42		.135
∅b	.97	1.09	.038	.043
∅D		22.22		.875
e	10.67	11.17	.420	.440
e1	5.21	5.71	.205	.225
L	7.93		.312	
∅p	3.84	4.19	.151	.165
∅p1	3.84	4.19	.151	.165
q	30.15 BSC		1.187 BSC	
R		13.33		.525
R1		4.77		.188
s	16.64	17.14	.655	.675

IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,881,106 5,017,508 5,049,961 5,187,117 5,486,715 6,306,728B1 6,259,123B1 6,306,728B1 4,850,072 4,931,844 5,034,796 5,063,307 5,237,481 5,381,025 6,404,065B1 6,162,665 6,534,343 6,583,505

Fig. 1 Output Characteristics



Fig. 2 Input Admittance



Fig. 3 $R_{DS(on)}$ vs. Drain Current



Fig. 4 Temperature Dependence of Drain to Source Resistance



Fig. 5 Drain Current vs. Case Temperature



Fig. 6 Temperature Dependence of Breakdown and Threshold Voltage



© 2004 IXYS All rights reserved

Fig.7 Gate Charge Characteristic Curve



Fig.8 Capacitance Curves



Fig.9 Source Current vs. Source to Drain Voltage



Fig.10 Transient Thermal Impedance



IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,881,106 5,017,508 5,049,961 5,187,117 5,486,715 6,306,728B1 6,259,123B1 6,306,728B1 4,850,072 4,931,844 5,034,796 5,063,307 5,237,481 5,381,025 6,404,065B1 6,162,665 6,534,343 6,583,505

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.