**Infineon**

MOSFET

OptiMOS^{TM}3 Power-Transistor, 120 V

Features

- N-channel, normal level
- Excellent gate charge x $R_{DS(on)}$ product (FOM)
- Very low on-resistance $R_{DS(on)}$
- 150 °C operating temperature
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC[1] for target application
- Ideal for high-frequency switching and synchronous rectification
- Halogen-free according to IEC61249-2-21

SuperSO8

Table 1   Key Performance Parameters

Parameter	Value	Unit
V_{DS}	120	V
$R_{DS(on),max}$	7.7	mΩ
I_D	98	A

Type / Ordering Code	Package	Marking	Related Links
BSC077N12NS3 G	PG-TDSON-8	077N12NS	-

[1] J-STD20 and JESD22

Table of Contents

1 Maximum ratings

at T_A=25 °C, unless otherwise specified

Table 2   Maximum ratings

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Continuous drain current	I_D	- - -	- - -	98 61 13.4	A	T_C=25 °C T_C=100 °C T_A=25 °C, R_{thJA}=45 K/W[1]
Pulsed drain current[2]	$I_{D,pulse}$	-	-	392	A	T_C=25 °C
Avalanche energy, single pulse	E_{AS}	-	-	330	mJ	I_D=50 A, R_{GS}=25 Ω
Gate source voltage	V_{GS}	-20	-	20	V	-
Power dissipation	P_{tot}	-	-	139	W	T_C=25 °C
Operating and storage temperature	T_j, T_{stg}	-55	-	150	°C	IEC climatic category; DIN IEC 68-1: 55/150/56

2 Thermal characteristics

Table 3   Thermal characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case, bottom	R_{thJC}	-	0.5	0.9	K/W	-
Thermal resistance, junction - case, top	R_{thJC}	-	-	18	K/W	-
Thermal resistance, junction - ambient, minimal footprint	R_{thJA}	-	-	75	K/W	-
Thermal resistance, junction - ambient, 6 cm² cooling area[1]	R_{thJA}	-	-	50	K/W	-

[1] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.
[2] see Diagram 3

3 Electrical characteristics

Table 4 Static characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	120	-	-	V	V_{GS}=0 V, I_D=1 mA
Gate threshold voltage	$V_{GS(th)}$	2	3	4	V	V_{DS}=V_{GS}, I_D=110 µA
Zero gate voltage drain current	I_{DSS}	- -	0.01 10	1 100	µA	V_{DS}=100 V, V_{GS}=0 V, T_j=25 °C V_{DS}=100 V, V_{GS}=0 V, T_j=125 °C
Gate-source leakage current	I_{GSS}	-	1	100	nA	V_{GS}=20 V, V_{DS}=0 V
Drain-source on-state resistance	$R_{DS(on)}$	-	6.6	7.7	mΩ	V_{GS}=10 V, I_D=50 A
Gate resistance[1]	R_G	-	1	1.5	Ω	-
Transconductance	g_{fs}	40	80	-	S	$\|V_{DS}\|$>2$\|I_D\|R_{DS(on)max}$, I_D=50 A

Table 5 Dynamic characteristics[1]

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Input capacitance	C_{iss}	-	4300	5700	pF	V_{GS}=0 V, V_{DS}=60 V, f=1 MHz
Output capacitance	C_{oss}	-	550	730	pF	V_{GS}=0 V, V_{DS}=60 V, f=1 MHz
Reverse transfer capacitance	C_{rss}	-	28	49	pF	V_{GS}=0 V, V_{DS}=60 V, f=1 MHz
Turn-on delay time	$t_{d(on)}$	-	15	-	ns	V_{DD}=60 V, V_{GS}=10 V, I_D=25 A, $R_{G,ext}$=2.7 Ω
Rise time	t_r	-	8	-	ns	V_{DD}=60 V, V_{GS}=10 V, I_D=25 A, $R_{G,ext}$=2.7 Ω
Turn-off delay time	$t_{d(off)}$	-	26	-	ns	V_{DD}=60 V, V_{GS}=10 V, I_D=25 A, $R_{G,ext}$=2.7 Ω
Fall time	t_f	-	7	-	ns	V_{DD}=60 V, V_{GS}=10 V, I_D=25 A, $R_{G,ext}$=2.7 Ω

Table 6 Gate charge characteristics[2]

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Gate to source charge	Q_{gs}	-	21	-	nC	V_{DD}=60 V, I_D=25 A, V_{GS}=0 to 10 V
Gate to drain charge	Q_{gd}	-	15	-	nC	V_{DD}=60 V, I_D=25 A, V_{GS}=0 to 10 V
Switching charge	Q_{sw}	-	29	-	nC	V_{DD}=60 V, I_D=25 A, V_{GS}=0 to 10 V
Gate charge total[1]	Q_g	-	66	88	nC	V_{DD}=60 V, I_D=25 A, V_{GS}=0 to 10 V
Gate plateau voltage	$V_{plateau}$	-	4.7	-	V	V_{DD}=60 V, I_D=25 A, V_{GS}=0 to 10 V
Output charge[1]	Q_{oss}	-	76	100	nC	V_{DD}=60 V, V_{GS}=0 V

[1] Defined by design. Not subject to production test.
[2] See ″Gate charge waveforms″ for parameter definition.

Table 7   Reverse diode

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Diode continous forward current	I_S	-	-	98	A	T_C=25 °C
Diode pulse current	$I_{S,pulse}$	-	-	392	A	T_C=25 °C
Diode forward voltage	V_{SD}	-	0.9	1.2	V	V_{GS}=0 V, I_F=50 A, T_j=25 °C
Reverse recovery time[1]	t_{rr}	-	98	-	ns	V_R=60 V, I_F=25, di_F/dt=100 A/μs
Reverse recovery charge[1]	Q_{rr}	-	264	-	nC	V_R=60 V, I_F=25, di_F/dt=100 A/μs

[1] Defined by design. Not subject to production test.

4   Electrical characteristics diagrams

Diagram 1: Power dissipation

P_{tot}=f(T_C)

Diagram 2: Drain current

I_D=f(T_C); V_{GS}≥10 V

Diagram 3: Safe operating area

I_D=f(V_{DS}); T_C=25 °C; D=0; parameter: t_p

Diagram 4: Max. transient thermal impedance

Z_{thJC}=f(t_p); parameter: D=t_p/T

Diagram 5: Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C; parameter: V_{GS}

Diagram 6: Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C; parameter: V_{GS}

Diagram 7: Typ. transfer characteristics

I_D=f(V_{GS}); |V_{DS}|>2|I_D|$R_{DS(on)max}$; parameter: T_j

Diagram 8: Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C

Diagram 9: Drain-source on-state resistance

98 %

typ

$R_{DS(on)}$=f(T_j); I_D=50 A; V_{GS}=10 V

Diagram 10: Typ. gate threshold voltage

1100 µA

110 µA

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}; parameter: I_D

Diagram 11: Typ. capacitances

Ciss

Coss

Crss

C=f(V_{DS}); V_{GS}=0 V; f=1 MHz

Diagram 12: Forward characteristics of reverse diode

- 25 °C
- 150 °C
- 25 °C, 98%
- 150 °C, 98%

I_F=f(V_{SD}); parameter: T_j

Diagram 13: Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω; parameter: $T_{j(start)}$

Diagram 14: Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=25 A pulsed; parameter: V_{DD}

Diagram 15: Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=1 mA

Gate charge waveforms

5 Package Outlines

DIM	MILLIMETERS	
	MIN	MAX
A	0.90	1.10
b	0.31	0.54
b1	0.02	0.22
c	0.15	0.35
D	5.15	5.49
D1	4.95	5.35
D2	3.70	4.40
E	5.95	6.35
E1	5.70	6.10
E2	3.40	3.80
e	1.27	
N	8	
L	0.45	0.71
M	0.45	0.75
Θ	8.5°	12°
aaa	0.25	
eee	0.08	

DOCUMENT NO.
Z8B00003332

SCALE

EUROPEAN PROJECTION

ISSUE DATE
10-04-2013

REVISION
04

Figure 1   Outline PG-TDSON-8, dimensions in mm

Dimension in mm

**Figure 2   Outline TDSON-8 Tape**

Figure 3   Outline Footprint TDSON-8

Revision History

BSC077N12NS3 G

Revision: 2015-12-15, Rev. 2.8

Previous Revision

Revision	Date	Subjects (major changes since last revision)
2.7	2014-10-02	Rev. 2.7
2.8	2015-12-15	Update of dynamic parameters td(on), td(off), tr, tf

Trademarks of Infineon Technologies AG

AURIX™, C166™, CanPAK™, CIPOS™, CoolGaN™, CoolMOS™, CoolSET™, CoolSiC™, CORECONTROL™, CROSSAVE™, DAVE™, DI-POL™, DrBlade™, EasyPIM™, EconoBRIDGE™, EconoDUAL™, EconoPACK™, EconoPIM™, EiceDRIVER™, eupec™, FCOS™, HITFET™, HybridPACK™, Infineon™, ISOFACE™, IsoPACK™, i-Wafer™, MIPAQ™, ModSTACK™, my-d™, NovalithIC™, OmniTune™, OPTIGA™, OptiMOS™, ORIGA™, POWERCODE™, PRIMARION™, PrimePACK™, PrimeSTACK™, PROFET™, PRO-SIL™, RASIC™, REAL3™, ReverSave™, SatRIC™, SIEGET™, SIPMOS™, SmartLEWIS™, SOLID FLASH™, SPOC™, TEMPFET™, thinQ!™, TRENCHSTOP™, TriCore™.

Trademarks updated August 2015

Other Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

We Listen to Your Comments
Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to:
erratum@infineon.com

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.