PerFET™ Power Transistor

FEATURES

- Excellent FOM
- Reliability meets AEC-Q101 requirements
- Wettable flank leads for enhanced AOI
- 100% UIS and Rg tested
- 175°C operating junction temperature
- RoHS Compliant
- Halogen-free

KEY PERFORMANCE PARAMETERS			
PARAMETER		**VALUE**	**UNIT**
V_{DS}		100	V
$R_{DS(on)}$ (max)	V_{GS} = 10V	24	mΩ
	V_{GS} = 7V	28.8	
Q_g	V_{GS} = 10V	8.1	nC

APPLICATIONS

- Solenoid and motor drivers
- DC-DC converters
- Load Switch
- SMPS

Pb-Free RoHS COMPLIANT HALOGEN FREE

PDFN56U



Note: MSL 1 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	100	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25°C	I_D	34	A
	T_C = 100°C		24	
	T_A = 25°C		7.5	
Pulsed Drain Current (Note 1)		I_{DM}	136	A
Single Pulse Avalanche Current (Note 2)		I_{AS}	6.5	A
Single Pulse Avalanche Energy (Note 2)		E_{AS}	6.3	mJ
Total Power Dissipation	T_C = 25°C	P_D	63	W
	T_C = 125°C		21	
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +175	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	2.38	°C/W
Junction to Ambient Thermal Resistance (Note 3)	$R_{\Theta JA}$	50	°C/W

Notes:

1. Pulse Width ≤ 100μs.
2. L = 0.3mH, V_{GS} = 10V, R_G = 25Ω, Starting T_J = 25°C.
3. Device on a PCB FR4 with 1 in^2 (single layer, 2 oz thickness) copper area for drain connection.

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 1mA	BV_{DSS}	100	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	$V_{GS(TH)}$	2.4	3	3.6	V
Gate Body Leakage	V_{GS} = ±20V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Drain-Source Leakage Current	V_{GS} = 0V, V_{DS} = 100V	I_{DSS}	--	--	1	μA
	V_{GS} = 0V, V_{DS} = 100V T_J = 125°C		--	--	100	
Drain-Source On-State Resistance (Note 4)	V_{GS} = 10V, I_D = 17A	$R_{DS(on)}$	--	19	24	mΩ
	V_{GS} = 7V, I_D = 17A		--	23	28.8	
Forward Transconductance (Note 4)	V_{DS} = 10V, I_D = 4.3A	g_{fs}	--	28	--	S
Dynamic (Note 5)						
Total Gate Charge	V_{DS} = 50V, I_D = 7.5A, V_{GS} = 7V	Q_g	--	6	--	nC
Total Gate Charge	V_{DS} = 50V, I_D = 7.5A, V_{GS} = 10V	Q_g	--	8.1	--	nC
Gate-Source Charge		Q_{gs}	--	2.8	--	
Gate-Drain Charge		Q_{gd}	--	2.1	--	
Input Capacitance	V_{DS} = 60V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	512	--	pF
Output Capacitance		C_{oss}	--	112	--	
Reverse Transfer Capacitance		C_{rss}	--	17	--	
Gate Resistance	f = 1.0MHz	Rg	--	1.1	--	Ω
Switching (Note 6)						
Turn-On Delay Time	V_{DD} = 50V, R_G = 6Ω, I_D = 7.5A, V_{GS} = 10V	$t_{d(on)}$	--	6.4	--	ns
Turn-On Rise Time		t_r	--	16	--	
Turn-Off Delay Time		$t_{d(off)}$	--	10	--	
Turn-Off Fall Time		t_f	--	8	--	
Source-Drain Diode						
Forward Voltage (Note 4)	I_S = 17A, V_{GS} = 0V	V_{SD}	--	--	1.1	V
Reverse Recovery Time	I_S = 7.5A, di/dt = 100A/μs	t_{rr}	--	41	--	ns
Reverse Recovery Charge		Q_{rr}	--	52	--	nC

Notes:

4. Pulse test: Pulse Width ≤ 300μs, duty cycle ≤ 2%.
5. Defined by design. Not subject to production test.
6. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM240NH10CR RLG	PDFN56U	2,500pcs / 13” Reel

CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature



On-Resistance vs. Gate-Source Voltage



CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Capacitance vs. Drain-Source Voltage



BV_{DSS} vs. Junction Temperature



Maximum Safe Operating Area, Junction-to-Case



Source-Drain Diode Forward Current vs. Voltage



Normalized Thermal Transient Impedance, Junction-to-Case



CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Power Dissipation



Drain Current



Normalized gate threshold voltage vs Temperature



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

PDFN56U









DETAIL A
(SCALE 2:1)



SUGGESTED PAD LAYOUT
(REFERENCE ONLY)



MARKING DIAGRAM

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEITA ED-7500B, EIAJ SC-111BB.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
5. DWG NO. REF: HQ2SD07-PDFN56U-023 REV B.

240NH10 = Device marking
Y = Year code
WW = Week code (01~52)
L = Lot code (1~9,A~Z)
F = Factory code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.