IXYS

Polar™ Power MOSFET

IXTK180N15P

V_{DSS} = 150V
I_{D25} = 180A
$R_{DS(on)}$ ≤ 11mΩ

N-Channel Enhancement Mode
Avalanche Rated



TO-264



G = Gate D = Drain
S = Source Tab = Drain

Symbol	Test Conditions	Maximum Ratings	
V_{DSS}	T_J = 25°C to 175°C	150	V
V_{DGR}	T_J = 25°C to 175°C, R_{GS} = 1MΩ	150	V
V_{GSS}	Continuous	± 20	V
V_{GSM}	Transient	± 30	V
I_{D25}	T_C = 25°C	180	A
$I_{L(RMS)}$	External Lead Current Limit	75	A
I_{DM}	T_C = 25°C, Pulse Width Limited by T_{JM}	380	A
I_A	T_C = 25°C	60	A
E_{AS}	T_C = 25°C	4	J
P_D	T_C = 25°C	800	W
dv/dt	$I_S \le I_{DM}$, $V_{DD} \le V_{DSS}$, $T_J \le 175°C$	10	V/ns
T_J		-55 ... +175	°C
T_{JM}		175	°C
T_{stg}		-55 ... +175	°C
T_L	1.6mm (0.062 in.) from Case for 10s	300	°C
T_{SOLD}	Plastic Body for 10s	260	°C
M_d	Mounting Torque	1.13/10	Nm/lb.in.
Weight		10	g

Features

- International Standard Package
- Avalanche Rated
- Low Package Inductance
- Fast intrinsic Diode
- Dynamic dv/dt Rated
- Low $R_{DS(on)}$ and Q_G

Advantages

- Easy to mount
- Space savings
- High power density

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{DSS}	V_{GS} = 0V, I_D = 250μA	150			V
$V_{GS(th)}$	$V_{DS} = V_{GS}$, I_D = 500μA	2.5		5.0	V
I_{GSS}	V_{GS} = ± 20V, V_{DS} = 0V			± 200	nA
I_{DSS}	$V_{DS} = V_{DSS}$, V_{GS} = 0V			25	μA
	T_J = 150°C			250	μA
$R_{DS(on)}$	V_{GS} = 10V, $I_D = 0.5 \bullet I_{D25}$, Note 1			11	mΩ

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	V_{DS} = 10V, I_D = 0.5 • I_{DSS}, Note 1	55	86		S
C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		7000		pF
C_{oss}			2250		pF
C_{rss}			515		pF
$t_{d(on)}$	**Resistive Switching Times**		30		ns
t_r	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 60A		32		ns
$t_{d(off)}$	R_G = 3.3Ω (External)		150		ns
t_f			36		ns
$Q_{g(on)}$	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 0.5 • I_{DSS}		240		nC
Q_{gs}			55		nC
Q_{gd}			140		nC
R_{thJC}				0.18	°C/W
R_{thCS}			0.15		°C/W

Source-Drain Diode

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
I_S	V_{GS} = 0V			180	A
I_{SM}	Repetitive, Pulse Width Limited by T_{JM}			380	A
V_{SD}	I_F = I_S, V_{GS} = 0V, Note 1			1.5	V
t_{rr}	I_F = 25A, -di/dt = 100A/μs		150		ns
Q_{RM}	V_R = 100V, V_{GS} = 0V		2.3		μC

Note 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.

TO-264 (IXTK) Outline



Terminals: 1 - Gate
2 - Drain
3 - Source
4 - Drain

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	4.82	5.13	.190	.202
A1	2.54	2.89	.100	.114
A2	2.00	2.10	.079	.083
b	1.12	1.42	.044	.056
b1	2.39	2.69	.094	.106
b2	2.90	3.09	.114	.122
c	0.53	0.83	.021	.033
D	25.91	26.16	1.020	1.030
E	19.81	19.96	.780	.786
e	5.46 BSC		.215 BSC	
J	0.00	0.25	.000	.010
K	0.00	0.25	.000	.010
L	20.32	20.83	.800	.820
L1	2.29	2.59	.090	.102
P	3.17	3.66	.125	.144
Q	6.07	6.27	.239	.247
Q1	8.38	8.69	.330	.342
R	3.81	4.32	.150	.170
R1	1.78	2.29	.070	.090
S	6.04	6.30	.238	.248
T	1.57	1.83	.062	.072

Fig. 1. Output Characteristics @ 25ºC



Fig. 2. Extended Output Characteristics @ 25ºC



Fig. 3. Output Characteristics @ 150ºC



Fig. 4. $R_{DS(on)}$ Normalized to I_D = 90A Value vs. Junction Temperature



Fig. 5. $R_{DS(on)}$ Normalized to I_D = 90A Value vs. Drain Current



Fig. 6. Drain Current vs. Case Temperature



Fig. 7. Input Admittance



Fig. 8. Transconductance



Fig. 9. Source Current vs. Source-To-Drain Voltage



Fig. 10. Gate Charge



Fig. 11. Capacitance



Fig. 12. Forward-Bias Safe Operating Area



Fig. 13. Maximum Transient Thermal Impedance