
**Is Now Part of**


**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**
**www.onsemi.com**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

# N-Channel UltraFET Power MOSFET 80 V, 75 A, 14 mΩ

## Packaging

JEDEC TO-220AB




## Features

- Ultra Low On-Resistance
  - $r_{DS(ON)}$ = 0.014Ω, $V_{GS}$ = 10V
- Simulation Models
  - Temperature Compensated PSPICE® and SABER™ Electrical Models
  - Spice and SABER Thermal Impedance Models
  - www.fairchildsemi.com
- Peak Current vs Pulse Width Curve
- UIS Rating Curve

## Symbol




## Ordering Information

| PART NUMBER | PACKAGE | BRAND |
|---|---|---|
| HUF75542P3 | TO-220AB | 75542P |

## Absolute Maximum Ratings $T_C$ = 25°C, Unless Otherwise Specified

| | | HUF75542P3 | UNITS |
|---|---|---|---|
| Drain to Source Voltage (Note 1) | $V_{DSS}$ | 80 | V |
| Drain to Gate Voltage ($R_{GS}$ = 20kΩ) (Note 1) | $V_{DGR}$ | 80 | V |
| Gate to Source Voltage | $V_{GS}$ | ±20 | V |
| Drain Current | | | |
| Continuous ($T_C$ = 25°C, $V_{GS}$ = 10V) (Figure 2) | $I_D$ | 75 | A |
| Continuous ($T_C$ = 100°C, $V_{GS}$ = 10V) (Figure 2) | $I_D$ | 58 | A |
| Pulsed Drain Current | $I_{DM}$ | Figure 4 | |
| Pulsed Avalanche Rating | UIS | Figures 6, 14, 15 | |
| Power Dissipation | $P_D$ | 230 | W |
| Derate Above 25°C | | 1.54 | W/°C |
| Operating and Storage Temperature | $T_J$, $T_{STG}$ | -55 to 175 | °C |
| Maximum Temperature for Soldering | | | |
| Leads at 0.063in (1.6mm) from Case for 10s | $T_L$ | 300 | °C |
| Package Body for 10s, See Techbrief TB334 | $T_{pkg}$ | 260 | °C |

NOTE:

1. $T_J$ = 25°C to 150°C.

***CAUTION:*** *Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.*

**Product reliability information can be found at http://www.fairchildsemi.com/products/discrete/reliability/index.html**
**For severe environments, see our Automotive HUFA series.**
**All Fairchild semiconductor products are manufactured, assembled and tested under ISO9000 and QS9000 quality systems certification.**

## Electrical Specifications $T_C = 25^oC$, Unless Otherwise Specified

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|---|---|---|---|---|---|---|
| **OFF STATE SPECIFICATIONS** | | | | | | |
| Drain to Source Breakdown Voltage | $BV_{DSS}$ | $I_D$ = 250µA, $V_{GS}$ = 0V (Figure 11) | 80 | - | - | V |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$ = 75V, $V_{GS}$ = 0V | - | - | 1 | µA |
| | | $V_{DS}$ = 70V, $V_{GS}$ = 0V, $T_C = 150^oC$ | - | - | 250 | µA |
| Gate to Source Leakage Current | $I_{GSS}$ | $V_{GS}$ = ±20V | - | - | ±100 | nA |
| **ON STATE SPECIFICATIONS** | | | | | | |
| Gate to Source Threshold Voltage | $V_{GS(TH)}$ | $V_{GS} = V_{DS}$, $I_D$ = 250µA (Figure 10) | 2 | - | 4 | V |
| Drain to Source On Resistance | $r_{DS(ON)}$ | $I_D$ = 75A, $V_{GS}$ = 10V (Figure 9) | - | 0.012 | 0.014 | Ω |
| **THERMAL SPECIFICATIONS** | | | | | | |
| Thermal Resistance Junction to Case | $R_{\theta JC}$ | TO-220 | - | - | 0.65 | $^oC/W$ |
| Thermal Resistance Junction to Ambient | $R_{\theta JA}$ | | - | - | 62 | $^oC/W$ |
| **SWITCHING SPECIFICATIONS** ($V_{GS}$ = 10V) | | | | | | |
| Turn-On Time | $t_{ON}$ | $V_{DD}$ = 40V, $I_D$ = 75A<br>$V_{GS}$ = 10V,<br>$R_{GS}$ = 3.9Ω<br>(Figures 18, 19) | - | - | 195 | ns |
| Turn-On Delay Time | $t_{d(ON)}$ | | - | 12.5 | - | ns |
| Rise Time | $t_r$ | | - | 117 | - | ns |
| Turn-Off Delay Time | $t_{d(OFF)}$ | | - | 50 | - | ns |
| Fall Time | $t_f$ | | - | 80 | - | ns |
| Turn-Off Time | $t_{OFF}$ | | - | - | 195 | ns |
| **GATE CHARGE SPECIFICATIONS** | | | | | | |
| Total Gate Charge | $Q_{g(TOT)}$ | $V_{GS}$ = 0V to 20V; $V_{DD}$ = 40V, $I_D$ = 75A, $I_{g(REF)}$ = 1.0mA (Figures 13, 16, 17) | - | 150 | 180 | nC |
| Gate Charge at 10V | $Q_{g(10)}$ | $V_{GS}$ = 0V to 10V | - | 80 | 96 | nC |
| Threshold Gate Charge | $Q_{g(TH)}$ | $V_{GS}$ = 0V to 2V | - | 5.7 | 7 | nC |
| Gate to Source Gate Charge | $Q_{gs}$ | | - | 15 | - | nC |
| Gate to Drain "Miller" Charge | $Q_{gd}$ | | - | 33 | - | nC |
| **CAPACITANCE SPECIFICATIONS** | | | | | | |
| Input Capacitance | $C_{ISS}$ | $V_{DS}$ = 25V, $V_{GS}$ = 0V,<br>f = 1MHz<br>(Figure 12) | - | 2750 | - | pF |
| Output Capacitance | $C_{OSS}$ | | - | 700 | - | pF |
| Reverse Transfer Capacitance | $C_{RSS}$ | | - | 250 | - | pF |

## Source to Drain Diode Specifications

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|---|---|---|---|---|---|---|
| Source to Drain Diode Voltage | $V_{SD}$ | $I_{SD}$ = 75A | - | - | 1.25 | V |
| | | $I_{SD}$ = 37.5A | - | - | 1.00 | V |
| Reverse Recovery Time | $t_{rr}$ | $I_{SD}$ = 75A, $dI_{SD}/dt$ = 100A/µs | - | - | 102 | ns |
| Reverse Recovered Charge | $Q_{RR}$ | $I_{SD}$ = 75A, $dI_{SD}/dt$ = 100A/µs | - | - | 255 | nC |

## Typical Performance Curves




FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE




FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 4. PEAK CURRENT CAPABILITY

## Typical Performance Curves (Continued)




FIGURE 5. FORWARD BIAS SAFE OPERATING AREA




NOTE: Refer to Fairchild Application Notes AN9321 and AN9322.

FIGURE 6. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY




FIGURE 7. TRANSFER CHARACTERISTICS




FIGURE 8. SATURATION CHARACTERISTICS




FIGURE 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE




FIGURE 10. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE

## Typical Performance Curves (Continued)




FIGURE 11. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE




FIGURE 12. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE




NOTE: Refer to Fairchild Application Notes AN7254 and AN7260.

FIGURE 13. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT

## Test Circuits and Waveforms




FIGURE 14. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 15. UNCLAMPED ENERGY WAVEFORMS




FIGURE 16. GATE CHARGE TEST CIRCUIT




FIGURE 17. GATE CHARGE WAVEFORMS




FIGURE 18. SWITCHING TIME TEST CIRCUIT




FIGURE 19. SWITCHING TIME WAVEFORM

## PSPICE Electrical Model

.SUBCKT HUF75542P3 2 1 3 ; rev 15 Feb 2000

CA 12 8 4.4e-9
CB 15 14 4.2e-9
CIN 6 8 2.5e-9

DBODY 7 5 DBODYMOD
DBREAK 5 11 DBREAKMOD
DPLCAP 10 5 DPLCAPMOD

EBREAK 11 7 17 18 87.2
EDS 14 8 5 8 1
EGS 13 8 6 8 1
ESG 6 10 6 8 1
EVTHRES 6 21 19 8 1
EVTEMP 20 6 18 22 1

IT 8 17 1

LDRAIN 2 5 1.0e-9
LGATE 1 9 2.6e-9
LSOURCE 3 7 1.1e-9

MMED 16 6 8 8 MMEDMOD
MSTRO 16 6 8 8 MSTROMOD
MWEAK 16 21 8 8 MWEAKMOD

RBREAK 17 18 RBREAKMOD 1
RDRAIN 50 16 RDRAINMOD 5.5e-3
RGATE 9 20 1.0
RLDRAIN 2 5 10
RLGATE 1 9 26
RLSOURCE 3 7 11
RSLC1 5 51 RSLCMOD 1e-6
RSLC2 5 50 1e3
RSOURCE 8 7 RSOURCEMOD 3.3e-3
RVTHRES 22 8 RVTHRESMOD 1
RVTEMP 18 19 RVTEMPMOD 1

S1A 6 12 13 8 S1AMOD
S1B 13 12 13 8 S1BMOD
S2A 6 15 14 13 S2AMOD
S2B 13 15 14 13 S2BMOD

VBAT 22 19 DC 1




ESLC 51 50 VALUE={(V(5,51)/ABS(V(5,51)))*(PWR(V(5,51)/(1e-6*230),2.5))}

.MODEL DBODYMOD D (IS = 2.5e-12 RS = 2.85e-3 XTI = 5.5 TRS1 = 2e-3 TRS2 = 1e-6 CJO = 3.2e-9 TT = 5.5e-8 M = 0.6)
.MODEL DBREAKMOD D (RS = 2.9e- 1TRS1 = 1e- 3TRS2 = 1e-6)
.MODEL DPLCAPMOD D (CJO = 3.4e- 9IS = 1e-3 0M = 0.8 N = 10)
.MODEL MMEDMOD NMOS (VTO = 3.06 KP = 4.8 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 1)
.MODEL MSTROMOD NMOS (VTO = 3.5 KP = 80 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u)
.MODEL MWEAKMOD NMOS (VTO = 2.67 KP = 0.08 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 10)
.MODEL RBREAKMOD RES (TC1 =1.3e- 3TC2 = -9e-7)
.MODEL RDRAINMOD RES (TC1 = 1.1e-2 TC2 = 2.5e-5)
.MODEL RSLCMOD RES (TC1 = 4.5e-3 TC2 = 1e-5)
.MODEL RSOURCEMOD RES (TC1 = 0 TC2 = 0)
.MODEL RVTHRESMOD RES (TC1 = -2.5e-3 TC2 = -1.1e-5)
.MODEL RVTEMPMOD RES (TC1 = -2.75e- 3TC2 = 0)

.MODEL S1AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -6.0 VOFF= -4.5)
.MODEL S1BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -4.5 VOFF= -6.0)
.MODEL S2AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -0.5 VOFF= 0.5)
.MODEL S2BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = 0.5 VOFF= -0.5)

.ENDS

NOTE: For further discussion of the PSPICE model, consult **A New PSPICE Sub-Circuit for the Power MOSFET Featuring Global Temperature Options**; IEEE Power Electronics Specialist Conference Records, 1991, written by William J. Hepp and C. Frank Wheatley.

## SABER Electrical Model

REV 15 Feb 00

```
template huf75542p3 n2,n1,n3
electrical n2,n1,n3
{
var i iscl
dp..model dbodymod =  (is = 2.5e-12, rs = 2.85e-3, xti = 5.5, trs1 = 2e-3, trs2 = 1e-6, cjo = 3.2e-9, tt = 5.5e-8, m = 0.6)
dp..model dbreakmod = (rs = 2.9e-1, trs1 = 1e-3, trs2 = 1e-6)
dp..model dplcapmod =  (cjo = 3.4e-9, is = 1e-30, m = 0.8, nl = 10)
m..model mmedmod = (type=_n, vto = 3.06, kp = 4.8, is = 1e-30, tox = 1)
m..model mstrongmod = (type=_n, vto = 3.5, kp = 80, is = 1e-30, tox = 1)
m..model mweakmod = (type=_n, vto = 2.67, kp = 0.08, is = 1e-30, tox = 1)
sw_vcsp..model s1amod =  (ron = 1e-5, roff = 0.1, von = -6.0, voff = -4.5)
sw_vcsp..model s1bmod =  (ron =1e-5, roff = 0.1, von = -4.5, voff = -6.0)
sw_vcsp..model s2amod =  (ron = 1e-5, roff = 0.1, von = -0.5, voff = 0.5)
sw_vcsp..model s2bmod =  (ron = 1e-5, roff = 0.1, von = 0.5, voff = -0.5)

c.ca n12 n8 = 4.4e-9
c.cb n15 n14 = 4.2e-9
c.cin n6 n8 = 2.5e-9
dp.dbody n7 n5 = model=dbodymod
dp.dbreak n5 n11 = model=dbreakmod
dp.dplcap n10 n5 = model=dplcapmod

i.it n8 n17 = 1

l.ldrain n2 n5 = 1e-9
l.lgate n1 n9 = 2.6e-9
l.lsource n3 n7 = 1.1e-9

m.mmed n16 n6 n8 n8 = model=mmedmod, l=1u, w=1u
m.mstrong n16 n6 n8 n8 = model=mstrongmod, l=1u, w=1u
m.mweak n16 n21 n8 n8 = model=mweakmod, l=1u, w=1u

res.rbreak n17 n18  = 1, tc1 = 1.3e-3, tc2 = -9e-7
res.rdrain n50 n16  = 5.5e-3, tc1 = 1.1e-2, tc2 = 2.5e-5
res.rgate n9 n20 = 1.0
res.rldrain n2 n5 = 10
res.rlgate n1 n9 = 26
res.rlsource n3 n7 = 11
res.rslc1 n5 n51  = 1e-6, tc1 = 4.5e-3, tc2 = 1e-5
res.rslc2 n5 n50 = 1e3
res.rsource n8 n7  = 3.3e-3, tc1 = 0, tc2 = 0
res.rvtemp n18 n19  = 1, tc1 = -2.75e-3, tc2 = 0
res.rvthres n22 n8  = 1, tc1 = -2.5e-3, tc2 = -1.1e-5

spe.ebreak n11 n7 n17 n18 = 87.2
spe.eds n14 n8 n5 n8 = 1
spe.egs n13 n8 n6 n8 = 1
spe.esg n6 n10 n6 n8 = 1
spe.evtemp n20 n6 n18 n22 = 1
spe.evthres n6 n21 n19 n8 = 1

sw_vcsp.s1a n6 n12 n13 n8 = model=s1amod
sw_vcsp.s1b n13 n12 n13 n8 = model=s1bmod
sw_vcsp.s2a n6 n15 n14 n13 = model=s2amod
sw_vcsp.s2b n13 n15 n14 n13 = model=s2bmod

v.vbat n22 n19 = dc=1

equations {
i (n51->n50) +=iscl
iscl: v(n51,n50) = ((v(n5,n51)/(1e-9+abs(v(n5,n51))))*((abs(v(n5,n51)*1e6/230))** 2.5))
}
}
```



## SPICE Thermal Model

REV 15 Feb 00

T75542

CTHERM1 th 6 4.1e-3
CTHERM2 6 5 5.5e-3
CTHERM3 5 4 8.6e-3
CTHERM4 4 3 1.5e-2
CTHERM5 3 2 1.6e-2
CTHERM6 2 tl 6.5e-2

RTHERM1 th 6 2.0e-4
RTHERM2 6 5 3.5e-3
RTHERM3 5 4 2.5e-2
RTHERM4 4 3 9.0e-2
RTHERM5 3 2 1.6e-1
RTHERM6 2 tl 2.3e-1

## SABER Thermal Model

SABER thermal model t75542

template thermal_model th tl
thermal_c th, tl
{
ctherm.ctherm1 th 6 = 4.1e-3
ctherm.ctherm2 6 5 = 5.5e-3
ctherm.ctherm3 5 4 = 8.6e-3
ctherm.ctherm4 4 3 = 1.5e-2
ctherm.ctherm5 3 2 = 1.6e-2
ctherm.ctherm6 2 tl = 6.5e-2

rtherm.rtherm1 th 6 = 2.0e-4
rtherm.rtherm2 6 5 = 3.5e-3
rtherm.rtherm3 5 4 = 2.5e-2
rtherm.rtherm4 4 3 = 9.0e-2
rtherm.rtherm5 3 2 = 1.6e-1
rtherm.rtherm6 2 tl = 2.3e-1
}



FAIRCHILD SEMICONDUCTOR®

**TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
AX-CAP®*
BitSiC™
Build it Now™
CorePLUS™
CorePOWER™
*CROSSVOLT*™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficentMax™
ESBC™
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™
F-PFS™
FRFET®
Global Power Resource℠
GreenBridge™
Green FPS™
Green FPS™ e-Series™
G*max*™
GTO™
IntelliMAX™
ISOPLANAR™
Marking Small Speakers Sound Louder and Better™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
mWSaver®
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
Solutions for Your Success™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
SYSTEM GENERAL ®*
TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®*
μSerDes™
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™

*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|---|---|---|
| Advance Information | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design. |
| Obsolete | Not In Production | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only. |

Rev. I66

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT**:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
**Phone**: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
**Fax**: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
**Email**: orderlit@onsemi.com

**N. American Technical Support**: 800−282−9855 Toll Free USA/Canada
**Europe, Middle East and Africa Technical Support:**
Phone: 421 33 790 2910
**Japan Customer Focus Center**
Phone: 81−3−5817−1050

**ON Semiconductor Website**: **www.onsemi.com**

**Order Literature**: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative