MOSFET – N-Channel, DUAL COOL® 33, POWERTRENCH®

30 V, 157 A, 1.28 mΩ

FDMC8010DC



Top Bottom

PQFN8 3.3X3.3, 0.65P
CASE 483AY
DUAL COOL 33

General Description

This N−Channel MOSFET is produced using **onsemi**'s advanced POWERTRENCH process. Advancements in both silicon and DUAL COOL package technologies have been combined to offer the lowest $r_{DS(on)}$ while maintaining excellent switching performance by extremely low Junction−to−Ambient thermal resistance.

Features

- DUAL COOL Top Side Cooling PQFN Package
- Max $r_{DS(on)}$ = 1.28 mΩ at V_{GS} = 10 V, I_D = 37 A
- Max $r_{DS(on)}$ = 1.74 mΩ at V_{GS} = 4.5 V, I_D = 32 A
- High Performance Technology for Extremely Low $r_{DS(on)}$
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Load Switch
- Motor Bridge Switch
- Synchronous Rectifier

MARKING DIAGRAM



6J = Specific Device Code
A = Assembly Plant Code
YW = Date Code (Year and Week)
Z = Lot Code

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering, marking and shipping information in the package dimensions section on page 2 of this data sheet.

MOSFET MAXIMUM RATINGS (T_A = 25°C Unless Otherwise Noted)

Symbol	Parameter	Ratings	Units
V_{DS}	Drain to Source Voltage	30	V
V_{GS}	Gate to Source Volage (Note 4)	±20	V
I_D	Drain Current −Continuous T_C = 25°C (Note 6) −Continuous T_C = 100°C (Note 6) −Continuous T_A = 25°C (Note 1a) −Pulsed (Note 5)	 157 99 37 788	A
E_{AS}	Single Pulse Avalance Energy (Note 3)	337	mJ
P_D	Power Dissipation T_C = 25°C	50	W
	Power Dissipation T_A = 25°C (Note 1a)	3.0	
T_J, T_{STG}	Operating and Storage Junction Temperature Range	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Ratings	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case (Bottom Drain)	2.5	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1a)	42	

August, 2023 − Rev. 4

Publication Order Number:
FDMC8010DC/D

PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package	Reel Size	Tape Width	Quantity
FDMC8010DC	6J	DUAL COOL 33	13”	12 mm	3000 Units

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V	30			V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C		15		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 24 V, V_{GS} = 0 V			10	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = 20 V, V_{DS} = 0 V			100	nA
ON CHARACTERISTICS						
$V_{GS(th)}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}$, I_D = 250 μA	1.0	1.4	3.0	V
$\Delta V_{GS(th)}/\Delta T_J$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C		–5		mV/°C
$r_{DS(on)}$	Static Drain to Source On Resistance	V_{GS} = 10 V, I_D = 37 A		0.91	1.28	mΩ
		V_{GS} = 4.5 V, I_D = 32 A		1.2	1.74	
		V_{GS} = 10 V, I_D = 37 A, T_J = 125°C		1.34	1.89	
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 37 A		231		S
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	V_{DS} = 15 V, V_{GS} = 0 V, f = 1 MHz		4720	7080	pF
C_{oss}	Output Capacitance			1540	2310	pF
C_{rss}	Reverse Transfer Capacitance			136	205	pF
R_g	Gate Resistance		0.1	0.5	1.1	Ω
SWITCHING CHARACTERISTICS						
$t_{d(on)}$	Turn–On Delay Time	V_{DD} = 15 V, I_D = 37 A, V_{GS} = 10 V, R_{GEN} = 6 Ω		15	26	ns
t_r	Rise Time			7	14	ns
$t_{d(off)}$	Turn–Off Delay Time			40	64	ns
t_f	Fall Time			5	10	ns
$Q_{g(TOT)}$	Total Gate Charge at 10 V	V_{DD} = 15 V I_D = 37 A		67	94	nC
$Q_{g(TOT)}$	Total Gate Charge at 4.5 V			32	44	nC
Q_{gs}	Gate to Source Charge			10		nC
Q_{gd}	Gate to Drain “Miller” Charge			7.5		nC
DRAIN–SOURCE DIODE CHARACTERISTICS						
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 2.3 A (Note 2)		0.7	1.2	V
		V_{GS} = 0 V, I_S = 37 A (Note 2)		0.8	1.3	
t_{rr}	Reverse Recovery Time	I_F = 37 A, di/dt = 100 A/μs		55	88	ns
Q_{rr}	Reverse Recovery Charge			48	76	nC

THERMAL CHARACTERISTICS

$R_{\theta JC}$	Thermal Resistance, Junction to Case	(Top Source)	5.0	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction to Case	(Bottom Drain)	2.5	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1a)	42	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1b)	105	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1c)	29	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1d)	40	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1e)	19	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1f)	23	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1g)	30	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1h)	79	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1i)	17	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1j)	26	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1k)	12	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1l)	16	

NOTES:
1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR−4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



a. 42°C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 105°C/W when mounted on a minimum pad of 2 oz copper

c. Still air, 20.9x10.4x12.7 mm Aluminum Heat Sink, 1 in^2 pad of 2 oz copper.
d. Still air, 20.9x10.4x12.7 mm Aluminum Heat Sink, minimum pad of 2 oz copper.
e. Still air, 45.2x41.4x11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, 1 in^2 pad of 2 oz copper.
f. Still air, 45.2x41.4x11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, minimum pad of 2 oz copper.
g. 200FPM Airflow, No Heat Sink,1 in^2 pad of 2 oz copper.
h. 200FPM Airflow, No Heat Sink, minimum pad of 2 oz copper.
i. 200FPM Airflow, 20.9x10.4x12.7 mm Aluminum Heat Sink, 1 in^2 pad of 2 oz copper.
j. 200FPM Airflow, 20.9x10.4x12.7 mm Aluminum Heat Sink, minimum pad of 2 oz copper.
k. 200FPM Airflow, 45.2x41.4x11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, 1 in^2 pad of 2 oz copper.
l. 200FPM Airflow, 45.2x41.4x11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, minimum pad of 2 oz copper.

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0%.
3. E_{AS} of 337 mJ is based on starting T_J = 25°C, L = 3 mH, I_{AS} = 15 A, V_{DD} = 30 V, V_{GS} = 10 V, 100% test at L = 0.1 mH, I_{AS} = 49 A.
4. As an N−ch device, the negative Vgs rating is for low duty cycle pulse occurrence only. No continuous rating is implied.
5. Pulse Id measured at 250 μs, refer to Figure 11 SOA graph for more details.
6. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro−mechanical application board design.

TYPICAL CHARACTERISTICS

T_J = 25°C Unless Otherwise Noted



Figure 1. On−Region Characteristics



Figure 2. Normalized On−Resistance vs Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs Junction Temperature



Figure 4. On−Resistance vs Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs Source Current

TYPICAL CHARACTERISTICS (continued)

T_J = 25°C Unless Otherwise Noted



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (continued)

T_J = 25°C Unless Otherwise Noted



Figure 13. Junction to Case Transient Thermal Response Curve



PQFN8 3.3X3.3, 0.65P
CASE 483AY
ISSUE A

DATE 08 SEP 2021



TOP VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.
4. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.70	0.75	0.80
A1	0.00	-	0.05
A3	0.20 REF		
b	0.27	0.32	0.37
D	3.20	3.30	3.40
D2	2.17	2.27	2.37
D3	1.45	1.55	1.65
D4	0.51 REF		
E	3.20	3.30	3.40
E2	1.85	1.95	2.05
E3	1.55	1.65	1.75
E4	0.51 REF		
E5	0.24	0.34	0.44
e	0.65 BSC		
e1	1.95 BSC		
k	0.90 REF		
L	0.30	0.40	0.50
z	0.52 REF		



FRONT VIEW



DETAIL A
SCALE: 2X



BOTTOM VIEW



LAND PATTERN
RECOMMENDATION

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON13674G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**PQFN8 3.3X3.3, 0.65P**	**PAGE 1 OF 1**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

◊