N-Channel Enhancement Mode MOSFET

Feature

- 150V/86A
  $R_{DS(ON)}$=9 mΩ(typ.) @VGS = 10V
- 100% Avalanche Tested
- 100% DVDS
- Reliable and Rugged
- Halogen Free and Green Devices Available
  (RoHS Compliant)

Pin Description



PDFN8L(5x6)

Applications

- UPS（Uninterruptible Power Supply）
- Power Management System



Single N-Channel MOSFET

Ordering and Marking Information

C2 HYG100N15 XYMXXXXXX	Package Code C2: PDFN8L(5x6) Date Code XYMXXXXXX

Note: HUAYI halogen free products contain molding compounds/die attach materials and 100% matte tin plate Termi-Nation finish;which are fully compliant with RoHS. HUAYI halogen free products meet or exceed the halogen free require-ments of IPC/JEDEC J-STD-020 for MSL classification at halogen free peak reflow temperature. HUAYI defines “Green” to mean halogen free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

HUAYI reserves the right to make changes, corrections, enhancements, modifications, and improvements to this pr-oduct and/or to this document at any time without notice.

Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (Tc=25℃ Unless Otherwise Noted)				
V_{DSS}	Drain-Source Voltage		150	V
V_{GSS}	Gate-Source Voltage		±20	V
T_J	Junction Temperature Range		-55 to 175	℃
T_{STG}	Storage Temperature Range			℃
I_S	Source Current-Continuous(Body Diode)	Tc=25°C	86	A
Mounted on Large Heat Sink				
I_{DM}	Pulsed Drain Current *	Tc=25°C	304	A
I_D	Continuous Drain Current	Tc=25°C	86	A
		Tc=100°C	61	A
P_D	Maximum Power Dissipation	Tc=25°C	166.7	W
		Tc=100°C	83.4	W
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case		0.9	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient **		80	°C/W
E_{AS}	Single Pulsed-Avalanche Energy ***	L=0.3mH	200	mJ

Note: * Repetitive rating；pulse width limited by max.junction temperature.
** Surface mounted on 1in2 FR-4 board.
*** Limited by $T_J$max , starting T_J=25°C, L = 0.3mH, R_G= 25Ω, V_{GS} =10V.

Electrical Characteristics(Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG100N15HS1			Unit
			Min	Typ.	Max	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V,I_{DS}=250μA	150			V
I_{DSS}	Drain-to-Source Leakage Current	V_{DS}=150V,V_{GS}=0V	-	-	1	μA
		T_J=125°C	-	-	50	μA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_{DS}=250μA	3	3.6	4.6	V
I_{GSS}	Gate-Source Leakage Current	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
$R_{DS(ON)}$	Drain-Source On-State Resistance	V_{GS}=10V,I_{DS}=50A	-	9	11	mΩ
Diode Characteristics						
V_{SD}	Diode Forward Voltage	I_{SD}=50A,V_{GS}=0V	-	0.89		V
t_{rr}	Reverse Recovery Time	I_{SD}=50A,dI_{SD}/dt=100A/μs	-	24	-	ns
Q_{rr}	Reverse Recovery Charge		-	12	-	nC

Electrical Characteristics (Cont.) (Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG100N15HS1			Unit
			Min	Typ.	Max	
Dynamic Characteristics						
R_G	Gate Resistance	V_{GS}=0V,V_{DS}=0V,F=1MHz	-	1.4	-	Ω
C_{iss}	Input Capacitance	V_{GS}=0V,	-	1892	-	pF
C_{oss}	Output Capacitance	V_{DS}=25V,	-	1108	-	
C_{rss}	Reverse Transfer Capacitance	Frequency=500KHz	-	50.6	-	
$t_{d(ON)}$	Turn-on Delay Time	V_{DD}=75V,R_G=4Ω, I_{DS}=50A,V_{GS}=10V	-	15	-	ns
T_r	Turn-on Rise Time		-	75	-	
$t_{d(OFF)}$	Turn-off Delay Time		-	18.5	-	
T_f	Turn-off Fall Time		-	54.6	-	
Gate Charge Characteristics						
Q_g	Total Gate Charge(V_{GS}=10V)	V_{DS}=120V, I_{DS}=50A	-	29	-	nC
Q_{gs}	Gate-Source Charge		-	11	-	
Q_{gd}	Gate-Drain Charge		-	8	-	
$V_{plateau}$	Gate plateau voltage		-	6.4	-	V

Note: *Pulse test，pulse width ≤ 300us，duty cycle ≤ 2%

Typical Operating Characteristics

Figure 1: Power Dissipation



Figure 2: Drain Current



Figure 3: Safe Operation Area



Figure 4: Thermal Transient Impedance



Figure 5: Output Characteristics



Figure 6: Drain-Source On Resistance



Typical Operating Characteristics(Cont.)

Figure 7: On-Resistance vs. Temperature



Figure 8: Source-Drain Diode Forward



Figure 9: Capacitance Characteristics



Figure 10: Gate Charge Characteristics



Avalanche Test Circuit



$$E_{AS} = \frac{1}{2} L I_{AS}^2$$



Switching Time Test Circuit





Gate Charge Test Circuit





Device Per Unit

Package Type	Unit	Quantity
PDFN8L(5x6)	Reel	5000

Package Information

PDFN8L(5x6）

(unit:mm)



Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak		
Temperature min (T_{smin}) Temperature max (T_{smax}) Time (Tsmin to Tsmax) (t_s)	100 °C 150 °C 60-120 seconds	150 °C 200 °C 60-120 seconds
Average ramp-up rate ($T_{smax}$to T_P)	3 °C/second max.	3°C/second max.
Liquidous temperature (T_L) Time at liquidous (t_L)	183 °C 60-150 seconds	217 °C 60-150 seconds
Peak package body Temperature (T_p)*	See Classification Temp in table 1	SeeClassification Tempin table 2
Time (t_P)** within 5°C of the specified classification temperature (T_c)	20** seconds	30** seconds
Average ramp-down rate ($T_p$to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.
*Tolerance for peak profile Temperature (T_p) is defined as a supplier minimum and a user maximum. ** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.		

Table 1.SnPb Eutectic Process – Classification Temperatures (Tc)

Package Thickness	Volume mm³ <350	Volume mm³ ⩾350
＜2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2.Pb-free Process – Classification Temperatures (Tc)

Package Thickness	Volume mm³ <350	Volume mm³ 350-2000	Volume mm³ ⩾2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
⩾2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HTRB	JESD-22, A108	168/500 Hrs, Bias @ 150°C
HTGB	JESD-22, A108	168 /500 Hrs, V_{gs}100% @ 150°C
PCT	JESD-22, A102	96 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	250/500 Cycles, -55°C~150°C

Customer Service

Worldwide Sales and Service: sales@hymexa.com
Technical Support:Technology@hymexa.com
Huayi Microelectronics Co., Ltd.
No.8928,Shangji Road,Economic and Technological Development Zone,Xi'an,China
TEL: (86-029) 86685706
FAX: (86-029) 86685705
E-mail: sales@hymexa.com
Web net: http://www.hymexa.com/