

# A04262E

# 60V N-Channel MOSFET

# **General Description**

- Trench Power MV MOSFET technology
- $\label{eq:low_RDS(ON)} \mbox{-} \mbox{Low Gate Charge}$
- ESD protected

# **Product Summary**

 $V_{\text{DS}} \\$ 60V  $I_D$  (at  $V_{GS}$ =10V) 16.5A R<sub>DS(ON)</sub> (at V<sub>GS</sub>=10V) < 6.5mΩ < 8.5mΩ  $R_{DS(ON)}$  (at  $V_{GS}$ =4.5V)

**Typical ESD protection** HBM Class 2


### **Applications**


- High efficiency power supply
- Secondary synchronus rectifier

## 100% UIS Tested 100% Rg Tested



SOIC-8





Orderable Part Number	Package Type	Form	Minimum Order Quantity
AO4262E	SO-8	Tape & Reel	3000
		,	

Parameter		Symbol	Maximum	Units
Drain-Source Voltag	е	V <sub>DS</sub>	60	V
Gate-Source Voltage	е	V <sub>GS</sub>	±20	V
Continuous Drain	T <sub>A</sub> =25°C		16.5	
Current	T <sub>A</sub> =70°C	I <sub>D</sub>	13.0	A
Pulsed Drain Current <sup>Ċ</sup>		I <sub>DM</sub>	65	
Avalanche Current <sup>C</sup>		I <sub>AS</sub>	23	A
Avalanche energy	L=0.3mH	E <sub>AS</sub>	79	mJ
V <sub>DS</sub> Spike <sup>G</sup>	10µs	V <sub>SPIKE</sub>	72	V
	T <sub>A</sub> =25°C	В	3.1	W
Power Dissipation <sup>B</sup>	T <sub>A</sub> =70°C	$-P_{D}$	2.0	vv
Junction and Storage	e Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C

Thermal Characteristics						
Parameter		Symbol	Тур	Max	Units	
Maximum Junction-to-Ambient A	t ≤ 10s	$R_{\theta JA}$	31	40	°C/W	
Maximum Junction-to-Ambient AD	Steady-State	IX <sub>θ</sub> JA	59	75	°C/W	
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	16	24	°C/W	



#### Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Тур	Max	Units	
STATIC F	PARAMETERS						
$BV_{DSS}$	Drain-Source Breakdown Voltage	I <sub>D</sub> =250μA, V <sub>GS</sub> =0V		60			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =60V, V <sub>GS</sub> =0V				1	μA
יטאא	Zero Gate Voltage Drain Gurrent		T <sub>J</sub> =55°C			5	μΛ
$I_{GSS}$	Gate-Body leakage current	$V_{DS}$ =0V, $V_{GS}$ =±20V				±10	μΑ
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ , $I_D=250\mu A$		1.2	1.65	2.2	V
		V <sub>GS</sub> =10V, I <sub>D</sub> =16.5A			5.2	6.5	mΩ
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance		T <sub>J</sub> =125°C		8.3	10.5	
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =14.5A			6.6	8.5	mΩ
<b>9</b> FS	Forward Transconductance	V <sub>DS</sub> =5V, I <sub>D</sub> =16.5A			70		S
$V_{SD}$	Diode Forward Voltage	I <sub>S</sub> =1A, V <sub>GS</sub> =0V			0.7	1	V
Is	Maximum Body-Diode Continuous Current					4	Α
DYNAMIC	PARAMETERS						
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =30V, f=1MHz			1650		pF
C <sub>oss</sub>	Output Capacitance				520		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			52		pF	
$R_g$	Gate resistance	f=1MHz		0.6	1.3	2.0	Ω
SWITCHI	NG PARAMETERS	•			•	•	
Q <sub>g</sub> (10V)	Total Gate Charge	-V <sub>GS</sub> =10V, V <sub>DS</sub> =30V, I <sub>D</sub> =16.5A			30	45	nC
Q <sub>g</sub> (4.5V)	Total Gate Charge				15	25	nC
$Q_{gs}$	Gate Source Charge				3.5		nC
$Q_{gd}$	Gate Drain Charge				6.5		nC
t <sub>D(on)</sub>	Turn-On DelayTime				6		ns
t <sub>r</sub>	Turn-On Rise Time	$V_{GS}$ =10V, $V_{DS}$ =30V, $R_L$ =1.8 $\Omega$ , $R_{GEN}$ =3 $\Omega$			5		ns
t <sub>D(off)</sub>	Turn-Off DelayTime				29		ns
t <sub>f</sub>	Turn-Off Fall Time				7		ns
t <sub>rr</sub>	Body Diode Reverse Recovery Time	I <sub>F</sub> =16.5A, di/dt=500A		19		ns	
Q <sub>rr</sub>	Body Diode Reverse Recovery Charge	I <sub>F</sub> =16.5A, di/dt=500A/μs			60		nC

A. The value of  $R_{\theta,IA}$  is measured with the device mounted on  $1in^2$  FR-4 board with 2oz. Copper, in a still air environment with  $T_A$  =25° C. The value in any given application depends on the user's specific board design.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

Rev.1.0: January 2016 www.aosmd.com Page 2 of 5

B. The power dissipation  $P_D$  is based on  $T_{J(MAX)}$ =150° C, using  $\leq$  10s junction-to-ambient thermal resistance.

C. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150° C. Ratings are based on low frequency and duty cycles to keep

D. The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.


E. The static characteristics in Figures 1 to 6 are obtained using  $<300\mu$ s pulses, duty cycle 0.5% max. F. These curves are based on the junction-to-ambient thermal impedance which is measured with the device mounted on  $1\text{in}^2$  FR-4 board with 2oz. Copper, assuming a maximum junction temperature of  $T_{J(MAX)}$ =150° C. The SOA curve provides a single pulse rating.

G. The spike duty cycle 5% max, limited by junction temperature TJ(MAX)=125  $^{\circ}$  C.



#### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)



(Note E)



#### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure A: Gate Charge Test Circuit & Waveforms




Figure B: Resistive Switching Test Circuit & Waveforms




Figure C: Unclamped Inductive Switching (UIS) Test Circuit & Waveforms





Figure D: Diode Recovery Test Circuit & Waveforms



Rev.1.0: January 2016 www.aosmd.com Page 5 of 5