

## MOSFET

### 650V CoolMOS™ CM8 Power Transistor

The CoolMOS™ 8th generation platform is a revolutionary technology for high voltage power MOSFETs, designed according to the superjunction (SJ) principle and pioneered by Infineon Technologies. The 650V CoolMOS™ CM8 series is the successor to the 650V CoolMOS™ 7 Family and is enhancing Infineon's WBG offering. It combines the benefits of a fast switching SJ MOSFET with excellent ease of use, e.g. low ringing tendency, implemented fast body diode (CFD) for all products with outstanding robustness against hard commutation and excellent ESD capability. Furthermore, extremely low switching and conduction losses of CM8, make switching applications even more efficient.

### Features

- Best in class 650V SJ MOSFET performance
- Suitable for hard and soft switching topologies thanks to an outstanding commutation ruggedness
- Integrated fast body diode and ESD protection
- .XT interconnection technology for best in class thermal performance

### Benefits

- Ease of use and fast design-in through low ringing tendency and usage across PFC and PWM stages
- Simplified thermal management due to our advanced die attach technique
- Increased power density solutions enabled by using products with smaller footprint and higher manufacturing quality due state of the art ESD protection
- Suitable for a wide variety of applications and power ranges

### Potential applications

- Power supplies and converters
- PFC stages & LLC resonant converters
- High efficiency switching applications
- e.g. Datacenter, AI Server, Telecom Power Supply

### Product validation




Fully qualified according to JEDEC for Industrial Applications

*Please note: For MOSFET paralleling the use of ferrite beads on the gate or separate totem poles is generally recommended.*

**Table 1** Key performance parameters

Parameter	Value	Unit
$V_{DS} @ T_{j,max}$	700	V
$R_{DS(on),max}$	40	mΩ
$Q_{g,typ}$	80	nC
$I_{D,pulse}$	230	A
$E_{oss} @ 400V$	9.1	μJ
Body diode $di_F/dt$	1300	A/μs
ESD class (HBM)	2	

PG-TO247-4



Part number	Package	Marking	Related links
IPZA65R040CM8	PG-TO247-4	65R040C8	see Appendix A



Table of contents

Description ..... 1

Maximum ratings ..... 3

Thermal characteristics ..... 4

Electrical characteristics ..... 5

Electrical characteristics diagrams ..... 7

Test circuits ..... 11

Package outlines ..... 12

Appendix A ..... 13

Revision history ..... 14

Trademarks ..... 15

Disclaimer ..... 15

# 1 Maximum ratings

at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

**Table 2 Maximum ratings**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Continuous drain current <sup>1)</sup>	$I_D$	-	-	62	A	$T_C = 25^\circ\text{C}$
				39		$T_C = 100^\circ\text{C}$
Pulsed drain current <sup>2)</sup>	$I_{D,pulse}$	-	-	230	A	$T_C = 25^\circ\text{C}$
Avalanche energy, single pulse	$E_{AS}$	-	-	135	mJ	$I_D = 4.9\text{A}$ ; $V_{DD} = 50\text{V}$ ; see table 10
Avalanche energy, repetitive	$E_{AR}$			0.68		
Avalanche current, single pulse	$I_{AS}$	-	-	4.9	A	-
MOSFET dv/dt ruggedness	dv/dt	-	-	120	V/ns	$V_{DS} = 0 \dots 400\text{V}$
Gate source voltage (static)	$V_{GS}$	-20	-	20	V	static;
Gate source voltage (dynamic)	$V_{GS}$	-30	-	30	V	AC ( $f > 1\text{ Hz}$ )
Power dissipation	$P_{tot}$	-	-	329	W	$T_C = 25^\circ\text{C}$
Storage temperature	$T_{stg}$	-55	-	150	$^\circ\text{C}$	-
Operating junction temperature	$T_j$					
Extended operating junction temperature	$T_j$	150	-	175	$^\circ\text{C}$	$\leq 50\text{ h}$ in the application lifetime
Mounting torque	-	-	-	60	Ncm	M3 and M3.5 screws
Continuous diode forward current	$I_S$	-	-	62	A	$T_C = 25^\circ\text{C}$
Diode pulse current <sup>2)</sup>	$I_{S,pulse}$			230		
Reverse diode dv/dt <sup>3)</sup>	dv/dt	-	-	70	V/ns	$V_{DS} = 0 \dots 400\text{V}$ , $I_{SD} \leq 62\text{A}$ , $T_j = 25^\circ\text{C}$ see table 8
Maximum diode commutation speed	di <sub>F</sub> /dt			1300	A/ $\mu\text{s}$	
Insulation withstand voltage	$V_{ISO}$	-	-	n.a.	V	$V_{rms}$ , $T_C = 25^\circ\text{C}$ , $t = 1\text{min}$

<sup>1)</sup> Limited by  $T_{j,max}$

<sup>2)</sup> Pulse width  $t_p$  limited by  $T_{j,max}$

<sup>3)</sup> Identical low side and high side switch with identical  $R_G$

## 2 Thermal characteristics

**Table 3 Thermal characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case	$R_{thJC}$	-	-	0.38	K/W	-
Thermal resistance, junction - ambient	$R_{thJA}$	-	-	62	K/W	leaded
Thermal resistance, junction - ambient for SMD version	$R_{thJA}$	-	-	-	K/W	-
Soldering temperature, wavesoldering only allowed at leads	$T_{sold}$	-	-	260	°C	1.6mm (0.063 in.) from case for 10s

### 3 Electrical characteristics

at  $T_j=25^\circ\text{C}$ , unless otherwise specified

**Table 4 Static characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	650	-	-	V	$V_{GS}=0V$ , $I_D=1mA$
Gate threshold voltage	$V_{(GS)th}$	3.7	4.2	4.7	V	$V_{DS}=V_{GS}$ , $I_D=0.68mA$
Zero gate voltage drain current	$I_{DSS}$	-	-	1	$\mu A$	$V_{DS}=650V$ , $V_{GS}=0V$ , $T_j=25^\circ\text{C}$
			88.9	-		$V_{DS}=650V$ , $V_{GS}=0V$ , $T_j=150^\circ\text{C}$
Gate-source leakage current	$I_{GSS}$	-	-	0.1	$\mu A$	$V_{GS}=20V$ , $V_{DS}=0V$
Drain-source on-state resistance	$R_{DS(on)}$	-	0.033	0.040	$\Omega$	$V_{GS}=10V$ , $I_D=25.0A$ , $T_j=25^\circ\text{C}$
			0.073	-		$V_{GS}=10V$ , $I_D=25.0A$ , $T_j=150^\circ\text{C}$
Gate resistance	$R_G$	-	1	-	$\Omega$	$f=1MHz$

**Table 5 Dynamic characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Input capacitance	$C_{iss}$	-	3796	-	pF	$V_{GS}=0V$ , $V_{DS}=400V$ , $f=250kHz$
Output capacitance	$C_{oss}$		44			
Effective output capacitance, energy related <sup>4)</sup>	$C_{o(er)}$	-	114	-	pF	$V_{GS}=0V$ , $V_{DS}=0...400V$
Effective output capacitance, time related <sup>5)</sup>	$C_{o(tr)}$	-	1247	-	pF	$I_D=\text{constant}$ , $V_{GS}=0V$ , $V_{DS}=0...400V$
Turn-on delay time	$t_{d(on)}$	-	22.8	-	ns	$V_{DD}=400V$ , $V_{GS}=13V$ , $I_D=13.5A$ , $R_G=5.3\Omega$ ; see table 9
Rise time	$t_r$		6.6			
Turn-off delay time	$t_{d(off)}$		95.8			
Fall time	$t_f$		5.8			

<sup>4)</sup>  $C_{o(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 400V

<sup>5)</sup>  $C_{o(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 400V


**Table 6 Gate charge characteristics**


Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate to source charge	$Q_{gs}$	-	22	-	nC	$V_{DD}=400V$ , $I_D=13.5A$ , $V_{GS}=0$ to $10V$
Gate to drain charge	$Q_{gd}$		25		nC	
Gate charge total	$Q_g$		80		nC	
Gate plateau voltage	$V_{plateau}$		5.8		V	

**Table 7 Reverse diode characteristics**

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Diode forward voltage	$V_{SD}$	-	0.9	-	V	$V_{GS}=0V$ , $I_F=13.5A$ , $T_j=25^\circ C$
Reverse recovery time	$t_{rr}$	-	120	150	ns	$V_R=400V$ , $I_F=13.5A$ , $di_F/dt=100A/\mu s$ ; see table 8
Reverse recovery charge	$Q_{rr}$		0.73	1.1	$\mu C$	
Peak reverse recovery current	$I_{rrm}$		11.8	-	A	


## 4 Electrical characteristics diagrams








**Diagram 9: Typ. transfer characteristics**




$I_D = f(V_{GS})$ ;  $V_{DS} = 20V$ ; parameter:  $T_j$

**Diagram 10: Typ. gate charge**




$V_{GS} = f(Q_{gate})$ ;  $I_D = 13.5 A$  pulsed; parameter:  $V_{DD}$

**Diagram 11: Forward characteristics of reverse diode**




$I_F = f(V_{SD})$ ; parameter:  $T_j$


**Diagram 12: Avalanche energy**




$E_{AS} = f(T_j)$ ;  $I_D = 4.9 A$ ;  $V_{DD} = 50 V$

**Diagram 13: Drain-source breakdown voltage**


$$V_{BR(DSS)} = f(T_j); I_D = 1 \text{ mA}$$

**Diagram 14: Typ. capacitances**


$$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 250 \text{ kHz}$$

**Diagram 15: Typ. Coss stored energy**


$$E_{oss} = f(V_{DS})$$

5 Test circuits

Table 8 Diode characteristics

Table with 2 columns: Test circuit for diode characteristics, Diode recovery waveform. The first column shows a circuit diagram with two diodes, resistors Rg1 and Rg2, and a current source IF. The second column shows a graph of voltage and current over time, highlighting parameters like VDS(peak), VDS, I\_F, I\_mm, and recovery time t\_rr.


Table 9 Switching times (ss)

Table with 2 columns: Switching times test circuit for inductive load, Switching times waveform. The first column shows a circuit diagram for switching an inductive load. The second column shows a graph of VDS and VGS over time, defining switching times t\_d(on), t\_r, t\_on, t\_d(off), t\_r, and t\_off.

Table 10 Unclamped inductive load (ss)

Table with 2 columns: Unclamped inductive load test circuit, Unclamped inductive waveform. The first column shows a circuit diagram for unclamped inductive load testing. The second column shows a graph of VDS and ID over time, highlighting the unclamped voltage V(BR)DS.

## 6 Package outlines



NOTES:  
 DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS

PACKAGE - GROUP NUMBER: PG-T0247-4-U02					
DIMENSIONS	MILLIMETERS		DIMENSIONS	MILLIMETERS	
	MIN.	MAX.		MIN.	MAX.
<b>A</b>	4.90	5.10	<b>E</b>	15.70	15.90
<b>A1</b>	2.31	2.51	<b>E1</b>	13.10	13.50
<b>A2</b>	1.90	2.10	<b>E2</b>	2.40	2.60
<b>A3</b>	0.05	0.25	<b>e</b>	5.08	
<b>b</b>	1.10	1.30	<b>e1</b>	2.79	
<b>b1</b>	0.65	0.79	<b>e2</b>	2.54	
<b>b2</b>	---	0.20	<b>N</b>	4	
<b>b3</b>	1.34	1.44	<b>L</b>	19.80	20.10
<b>c</b>	0.58	0.66	<b>øP</b>	3.50	3.70
<b>D</b>	20.90	21.10	<b>øP1</b>	7.00	7.40
<b>D1</b>	16.25	16.85	<b>øP2</b>	2.40	2.60
<b>D2</b>	1.05	1.35	<b>Q</b>	5.60	6.00
<b>D3</b>	24.97	25.27	<b>S</b>	6.15	
<b>D4</b>	4.90	5.10	<b>T</b>	9.80	10.20
			<b>U</b>	6.00	6.40

**Figure 1** Outline PG-T0247-4, dimensions in mm

## 7 Appendix A

**Table 11**    **Related links**

- [IFX CoolMOS CM8 Webpage](#)
- [IFX CoolMOS CM8 application note](#)
- [IFX CoolMOS CM8 simulation model](#)
- [IFX Design tools](#)

**Revision history**

IPZA65R040CM8

**Revision 2025-03-07, Rev. 2.1**

Previous revisions

Revision	Date	Subjects (major changes since last revision)
2.0	2024-12-19	Release of final version
2.1	2025-03-07	Update of maximum transient thermal impedance and SOA

**Trademarks**

All referenced product or service names and trademarks are the property of their respective owners.

**We Listen to Your Comments** Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: [erratum@infineon.com](mailto:erratum@infineon.com)

**Published by**

Infineon Technologies AG

81726 München, Germany

© 2025 Infineon Technologies AG

All Rights Reserved.

**Important notice**

The products which may also include samples and may be comprised of hardware or software or both ("Product") are sold or provided and delivered by Infineon Technologies AG and its affiliates ("Infineon") subject to the terms and conditions of the frame supply contract or other written agreement(s) executed by a customer and Infineon or, in the absence of the foregoing, the applicable Sales Conditions of Infineon. General terms and conditions of a customer or deviations from applicable Sales Conditions of Infineon shall only be binding for Infineon if and to the extent Infineon has given its express written consent.

For the avoidance of doubt, Infineon disclaims all warranties of non-infringement of third-party rights and implied warranties such as warranties of fitness for a specific use/purpose or merchantability.

Infineon shall not be responsible for any information with respect to samples, the application or customer's specific use of any Product or for any examples or typical values given in this document.

The data contained in this document is exclusively intended for technically qualified and skilled customer representatives. It is the responsibility of the customer to evaluate the suitability of the Product for the intended application and the customer's specific use and to verify all relevant technical data contained in this document in the intended application and the customer's specific use. The customer is responsible for properly designing, programming, and testing the functionality and safety of the intended application, as well as complying with any legal requirements related to its use.

Unless otherwise explicitly approved by Infineon, Products may not be used in any application where a failure of the Product or any consequences of the use thereof can reasonably be expected to result in personal injury. However, the foregoing shall not prevent the customer from using any Product in such fields of use that Infineon has explicitly designed and sold it for, provided that the overall responsibility for the application lies with the customer.

If the Product includes security features:

Because no computing device can be absolutely secure, and despite security measures implemented in the Product, Infineon does not guarantee that the Product will be free from intrusion, data theft or loss, or other breaches ("Security Breaches"), and Infineon shall have no liability arising out of any Security Breaches.

If this document includes or references software:

The software is owned by Infineon under the intellectual property laws and treaties of the United States, Germany, and other countries worldwide. All rights reserved. Therefore, you may use the software only as provided in the software license agreement accompanying the software. If no software license agreement applies, Infineon hereby grants you a personal, non-exclusive, non-transferable license (without the right to sublicense) under its intellectual property rights in the software (a) for software provided in source code form, to modify and reproduce the software solely for use with Infineon hardware products, only internally within your organization, and (b) to distribute the software in binary code form externally to end users, solely for use on Infineon hardware products. Any other use, reproduction, modification, translation, or compilation of the software is prohibited.

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).