MOSFET – Power, N-Channel, Ultrafet

100 V, 56 A, 25 mΩ

HUF75639G3, HUF75639P3, HUF75639S3S, HUF75639S3



These N−Channel power MOSFETs are manufactured using the innovative Ultrafet process. This advanced process technology achieves the lowest possible on− resistance per silicon area, resulting in outstanding performance. This device is capable of withstanding high energy in the avalanche mode and the diode exhibits very low reverse recovery time and stored charge. It was designed for use in applications where power efficiency is important, such as switching regulators, switching converters, motor drivers, relay drivers, low−voltage bus switches, and power management in portable and battery− operated products.

Formerly developmental type TA75639.

Features

- 56 A, 100 V
- Simulation Models
  - Temperature Compensated PSPICE® and SABER™ Electrical Models
  - Spice and Saber Thermal Impedance Models
  - www.onsemi.com
- Peak Current vs Pulse Width Curve
- UIS Rating Curve
- Related Literature
  - TB334, “Guidelines for Soldering Surface Mount Components to PC Boards”
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant



TO−247−3LD
CASE 340CK



TO−220−3LD
CASE 340AT



D2PAK−3
CASE 418AJ



I2PAK
CASE 418AV

MARKING DIAGRAMS



&Y	= **onsemi** Logo
&Z	= Assembly Plant Code
&3	= 3−Digit Date Code
&K	= 2−Digit Lot Traceability Code
75639x	= Specific Device Code
x	= G/P/S

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ORDERING INFORMATION

PART NUMBER	PACKAGE	BRAND
HUF75639G3	TO−247	75639G
HUF75639P3	TO−220AB	75639P
HUF75639S3ST	TO−263AB	75639S
HUF75639S3	TO−262AA	75639S

PACKAGING



Figure 1.

ABSOLUTE MAXIMUM RATINGS T_C = 25°C unless otherwise specified

Description	Symbol	Ratings	Units
Drain to Source Voltage (Note 1)	V_{DSS}	100 V	V
Drain to Gate Voltage (R_{GS} = 20 kΩ) (Note 1)	V_{DGR}	100 V	V
Gate to Source Voltage	V_{GS}	±20 V	V
Drain Current Continuous (Figure 2) Pulsed Drain Current	 I_D I_{DM}	 56 Figure 4	 A
Pulsed Avalanche Rating	E_{AS}	Figures 6, 14, 15	
Power Dissipation Derate Above 25°C	P_D	200 1.35	W W/°C
Operating and Storage Temperature	T_J, T_{STG}	−55 to 175°C	°C
Maximum Temperature for Soldering Leads at 0.063in (1.6 mm) from Case for 10s Package Body for 10 s, See Techbrief 334	 T_L T_{pkg}	 300 260	 °C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. T_J = 25°C to 150°C.

ELECTRICAL SPECIFICATION T_J = 25 °C unless otherwise specified

SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
OFF STATE SPECIFICATIONS						
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V (Figure 11)	100	–	–	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 95 V, V_{GS} = 0 V	–	–	1	μA
		V_{DS} = 90 V, V_{GS} = 0 V, T_C = 150°C	–	–	250	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±20 V	–	–	±100	nA
ON STATE SPECIFICATIONS						
$V_{GS(TH)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA (Figure 10)	2	–	4	V
$R_{DS(on)}$	Drain to Source On Resistance	I_D = 56 A, V_{GS} = 10 V (Figure 9)	–	21	25	mΩ
THERMAL SPECIFICATIONS						
$R_{\theta JC}$	Thermal Resistance Junction to Case	(Figure 3)	–	–	0.74	°C/W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	TO−247	–	–	30	°C/W
		TO−220, TO−263, TO−262	–	–	62	°C/W
SWITCHING SPECIFICATIONS (V_{GS} = 10 V)						
t_{ON}	Turn−On Time	V_{DD} = 50 V, $I_D \cong$ 56 A, R_L = 0.89 Ω, V_{GS} = 10 V, R_{GS} = 5.1 Ω	–	–	110	ns
$t_{d(ON)}$	Turn−On Delay Time		–	15	–	ns
t_r	Rise Time		–	60	–	ns
$td_{(OFF)}$	Turn−Off Delay Time		–	20	–	ns
t_f	Fall Time		–	25	–	ns
t_{OFF}	Turn−Off Time		–	–	70	ns
GATE CHARGE SPECIFICATIONS						
$Q_{g(TOT)}$	Total Gate Charge	V_{GS} = 0 V to 20 V; V_{DD} = 50 V, $I_D \cong$ 56 A, R_L = 0.89 Ω, $I_{g(REF)}$ = 1.0 mA (Figure 13)	–	110	130	nC
$Q_{g(10)}$	Gate Charge at 10 V	V_{GS} = 0 V to 10 V	–	57	75	nC
$Q_{g(TH)}$	Threshold Gate Charge	V_{GS} = 0 V to 2 V	–	3.7	4.5	nC
Q_{gs}	Gate to Source Gate Charge		–	9.8	–	nC
Q_{gd}	Gate to Drain “Miller” Charge		–	24	–	nC
CAPACITANCE SPECIFICATIONS						
C_{ISS}	Input Capacitance	V_{DS} = 25 V, V_{GS} = 0 V, f = 1 MHz (Figure 12)	–	2000	–	pF
C_{OSS}	Output Capacitance		–	500	–	pF
C_{RSS}	Reverse Transfer Capacitance		–	65	–	pF

SOURCE TO DRAIN DIODE SPECIFICATIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Source to Drain Diode Voltage	V_{SD}	I_{SD} = 56 A	–	–	1.25	V
Reverse Recovery Time	t_{rr}	I_{SD} = 56 A, dI_{SD}/dt = 100 A/μs	–	–	110	ns
Reverse Recovered Charge	Q_{RR}	I_{SD} = 56 A, dI_{SD}/dt = 100 A/μs	–	–	320	nC

TYPICAL PERFORMANCE CURVES



Figure 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE



Figure 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE



Figure 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE



Figure 4. PEAK CURRENT CAPABILITY

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)



Figure 5. FORWARD BIAS SAFE OPERATING AREA



Figure 6. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY



Figure 7. SATURATION CHARACTERISTICS



Figure 8. TRANSFER CHARACTERISTICS



Figure 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE



Figure 10. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)



Figure 11. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE



Figure 12. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



Figure 13. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT

TEST CIRCUITS AND WAVEFORMS



Figure 14. UNCLAMPED ENERGY TEST CIRCUIT



Figure 15. UNCLAMPED ENERGY WAVEFORMS



Figure 16. GATE CHARGE TEST CIRCUIT



Figure 17. GATE CHARGE WAVEFORM



Figure 18. SWITCHING TIME TEST CIRCUIT



Figure 19. RESISTIVE SWITCHING WAVEFORMS

PSPICE Electrical Model

```
SUBCKT HUF75639 2 1 3 ;       rev Oct. 98
CA  12  8 2.8e−9
CB  15  14 2.65e−9
CIN  6  8 1.9e−9

DBODY 7 5 DBODYMOD
DBREAK 5 11  DBREAKMOD
DPLCAP 10 5 DPLCAPMOD

EBREAK 11 7 17  18 110
EDS  14  8  5  8 1
EGS  13  8  6  8 1
ESG 6 10 6 8 1
EVTHRES 6 21 19 8  1
EVTEMP 20 6 18 22 1

IT  8  17  1

LDRAIN 2 5 2e−9
LGATE 1  9 1e−9
LSOURCE  3  7 0.47e−9

RLGATE 1 9 10
RLDRAIN 2 5 20
RLSOURCE 3 7 4.69

MMED 16 6 8 8 MMEDMOD
MSTRO 16 6 8 8 MSTROMOD
MWEAK 16 21 8 8 MWEAKMOD

RBREAK  17  18  RBREAKMOD  1
RDRAIN 50 16 RDRAINMOD 1.3e−2
RGATE  9  20 0.7
RSLC1 5 51 RSLCMOD 1e−6
RSLC2 5 50 1e3
RSOURCE  8  7  RSOURCEMOD 4.5e−3
RVTHRES 22 8 RVTHRESMOD  1
RVTEMP 18 19 RVTEMPMOD 1

S1A  6  12  13  8  S1AMOD
S1B  13  12  13  8  S1BMOD
S2A  6  15  14  13  S2AMOD
S2B 13  15  14  13  S2BMOD

VBAT 22 19  DC  1

ESLC 51 50 VALUE = {(V(5,51)/ABS(V (5,51)))*(PWR(V(5,51)/(1e−6*115),4))}

.MODEL DBODYMOD D (IS = 1.4e−12  RS = 3.3e−3 XTI = 4.7  TRS1 = 2e−3  TRS2 = 0.1e−5  CJO = 3.3e−9  TT = 6.1e−8 M = 0.7)
.MODEL DBREAKMOD D (RS = 3.5e−  1TRS1 = 1e−  3TRS2 = 1e−6)
.MODEL DPLCAPMOD D (CJO = 2.2e−  9IS = 1e−3  0N = 10 M = 0.95 vj = 1.0)
.MODEL MMEDMOD NMOS (VTO = 3.5 KP = 4.8 IS = 1e−30 N = 10 TOX = 1 L = 1u W = 1u Rg = 0.7)
.MODEL MSTROMOD NMOS (VTO = 3.97 KP = 56.5 IS = 1e−30 N = 10 TOX = 1 L = 1u W = 1u)
.MODEL MWEAKMOD NMOS (VTO =3.11 KP = 0.085 IS = 1e−30 N = 10 TOX = 1 L = 1u W = 1u RG = 7 RS = 0.1)
.MODEL RBREAKMOD RES (TC1 = 0.8e−  3TC2 = 1e−6)
.MODEL RDRAINMOD RES (TC1 = 1e−2  TC2 = 1.75e−5)
.MODEL RSLCMOD RES (TC1 = 2.8e−3 TC2 = 14e−6)
.MODEL RSOURCEMOD RES (TC1 = 0 TC2 = 0)
.MODEL RVTHRESMOD RES (TC = −2.0e−3 TC2 = −1.75e−5)
.MODEL RVTEMPMOD RES (TC1 = −2.75e−  3TC2 = 0.05e−9)

.MODEL S1AMOD VSWITCH (RON = 1e−5  ROFF = 0.1  VON = −6.0  VOFF = −3.5)
.MODEL S1BMOD VSWITCH (RON = 1e−5  ROFF = 0.1  VON = −3.5  VOFF = −6.0)
.MODEL S2AMOD VSWITCH (RON = 1e−5  ROFF = 0.1  VON = −2.5  VOFF = 4.95)
.MODEL S2AMOD VSWITCH (RON = 1e−5  ROFF = 0.1  VON = 4.95  VOFF = −2.5)

.ENDS
```



NOTE: For further discussion of the PSPICE model, consult **A New PSPICE Sub−Circuit for the Power MOSFET Featuring Global Temperature Options**; IEEE Power Electronics Specialist Conference Records, 1991, written by William J. Hepp and C. Frank Wheatley.

SABER Electrical Model

nom temp=25 deg c 100v Ultrafet

REV Oct. 98

```
template huf75639 n2,n1,n3
electrical n2,n1,n3
{
var i iscl
d..model dbodymod = (is=1.4e-12, xti=4.7, cjo=33e-10,tt=6.1e-8, m=0.7)
d..model dbreakmod = ()
d..model dplcapmod = (cjo=22e-10,is=1e-30,n=10,m=0.95, vj=1.0)
m..model mmedmod = (type=_n,vto=3.5,kp=4.8,is=1e-30, tox=1)
m..model mstrongmod = (type=_n,vto=3.97,kp=56.5,is=1e-30, tox=1)
m..model mweakmod = (type=_n,vto=3.11,kp=0.085,is=1e-30, tox=1)
sw_vcsp..model s1amod = (ron=1e-5,roff=0.1,von=-6.0,voff=-3.5)
sw_vcsp..model s1bmod = (ron=1e-5,roff=0.1,von=-3.5,voff=-6.0)
sw_vcsp..model s2amod = (ron=1e-5,roff=0.1,von=-2.5,voff=4.95)
sw_vcsp..model s2bmod = (ron=1e-5,roff=0.1,von=4.95,voff=-2.5)

c.ca n12 n8 = 28.5e-10
c.cb n15 n14 = 26.5e-10
c.cin n6 n8 = 19e-10

d.dbody n7 n71 = model=dbodymod
d.dbreak n72 n11 = model=dbreakmod
d.dplcap n10 n5 = model=dplcapmod

i.it n8 n17 = 1

l.ldrain n2 n5 = 2.0e-9
l.lgate n1 n9 = 1e-9
l.lsource n3 n7 = 4.69e-10

m.mmed n16 n6 n8 n8 = model=mmedmod, l=1u, w=1u
m.mstrong n16 n6 n8 n8 = model=mstrongmod, l=1u, w=1u
m.mweak n16 n21 n8 n8 = model=mweakmod, l=1u, w=1u

res.rbreak n17 n18 = 1, tc1=0.8e-3,tc2=-1e-6
res.rdbody n71 n5 = 3.3e-3, tc1=2.0e-3, tc2=0.1e-5
res.rdbreak n72 n5 = 3.5e-1, tc1=1e-3, tc2=1e-6
res.rdrain n50 n16 = 13e-3, tc1=1e-2,tc2=1.75e-5
res.rgate n9 n20 = 0.7
res.rldrain n2 n5 = 20
res.rlgate n1 n9 = 10
res.rlsource n3 n7 = 4.69
res.rslc1 n5 n51 = 1e-6, tc1=2.8e-3,tc2=14e-6
res.rslc2 n5 n50 = 1e3
res.rsource n8 n7 = 4.5e-3, tc1=0,tc2=0
res.rvtemp n18 n19 = 1, tc1=-2.75e-3,tc2=0.05e-9
res.rvthres n22 n8 = 1, tc1=-2e-3,tc2=-1.75e-5

spe.ebreak n11 n7 n17 n18 = 110
spe.eds n14 n8 n5 n8 = 1
spe.egs n13 n8 n6 n8 = 1
spe.esg n6 n10 n6 n8 = 1
spe.evtemp n20 n6 n18 n22 = 1
spe.evthres n6 n21 n19 n8 = 1

sw_vcsp.s1a n6 n12 n13 n8 = model=s1amod
sw_vcsp.s1b n13 n12 n13 n8 = model=s1bmod
sw_vcsp.s2a n6 n15 n14 n13 = model=s2amod
sw_vcsp.s2b n13 n15 n14 n13 = model=s2bmod

v.vbat n22 n19 = dc=1

equations {
i (n51->n50) +=iscl
iscl: v(n51,n50) = ((v(n5,n51)/(1e-9+abs(v(n5,n51))))*((abs(v(n5,n51)*1e6/115))** 4))
}
}
```



Spice Thermal Model

REV APRIL 1998

HUF75639

CTHERM1 TH 6 2.8e−3
CTHERM2 6 5 4.6e−3
CTHERM3 5 4 5.5e−3
CTHERM4 4 3 9.2e−3
CTHERM5 3 2 1.7e−2
CTHERM6 2 TL 4.3e−2

RTHERM1 TH 6 5.0e−4
RTHERM2 6 5 1.5e−3
RTHERM3 5 4 2.0e−2
RTHERM4 4 3 9.0e−2
RTHERM5 3 2 1.9e−1
RTHERM6 2 TL 2.9e−1

Saber Thermal Model

Saber thermal model HUF75639

template thermal_model th tl
thermal_c th, tl
{
ctherm.ctherm1 th 6 = 2.8e−3
ctherm.ctherm2 6 5 = 4.6e−3
ctherm.ctherm3 5 4 = 5.5e−3
ctherm.ctherm4 4 3 = 9.2e−3
ctherm.ctherm5 3 2 = 1.7e−2
ctherm.ctherm6 2 tl = 4.3e−2

rtherm.rtherm1 th 6 = 5.0e−4
rtherm.rtherm2 6 5 = 1.5e−3
rtherm.rtherm3 5 4 = 2.0e−2
rtherm.rtherm4 4 3 = 9.0e−2
rtherm.rtherm5 3 2 = 1.9e−1
rtherm.rtherm6 2 tl = 2.9e−1
}



PSPICE is a trademark of MicroSim Corporation.
Saber is a registered trademark of Sabremark Limited Partnership.



TO−220−3LD
CASE 340AT
ISSUE B

DATE 08 AUG 2022

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.00	--	4.70
A1	SEE NOTE "F"		
A2	2.10	--	2.85
b	0.55	--	1.00
b2	1.10	--	1.62
b4	1.42	--	1.62
c	0.36	--	0.60
D	13.90	--	16.30
D1	8.13	--	9.40
D2	11.50	--	14.30
D3	15.42	--	16.51
E	9.65	--	10.67
E1	7.59	--	8.65
e	2.40	--	2.67
H1	6.06	--	6.69
L	12.70	--	14.04
L1	2.70	--	4.10
P	3.50	--	4.00
Q	2.50	--	3.40
z	2.13 REF		
z1	2.06 REF		
Θ	3°	–	5°







GENERIC MARKING DIAGRAM*

XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

NOTES:
A) REFERENCE JEDEC, TO-220, VARIATION AB
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
E) DOES NOT COMPLY JEDEC STANDARD VALUE.
F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
G) PRESENCE IS SUPPLIER DEPENDENT
H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

DOCUMENT NUMBER:	**98AON13818G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−220−3LD**	**PAGE 1 OF 1**

TO−247−3LD SHORT LEAD
CASE 340CK
ISSUE A

DATE 31 JAN 2019



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.40	1.50	1.60
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D	20.32	20.57	20.82
D1	13.08	~	~
D2	0.51	0.93	1.35
E	15.37	15.62	15.87
E1	12.81	~	~
E2	4.96	5.08	5.20
e	~	5.56	~
L	15.75	16.00	16.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
ØP1	6.60	6.80	7.00
Q	5.34	5.46	5.58
S	5.34	5.46	5.58

NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13851G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−247−3LD SHORT LEAD**	**PAGE 1 OF 1**

D²PAK–3 (TO–263, 3–LEAD)
CASE 418AJ
ISSUE F

DATE 11 MAR 2021



SCALE 1:1



RECOMMENDED
MOUNTING FOOTPRINT

* For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: INCHES
3. CHAMFER OPTIONAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.005 PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AT DATUM H.
5. THERMAL PAD CONTOUR IS OPTIONAL WITHIN DIMENSIONS E, L1, D1, AND E1.
6. OPTIONAL MOLD FEATURE.
7. ①, ② … OPTIONAL CONSTRUCTION FEATURE CALL OUTS.

	INCHES		MILLIMETERS	
DIM	MIN.	MAX.	MIN.	MAX.
A	0.160	0.190	4.06	4.83
A1	0.000	0.010	0.00	0.25
b	0.020	0.039	0.51	0.99
c	0.012	0.029	0.30	0.74
c2	0.045	0.065	1.14	1.65
D	0.330	0.380	8.38	9.65
D1	0.260	---	6.60	---
E	0.380	0.420	9.65	10.67
E1	0.245	---	6.22	---
e	0.100 BSC		2.54 BSC	
H	0.575	0.625	14.60	15.88
L	0.070	0.110	1.78	2.79
L1	---	0.066	---	1.68
L2	---	0.070	---	1.78
L3	0.010 BSC		0.25 BSC	
M	0°	8°	0°	8°







DETAIL C
TIP LEADFORM
ROTATED 90° CW



VIEW A–A

VIEW A–A
OPTIONAL CONSTRUCTIONS

GENERIC MARKING DIAGRAMS*



IC **Standard** **Rectifier** **SSG**

XXXXXX = Specific Device Code
A = Assembly Location
WL = Wafer Lot
Y = Year
WW = Work Week
W = Week Code (SSG)
M = Month Code (SSG)
G = Pb–Free Package
AKA = Polarity Indicator

*This information is generic. Please refer to device data sheet for actual part marking. Pb–Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON56370E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**D²PAK–3 (TO–263, 3–LEAD)**	**PAGE 1 OF 1**



I2PAK (TO−262 3 LD)
CASE 418AV
ISSUE A

DATE 30 AUG 2022



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.06	4.45	4.83
A1	1.14	1.27	1.40
A2	2.03	2.41	2.79
b	0.64	0.77	0.90
b2	1.14	1.46	1.78
c	0.33	0.49	0.64
D	8.64	9.15	9.65
D1	6.86	7.37	7.88
E	9.65	9.97	10.29
E1	6.22	7.28	8.33
e	2.54 BSC		
e1	5.08 BSC		
L	12.70	13.72	14.73
L1	2.80	3.38	3.96
L3	1.00	1.20	1.40
z	2.13 REF		
Θ	0°	--	7°
Θ1	0°	--	5°

NOTES:

A. EXCEPT WHERE NOTED CONFORMS TO TO262 JEDEC VARIATION AA.
B. DOES NOT COMPLY JEDEC STD. VALUE.
C. ALL DIMENSIONS ARE IN MILLIMETERS.
D. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS.
E. DIMENSION AND TOLERANCE AS PER ANSI Y14.5-1994.
F. LOCATION OF PIN HOLE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF PACKAGE)
G. MAXIMUM WIDTH FOR F102 DEVICE = 1.35 MAX.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13814G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**I2PAK (TO−262 3 LD)**	**PAGE 1 OF 1**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales