


CAPI SNAP Education Series: User Guide

CAPI SNAP Education hls_latency_eval : howto? V2.0



Architecture of the SNAP git files



Action overview

Purpose: Providing to SNAP user a simple example to let him optimize the data exchanges between an application and an action with a minimum of latency.

Access to external interfaces are :

- Host memory server

When to use it:


- Understand how to optimize latencies access

Memory management:

- Application is managing address of Host memory
- Data are read 64B words one after the other

Known limitations:

- HLS requires transfers to be 64 byte aligned and a size of multiples of 64 bytes



Action usage

Usage: `./snap_latency_eval [-h] [-v, --verbose] [-V, --version]`
`-C, --card <cardno>` can be (0...3)
`-t, --timeout` timeout in sec to wait for done.
`-T, -- Action timeout` Number max of reads done by the action * 0xF.
`-v, --verbose` verbose mode displays text sent and received
`-N, --no-irq` disable Interrupts (=> polling status)

Example :

```
export SNAP_TRACE=0x0
snap_maint -v
```

```
snap_latency_eval
snap_latency_eval -T 500
```


```
$SNAP_TRACE=0xF snap_latency_eval -N
```

Options: (default option in **bold**)


SNAP_TRACE=0x0 → no debug trace
 SNAP_TRACE=0xF → full debug trace
SNAP_CONFIG=FPGA → hardware execution
 SNAP_CONFIG=CPU → software execution

latency_eval registers

Purpose: code is written to minimize the latency of the back and forth data exchange




Application Code + software action code: what's in it?



Application calling the software action: latency_eval processing code will be bypassed in the software action since this software action should be coded as an independent and parallel thread to show the same effect. The purpose here is to show how coding the application and the hardware action.

Hardware action Code : what's in it?



Constants - Ports

Constants: ➔ \$ACTION_ROOT = snap/actions/hls_helloworld

Constant name	Value	Type	Definition location	Usage
LATENCY_EVAL_ACTION_TYPE	0x10141009	Fixed	\$ACTION_ROOT/include/action_changecase.h	latency_eval ID - list is in snap/ActionTypes.md
RELEASE_LEVEL	0x00000020	Variable	\$ACTION_ROOT/hw/action_uppercase.H	release level – user defined

Ports used:

Ports name	Description	Enabled
din_gmem	Host memory data bus input Addr : 64bits - Data : 512bits	Yes
dout_gmem	Host memory data bus output Addr : 64bits - Data : 512bits	Yes
d_ddrmem	DDR3 - DDR4 data bus in/out Addr : 33bits - Data : 512bits	NOT used
nvme	NVMe data bus in/out Addr : 32bits - Data : 32bits	No (soon)

MMIO Registers

Read and Write are considered from the application / software side

act_reg.Control		This header is initialized by the SNAP job manager. The action will update the Return code and read the flags value.									
CONTROL		If the flags value is 0, then action sends only the action_RO_config_reg value and exit the action, otherwise it will process the action									
Simu - WR	Write@	Read@	3	2	1	0	Typical Write value		Typical Read value		
0x3C40	0x100	0x180	sequence			flags	short action type	f001_01_00			
0x3C41	0x104	0x184	Retc (return code 0x102/0x104)						0	0x102 - 0x104	SUCCESS/FAILURE
0x3C42	0x108	0x188	Private Data						c0febabe		
0x3C43	0x10C	0x18C	Private Data						deadbeef		
action_reg.Data		Action specific - user defined - need to stay in 108 Bytes									
intersect_job_t		This is the way for application and action to exchange information through this set of registers									
Simu - WR	Write@	Read@	3	2	1	0	Typical Write value		Typical Read value		
0x3C44	0x110	0x190	[snap_addr]in.addr (LSB)								
0x3C45	0x114	0x194	[snap_addr]in.addr (MSB)								
0x3C46	0x118	0x198	[snap_addr]in.size								
0x3C47	0x11C	0x19C	[snap_addr]in.flags (SRC, DST, ...)			[snap_addr]in.type (DRAM, NVME,...)					
0x3C48	0x120	0x1A0	[snap_addr]src_result.addr (LSB)								
0x3C49	0x124	0x1A4	[snap_addr]src_result.addr (MSB)								
0x3C4A	0x128	0x1A8	[snap_addr]src_result.size								
0x3C4B	0x12C	0x1AC	[snap_addr]src_result.flags (SRC, DST, ...)			[snap_addr]src_result.type (DRAM, NVME,...)					
0x3C4C	0x130	0x1B0	MAX_reads (LSB)								
0x3C4D	0x134	0x1B4	MAX_reads (LSB)								

\$ACTION_ROOT/hw/action_uppercase.H

```
typedef struct {
    CONTROL Control; /* 16 bytes */
    latency_eval_job_t Data; /* 108 bytes */
    uint8_t padding[SNAP_HLS_JOBSIZE - sizeof(latency_eval_job_t)];
} action_reg;
```

\$ACTION_ROOT/include/action_changecase.h

```
typedef struct latency_eval_job {
    struct snap_addr in; /* input data */
    struct snap_addr out; /* offset table */
    uint64_t MAX_reads; /* setting MAX number of reads (timeout) */
} latency_eval_job_t;
```

\$SNAP_ROOT/actions/include/hls_snap.H

```
typedef struct {
    snapu8_t sat; // short action type
    snapu8_t flags;
    snapu16_t seq;
    snapu32_t Retc;
    snapu64_t Reserved; // Priv_data
} CONTROL;
```

\$SNAP_ROOT/software/include/snap_types.h

```
typedef struct snap_addr {
    uint64_t addr;
    uint32_t size;
    snap_addrtype_t type; /* DRAM, NVME, ... */
    snap_addrflag_t flags; /* SRC, DST, EXT, ... */
} snap_addr_t;
```

Performances measurements

Measurements on a POWER8 (Antipode) with a N250S card

To run these performances, run the following:

```
$ snap_maint -v
```

```
$ snap_latency_eval
```

What do we measure?

These numbers are the measurements results of the following sequence time:

START TIMER

- The **application writes** a 64B word to host memory @in
- The **action reads** (continuously) the host memory address @in
- The **action process** the 64B word read
- The **action writes** back the 64B word result to the host memory at @out
- The **application reads** continuously the host memory at @out and compares it to the expected word until it matches



STOP TIMER

This measurement is done 26 times to evaluate possible differences

```
$ ./snap_latency_eval
Type snap_latency_eval -h to get more options
PARAMETERS:
  type_in:      0 HOST_DRAM
  addr_in:      0000010004da0000
  type_out:     0 HOST_DRAM
  addr_out:     0000010004db0000
  size_in/out:  00000040
  prepare latency_eval job of 40 bytes size
Action Timeout: MAX reads set to: 1006632900
SNAP registers set + action start took 10 usec
SNAP action processing for word with letter a took 5 usec
SNAP action processing for word with letter b took 4 usec
SNAP action processing for word with letter c took 4 usec
SNAP action processing for word with letter d took 5 usec
SNAP action processing for word with letter e took 3 usec
SNAP action processing for word with letter f took 5 usec
SNAP action processing for word with letter g took 3 usec
SNAP action processing for word with letter h took 5 usec
SNAP action processing for word with letter i took 5 usec
SNAP action processing for word with letter j took 2 usec
SNAP action processing for word with letter k took 3 usec
SNAP action processing for word with letter l took 6 usec
SNAP action processing for word with letter m took 4 usec
SNAP action processing for word with letter n took 5 usec
SNAP action processing for word with letter o took 3 usec
SNAP action processing for word with letter p took 3 usec
SNAP action processing for word with letter q took 2 usec
SNAP action processing for word with letter r took 3 usec
SNAP action processing for word with letter s took 3 usec
SNAP action processing for word with letter t took 3 usec
SNAP action processing for word with letter u took 5 usec
SNAP action processing for word with letter v took 2 usec
SNAP action processing for word with letter w took 5 usec
SNAP action processing for word with letter x took 2 usec
SNAP action processing for word with letter y took 5 usec
SNAP action processing for word with letter z took 5 usec
SNAP action processing stats: MIN: 2 usec - MAX: 6 usec - AVG: 4
usec
SUCCESS
SNAP latency_eval closing action took 17 usec
```

Path of improvements

History of this document and of the action release level

V2.0: initial document