unit_linked

November 1, 2026

1 PROTOTYPE UNIT-LINKED LIABILITIES

The purpose of this notebook is to showcase how unit-linked pension liabilities work inside the OSEM model, using the same production classes and loop helpers that `main.py` calls when `liability_mode=unit_linked`.

Unit-linked products differ from the static cash-flow liability mode: they do **not** upload a pre-scheduled outflow vector. Cash flows emerge each period from policy state (account value, premiums, fees) and stochastic mortality / lapse liquidations.

Detailed methodology: `Documentation/Unit_Linked_Methodology.md` and `Liability_Dev/Unit_Linked_Methodology.html`.

[1]:
```
import os
import pandas as pd
import datetime as dt
from pathlib import Path
import sys

base_folder = next(path for path in [Path.cwd(), *Path.cwd().parents] if (path /
 ↪ "ALM.ini").is_file())
sys.path.insert(0, str(base_folder / "src"))
os.chdir(base_folder)
```

[2]:
```
from osem.ConfigurationClass import Configuration
from osem.ImportData import (
    get_configuration,
    get_settings,
    get_unit_linked_policies,
    get_unit_linked_fund,
    get_society,
)
from osem.UnitLinkedClasses import UnitLinkedPolicy, UnitLinkedFund,␣
 ↪UnitLinkedPortfolio
from osem.SocietyClass import Society
from osem.MainLoop import (
    capitalize_policies,
    apply_premiums,
    apply_admin_fees,
```

```
    apply_mortality,
    apply_lapse,
    process_unit_linked_period,
)
```

1.1 Input files

Unit-linked runs need the usual ALM configuration plus three liability-specific files under `Input/`.

1.1.1 Parameters.csv

Adds two fields used by the UL path:

- `liability_mode` … `cashflow` (default) or `unit_linked`
- `random_seed` … integer seed for reproducible mortality / lapse draws

Other parameters (modelling date, projection length, EIOPA files) are shared with the asset side.

1.1.2 Unit_Linked_Policies.csv

In-force policy file at modelling date. Columns:

- `Policy_ID` … unique identifier
- `Birth_Date` … for age-based mortality (`dd/mm/yyyy`)
- `Is_Female` … 0/1 selects mortality column
- `Is_Guaranteed` … 0/1; if 1, GV is capitalized with MV
- `Premium` … opening annual premium
- `MV` … opening account / reserve value
- `GV` … opening guaranteed value

1.1.3 Unit_Linked_Fund.csv

Single-pool fund parameters (one row in the MVP):

- `Fund_ID`
- `Lapse_Rate` … annual lapse probability
- `Admin_Fee` … annual fee as share of MV
- `Entry_Fee` … share of gross premium to insurer
- `Premium_Growth` … annual premium growth rate

1.1.4 mortality.csv

Age-indexed annual mortality rates with columns `AGE`, `MALE`, `FEMALE` (already used by `Society`).

Set up the base folder

[3]:
```
base_folder = os.getcwd()  # Get current working directory
```

Most of the run settings are saved in the configuration file:

[4]:
```
conf: Configuration
conf = get_configuration(os.path.join(base_folder, "ALM.ini"), os)
```

These lines of code extract the absolute locations of inputs:

[5]:
```
parameters_file = conf.input_parameters
ul_policies_file = conf.input_unit_linked_policies
ul_fund_file = conf.input_unit_linked_fund
mortality_file = conf.input_mortality
```

[6]:
```
paramfile = pd.read_csv("Input/Parameters.csv").set_index("Parameter")
```

[7]:
```
display(paramfile)
```

Parameter	Value
EIOPA_param_file	Input/Param_no_VA.csv
EIOPA_curves_file	Input/Curves_no_VA.csv
country	Slovenia
run_type	Risk Neutral
n_proj_years	50
Precision	1E-10
Tau	0.0001
compounding	-1
Modelling_Date	29/04/2023
liability_mode	cashflow
random_seed	42

The settings object holds modelling date, projection horizon, liability mode, and random seed.

`liability_mode` only gates which liability branch `main.py` takes. This notebook calls the unit-linked helpers directly, so it runs the same way whether the repository default in `Input/Parameters.csv` is `cashflow` or `unit_linked` (see the last section for how to switch).

[8]:
```
settings = get_settings(parameters_file)
```

[9]:
```
print("modelling_date:", settings.modelling_date)
```

```
modelling_date: 2023-04-29
```

[10]:
```
print("liability_mode:", settings.liability_mode)
```

```
liability_mode: cashflow
```

[11]:
```
print("random_seed:", settings.random_seed)
```

```
random_seed: 42
```

[12]:
```
print("end_date:", settings.end_date)
```

```
end_date: 2073-04-29
```

1.2 Loading unit-linked objects

A Python generator reads the policy CSV into `UnitLinkedPolicy` instances keyed by `policy_id`.

[13]:
```
policy_generator = get_unit_linked_policies(ul_policies_file)
ul_policies = {policy.policy_id: policy for policy in policy_generator}
```

Inspect a single policy (static metadata is frozen after import):

[14]:
```
example_id = sorted(ul_policies.keys())[0]
policy = ul_policies[example_id]
```

[15]:
```
display(ul_policies.keys())
```

```
dict_keys([1001, 1002, 1003, 1004, 1005])
```

[16]:
```
print(policy)
```

```
UnitLinkedPolicy(policy_id=1001, birth_date=datetime.date(1970, 3, 15),
is_female=True, is_guaranteed=False, premium=5000.0, mv=120000.0, gv=0.0)
```

[17]:
```
print("Age at modelling date:", policy.age_at(settings.modelling_date))
```

```
Age at modelling date: 53
```

Fund parameters and mortality society:

[18]:
```
ul_fund = get_unit_linked_fund(ul_fund_file)
```

[19]:
```
display(ul_fund)
```

```
UnitLinkedFund(fund_id=1, lapse_rate=0.04, admin_fee=0.01, entry_fee=0.03,␣
↪premium_growth=0.02)
```

[20]:
```
society = get_society(mortality_file)
```

[21]:
```
print("Male q at age 50:", society.mortality_rate(50, is_female=False))
```

```
Male q at age 50: 0.020122
```

[22]:
```
print("Female q at age 50:", society.mortality_rate(50, is_female=True))
```

```
Female q at age 50: 0.009009
```

1.3 Portfolio wrapper and state DataFrames

`UnitLinkedPortfolio` mirrors the equity/bond portfolio pattern. Simulation state lives in DataFrames (rows = `policy_id`, columns = modelling dates), not on the frozen dataclasses.

There is no separate boolean "active" matrix: `init_policy_state_to_dataframe` returns just `(mv_df, gv_df, premium_df)`, and a policy that dies or lapses has its row dropped from all three (see `apply_mortality` / `apply_lapse` in steps 4-5 below) rather than being flagged inactive in place.

[23]:
```
ul_ptf = UnitLinkedPortfolio(ul_policies)
ul_mv_df, ul_gv_df, ul_premium_df = ul_ptf.init_policy_state_to_dataframe(
```

```
    modelling_date=settings.modelling_date
)
```

[24]:
```
print("Opening UL reserve:", ul_ptf.total_reserve(ul_mv_df, settings.
  ↪modelling_date))
```

```
Opening UL reserve: 720000.0
```

[25]:
```
display(ul_mv_df)
```

```
      2023-04-29
1001    120000.0
1002    250000.0
1003     75000.0
1004    180000.0
1005     95000.0
```

[26]:
```
display(ul_premium_df)
```

```
      2023-04-29
1001      5000.0
1002      8000.0
1003      3000.0
1004      6000.0
1005      4500.0
```

[27]:
```
print(f"{ul_mv_df.shape[0]} policies in force at the modelling date.")
print("There is no separate boolean active-flag matrix: a policy that later␣
  ↪dies or lapses")
print("simply has its row dropped from mv_df / gv_df / premium_df (see steps␣
  ↪4-5 below).")
```

```
5 policies in force at the modelling date.
There is no separate boolean active-flag matrix: a policy that later dies or
lapses
simply has its row dropped from mv_df / gv_df / premium_df (see steps 4-5
below).
```

1.4 Dual cash accounts

- `bank_account` — fund / policyholder pool cash (flows into `trade()` in the full ALM run)
- `company_account` — insurer fee revenue (entry fee and admin fee; **not** passed through trading)

In this notebook we track toy cash balances to illustrate the methodology without running the full asset ALM loop.

[28]:
```
previous_date = settings.modelling_date
bank_account = pd.DataFrame(data=[0.0], columns=[previous_date])
company_account = pd.DataFrame(data=[0.0], columns=[previous_date])
```

[29]:
```
display(bank_account)
```

```
   2023-04-29
0         0.0
```

[30]:
```
display(company_account)
```

```
   2023-04-29
0         0.0
```

1.5 Period length

Modelling steps need not be exactly one year. OSEM uses the same convention as the asset side:

$$\Delta t = \frac{currentDate - previousDate}{365.25}$$

Annual fund rates and mortality are converted to the elapsed period (see steps below).

[31]:
```
current_date = previous_date + dt.timedelta(days=365)
time_frac = (current_date - previous_date).days / 365.25
```

[32]:
```
print("previous_date:", previous_date)
```

```
previous_date: 2023-04-29
```

[33]:
```
print("current_date:", current_date)
```

```
current_date: 2024-04-28
```

[34]:
```
print("time_frac:", time_frac)
```

```
time_frac: 0.999315537303217
```

1.6 Where UL sits in the ALM main loop

In `main.py`, after equities/bonds are marked to market and `Portfolio return` is computed, and **before** proportional `trade()`:

1. Capitalize MV (and GV if guaranteed) by the **period** portfolio return
2. Grow premiums; credit gross premium to `bank_account`; credit entry fee to `company_account`; add net to MV
3. Deduct admin fee from MV; credit `company_account`
4. Stochastic mortality (full MV liquidation if drawn)
5. Stochastic lapse on survivors
6. UL reserve = sum of active MV

This notebook uses an illustrative period return `r_period` (in the full run it comes from the asset portfolio).

[35]:
```
# Illustrative period return from the asset MTM step in main.py
# (that value already embeds time_frac on the asset side)
```

```
r_period = 0.05
print("Illustrative portfolio_return (period factor):", r_period)
```

```
Illustrative portfolio_return (period factor): 0.05
```

1.7 Step-by-step walkthrough

Carry forward previous state into the new date column, then apply each helper used by `process_unit_linked_period`.

[36]:
```
# Working copies so cells remain re-runnable independently after reload
mv_df = ul_mv_df.copy()
gv_df = ul_gv_df.copy()
premium_df = ul_premium_df.copy()

mv_df[current_date] = mv_df[previous_date]
gv_df[current_date] = gv_df[previous_date]
premium_df[current_date] = premium_df[previous_date]
bank_account[current_date] = bank_account[previous_date]
company_account[current_date] = company_account[previous_date]
```

1.7.1 1) Capitalize

Active policies:

$$MV_t = MV_t * (1 + r_t)$$

Where: - $r_t ...$ is the calculated portfolio return at time t. - MV_t^i ... is the market value of the policy i at time t.

Guaranteed policies also capitalize GV the same way.

[37]:
```
print("MV before capitalize:")
display(mv_df[[previous_date, current_date]])

mv_df, gv_df = capitalize_policies(
    mv_df, gv_df, ul_policies, current_date, portfolio_return=r_period
)

print("MV after capitalize:")
display(mv_df[[current_date]])
print("GV after capitalize (guaranteed policies only change):")
display(gv_df[[current_date]])
```

```
MV before capitalize:
```

	2023-04-29	2024-04-28
1001	120000.0	120000.0
1002	250000.0	250000.0
1003	75000.0	75000.0

```
1004    180000.0    180000.0
1005     95000.0     95000.0
```

```
MV after capitalize:
```

```
      2024-04-28
1001    126000.0
1002    262500.0
1003     78750.0
1004    189000.0
1005     99750.0
```

```
GV after capitalize (guaranteed policies only change):
```

```
      2024-04-28
1001         0.0
1002    210000.0
1003         0.0
1004         0.0
1005         0.0
```

1.7.2 2) Premiums and entry fee

$$P_t^{i,G} = P_{t-1}^{i,G} * (1 + pg_t)^{\Delta t}$$

$$F_t^{i,P} = P_t^{i,G} * f_t^P$$

$$P_t^{i,N} = P_t^{i,G} - F_t^{i,P}$$

$$b_t^c = b_t^c + F_t^{i,P}$$

$$MV_t^i = MV_t^i + P_t^{i,N}$$

Where: - pg_t ... premium growth for the period t. - Δt ... is the time fraction or the length of the period (in years) - $P_t^{i,G}$ ... is the gross premium for the policy i at time t - f_t^P ... is the entry fee charged by the asset manager at time t - $F_t^{i,P}$ ... is the size of the the entry fee, collected at time t in policy i - $P_t^{i,N}$ ... is the net premium for the policy i at time t - b_t^c ... is the company bank account at time t - MV_t^i ... is the market value of policy i at time t

[38]:
```
mv_df, premium_df, gross_premium, entry_fee = apply_premiums(
    mv_df, premium_df, ul_fund, current_date, time_frac
)
bank_account[current_date] += gross_premium
company_account[current_date] += entry_fee

print("gross_premium:", gross_premium)
print("entry_fee (to company_account):", entry_fee)
```

```
print("bank_account:", float(bank_account.loc[0, current_date]))
print("company_account:", float(company_account.loc[0, current_date]))
display(mv_df[[current_date]])
display(premium_df[[current_date]])
```

```
gross_premium: 27029.633633546677
entry_fee (to company_account): 810.8890090064004
bank_account: 27029.633633546677
company_account: 810.8890090064004
```

	2024-04-28
1001	130946.932948
1002	270415.092717
1003	81718.159769
1004	194936.319538
1005	104202.239653

	2024-04-28
1001	5099.930874
1002	8159.889399
1003	3059.958525
1004	6119.917049
1005	4589.937787

1.7.3 3) Admin fee

Actual administration fee:

$$adminFee_t = 1 - (1 - f_t^A)^{\Delta t}$$

$$F_t^{i,A} = MV_t^i * adminFee_t$$

$$MV_t^i = MV_t^i - F_t^{i,A} = MV_t^i * (1 - adminFee_t)$$

$$b_t^c = b_t^c + F_t^{i,A}$$

Where: - f^A ... is the relative size of the administration fee (on a yearly basis) - $F_t^{i,A}$ ... is the absolute size of the administration fee collected by the company - $adminFee_t$ ... is the relative size of the administration fee given the length of the period t

[39]:
```
mv_df, admin_fee = apply_admin_fees(mv_df, ul_fund, current_date, time_frac)
company_account[current_date] += admin_fee

print("admin_fee (to company_account):", admin_fee)
print("company_account:", float(company_account.loc[0, current_date]))
display(mv_df[[current_date]])
```

```
admin_fee (to company_account): 7816.860292067925
company_account: 8627.749301074326

         2024-04-28
1001  129638.355408
1002  267712.783401
1003   80901.534697
1004  192988.283920
1005  103160.926907
```

1.7.4 4) Mortality sampling (stochastic)

For each **active** policy (sorted by `policy_id`):

$$mF_t^i = 1 - (1 - q_t^i)^{\Delta t}$$

$u \sim \text{Uniform}(0, 1)$

If the fund is guaranteed then:

$$b_t^f = b_t^f - max(MV_t^i, GV_t^i) I_{u<mF_t^i}$$

Otherwise:

$$b_t^f = b_t^f - MV_t^i I_{u<mF_t^i}$$

If the draw liquidates the policy it is **removed** from the state matrices entirely: `mv_df`, `gv_df` and `premium_df` all drop that row. It is not zeroed in place, so a liquidated policy cannot be charged a premium or a fee in any later period.

Where: - b_t^f ... is the fund's own bank account - mF_t^i ... is the the probability, the client in policy i dies within period t. - q_t^i ... is the probability that a person that is the same age as client in policy i in the same year as the start of period t.

Using a forced RNG that always survives makes the path deterministic for teaching.

[40]:
```
class AlwaysSurvive:
    def random(self):
        return 0.99

mv_df, gv_df, premium_df, death_total, deaths = apply_mortality(
    mv_df, gv_df, premium_df, ul_policies, society, current_date, time_frac,␣
 ↪AlwaysSurvive()
)
bank_account[current_date] -= death_total

print("deaths:", deaths, "death_total:", death_total)
print("policies remaining in force:", mv_df.shape[0])
display(mv_df[[current_date]])
```

```
deaths: 0 death_total: 0.0
policies remaining in force: 5

         2024-04-28
1001   129638.355408
1002   267712.783401
1003    80901.534697
1004   192988.283920
1005   103160.926907
```

1.7.5 5) Lapse sampling (survivors only)

Same Bernoulli pattern with period-scaled `lapse_rate` on policies that remain active after mortality.

For each **active** policy (sorted by `policy_id`):

$$lF_t^i = 1 - (1 - l_t)^{\Delta t}$$

$u \sim \text{Uniform}(0, 1)$

If the fund is guaranteed then:

$$b_t^f = b_t^f - max(MV_t^i, GV_t^i) I_{u<lF_t^i}$$

Otherwise:

$$b_t^f = b_t^f - MV_t^i I_{u<lF_t^i}$$

If the draw liquidates the policy it is **removed** from the state matrices entirely: `mv_df`, `gv_df` and `premium_df` all drop that row. It is not zeroed in place, so a liquidated policy cannot be charged a premium or a fee in any later period.

Where: - b_t^f ... is the fund's own bank account - lF_t^i ... is the the probability, the client in policy i lapses within period t. - l_t ... is the probability that a person lapses in the same year as the start of period t.

[41]:
```
mv_df, gv_df, premium_df, surrender_total, lapses = apply_lapse(
    mv_df, gv_df, premium_df, ul_fund, current_date, time_frac, AlwaysSurvive()
)
bank_account[current_date] -= surrender_total

print("lapses:", lapses, "surrender_total:", surrender_total)
print("UL reserve:", ul_ptf.total_reserve(mv_df, current_date))
print("policies remaining in force:", mv_df.shape[0])
print("bank_account:", float(bank_account.loc[0, current_date]))
print("company_account:", float(company_account.loc[0, current_date]))
```

```
lapses: 0 surrender_total: 0.0
UL reserve: 774401.8843324725
policies remaining in force: 5
bank_account: 27029.633633546677
company_account: 8627.749301074326
```

1.8 One-shot orchestrator (`process_unit_linked_period`)

The production helper carry-forwards state, runs steps 1–5, and returns cash-flow totals. Signs for summary reporting are applied in `main.py` (benefits logged negative).

[42]:
```
mv2, gv2, prem2 = ul_ptf.init_policy_state_to_dataframe(previous_date)

mv2, gv2, prem2, cfs = process_unit_linked_period(
    current_date=current_date,
    previous_date=previous_date,
    portfolio_return=r_period,
    time=time_frac,
    mv_df=mv2,
    gv_df=gv2,
    premium_df=prem2,
    policies=ul_policies,
    fund=ul_fund,
    society=society,
    random_seed=settings.random_seed,
    proj_period=0,
)

display(pd.Series(cfs, name="cashflows"))
print("UL reserve:", ul_ptf.total_reserve(mv2, current_date))
print("policies remaining in force:", mv2.shape[0])
display(mv2[[current_date]])
```

```
gross_premium     27029.633634
entry_fee           810.889009
admin_fee          7816.860292
death            267712.783401
surrender             0.000000
deaths                1.000000
lapses                0.000000
in_force              4.000000
Name: cashflows, dtype: float64
```

```
UL reserve: 506689.10093148355
policies remaining in force: 4
```

```
         2024-04-28
1001  129638.355408
1003   80901.534697
```

```
1004  192988.283920
1005  103160.926907
```

1.9 Reproducibility

The same `random_seed` and `proj_period` produce the same draws. Different seeds can change liquidations.

[43]:
```python
def run_seeded(seed: int):
    mv, gv, prem = ul_ptf.init_policy_state_to_dataframe(previous_date)
    *_, cfs = process_unit_linked_period(
        current_date=current_date,
        previous_date=previous_date,
        portfolio_return=r_period,
        time=time_frac,
        mv_df=mv,
        gv_df=gv,
        premium_df=prem,
        policies=ul_policies,
        fund=ul_fund,
        society=society,
        random_seed=seed,
        proj_period=1,
    )
    return cfs["deaths"], cfs["lapses"], cfs["in_force"]

print("seed 42:", run_seeded(42))
print("seed 42 again:", run_seeded(42))
print("seed 99:", run_seeded(99))
```

```
seed 42: (0.0, 1.0, 4.0)
seed 42 again: (0.0, 1.0, 4.0)
seed 99: (0.0, 0.0, 5.0)
```

1.10 Multi-period illustration

Roll several periods with a fixed illustrative return and the configuration seed. Track reserve, company account, and policies in force.

`proj_period` counts completed periods and starts at 0, matching `main.py`, so that the draws here reproduce those of a production run with the same seed.

The `Bank account` column goes deeply negative. That is an artifact of this standalone illustration: there is no asset book here, so death and surrender payments are drawn from an account that opens at zero and is never replenished by asset income or `trade()`. In a full run the same flows are netted against the portfolio. Read it as a cumulative fund cash flow, not as a balance.

[44]:
```python
n_periods = 10
mv, gv, prem = ul_ptf.init_policy_state_to_dataframe(settings.modelling_date)
company = pd.DataFrame(data=[0.0], columns=[settings.modelling_date])
```

```
bank = pd.DataFrame(data=[0.0], columns=[settings.modelling_date])

history = []
prev = settings.modelling_date
for k in range(1, n_periods + 1):
    curr = prev + dt.timedelta(days=365)
    tf = (curr - prev).days / 365.25
    company[curr] = company[prev]
    bank[curr] = bank[prev]

    mv, gv, prem, cfs = process_unit_linked_period(
        current_date=curr,
        previous_date=prev,
        portfolio_return=0.04,
        time=tf,
        mv_df=mv,
        gv_df=gv,
        premium_df=prem,
        policies=ul_policies,
        fund=ul_fund,
        society=society,
        random_seed=settings.random_seed,
        proj_period=k - 1,
    )
    bank[curr] += cfs["gross_premium"] - cfs["death"] - cfs["surrender"]
    company[curr] += cfs["entry_fee"] + cfs["admin_fee"]

    history.append({
        "date": curr,
        "UL reserve": ul_ptf.total_reserve(mv, curr),
        "Company account": float(company.loc[0, curr]),
        "Bank account": float(bank.loc[0, curr]),
        "In force": cfs["in_force"],
        "Deaths": cfs["deaths"],
        "Lapses": cfs["lapses"],
        "Gross premium": cfs["gross_premium"],
    })
    prev = curr


history_df = pd.DataFrame(history).set_index("date")
display(history_df)

try:
    ax = history_df[["UL reserve", "Company account"]].plot(
        figsize=(9, 4), title="UL reserve and company account"
    )
    ax.set_ylabel("Amount")
```

```
except ImportError:
    print("Install matplotlib to plot this table (optional).")
```

```
              UL reserve  Company account   Bank account  In force  Deaths  \
date
2024-04-28  502036.068923      8555.798335 -238208.132742       4.0     1.0
2025-04-28  535382.796668     14537.391590 -218961.254499       4.0     0.0
2026-04-28  361389.714927     20880.823544 -408026.216153       2.0     0.0
2027-04-28  383522.924501     25109.310800 -396120.107919       2.0     0.0
2028-04-27  406539.946060     29577.272016 -383976.042125       2.0     0.0
2029-04-27  430471.513783     34294.081352 -371589.262908       2.0     0.0
2030-04-27  455349.363078     39269.436160 -358954.919357       2.0     0.0
2031-04-27  481206.262048     44513.367465 -346068.063605       2.0     0.0
2032-04-26  508076.043928     50036.250770 -332923.648902       2.0     0.0
2033-04-26  535993.640518     55848.817211 -319516.527628       2.0     0.0

            Lapses  Gross premium
date
2024-04-28     0.0   27029.633634
2025-04-28     0.0   19246.878242
2026-04-28     2.0   19631.549716
2027-04-28     0.0   11906.108233
2028-04-27     0.0   12144.065794
2029-04-27     0.0   12386.779217
2030-04-27     0.0   12634.343552
2031-04-27     0.0   12886.855751
2032-04-26     0.0   13144.414704
2033-04-26     0.0   13407.121274
```



1.11 Connection to the full ALM run

In `src/osem/main.py` with `liability_mode=unit_linked`:

1. Assets still evolve first (dividends, coupons, growth, bond reprice).
2. `Portfolio return` from the asset book capitalizes UL accounts.
3. UL cash flows update `bank_account` and `company_account`.
4. Proportional `trade()` invests / disinvests using **fund** cash only (`company_account` is excluded).

Switch the mode in `Input/Parameters.csv`:

```
liability_mode,unit_linked
random_seed,42
```

Then run the model as a module (`python -m osem.main`, or the `osem` console script after `pip install -e .`) and inspect `Output/Results.csv` for the UL summary columns.

Run this notebook from the repository root so `ALM.ini` and `Input/` resolve correctly.

1.12 Out of scope for this MVP

New business, lifecycle fund migration, full DCF reserving, company-account payouts, morbidity / retirement, and multi-fund asset buckets are not modelled yet.