Teaching basic computer architecture, assembly language programming, and operating system design using RISC-V

Liliana Andrade, Mounir Benabdenbi,
Olivier Muller, Frédéric Rousseau,
Frédéric Pétrot

tima.imag.fr/sls/people/petrot

frederic.petrot@univ-grenoble-alpes.fr

RISC-V®
The RISC-V Week
Paris • October 1 to 3

Grenoble INP ensimag · POLYTECH GRENOBLE · Grenoble INP phelma

Outline

Grenoble INP ensimag

Preamble

Today's view on computers and processors

What computer a typical first year Computer Science (CS) students owns?

- You name it! But all are x86-64 based!

What processors do typical first year CS students know?

- Intel Core Ix, sometimes named x86 (or x86-64 for the connoisseurs)
- AMD Ryzen, but wait, this is also an x86!
- Atom, that's in my tablet, x86, uh, ...

Other devices

they know phone brands, but not the processors in them

1991 1992 1993 ... 2015 2016 2017

Intel did it right!

Grenoble INP ensimag

Preamble

Intel did it right, but ...

- "[x86] mov is Turing-complete", Stephen Dolan, 2013.
  Actual code generator `https://github.com/xoreaxeaxeax/movfuscator`
  But wait, why bother with instructions?
- "[x86] Page-faults are Turing-complete", Julian Bangert and Sergey Bratus, 2015.
  Actual code generator `https://github.com/jbangert/trapcc`

Although x86 is the mainstream desktop computer architecture, it may be worth using something else as a pedagogical vehicule!

Grenoble INP ensimag

Outline

Grenoble INP ensimag

Introduction

Teaching computer engineering using RISC-V

Target students

Bologna style L3/M1/M2 in Computer Science or Electrical Engineering
In reality engineering schools in Grenoble
Ensimag, computer science
Phelma, electronic and micro-electronic engineering
Polytech Grenoble, electronics engineering and industrial IT

Goal

Unifying a set of classes using various processors under the RISC-V umbrella

Outline

Grenoble INP ensimag

Overview of the curriculum

Basic computer architecture
(Computer Science, 3rd year, ≈250 students, Electronics Engineering, 5th year, ≈20 students)

- digital circuit design for computer scientists
- ISA interpretation using a finite state machine + data-path

Assembly language programming
(Computer Science, 3rd year, ≈250 students)

- basic instruction usage
- function calling conventions and C ABI

Grenoble INP ensimag

Overview of the curriculum

Computer architecture (Computer Science, 4th year, ≈40 students)

- 5 pipeline stages processor
- multiprocessor and atomic operations

Operating system implementation (Computer Science, 4th year, ≈75 students)

- boot, interrupt, kernel threads
- virtual memory, processes

Grenoble INP ensimag

Overview of the curriculum

System level design in SystemC (Computer Science, 5th year, ≈20 students)

- hardware modeling in SystemC, transaction level modeling
- modeling in SystemC with native or cross-compiled software

HW/SW system integration (Electrical Engineering, 5th year, ≈40 students)

- performance analysis of a cache-based multiprocessing system
- HW/SW integration on FPGA

Overview of the curriculum

	L3/Bachelor	M1/Master	M2/Master
Ensimag	Basic computer architecture	Operating system implementation	System level design in SystemC
	Assembly language programming	Computer architecture	
Polytech		Computer architecture	Basic computer architecture
Phelma			HW/SW system integration

Outline

Basic computer architecture

Class and practical objectives

Write VHDL code interpreting instructions to understand why a computer needs to be powered, how it might execute a program, and why it is not indefinitely fast

What do we provide the students?

- VHDL of an FSM squeleton and a data-path with a few missing parts
- ordered list of instructions (encoding+behavior) to implement
- test environment to check their implementation



Basic computer architecture

What do we expect from the students?

- Proper decoding and execution of instructions with FSM+data-path
- Add missing parts in the data-path
  - condition computations for branches
  - control and status registers
  - interruptions
- Mapping on Xilinx FPGA board with 100 MHz minimal frequency target
- Own unitary test for each instruction
  - shall not depend upon future implemented instructions
  - are pretty easy develop as the micro-architecture is naïve

Basic computer architecture

MIPS I neat, not so hype anymore

- all instructions are 32-bit
- 38 instructions including `eret`
- 3 instruction formats
- 5 immediate formats, zero or sign extended, 16-bit or 26-bit
- reg/reg instructions update `rd`, reg/imm instructions update `rt`
  ⇒ `sllv` and `srav` instead of `slli/srai`
- delay slot, hidden from the students
- branch target computed using pc + 4

⇒ both former specificities assume pipeline implementations

RISC-V rv32i stylish and trendy

- all instructions are 32-bit
- 32 integer instruction including `mret`
- 6 instruction formats
- 6 immediate formats, sign extended, weirdly built, 12-bit or 20-bit
- all instructions update rd
- no delay slot
- branch target computed using pc as is

⇒ no specific implementation strategy inferred

Basic computer architecture



Basic computer architecture

Conclusion

Complexity is alike, but RISC-V has a few interesting features:

- all instructions update rd
- no delay slot
- branch computed using pc directly
- strange ways to compute the immediats
  example: branch offset $\Leftarrow (IR_{31}^{20} \parallel IR_7 \parallel IR_{30\ldots25} \parallel IR_{11\ldots8} \parallel 0)$

And is much more attractive to our students
google "RISC-V processor" : "Environ 9.050.000 résultats (0,60 secondes)"
google "mips processor" : "Environ 3.380.000 résultats (0,62 secondes)"

Small demo

Sneaking into some code
FPGA demo

Introduction to asm programming (3rd year, ≈250 students)

Objective of the class

- writing simple programs in asm
- understand variable classes: data, heap, stack
- systematically translate 'C' statements in asm
- ABI oriented towards function calling conventions

What did we do in the past?

- used an x86 subset
  guaranteed headache, 13 different ABI running in the wild!
- moved to MIPS ISA, excluding unaligned word accesses, and MIPS o32 ABI

Grenoble INP ensimag

Introduction to asm programming (3rd year, ≈250 students)

What do we provide the students?

- Cross-development environment
- QEMU mimicking system of the “Basic Computer Architecture” class
- C source code of the exercises

What do we expect from the students?

- assembly code written as literally as possible
  e.g. as generated by `gcc -O0`
- agile usage of the cross-dev environment
  particularly `gdb` using remote connection on `QEMU`
- ability to call and be called from C functions
- understand low-level interrupt service routines

Introduction to asm programming (3rd year, ≈250 students)

MIPS I ABI in a nutshell

- all instructions but stores have their results in right-hand-side
- registers have hardware and software names
  `$0, ..., $31` vs `$zero, $at, $v0, ..., $a0, ..., $t0, ..., $s0, ...`
- register `$zero` writable but always reads as zero
- 4 first arguments in `$a0, ..., $a3` and return value in `$v0`
- all jumps followed by a `nop` to avoid explaining the delay slot
- macros make use of the implicit register `$1` (`$at`)

Introduction to asm programming (3rd year, ≈250 students)

- macro accept weirdly written asm lines
  `addi $t0, 0xf00d` ⇒ `addi $t0, $t0, 0xf00d`
  `lw` and `sw` accept constants and symbols as arguments
  `lb $t0, 0xdeadbeef` ⇒ `li $t0, 0xdeadbeef / lb $t0, 0($t0)`
  `sw $t0, variable` ⇒ `la $at, variable / sw $t0, 0($at)`
  But who knows if that is what the student meant to write ???
- sign extended or zero extended 16-bit immediates
  visual instruction type and constant binary decoding easy for the teacher
  `addi $v0,$v0,0xffffdead` ⇒ "operand out of range" although sign extended
  `ori $v0,$v0,0xdead` ⇒ no error although zero extended
- interrupt/exception/traps all jump at same address
  ⇒ everything done in software
- access to cause, status and timer related registers using two simple instructions `mfc0/mtc0`

Introduction to asm programming (3rd year, ≈250 students)

RISC-V psABI quite similar in spirit to MIPS

- all instructions but stores have their results in right-hand-side
- registers have hardware and software names
  `x0, ..., x31` vs `zero, ra, ..., a0, ..., t0, ..., s0, ...`
- register `zero` writable but always reads as zero
- 20 and 12 bit immediates always sign extend
  `addi x31, x31, 0xbad` ⇒ "invalid operand error"
  `0x00000bad` ≠ `0xfffffbad`
- even stranger:

```
li x31, 0xdeadbeef => lui  x31,      0xdeadc
                      addi x31, x31, 0xffffeef
```

- `sw` and `lw` accept a symbol as argument, but not a constant

Introduction to asm programming (3rd year, ≈250 students)

- 8 first arguments in `a0`, ..., `a7` and return value in `a0`
- no delay slot to hide
- access to cause, status and timer related registers using `csrrw` instructions
- only machine mode interrupt/exception/traps presented, configuration without vectors ⇒ everything done in software
- CLINT and PLIC make things more complex than MIPS to handle simple timer interrupt



Introduction to asm programming (3rd year, ≈250 students)

Stack layouts

MIPS I r3000

high addresses	5th parameter	other ones above
↓	room for `$a3`	needed only if callee
↓	room for `$a2`	wants them back after
↓	room for `$a1`	calling an other function
↓	room for `$a0`	`$sp` in caller (f)
↓	`$ra`	return address (g)
↓	registers to be	
↓	saved	
↓	local variables	
↓	parameter $n-1$	when calling
↓	...	an other
↓	parameter 5	function (h)
↓	room for `$a3`	
↓	room for `$a2`	
low addresses	room for `$a1`	for the next call (h)
	room for `$a0`	`$sp` in callee (g)

RISC-V rv32i

high addresses	f local variables	sp in callle (f)
↓	`ra`	return address
↓	other registers	
↓	to save	
↓	g local variables	
↓	parameter $n-1$	preparing call to
↓	...	next function h
↓	parameter 8	sp in callee (g)
low addresses	...	

A bit easier to explain to students

Introduction to asm programming (3rd year, ≈250 students)

Conclusion

Complexity is alike, but RISC-V rv32i has a few interesting features:

- (very) low integer instruction count
- integer calling conventions pretty simple for fixed number of parameters
- no delay slot
- an unusual pc-relative instruction `auipc`

Small demo

Small function example
QEMU demo

Operating System Implementation (4th year, ≈75 students)

Objective of the class

- understand what happens when a computer is turned on
- understand virtual memory to physical memory translation
- learn to implement:
  boot, kernel threads,
  page tables, frame allocation (overlays ⇒ no file system, no page faults)
  user processes, queues, shared memory, ...
- do all that on RISC-V 64 using QEMU sifive_u board

What did we do (and still do) before?

- originally developed for x86-32
- hiding quite a few stuff under the carpet
- still in use: only 2 groups over 8 did it on RISC-V last year

Grenoble INP ensimag

Operating System Implementation (4th year, ≈75 students)

What do we provide the students?

- skeleton of code, with set of (complex) Makefiles
- header files with helper functions
  inline asm stuff, Linux priority queues, ...
- ≈ 15 userland tests stressing the implementation

What do we expect from the students?

- handle timer interrupts
- build all OS functions first in kernel mode
  starting by process creation and context switch
- add (limited) support for virtual memory
- understand that there is one page table structure per process
- add system calls to wrap the kernel OS functions

Grenoble INP ensimag

Operating System Implementation (4th year, ≈75 students)

What changes when using RISC-V

- move to 64-bit
- boot phase can be fully written by the students
  no gory details of x86 legacy to skip over
  avoid hardwired stuffs that are hardly explainable: `idt`, `gdt`, `tss`, ...
  ⇒ still need to configure the `pmp` areas
- simpler interruption mechanism and implementation of system calls
  no implicit push of things on stack
  ⇒ interruption setup a bit complex: `m[ei]deleg`, shadow registers, ...

Operating System Implementation (4th year, ≈75 students)

And page tables, somehow more complex on RISC-V

x86 page tables



RISC-V SV39 page tables



Operating System Implementation (4th year, ≈75 students)

Conclusion

x86-32 vs RISC-V 64 fight not over!

- x86 students like x86 as they know its name
- x86 page table structure
- x86 see only kernel and user mode
- RISC-V boot process from start address user mode
- RISC-V no weird hw tables to update here and there
- RISC-V no implicit stuff pushed on or popped from the stack

Overall different, allowing to go a bit more in depth on hw related matters

Small demo

Setting and activating the page tables

Grenoble INP ensimag

Computer architecture (4th year, ≈35 students)

Objective of the class

- detail how simple 3/4/5/6 stage pipeline processors work
  bypasses, interlocks
- explain cache coherency and memory consistency issues and solutions
  MSI, MESI protocols, plus atomic operation support

What did we do (and still do) before?

- CAAQA with 5-stage pipeline MIPS, like everyone does!

Grenoble INP ensimag

Computer architecture (4th year, ≈35 students)

Main changes due to RISC-V in classical 5-stage pipeline

On branches

- non-conditional branches have no delay slot
  kill (at least) 1 following instruction
- conditional branches are complex and resolved late
  kill 2 following instructions if branch taken

⇒ Quite expensive, ...

Computer architecture (4th year, ≈35 students)



Computer architecture (4th year, ≈35 students)

Conclusion

Simple 5-stage pipeline implementation of RISC-V is:

- less efficient or harder
  branch instructions will increase the CPI
  or a branch predictor must be added
- a bit bigger, because pc must be propagated
- but the critical path should be shorter

Numerous atomic memory operations to present

No demo

Lucky you!

Grenoble INP ensimag

System level design in SystemC (5th year, ≈20 students)

Objective of the class

Class targeting an in-depth presentation of SystemC TLM concepts and modeling

- introduce the notion of virtual prototype
- show how to model and simulate a digital system in SystemC before its actual implementation
  - using "native" simulation, through dedicated APIs
  - using an instruction accurate simulator
- build the same system on a (cheap) FPGA board and run the same software

What did we do before?

- Originally developed around Xilinx' microblaze
  - SystemC model from the SoCLib library
  - microblaze RTL model from Xilinx

System level design in SystemC (5th year, ≈20 students)



System level design in SystemC (5th year, ≈20 students)

Using RISC-V

Interest

- very parameterizable architecture
- compressed instructions

But needs

- simple SystemC compatible ISS
  ⇒ developed a SoCLib rv32imafc model (machine mode only)
- synthesizable core on Xilinx FPGAs
  ⇒ have (a very very slow) one from Basic Architecture class, good enough

Note that keeping in pace with Vivado hurts, ...

Small demo

Native and cross-compiled top level
System execution

HW/SW System Integration with RISC-V (5th year, ≈40 students)

Objective of the class

Teaching the link between HW and SW in SoCs

- SW environment (assembly, linker, ISA simul., compil., debug)
- HW environment (SoC generation, emulation, ...)
- exceptions, interrupts and traps
- multi-tasking, multi-processing and memory coherence
- development and integration of a custom peripheral with its HAL
- HW and SW mapping ⇒ C application on FPGA

Grenoble INP ensimag

HW/SW System Integration with RISC-V (5th year, ≈40 students)

Needs

- tunable, fast to simulate HW/SW platform
- open source and synthesizable HW/SW SoC ⇒ FPGA evaluation
- platform widely accepted and well supported

⇒ Berkeley's RISC-V based Rocket Chip SoC generator



HW/SW System Integration with RISC-V (5th year, ≈40 students)

Design Flow



HW/SW System Integration with RISC-V (5th year, ≈40 students)

Show impact of array placement in memory on L1 collision

L1 data-cache: 8 kB, 256 blocks, 32-byte each
x , y arrays of 4096 elements of 32-bit
address of x is `0x8101_0000`, address of y is `0x8101_4000`

```
loop: for (i = 0; i < 4096; i++)
          s += x[i] + y[i];
```

- paper analysis of execution to evaluate dcache miss rate
- execution with `spike` to gather statistics
- propose a better placement of y to avoid collision
  hint: make sure x and y never share a line

Small demo

Cache statistics with `spike`, with the bad and the good choices

HW/SW System Integration with RISC-V (5th year, ≈40 students)

Real-time multi-tasking

Students

- analyze and complete assembly code
  - memory tasks allocation, init stacks, ...
  - save/restore contexts, switch tasks, scheduling, ...
  - time allocation: give #ticks per task
- code two simple tasks in C, *e.g.* increment in turn a shared variable
- simulate and debug using Spike simulator: functional validation

Grenoble INP ensimag

HW/SW System Integration with RISC-V (5th year, ≈40 students)

Real-time multi-tasking

- simulate the HW using the cycle-accurate bit-accurate C++ Emulator

T1 = T2 = 100 ticks



T1 = 100 ticks, T2 = 300 ticks



Outline

Grenoble INP ensimag

Take away

Momentum around RISC-V brings in some freshness

Opportunity to renew classes

Not a revolution: basics are basics, but:

- benefit from the hype
- make student aware that x86-64 doesn't rule them all
- escape complex CISC or complex RISC ISA

Benefit for teachers

- clean and orthogonal ISA (at least for rv32i)
- simple integer calling conventions
- stable cross-development tools, including simulators
- actual implementations on FPGA (even too many perhaps!) and ASIC

$\Rightarrow$ useful replacement to a mix of x86/MIPS/whatever all along the curriculum

Take away

Fear

Are we taking a reckless risk(-v)?

Thanks

Students/Engineers/PhD that have contributed to the classes

- Noureddine Ait-Said (IRT)
- Amaury Butaux (TIMA)
- Marius Leblanc (TIMA)
- Loïc Jovanovic (TIMA)
- Robin Stieglitz (IDEX)
- Arthur Vianes (IDEX)

Sponsors

Grenoble INP ensimag