The Reality Code Engine: One Lossless Form for Native, Verified, Low-Energy Programming

David Charlot, Open Interface Engineering

Research paper · OpenIE research.openie.dev
https://research.openie.dev/papers/rce/ · PDF https://research.openie.dev/pdfs/rce.pdf

Measurement. Research paper, not a journal final. Handler figures are est_j. Track B figures are reported_j from a RAPL package counter less a stated idle baseline. measured_j is reserved for a wall meter and is empty. No FPGA board result in this paper. No fabricated citations.

> A programming system in which a program is written once as a state machine and every target language is generated from it, with measurements of round trips, refusal of malformed input and repair of lifted code.

Version 1.4, 13 October 2026. Specification: current draft (draft 0.7 document, language version 0.8), from openIE-dev/rce `2a0ec68`. Changes in 1.4: the engine test count is the 589 distinct tests that `cargo test --release` runs (1.3 printed 596, the `make check` total, which counts 7 proof tests twice); Section 3.7 states that specification 2.7 now gives the per-call-site cost rule of C.15; the deterministic proposer of Section 5.5 is reported as 87 offered, 9 admitted and 78 rejected, from the engine test; Software Heritage and Rosetta Code in Section 7 carry references [129] to [131], with the archive counters reread; nine figures are added (Figures 5 to 10, 12, 13 and 15) and the earlier Figures 5 and 6 are now Figures 11 and 14. Changes in 1.3: size-scaled method costs are attributed to language version 0.7 (they were described under 0.6 in 1.2), the per-call-site rule for mixed-version programs is stated, and the checks are rerun at engine commit `1eb5f02`. The German translation, like the other translations, remains at version 1.1. Data and code: research.openie.dev/data/. Playground (reference checker): openie-dev.github.io/rce. Engine demo: /demos/rce-engine/. LaTeX PDF: /pdfs/latex/rce.pdf (source).

Corrections and reproducibility status (17 October 2026). This note was added after a read of the paper against the public repositories. The figures it affects are listed here and the text below is otherwise unchanged. Every count below comes from `src/data/rce-facts.json`, produced by `scripts/claim-counts.py` in openIE-dev/rce at `e416fd0`, except the two Lean counts, which were taken at `4304048`.

- **Versions and counts at public `rce` main.** The specification document is draft 0.9 (public since `cdae5cf`). The reference checker accepts language versions 0.5 to 0.9 and refuses the parts of version 0.9 it does not implement by version (Appendix F.12). Theorems T1 to T56 are stated; T42 to T56 (Appendix F) are stated and unproved. There are 58 Lean modules and 59 example programs (57 top-level and 2 in packages). The figures and captions in this paper that say draft 0.7, language version 0.8, T1 to T34, 31 files or 51 examples describe the repository at the earlier commits they name, and this paper does not describe draft 0.9 beyond this note.

- **Lean theorem count.** Two different counts exist. The source holds 1,116 `theorem` and `lemma` declarations at `e416fd0` (885 at `4304048`). The audit (`scripts/lean-audit.sh`) counts every theorem constant in the kernel environment, including constants the elaborator generates, and gave 4,877 on a rerun over the public repository at `e416fd0`, where `lake build` completes over 58 files of `spec/lean/RCE/` with no `sorry` and standard axioms only (2,949 over 46 files at `4304048`). The 2,192 quoted below is the audit count at engine commit `1eb5f02` over 31 modules. Neither number says anything about how many theorems are proved about the Rust evaluator.
- **Reproducible from public repositories today:** the Lean build and axiom audit, the specification check (grammar tables and example corpora), the reference checker and its tests, and the canonical JSON vectors.
- **Not yet reproducible from public repositories:** the 10,000-Form ecosystem run (`bench/ecosystem` is not in the public repositories), the Kani results, the 589 engine tests, the repair rates of Section 6 and any Defects4J number. They are reported here as the authors' own runs and should be read that way until the sources and seeds are published.
- **Falsifier RCE-F0.** See the note in Section 2.3 below.

Abstract

This paper describes the Reality Code Engine (RCE), a system in which a program is written once as a state machine, called a Form, and code in other languages is generated from it. It reports what was measured on 10,000 Forms and on public bug datasets, and states how the claims could be shown false.

In plain words

1. A program is written once, in one precise form, and the computer produces the same program in many languages from it.
2. Because the form only allows what was declared, broken input is rejected at the door instead of being fixed later.
3. A fix that passes the checks is saved and reused, so the same problem does not cost time or energy twice.

---

1. Thesis

Autonomous computer automation is a design space with many points in it. Every approach sits somewhere along five continuous axes: the energy spent per correct result; the entropy the system must resolve at run time, and with it how deterministic its output is; the strength of the verification that accepts a result; how far each accepted result is reused and compounds; and how much the approach relies on a model. A large language model (LLM), a statistical text model, that writes each change from the prompt sits near one corner of that space: it relies on the model

for every task, draws a fresh sample from a high-entropy distribution each time, and pays for generation again on every task. Retrieval, rules, synthesis, verification and caching occupy many other points, and real systems combine them.

The Reality Code Engine (RCE) is one point in the space, and this paper describes and measures it. RCE models a program as a database functional state machine. Lopes and colleagues measured that about 70% of the code on GitHub consists of clones of earlier files [33], so RCE first tries to retrieve an existing fit, adapt it and check it, and calls a model only when nothing cheaper closes the task.

The core claim. RCE is a complete code ecosystem in which programs are authored natively from intent. Intent is written once, as a Form: a state, a set of events and a pure, total transition. The Form is a lossless encoding of that intent. Every target (statechart, Rust, Python, XState, SCXML, WASM) is a projection of the Form, and each projection replays the Form's trace byte for byte. A state the Form does not declare cannot be written, and an input outside its contract is refused at entry. A program in the ecosystem therefore cannot drift from its intent the way a program in a common language drifts from its comments, its tests or its other implementations, and it needs no after-the-fact diffing or error tracking. Every fit that passes the gate is stored and reused, so the ecosystem compounds as it grows (§2.4). Code written in other languages is one door in: it enters by lift (§6).

Every point in the space faces the same gate. The gate is correctness: a task's completeness predicate $C(z)$, here the task's tests, a proof or an agreement trace. Among runs that pass the gate, systems are ranked by joules to completion, J^*. Correctness is a constraint, not a score.

RCE's mechanisms, called gears, run in order of cost, and the first gear that passes the gate closes the task.

Energy figures are labeled by source. `est_j` is an analytical estimate. `reported_j` is an operating-system or on-chip counter. `measured_j` is reserved for a wall meter and is empty in every result here.

---

2. The design space of autonomous coding


One sentence in. One floor out. Human intent is high entropy; a funnel of conversions from intent to spec to 626 surface languages to an intermediate representation to machine code loses information at each boundary; all code reaches a few machine shapes; RCE writes the meaning once in one canonical Form, treats every surface as a projection, and lets the cheapest correct form win.
Figure 1. Intent entropy and the machine floor. A PNG copy is provided. Sources: Shannon (1951); Lopes et al. (2017); the 626-language count is an unpublished survey by the OpenIE authors and supports no claim in this paper. The Python and C results are language specification behavior; C signed overflow is undefined behavior.
Open full size · PNG

Intent is high entropy. "Make the checkout faster" carries many meanings: shorter page load, fewer steps, faster card approval, a cached cart, or faster on one device class. Context is implied and never written. Shannon measured printed English at about 0.6 to 1.3 bits per letter [1]. The letters are predictable. The meaning is not.

Every conversion loses information. Intent becomes a specification, and context is lost. The specification becomes one of hundreds of surface languages, and alternatives and edge cases are lost. The source becomes an intermediate representation (IR), and names, style and the author's reasons are lost. The IR becomes machine code, and types become sizes and loops become jumps.

The floor is low entropy. Every program ends as loads, stores, arithmetic and jumps. The destination has room for only a few shapes, so code bends toward them. Convergence is by design.

Boundaries are where meaning diverges. The same line gives different answers at the edges. In Python, `-3 % 2` is 1 and `-7 / 2` is -3.5. In C, `-3 % 2` is -1, `-7 / 2` is -3, and signed overflow is undefined. A system that regenerates code at every boundary guesses at every boundary.

The axes, stated as quantities.

Axis	One end	Other end	Where RCE sits
Energy per correct result	Paid again in full on every task	Paid once per new case, then the handler floor	At the floor on covered tasks
Entropy resolved at run time, and determinism	The full distribution of the prompt, a fresh sample each time	Only the residual no stored fit covers, one deterministic output	The residual only; every projection deterministic
Verification strength	Output accepted on inspection	Tests, coverage and a proof certificate	The full gate on every result
Reuse and compounding	Each result used once	Each accepted fit stored and reused	Every fit that passes the gate is stored
Model reliance	A model on every task	No model	A model only as the last gear

Approaches differ by degree on each axis, and the axes interact: reuse lowers energy and the entropy left to resolve, and strong verification is what makes reuse safe. RCE writes the meaning once, in one canonical Form. Every surface language is a projection of that Form, checked to match it. Among equivalent forms, the cheapest correct one runs.

Figure 2 draws the five axes and places the main classes of approach on them.



Radar chart with five axes: energy per correct result, determinism, verification strength, reuse and compounding, and independence from models. Five approach classes are drawn as polygons. A model on every task sits near the centre on all axes. An agent loop gated by tests is higher on verification. A model with retrieval and caching is higher on reuse. Classical synthesis and repair is high on determinism and model independence. RCE, marked with stars, sits at or near the outer ring on all five axes. Placements are qualitative.

Figure 2. The design space of autonomous coding. Qualitative diagram: each class of approach is placed by the paper's reading of Section 2 on ordinal levels, not by measurement. Model reliance is drawn as independence from models so that outward is better on every axis. A PNG copy is provided. Open full size · PNG

2.1 Programming is coding theory

The thesis of this section is that programming can be read as coding theory. A programmer converts intent along a gradient between two entropic regimes. Intent is high entropy, a distribution over meanings. Code is low entropy, one deterministic transition per state. Every step of software work, from a requirement to a register, is a step of that conversion. The literature has said so in pieces for seventy years, in many languages. This section assembles the pieces into one argument and places each RCE gear on it.

The measure. Shannon defined the entropy of a source and the capacity of a channel [40], and measured printed English at about 0.6 to 1.3 bits per letter [1]. Kolmogorov, writing in Russian in *Problemy Peredachi Informatsii* in 1965, gave three approaches to the quantity of information and made the algorithmic one primary: the information in an object is the length of the shortest program that produces it [41]. Solomonoff had reached the same object as a theory of inductive inference [42], and Chaitin showed that program size obeys identities formally identical to Shannon's [43]. Rissanen turned the idea into a rule for choosing models, the minimum description length [44]. Together they say that a program is a code word: a description of a behavior, and the shortest correct one is the floor. RCE's extraction rule, keep the least-joule fit among equivalent fits (Proposition 3), is that rule with joules in place of bits.

Code sits in the low-entropy regime, and people measured it. Hindle, Barr, Su, Gabel and Devanbu found that code is "very repetitive, and in fact even more so than natural languages," at lower cross-entropy under the same n-gram models [35]. Gabel and Su found that most lines of a project already exist elsewhere [34], and Lopes et al. found that most files on GitHub are clones [33]. Tu, Su and Devanbu found that code is also local: what was written nearby predicts what comes next [46]. Ray and colleagues found that buggy lines are less natural, with higher entropy, and that the entropy falls when the bug is fixed [45]. In 2025 Yang, Kolak, Hellendoorn and Martins used the entropy change a patch induces to rank repair candidates and to separate correct patches from overfitting ones [51]. Allamanis, Barr, Devanbu and Sutton surveyed the field under the name naturalness [47]. The result is not only an English-language one. Prem Devanbu stated it as a keynote at the India Software Engineering Conference in 2013 [50]. Sridhara, Sinha and Mani at IBM Research India measured the natural-language artifacts around code at the same venue and found that commit messages are the most regular and Stack

Overflow prose behaves like ordinary English [49]. In China, the *Journal of Software* (软件学报) published a review of code naturalness research in 2022, which states the cross-entropy measure and the finding that defective code has higher entropy [48]. In Japan, Doi, Higo, Arima, Shimonaka and Kusumoto at Osaka University used n-gram naturalness, first in a Japanese-language IEICE technical report and then at ICPC 2018, to tell machine-generated source files from human-written ones [73, 74]. Generated code sits even lower on the entropy scale than human code, because a generator is a fixed conversion. In Brazil, Arrebola's doctoral thesis built code suggestion on n-gram and topic models segmented by project and maintainer, and evaluated it by cross-entropy, the bits needed to encode the next token [75]. The two regimes are visible in one repository: the prose around the code is high entropy, and the code is low.

The measure matters. Febres, Jaffé and Gershenson, working from Venezuela and Mexico, compared English, Spanish and program text by vocabulary diversity per message length and found the program text more diverse [76]. Rahman, Palani and Rigby found that much of the n-gram predictability of code comes from syntax tokens, and that code is still repetitive, less than first reported, once those are removed, with API usage the most repetitive part [77]. Both results sharpen the claim rather than reverse it. Diversity of symbols is not predictability, and the low-entropy regime is a property of the conditional distribution of the next step, which is what a deterministic transition fixes. RCE's G0 keys on shapes, not on surface tokens, for that reason.

Intent sits in the high-entropy regime. Zave and Jackson showed that a requirement is a statement about the environment, a specification is a statement at the interface, and the gap between them is filled only by domain knowledge that is often unwritten [64]. Brooks split the difficulty of software into essence and accident: the essence is the conceptual construct, and most of it is specification and design, not representation [61]. Naur argued that a program is the visible part of a theory held by its programmers, and that the theory is not fully recoverable from the text [62]. Read through Shannon, all three say the same thing. Intent carries more uncertainty than any one program, and writing the program is the act that removes it. What remains in a programmer's head after the code is written is the part of the intent the code did not encode.

The conversion is a refinement, and refinement is a narrowing. Hoare gave programs a logic in which a program is correct relative to a pre- and postcondition [54]. Wirth taught stepwise refinement: decompose a task into instructions by successive decisions, each one fixing a choice the specification left open [53]. Dijkstra's guarded commands made the open choices explicit as nondeterminacy, and derived programs from specifications by removing it [52]. In Munich, Bauer and Wössner's CIP project built program development as a sequence of correctness-preserving transformations from specification to program [58]. In France, Abrial's B method and then Event-B carried refinement to industrial scale, with proof obligations at each step [55, 56]. In Finland, Back and von Wright gave refinement its lattice-theoretic calculus [57]. In each, a specification denotes a set of acceptable behaviors and each refinement step shrinks the set, until one deterministic behavior remains. That is entropy reduction with a proof at every step. RCE's Form is the last element of that chain: a total, deterministic transition δ over database states, with every choice resolved (§3.2).

Synthesis is search that narrows a hypothesis space. Gulwani's FlashFill learns a string program from a few input-output examples by representing the set of all consistent programs and intersecting it with each new example [59]. Gulwani, Polozov and Singh frame program synthesis in general as search through a space of programs constrained by intent [60], and Solar-Lezama's sketching fills holes in a partial program with a solver [27]. Each example or constraint is a measurement that removes hypotheses. Shannon's measure counts how many such measurements are needed. RCE's G2 is that gear.

What the conversion produces has one shape. Gurevich proved that every sequential algorithm is captured by an Abstract State Machine at its own level of abstraction [2]. Codd made the state a relation [5], and event sourcing makes the state the fold of an append-only log [14]. Under Curry and Howard, a proof is a program and a proposition is a type [18, 72], so a verified fit is a proof of its specification. These are the reasons the low-entropy regime has few shapes: the destination is a state machine over a database, whatever the surface language.

Low entropy decays without a gate. Lehman observed over decades of large systems that a program in use must keep changing, and that its complexity grows unless work is done to reduce it [63]. Torres, Baltes, Treude and Wagner measured structural and textual entropy over the commit histories of 25 projects and found the two rise together [78]. Entropy flows back into code from the environment. A system that keeps code in the low-entropy regime needs a gate on every change, and RCE's gate is correctness (§4.3).

Compilers already do source coding. Franz and Kistler shipped programs as compressed abstract syntax trees and generated native code on load, which is source coding of a program over its own grammar [67]. Fraser inferred statistical models of code from a corpus to compress it [68]. Futamura showed in 1971, in the Japanese journal *Systems, Computers, Controls*, that specializing an interpreter to a program yields a compiled program, and that specializing the specializer yields a compiler [70]. Ershov in Novosibirsk developed the same idea as mixed computation [71]. The Cousots' abstract interpretation computes a sound, lower-information description of every behavior of a program [69]. The analogy to channel coding is this paper's reading, not a cited theorem: types, tests and proofs add checked redundancy so that a wrong program is detected before it runs, as a parity check detects a corrupted word.

Erasure is where the joules go. Landauer showed that a logically irreversible step, the erasure of one bit, dissipates at least $k_B T \ln 2$ [65]. Bennett showed that computation can in principle be made logically reversible, so the erasure, not the computation, carries the bound [66]. Converting high-entropy intent to one low-entropy program discards every alternative the intent allowed. That discard is an erasure of information about the alternatives, and it has a thermodynamic floor. RCE pays the discard once per new case and stores the result, so a repeat case erases nothing new.

2.2 How RCE converts, and where each gear sits

Read as coding theory, a task arrives as a message whose remaining uncertainty is what no stored fit already resolves. Each gear removes uncertainty at a different price, and the gears are ordered by that price (§4.2).

Gear	What it does to the uncertainty	Lineage in the argument above
G0 Lookup	Recognizes that the intent was already encoded; resolves it by retrieval, at the handler floor	Repetitiveness and clones [33, 34, 35]; locality [46]
G1 Rules	Applies a known guarded rewrite; resolves a recurring residual with no search	Correctness-preserving transformation [52, 58]; refinement with proof obligations [55, 56]
G2 Synthesis	Searches a hypothesis space and narrows it by examples, constraints and a solver	Program synthesis as search [27, 59, 60]
G3 to G5 Models	Samples from a learned distribution over code when no lower gear closes the gap; a proposer only	Cross-entropy models of code [35, 47]
Gate	Accepts a candidate only with tests, coverage and a proof certificate	Hoare logic [54]; Curry-Howard [18, 72]
Promotion	Stores the accepted fit, so the same residual costs G0 next time	Minimum description length [44]; Landauer erasure paid once [65]

Positions on the axes of Section 2 differ in where the conversion is paid. An approach that samples the full distribution of the prompt on every task pays the high-entropy side again each time. An approach that stores and reuses accepted fits pays only for the residual, and only once. Most systems sit between those ends, and RCE sits at the reuse end.

2.3 The ecosystem at large N

The claim of §1 is measured directly. The benchmark was preregistered before the run (`bench/ecosystem/PREREG.json`). A seeded generator writes 10,000 Forms, each a source, a rule whose body is a random arithmetic term of depth up to 3 over eight operators, and a sink. The engine is frozen at commit `a079967`, and no model is called.

Property	What is checked per Form	N	Holds	Model calls
Lossless encoding	Form IR to canonical JSON to Form IR to canonical JSON is the identity	10,000	10,000	0
Deterministic projection	Two compiles give the same bytes; XState and SCXML projections of the original and of the round tripped Form are byte identical	10,000	10,000	0

Property	What is checked per Form	N	Holds	Model calls
Faithful projection, Python	The emitted Python module prints the reference trace byte for byte on 40 seeded events	10,000	9,999	0
Gate at entry, inputs	Five malformed payload kinds (wrong type, null, missing field, empty, nested) all refused, no accepted outcome	10,000	10,000	0
Gate at entry, specifications	A specification with a flow to an undeclared node is refused before compile	10,000	10,000	0

Figure 3 shows the same counts.


Horizontal bar chart of five checks on 10,000 Forms. Lossless encoding, deterministic projection, gate at entry on malformed inputs and gate at entry on specifications each hold on 10,000 of 10,000. The Python trace replay holds on 9,999 of 10,000. Zero model calls.

Figure 3. The ecosystem at large N. Data figure: the five checks of the table above on 10,000 preregistered Forms, frozen engine at commit `a079967`, 0 model calls, with Wilson 95% intervals computed from the counts. Source: `bench/ecosystem`. A PNG copy is provided. Open full size · PNG

RCE-F0 and the Python miss. Section 9 states RCE-F0 as: on a preregistered run of at least 10,000 Forms, any projection prints a trace that differs from the Form's reference trace, or any malformed input is accepted. This run is preregistered, has 10,000 Forms, and one emitted Python module did not print the reference trace, so the observation as written meets the condition of RCE-F0. The paper reports the miss and the regression test below, and it does not give a root cause. Read the text of RCE-F0 as stated: the claim it defeats is that projections are faithful, and the Python projection of this run did not meet that claim on one Form. Whether the miss comes from the emitter or from the harness is open here. The fact that the same Form replays identically under 32 hash seeds does not settle it.

The one Python miss is counted as a miss; the same Form and events replay identically under 32 hash seeds in the regression test `tests/form_ecosystem_regress.rs`. Energy here is `est_j` only; the whole run took 393 s of CPU time on one core. The generated Forms are small, so this table measures the encoding, the projections and the gate. Lifted Forms from real programs are measured under the protocol of §8.7.

2.4 Gated, verified recursive self-improvement

Good (1965) [111] defined the ultraintelligent machine as one that could design better machines, so that improvement would recurse. Yudkowsky (2013) [113] cast the question as one of returns: whether each unit of improvement makes the next unit cheaper or dearer. Schmidhuber's Gödel machine (2007) [112] gave a formal answer with a guarantee: a program rewrites any part of itself, including its own search, only after proving that the rewrite improves its expected utility.

Löb's theorem (1955) [114] is the obstacle a self-trusting prover meets, which Yudkowsky and Herreshoff (2013) [115] named the Löbian obstacle: a system cannot in general prove the soundness of a successor that uses its own proof system. Recent systems drop the proof requirement and select by measured score: STOP (Zelikman et al., 2023) [116] improves the scaffold that improves code, the Darwin Gödel Machine (Zhang et al., 2025) [117] keeps an archive of self-modified coding agents chosen by benchmark score, AlphaEvolve (Novikov et al., 2025) [118] evolves programs under automatic evaluators, and Voyager (Wang et al., 2023) [119] grows a library of verified skills that later tasks reuse.

RCE takes the structure of the Gödel machine and the library of Voyager, with two differences that avoid the obstacle for the objects it promotes. First, the object that improves is not the prover. RCE promotes handlers, rewrites and gears, and each is checked against a fixed, separately certified kernel: the Kani harnesses and the SMT encoding never change through promotion, so no step needs to trust a successor's proof system. Second, the gate is a proof of correctness at the boundary, not a score. A score can rise while an interface assumption breaks; a proof at the boundary cannot be passed by a change that breaks it.

Proposition R1 (monotone correctness). If every promoted change passes the check of its boundary, and the checks of the other boundaries are unchanged, then every property established by those checks before the promotion still holds after it.

Proposition R2 (compounding). Let a workload be a multiset of tasks and let a promoted handler close every task of its shape. Then the number of escalations in round t is nonincreasing in t, and a correction promoted before round 1 lowers the cumulative escalations of every horizon by the escalations it closes in each later round. In the engine demo's reference workload, cumulative escalations over eight rounds fall from 21 to 15 with one correction at the sinks, and reach zero in the last round in both cases, with every task closed correctly and no promotion refused.

Figure 4 draws the mechanism of Propositions R1 and R2 with the reference workload's totals.



Diagram of the RCE stack as six levels from intent at the top through Form, gate, projections and runtime to hardware and energy. A correction promoted at the runtime level after passing its boundary check is shown with arrows rising through every level above it. A small bar chart beside it gives cumulative escalations over eight rounds on the engine demo reference workload: 21 with no correction and 15 with one correction at the sinks.

Figure 4. Corrections compound upward. Diagram of the stack, with a data inset: cumulative escalations over eight rounds of the engine demo's reference workload, 21 with no correction and 15 with one correction at the sinks (Proposition R2; RCE engine demo). A PNG copy is provided. Open full size · PNG

Proposition R3 (falling cost). Since a promoted handler is executed in place of a model call, and its cost is the op count of the handler priced by the substrate table, the energy of a round falls toward the energy of the handlers alone as escalations fall toward zero.

Futamura's projections (1971, republished 1999) [120] and Turchin's supercompilation (1986) [121] give the limit of this process. Specializing an interpreter to a program yields a compiled program; specializing the specializer yields a compiler. RCE's promotions specialize the general escalation path to the shapes that actually occur, so the engine converges toward the residual program of its workload: the part of the computation that a model or a person must still supply. Recursive self-improvement under a gate is that convergence, made with checked steps. The Compounding layer of the RCE engine demo runs this workload in the browser.

---

3. The Form

3.1 The strongest formal statement of "same form"

The scope of the theorem is stated first. Gurevich's sequential postulates cover sequential algorithms; parallel and interactive algorithms need the further postulates of Blass and Gurevich [3]. Blass, Dershowitz and Gurevich argue that no single equivalence relation on algorithms fits every purpose [79], and Moschovakis and Vardi set out the debate over what an algorithm is [80, 81]. A web handler that does input and output sits outside the sequential theorem. The Form handles interaction the way the interactive line does: each input is an event in E, and the state machine steps on it. So "one Form" is a modelling choice grounded in the sequential theorem and extended by convention, with production precedents in the Elm architecture [83], durable workflow event histories [84] and stream semantics such as Flo [82]. The propositions of Section 3.4 are stated for that choice.

Gurevich's Abstract State Machine (ASM) theorem is the strongest formal statement that every algorithm has one shape [2]. An abstract state machine is a machine whose states are first-order structures and whose step is a finite set of guarded updates. Gurevich states three postulates. Sequential Time: an algorithm has states, initial states and a one-step map τ. Abstract State: states are first-order structures over one fixed vocabulary, closed under isomorphism. Bounded Exploration: a finite set of terms decides each step. His Main Theorem (Theorem 6.13) reads: "For every sequential algorithm A, there exists an equivalent sequential abstract state machine B." Blass and Gurevich extend it to parallel algorithms [3]. Dershowitz and Gurevich add a fourth axiom, that initial operations are computable, and from it derive Church's thesis [4].

3.2 Definitions

Definition 1 (the Form). A program is a tuple

$$P = (S, E, \delta, D, \lambda)$$

- $S = \Sigma_c \times \Sigma_d$, the state space: structures over a fixed vocabulary Σ, split into control regions Σ_c and data Σ_d. Σ_d holds the logical clock, the input count and the typed relations (in the language, also the declared regions). Each state is a database instance in Codd's sense [5].
- E, the event alphabet, including the logical clock tick.

- $\delta : S \times E \to S \times O^*$, the transition: total, deterministic and pure, written as a finite set of guarded updates "if φ then $f(\bar{t}) := t_0$", each step reading a bounded set of locations. It returns the next state and the outputs of the step. Write $\delta_1 = \pi_1 \circ \delta$ for its state component.
- D, the durable log: a sequence of entries $\{seq, event, prev_hash, state_hash, hash\}$, where $state_hash$ is the SHA-256 of the canonical JSON of the state after the step, $hash$ is the SHA-256 of the canonical JSON of the first four fields, and the first $prev_hash$ is 64 zeros. The log is a hash chain, so changing any past entry changes every later $hash$.
- $\lambda = \pi_2 \circ \delta : S \times E \to O^*$, the output map. A Mealy machine reads both arguments [6]; a Moore machine reads the state only [7].

Definition 2 (Form and fit). The *form* is the tuple shape with four invariants: δ is deterministic and pure; exploration is bounded; the vocabulary is fixed; state is the fold of the log,

$$\mathrm{state}(D) = \mathrm{foldl}(\delta_1, s_0, D).$$

A log may also carry each entry's outcome, outputs and state. These are derived: they are not hashed, and they must equal replay (T1 and T3 of §3.7). Two kinds of rejection are distinct. In the engine profile every event is applied, and an input that fails its contract produces a `reject` output and an error row. In the language a refused event leaves the state unchanged (T8) and is recorded as refused.

The *fit* is the data that fills the shape: the vocabulary Σ, the alphabets E and O, the rule program Π that defines δ, the output rules that define λ, and the initial data s_0. In Gurevich's terms the fit is the vocabulary, the ASM program and the initial structures. In Codd's terms Σ is the schema and s_0 is the instance. In product-line terms a fit is a feature selection [8]. In syntax-guided synthesis (SyGuS) terms a fit is a term from a grammar that meets a specification [9].

Definition 3 (fit equivalence). Two fits are equivalent when, for every event sequence L, their output sequences under λ are equal.

Definition 4 (fit language). A grammar whose terms denote fits. Programming languages, SCXML documents, XState configurations and `.rce` specifications are fit languages. A fit language is complete when every ASM program over Σ has a term in it.

Definition 5 (control projection). Split $\Sigma = \Sigma_c \cup \Sigma_d$ into finite control symbols and data relations. The statechart of P is the projection of δ onto Σ_c: states are values of Σ_c, transitions carry an event and a guard over Σ_d, and actions are updates to Σ_d. Harel's statecharts give the hierarchy and the orthogonal regions [10].

Definition 6 (fit e-graph). For a fit F and a set R of sound rewrites, the fit e-graph $EG(F, R)$ is the saturated e-graph of F's rule terms under R [11, 12]. Each e-class holds fits equivalent by Definition 3.

Definition 7 (joule cost). $\mathrm{cost}_J(t)$ is the estimated energy (`est_j`) to run term t once on a named substrate, weighted by the expected number of runs.

3.3 Why “database functional state machine”

A finite relational structure is a database instance, so a Gurevich state is a database and each step is a bounded transaction. *Database*: S is a relational structure. *Functional*: δ and λ are pure. *State machine*: runs are folds of δ over events. Moseley and Marks draw the same line in architecture [13]. Event sourcing draws it in application state: “Capture all changes to an application state as a sequence of events” [14]. Dedalus draws it in logic, where mutable state is a relation indexed by time [15].

3.4 Propositions

Proposition 1 (the Form captures every sequential algorithm). For every sequential algorithm A there is a Form instance P whose runs are the runs of A.

Proof sketch. Theorem 6.13 gives an ASM B with the states, initial states and one-step map of A. Set $E = \{\varepsilon\}$, $\delta(s, \varepsilon) = \tau_B(s)$, $D = (s_0, \varepsilon^n)$ and λ the identity. The fold after n ticks is $\tau_A^n(s_0)$. By Gurevich’s Corollary 3.3, P and A have the same runs. ∎

Proposition 1b (interactive programs). Extend Σ with a nullary input symbol set to e before each step; then $\delta(s, e) = \tau(s[in := e])$ is a sequential algorithm over the extended vocabulary, and Proposition 1 applies. The construction is ours.

Proposition 1c (computability). Under the Dershowitz and Gurevich axiom, every Form instance computes a Turing-computable function [4, 16, 17]. The Form adds no power. It gives every program in the class one shape.

Proposition 1d (proofs are fits). “For each proof of a given proposition, there is a program of the corresponding type” [18]. A type is a specification and a proof is a fit that meets it. The correctness gate is the existence of that proof or of a passing acceptance test.

Proposition 2 (one generator). One function $G : \mathrm{Fit} \to \mathrm{Program}$ generates a runnable program for every fit and reads no domain. *Basis:* every program is a Form instance, so G emits a typed store, an event type, compiled rules, a log with a fold and an output dispatcher. Scaffolders such as Rails generators, JHipster and Yeoman are G restricted to small fit languages. Product-line engineering starts from “the systematic discovery and exploitation of commonality across related software systems” [8]; the commonality is the Form.

Proposition 3 (least-energy extraction). Extraction with cost_J returns the least-joule term the extractor finds in the e-class of F. *Proof sketch.* The rewrites are sound, so every term in the e-class has F’s observable behavior and passes the same gate. Extraction minimizes the cost, and the cost is joules. ∎ This is Mixture of Limits applied to code: keep the minimal fit that does the task, and the rest is waste.

Proposition 4 (replay determinism). If δ reads no wall clock, orders updates without names and logs every input, two replays of one D give identical state hashes at every step.

Proposition 5 (statechart projection is sound). Project each state of a run onto Σ_c. The result is a run of the emitted statechart under the same events.

Proposition 6 (coordination budget). Rules tagged monotone run on replicas without coordination; only non-monotone rules need a coordination point. *Basis:* the CALM theorem, "the programs that have consistent, coordination-free distributed implementations are exactly the programs that can be expressed in monotonic logic" [19].

The tag is derived from the rule, never declared, and the IR check refuses a Form whose stored tag differs from the derived one (specification, Appendix D.5):

Rule has	Tag	Reason
no resolve, read, join or scan	monotone	its writes only add keys and grow counters
a resolve	not monotone	it deletes escalation rows
a read of its own sink	not monotone	read, modify, write
a keyed join	not monotone	the joined row may be absent now and present later, or overwritten
a scan	not monotone	it observes the whole relation, including what is absent

The tag is sound and not complete: a join against an insert-only relation would be monotone, but the profile does not prove that a relation is insert-only, so the tag does not claim it. A Form is coordination-free when every rule is monotone. Every read, join and scan sees the state at the event's entry, so the post-state of an input event does not depend on the order in which rules for different sinks run; only the output order does, and it is fixed by content hash.

Proposition 7 (intelligence as a joule derivative). Let X count tasks through the gate and J the joules spent. $\iota = dX/dJ$ is read in hindsight from D, which records every event and its `est_j`. Extraction under cost_J holds the gate fixed and does not raise J, so at equal X it does not lower ι.

3.5 Graph, e-graph and statechart

Structure	Part of the Form	What it decides
Statechart	Guards of δ over Σ_c	Which transition fires
Dataflow graph	Read and write dependencies of δ and λ (Kahn process networks [20])	What runs, and in what order
E-graph	The equivalence class of the fit	Which equivalent fit runs

The statechart and the graph describe one fit. The e-graph describes every fit equivalent to it. Extraction chooses among them by joules.

3.6 One ecosystem, lossless, and the universality thesis

Lossless by construction. Shannon's source coding theorem fixes the floor for a lossless code at the entropy of the source [40]. A Form is a lossless code for intent in a narrow sense that can be checked: the canonical serialization of the Form is injective, so two Forms that differ in any state, event or transition have different shape hashes, and decoding the serialization gives back the same Form. Each projection to a target is a function of the Form alone. Bidirectional transformations make the round trip precise. Foster, Greenwald, Moore, Pierce and Schmitt define a lens as a pair of get and put functions with round trip conditions that make a view and its source agree [122], Hofmann, Pierce and Wagner extend the conditions to symmetric lenses [123], and Czarnecki and colleagues survey the same consistency conditions across model engineering, databases and programming languages [124]. RCE's round trip condition is the GetPut condition at the level of the whole program: lift a projection back and the shape hash is unchanged.

Correct by construction. Dijkstra proposed in 1968 that a program and its proof be developed together, so that correctness is designed in rather than tested for [125]. Hall and Chapman carried the approach into a commercial secure system with formal specification and refinement at every step [126]. Minsky's rule for typed functional programming, make illegal states unrepresentable, says the same at the type level: a type that cannot hold a bad value removes the need to check for it [127]. Turner's total functional programming requires every function to terminate on every input, so that a program denotes a mathematical function with no hidden failure [128]. RCE's Form is total in Turner's sense, its contract types make undeclared states unrepresentable in Minsky's sense, and the refinement chain of §2.1 ends in it in Dijkstra's sense. The consequence is the one stated in §1: an error is refused at entry, so there is nothing to diff or track after the fact.

The universality thesis. Stated in theory terms, the thesis is that there is one universal Form. Programs are authored in it natively, every existing language is reachable from it as a faithful projection, and every existing program enters it by lift. Gurevich's thesis gives the ground: every sequential algorithm is captured, step for step, by an Abstract State Machine at its own level of abstraction [2], and parallel algorithms likewise [3]. A Form is such a machine over a database state.

Proposition U1 (capture). If a program in language L is a sequential or parallel algorithm in Gurevich's sense, then there is a Form whose transition simulates it step for step at the program's level of abstraction [2, 3].

Proposition U2 (faithful projection). If the projection π_L of a Form to L preserves the Form's trace on every input in the contract, then the Form and its projection are interchangeable for every observer of the trace, and L adds nothing the Form lacks.

Proposition U3 (lift by construction). Every programming language in use has a formal grammar, a parser that yields a concrete syntax tree, an abstract syntax tree and a semantics fixed by its specification or reference implementation. A lift λ_L is built per language in three stages: the grammar, then the abstract syntax tree, then the Form, with each construct of L given its Form rule by the semantics of L. A lift so built satisfies $\pi_L(\lambda_L(p)) \equiv p$ on behavior and $\lambda_L(\pi_L(F)) = F$ on shape hash, so the pair is a lens in the sense of [122], and a program in L is held as a Form with no loss.

Proposition U4 (replacement). If U2 and U3 hold for language L, then no program needs to be written in L: it is written once as a Form and emitted as L where a platform requires it.

U1 is a theorem. U2 is checked per target by differential testing (§5.1) and at large N in §2.3. U3 is a construction, built language by language from the grammar up, and §8.7 states how the construction is measured as it is built.

3.7 The language: versions 0.6 and 0.7, costs and theorem status

The RCE language is defined by a written specification, currently the draft 0.7 document at language version 0.8 (/rce/spec/; source in the rce repository). Each module selects its language version with a first-line comment. A module without it is version 0.5, the language of sections 2 to 10. A module that declares `# rce-version: 0.6` also gets Appendix C: `par`, `for ... par`, `with budget`, workgroups, LVars, sessions and supervisors. A module that declares `# rce-version: 0.7` has the language of version 0.6 with one difference, the cost of standard library methods below (Appendix C.15). Appendix D defines the engine profile, the handler specs and fits that this paper's engine runs. A version 0.5 module never sees Appendix C, so every valid version 0.5 program is accepted unchanged.


Diagram. Three version cards. Version 0.5, no declaration: the language of sections 2 to 10, with no budgets. Version 0.6, first line # rce-version: 0.6: version 0.5 plus Appendix C, where 23 words become keywords and par, for par, with budget, workgroups, LVars, sessions and supervisors are added; a standard library method costs c_call, 4. Version 0.7, first line # rce-version: 0.7: the syntax and rules of 0.6 with one difference, method cost 4 plus work(m, n, k). Errata apply to every version. Below, the per-call-site rule: a 0.6 module under a budget calls a function in a 0.7 module that sorts 8 elements; the sort is charged 4 plus 24 because it is written in the 0.7 module, so the call costs 24 more than the same call into a 0.6 function.

Figure 5. Version gates: the first line fixes the meaning. Diagram: each module declares its version on its first line. A module without a declaration is version 0.5, the language of sections 2 to 10, with no budgets. `# rce-version: 0.6` adds Appendix C (23 new keywords; `par`, `for ... par`, `with budget`, workgroups, LVars, sessions, supervisors), and a standard library method costs $c_{call} = 4$. `# rce-version: 0.7` has the syntax and rules of 0.6 and differs only in method cost, $4 + w(m, n, k)$. Errata apply to every version. The version of the module that contains the call expression governs its cost: a 0.6 function under `with budget` that calls an imported 0.7

function sorting 8 elements is charged 24 more than the same call into an identical 0.6 function. Source: specification 2.7, C.6.4 and C.15; listings abridged from `spec/checker/tests/call_site_cost.rs`. A PNG copy is provided. Open full size · PNG

Budgets count work. A `with budget` block charges each operation a fixed cost from the table of Appendix C.6.4 and traps with `budget` when the count runs out. The count is a proxy for work, not a measurement of time or energy; `est_j` is separate.

Operation	Cost
call of a user function or a closure, c_{call}	4
standard library method on receiver size n, first-argument size k	4 in version 0.6; $4 + w(m, n, k)$ in version 0.7
channel send or receive	8
`spawn`	32
one `par` branch or `for ... par` chunk	16
list or map literal, or comprehension, with n results; `[x; n]`	$4 + n$
index, slice, member access; unary operators; `and`, `or`; integer, bool and text operators and comparisons	1
float `+`, `-`, `*`	2
float `/`, `%`	8

Sizes are the UTF-8 byte length of a text, the length of a list and the number of entries of a map; any other value has size 0. The method work w is fixed by the method's complexity class in the reference evaluator: $n + k$ for the linear methods on text, lists and maps (maps are ordered association lists), $n\lceil \log_2 n \rceil$ for `sort` (0 when $n \leq 1$), and 0 for the remaining methods. The calls that `map`, `filter` and `fold` make to their function argument are charged as calls in addition. The arithmetic saturates at the largest 128-bit integer, and w never decreases when n or k grows. The reference evaluator and the emitted Rust, Python and JavaScript runtimes compute the same function, and a test checks that the budget trap falls on the same operation in all four.



Line chart on log scales of the budget cost of one standard library method call against receiver size n from 1 to 1,024, with no argument. Under version 0.6 every method costs 4 at every size. Under version 0.7 linear methods on text, lists and maps cost 4 plus n, reaching 1,028 at n = 1,024, and sort costs 4 plus n times the ceiling of log base 2 of n, reaching 10,244 at n = 1,024. Constant-class methods cost 4 in both versions. A marker shows that sorting 8 elements costs 28 in version 0.7, 24 more than in 0.6.

Figure 6. Method cost by receiver size, versions 0.6 and 0.7. Data figure: budget units charged for one standard library method call with no argument ($k = 0$), against receiver size n, from the C.6.4 cost table. In version 0.6 every method costs $c_{call} = 4$

. In version 0.7 a linear method on a text, list or map costs $4 + n + k$, sort costs $4 + n\lceil \log_2 n \rceil$ (work 0 for $n \leq 1$), and every other method costs 4. Sorting 8 elements costs 28 in 0.7, 24 more than in 0.6. Budget units count operations; they are not a measurement of time or energy. Values computed by the reference evaluator's `conc::method_work` (rce `ac95172`). A PNG copy is provided. Open full size · PNG

Which version governs a cost. A program may join modules of different versions. The cost of a method call is fixed by the declared version of the module that contains the call expression, including a call inside a closure written there, and not by the version of the function being run, of its caller or of the program's first module. The rule is lexical, so linking modules changes no cost; specification 2.7 states the same rule and points to C.15. Tests check it at the boundary in both directions on the reference evaluator and on the emitted Rust, Python and JavaScript programs: a 0.6 function under `with budget` that calls an imported 0.7 function sorting an 8-element list is charged 24 more than the same call to an identical 0.6 function.

Theorem status. The specification states theorems T1 to T34 and records the status of each exactly. The proofs are in Lean 4 (v4.12.0, no Mathlib) over a core calculus. The words used for the level of a result are these. *Proved* means a Lean proof about the core semantics of the language. *Proved on a semantics* means a Lean proof over a small-step semantics of a core of RCE. *Model* means a Lean proof about an abstract model that is not connected to the RCE semantics or to the reference evaluator. *Vectors* means the reference evaluator's results on generated programs are checked against the model by the Lean kernel, which is a correspondence on samples, not a proof about the evaluator. *Tested* means differential testing on stated inputs. *Checked mechanically* means decided by a program, such as an LALR(1) table builder.

	Statement	**Level**
T1	determinism: one result per state and event; one result per tick of the concurrency semantics	proved
T2	totality of δ, with an explicit bound on evaluation steps; structural recursion and bound composition along the call graph	proved (the Lean expression core has no user function calls; recursion and composition are proved on separate models)
T3	the runtime state is $\mathrm{foldl}(\delta_1, s_0, D)$ and replay reproduces every hash and output	proved
T4	progress, including ticks (some task moves, or the run ends or reports `Deadlock`)	proved
T5	preservation, including the integer range of every written field	proved
T6	memory safety, full borrow paths, no mutable sharing between tasks	proved for the ownership core and an instrumented semantics of borrow paths

	Statement	Level
T7	name independence of log hashes, ids and select choices	proved
T8	atomicity: a refused event leaves the state unchanged	proved
T9-F	the Form IR targets (Rust, WASM, Python, XState, SCXML) print the reference trace	tested
T9-L	the program emitters (`rust`, `python`, `js`) agree with the reference evaluator	proved for the Rust emitter on a core, as a verified translation into MiniRust, a deep embedding of the emitted Rust subset; that `rustc` implements MiniRust is trusted and tested; the other emitters tested
T10	the grammar is unambiguous	checked mechanically (LALR(1), 0 conflicts, for both versions) and sampled by a fuzzer
T11	select fairness	proved on the rotation model
T12	a linear handle is consumed exactly once on every path	proved on a statement model
T13	f32 operations give the same bits on targets that agree on IEEE 754	proved for multiplication; for addition, subtraction and division the single-rounding property is Figueroa's theorem, cited and not mechanized
T14	checked u64 arithmetic is exact in range	proved
T15	iterators end, respect the loop limit and are prefix-consistent	proved
T16 to T31	version 0.6 concurrency: `par` determinism, commutation, reductions, deadlock freedom, deadlines, workgroups, vector clocks, priorities, scopes, actors, sessions, LVars, atomic batches, replicas	proved on a semantics: T16, T17, T19a, T20, T23; proved on a model of runs: T24; proved on a session calculus: T28; model: T18, T19b, T21, T22, T25, T26, T31; model with vectors: T27, T29, T30. None is a proof about the Rust reference evaluator
T32	foreign replay: for every oracle, replay of the log equals the live run, and an answer contract holds of every logged answer	proved
T33	`&mut` write-back: copying out on every outcome equals in-place update; copying out only on success does not	proved
T34	the order-preserving ANF pass before every emitter gives the same value, store and trace of charges and emits	proved for a core fragment with full ANF; the implementation is tested differentially on every target, including a sweep of budgets across the trap point

T9 has two target sets because the paper's engine and the language have two compilers. T9-F is the claim about `rce form --emit`, which §5.1 measures. T9-L is the claim about the language's program emitters. A target outside these sets has no T9 claim.


Grid of 35 entries, T1 to T34 with T9 split into T9-F and T9-L and T19 into T19a and T19b, each with a coded level. Proved: T1, T2, T3, T4, T5, T7, T8, T14, T15, T32, T33; Proved for a stated core or fragment; rest tested or cited: T6, T9-L, T13, T34; Proved on a small-step semantics of a core of RCE: T16, T17, T19a, T20, T23; Proved on a named model (rotation, statement, runs, session calculus): T11, T12, T24, T28; Model: T18, T19b, T21, T22, T25, T26, T31; Model, with evaluator vectors checked by the Lean kernel: T27, T29, T30; Tested: T9-F; Checked mechanically (LALR(1) tables): T10.

Figure 7. Theorem status, T1 to T34. Level of each theorem as recorded in the current specification (draft 0.7 document, language version 0.8); theorems added after T34 are not shown. `P`: Lean proof about the core semantics. `P*`: proved for a stated core or fragment, the rest tested or cited. `S`: proved on a small-step semantics of a core of RCE. `M+`: proved on a named model (rotation model, statement model, model of runs, session calculus). `M`: Lean proof about an abstract model. `MV`: model, with reference evaluator vectors checked by the Lean kernel. `T`: differential testing. `C`: checked mechanically. T16 to T31 belong to version 0.6, and none is a proof about the Rust reference evaluator. Lean 4 v4.12.0, no Mathlib. Source: `spec/book/10-theorems.md` and Appendix C.13. A PNG copy is provided. Open full size · PNG

Checks run for this version. At engine commit `1eb5f02`, `lake build` completes over the 31 files of `spec/lean/RCE/` with no `sorry` (46 files at public `4304048`, 58 at `e416fd0`), and the standing audit reports the axioms of 2,192 theorem constants (the audit counts every kernel theorem constant; see the corrections note above) as only `propext`, `Quot.sound` and `Classical.choice`. Kani verifies 10 of 10 kernel harnesses (§5.3). The engine tests (`cargo test --release`) pass 589 distinct tests with 0 failures (2 ignored); `make check` reports 596 because its proof step runs 7 of those tests a second time. The reference checker, built from the public repository as its continuous integration builds it, passes 56 tests in the default build and 112 with the version 0.6 and 0.7 suites enabled, with 0 failures, and 57 with the tree-sitter agreement test. The specification check builds the LALR(1) tables of version 0.5 and of versions 0.6 and 0.7, which share a grammar, with 0 conflicts and parses every example with three parsers, and the WebAssembly build of the checker passes 401 of 401 checks against the example corpora.




Figure 8. Verification at a glance, engine commit `1eb5f02`. Data figure. Engine tests (`cargo test --release`): 589 pass, 0 fail, 2 ignored; `make check` reports 596 because it runs 7 proof tests twice. Lean 4: `lake build` over the 31 files of `spec/lean/RCE/` with no `sorry`; the audit reports 2,192 theorem constants (audit count, not source declarations) whose axioms are only `propext`, `Quot.sound` and `Classical.choice`. Kani 0.67.0 verifies 10 of 10 kernel harnesses with 0 of 7,425 checks failed (bars: checks per harness). The WebAssembly build of the checker passes 401 of 401 checks against the example corpora. The specification check builds LALR(1) tables with 0 conflicts for version 0.5 (932 states) and for versions 0.6 and 0.7 (1,110 states), accepts 51 of 51 valid examples and refuses 12 of 12 syntax rejects and 64 of 64 ill-typed or inadmissible programs. The Lean, WebAssembly and specification checks were run on the public repository at `ac95172`, whose specification sources are identical to the engine's. A PNG copy is provided.
Open full size · PNG

A convergence observation. The catalogue at agentlanguages.dev, read on 13 October 2026, lists 42 languages designed for AI agents to author code, grouped by its editors into a syntactic camp, a verification camp and an orchestration camp. Several design choices in this paper, such as mechanically checked contracts, hash-chained logs, deterministic replay and one canonical form per program, appear in its descriptions of other projects that were developed independently. This is an observation that the choices recur. It is not evidence that they are correct, and this paper makes no comparison with those projects.

---

4. The engine: gears, gate and receipts

4.1 The engine is a Form

RCE runs software as a graph of small deterministic handlers. A handler that cannot decide raises an escalation. A resolver answers the escalation once, and the answer is installed as a permanent handler, so the next case of the same shape runs with no resolver. The engine meets every Form invariant, each checked by a named test in `tests/form_laws.rs`:

Invariant	What the engine does
Reload is a verified fold	Reload reads the log verbatim, recomputes every hash and link, and folds the rest with δ. Nothing is re-stamped. A broken chain refuses to load.
Name-free tick order	Handlers run in topological rank order, then by a name-free node key. Outputs are staged and delivered after all handlers run, as in ASM semantics. Renaming every node gives the same anonymous state hash at every entry.
No silent drop	A full mailbox holds the message in an ordered queue and logs `Backpressure`. With capacity 1 and 10 tasks, 9 `Backpressure` entries are logged and all 10 tasks close.
Payloads are in the log	Inputs, ticks, external handler results, installs and faults are log entries. The state hash after every entry matches a fold from an empty engine, on 1,000 random logs.
Logical clock	Liveness counts ticks, not wall time.
Stable hashes	SHA-256 (Secure Hash Algorithm, 256-bit) over canonical JSON, keys sorted at every depth, for entries, states, shapes and rule ids.

4.2 The gears

Each gear is tried only when the gear below it does not pass the gate. That order is one fixed cascade.

Gear	Method	Lineage
G0 Lookup	A shared handler library keyed by SHA-256 shape hash; for code repair, localization to ranked functions	Code search and retrieval [21]
G1 Rules	Deterministic, guarded repair templates and schema-derived validators, each checked for mutation sensitivity	PAR, TBar, AVATAR, FixMiner [22, 23, 24, 25]; codemods such as Coccinelle [26]
G2 Synthesis	Enumeration over the handler grammar, solvers and e-graphs	Sketching, SyGuS, egg [27, 9, 12]
G3 to G5 Models	A typed decision model, a local small model, then a remote model, last	Model cascades [28]

4.3 The gate

A candidate is promoted only when it passes the gate. The gate replays the node's recorded inputs, runs the candidate in shadow on fresh samples with a coverage bound (the rule of three at a declared error budget), checks the output schema, and requires the proof certificate of Section 5. A rejected candidate is logged with its counterexample.



Diagram. Four gear boxes stacked from cheapest to costliest: G0 Lookup, a shared handler library keyed by SHA-256 shape hash; G1 Rules, guarded repair templates and schema-derived validators; G2 Synthesis, enumeration over the handler grammar, solvers and e-graphs; G3 to G5 Models, a typed decision model, a local small model and a remote model, marked as proposers only. Each gear sends its candidate to one gate with five checks: replay of recorded inputs, a shadow run with a coverage bound, an output schema check, the Kani proof certificate, and for rewrites a randomized check then a Z3 proof. A pass promotes the candidate to a stored handler, which feeds G0; a fail is logged with its counterexample and escalates to the next gear.

Figure 9. Models propose, checkers decide. Diagram: gears run in order of cost: G0 Lookup, G1 Rules, G2 Synthesis, G3 to G5 Models (a typed decision model, a local small model, then a remote model). Every candidate passes through the same gate: replay of the node's recorded inputs, a shadow run on fresh samples with a coverage bound, an output schema check and the Kani proof certificate; a proposed rewrite also needs a randomized check and then a Z3 proof. A candidate that passes is promoted and closes the same shape at G0 next time; one that fails is logged with its counterexample and the next gear is tried. The Kani harnesses and the SMT encoding do not change through promotion. Source: Sections 2.2, 4.2, 4.3, 4.6, 5.2 to 5.5. A PNG copy is provided. Open full size · PNG

4.4 Receipts

Every promotion, refusal, deferral and install is a mutation in an append-only log chained with SHA-256, so tampering with any past entry breaks the chain [29, 30]. Each handler's cost is priced from interpreter operation counts with the host cost table of FGIR, the native-code backend of flowG, and labeled `est_j`. Each foreman call carries its receipt. A receipt names the gear, the method of the estimate (`basis`), the candidates tried and whether the gear resolved the escalation. Its `est_j` field is required: it is a finite non-negative number, or null, and null is allowed only when `basis` says `unpriced`, as for a model call with no energy figure. A receipt with the field missing does not parse. An unpriced cost is never read as zero, so a total over receipts reports its priced and unpriced invocations separately, and a saving that depends on an unpriced resolution is reported as unknown. The ladder runs add a package energy counter on a subsample, labeled `reported_j`.



Diagram. Top: three log entries, seq 0, 1 and 2, each with fields seq, event, prev_hash, state_hash and hash. The first prev_hash is 64 zeros; each later prev_hash equals the previous entry's hash, drawn as arrows. state_hash is the SHA-256 of the state after the step; hash is the SHA-256 of the canonical JSON of event, prev_hash, seq and state_hash. Bottom: a gear receipt with fields gear, gear_name, est_j, basis, candidates_tried and resolved, beside the rule that est_j is required and is either a finite non-negative number or null, with null allowed only when basis says unpriced; unpriced cost is never read as zero joules.

Figure 10. The log is a hash chain; every cost carries a basis. Diagram: entries of the durable log D are `{seq, event, prev_hash, state_hash, hash}`. `state_hash` is the SHA-256 of the canonical JSON of the state after the step; `hash` is the SHA-256 of the canonical JSON of `{event, prev_hash, seq, state_hash}`; the first `prev_hash` is 64 zeros, so changing any past entry changes every later hash. A gear receipt carries `gear`, `gear_name`, `est_j`, `basis`, `candidates_tried` and `resolved`. `est_j` is required and is a finite non-negative number, or null only when `basis` says unpriced; model-call receipts carry `est_uj` in microjoules under the same rule. An unpriced cost is never read as 0 J. Hash labels are symbolic. Source: specification 6.1 and Section 4.4. A PNG copy is provided. Open full size · PNG

4.5 The Form compiler

`rce form` takes a specification and its fit and emits five targets from one Form IR:

```
.rce spec + fit
  lower ─► normalize ─► egg e-graph, equality saturation (+ admitted proposals)
  ─► extract (cost = est_j) ─► Form IR (typed relations, regions, rules with SHA-256 ids)
     ├─ Rust crate (pure step, typed state, SHA-256 log and fold, tests)
     │  └─ WASM (the same crate on wasm32-wasip1)
     ├─ Python (standard library only)
     ├─ XState v5 machine
     └─ SCXML document, executed by SCION
```

The IR fixes one behavior at every numeric edge: checked 64-bit integer overflow is an error and never wraps; integer `/` truncates toward zero ($-7/2 = -3$); `%` takes the dividend's sign ($-3 \bmod 2 = -1$); division by zero is an error; floats are IEEE 754 binary64 and a non-finite result is an error; null and absent are distinct; time is the logical clock only. Every target is generated. None is authored.

A process, HTTP or closure handler has no term, so its logged results compile to a recorded oracle keyed by the SHA-256 of the canonical input. `rce scan DIR --form` lifts existing Rust, Python, TypeScript and Go into the Form's schema, and every lifted element is labeled as a syntactic lift.

4.6 Method: the whole stack evaluated, every interface assumption explicit

A program is a stack of levels: tokens and statements; handlers; the Form, a single step function $\delta : S \times E \to S \times O^*$ over $S = \Sigma_c \times \Sigma_d$ (control regions; data: the clock, the input count and typed relations); the log, a SHA-256 hash chain whose entries record each event, the hash of the state it produced and the hash of the previous entry; the rewrites that transform the Form; and the substrate that executes it. Each level rests on assumptions about the level below. RCE does not treat any level as fixed. It evaluates the whole stack, writes each interface assumption down as a checkable statement, and checks it on every run.

Boundary	Assumption	Check
source to handler	an input satisfies its source contract	the contract check at the input event of δ
handler to sink	every Ok output satisfies the output schema	handler proof (verify::handler_proof), total and deterministic by the Kani-checked kernel evaluator
log to state	every entry carries the hash of the state it produced	kernel fold, which refuses the first entry whose hash does not match (Kani harness `fold_rejects_wrong_state`)
rewrite to Form	a rewrite preserves the output for every input	randomized check, then an SMT proof with Z3
stub to foreman	a handler that cannot decide escalates instead of guessing	stub handlers emit escalations; resolutions are promoted only through the promotion path
Form to target	every emitted target computes the same δ	every target carries the same reference trace

A failed check locates the break at the boundary where it occurs. The correction is made at that level, passed through the check of that boundary, and promoted. Every level above the corrected one inherits the correction without further change, because each level above consumes the corrected level only through the interface whose assumption is now checked. This is the sense in which corrections carry upward and compound. The RCE engine demo runs this in the browser on the RCE core compiled to WebAssembly: its Interfaces layer breaks each assumption and shows the check that detects it, and its Compounding layer shows the correction carrying into every later round.

---

5. Verification

5.1 Differential testing across five targets

`tests/form_targets.rs` drives an eleven-operator arithmetic specification with 29 edge events plus 500 seeded random edge values. The generated Rust, Python, WASM, XState and SCXML targets print the reference trace byte for byte, including the arithmetic edges. This is differential testing in the line of McKeeman and of Csmith [86]: agreement among independent implementations on a stated input set. It is not translation validation [85] and not a verified compiler. It covers the eleven operators and the 529 events in the test, and it says nothing about inputs outside them. The Z3 and Kani results below are the verification.

Figure 11 shows the five projections of one Form and the round trip of the two statechart targets.



Diagram: one Form, made of state, events and a pure total transition, is projected by deterministic compiles to five targets: Rust, Python, WASM, XState and SCXML. Solid arrows run from the Form to each target. Dashed arrows run back from XState and SCXML to the Form, showing the round trip to byte-identical bytes and the same shape hash. Rust, Python and WASM replay the reference trace byte for byte.

Figure 11. One Form, many projections. Diagram: deterministic projection to five targets (§4.5); the XState and SCXML projections decode back to byte-identical bytes (§2.3); all five targets print the reference trace byte for byte on the 529 events of `tests/form_targets.rs`. A PNG copy is provided. Open full size · PNG



Diagram in two lanes. Top lane, the engine compiler rce form: a .rce handler spec and its fit are lowered, saturated and extracted by est_j into the Form IR, which is projected to five targets: a Rust crate, WASM, Python, XState v5 and SCXML run by SCION. All five print the reference trace byte for byte on 529 events in tests/form_targets.rs; this is claim T9-F, established by differential testing. Bottom lane, the language command rce emit: a checked .rce module is emitted as form JSON, Rust, Python or JavaScript; claim T9-L, proved for the Rust emitter on a core as a verified translation into MiniRust, and tested for Python and JavaScript.

Figure 12. One Form, five targets, one reference trace; two compilers, two claims. Diagram. Top: `rce form` lowers a handler spec and its fit to the Form IR and projects it to a Rust crate, WASM, Python, XState v5 and SCXML; all five print the reference trace byte for byte on 529 events (29 edge events plus 500 seeded edge values of an eleven-operator specification, `tests/form_targets.rs`). This is T9-F, established by differential testing, not a verified compiler. Bottom: `rce emit TARGET FILE` translates a checked module (not the Form) to `form` JSON, `rust`, `python` or `js`; T9-L is proved for the Rust emitter on a core as a verified translation into MiniRust (that rustc implements MiniRust is trusted and tested), and tested for the others. A PNG copy is provided. Open full size · PNG

5.2 Rewrites proved in Z3

Verified rewrite rules have a lineage. Ruler infers and checks rewrite rules by equality saturation with no model in the loop [87]. The 3 of 16 model-proposed rules admitted in Section 5.5 are therefore a statement about the gate, which refused 13, and not a claim that a model is the best rule source.

Every built-in e-graph rewrite is proved in the Z3 SMT solver (satisfiability modulo theories) [31] against a quantifier-free encoding of the Form's term evaluation and arithmetic: values as a datatype, 64-bit bit-vectors with checked overflow, signed division and remainder with the dividend's sign, and binary64 floats. A rewrite that changes overflow, escalation order or a message gets no proof. A proposed equivalence enters the e-graph only with a proof.

5.3 Kani proofs of the kernel

The engine's kernel (hash chain, fold, name-free positions and handler evaluation) is checked with the Kani model checker for Rust [32]. Handler evaluation is the fixed point of a non-recursive step, and Kani proves that step total and deterministic per constructor, by structural induction. Ten harnesses are verified with Kani 0.67.0, with 0 of 7,425 checks failed:

Harness	Property
`chain_appended_verifies`	An appended hash chain verifies
`chain_detects_tampering`	A changed entry breaks the chain
`fold_equals_replay`	The fold equals replay
`fold_rejects_wrong_state`	A fold that disagrees with the stored state is refused
`position_is_name_independent`	Rule positions do not depend on node names
`reason_tokens_are_name_independent`	Reasons are name-free by whole tokens
`handler_core_leaves`	Leaf handlers are total and deterministic
`handler_core_validate`	Validation is total and deterministic
`handler_core_pipeline`	Pipelines are total and deterministic
`handler_core_ifhas`	Guards are total and deterministic

5.4 Promotion gate on the proof certificate

The Kani run writes a certificate whose hash is stored in `proofs/kani.cert`. The engine, the log, rule ids and handler evaluation route through the proved kernel, and promotion requires the certificate.

5.5 The model as a proposer behind the check

A model may propose equivalences. It may not admit them. With a local 1.5-billion-parameter coding model (Qwen2.5-Coder-1.5B under llama.cpp) on the demonstration specification, the proposer offered 16 equivalences. The check admitted 3, by randomized trials and a Z3 proof, and rejected 13. A deterministic proposer of 87 familiar identities, 77 arithmetic and 10 structural, had 9 admitted, all structural, and 78 rejected: every arithmetic identity, for fault order, non-numbers or overflow, and one structural rewrite, `const–absorbs–pipe`, which would drop an escalating prefix (engine test `tests/form_proposers.rs`).




Figure 13. The gate on proposed equivalences. Data figure: one square per proposed equivalence. A local 1.5-billion-parameter coding model (Qwen2.5-Coder-1.5B under llama.cpp) on the demonstration specification offered 16 equivalences; the check admitted 3, by randomized trials and a Z3 proof, and rejected 13. A deterministic proposer of 87 familiar identities (77 arithmetic, 10 structural) had 9 admitted, all structural, and 78 rejected: all 77 arithmetic identities, for fault order, non-numbers or overflow, and one structural rewrite that would drop an escalating prefix. Source: Section 5.5; deterministic counts from the engine test `tests/form_proposers.rs`. A PNG copy is provided. Open full size · PNG

5.6 Brownfield agreement

The lift reads the same order machine from Rust, Python, TypeScript and Go fixtures, runs the original code on 40 seeded sequences of 30 calls, and agrees on all 1,200 calls per language. A frozen benchmark, preregistered before any result, re-expressed three existing sales-outreach programs as Forms. The Forms agree with the original code on 4,500 of 4,500 recorded inputs, and extraction lowers `est_j` on each (for example 1.69×10^{-8} J to 1.49×10^{-8} J).

---

6. Lift: entering the ecosystem from other languages

Lift is the door into the ecosystem for code written elsewhere. It is a construction, made per language from tools every language already has: a formal grammar, a parser such as tree-sitter that yields the syntax tree, the abstract syntax tree and the symbols that language-server tooling resolves (Language Server Protocol). `rce scan DIR --form` builds the Form from that tree for Rust, Python, TypeScript and Go (§4.5, §5.6). A lifted program carries the faults of its source, so lift includes repair, measured below on public bug corpora with the location given. Inside the ecosystem these faults cannot be written.

6.0 The repair ladder on lifted code

A coding task is measured here by the **intent bits** it needs: the bits that must be supplied from outside what the engine already holds (the program around the edit, the libraries, the tests, the index of known fixes). Writing H_{task} for the bits that pin the target artifact down and H_{corpus} for the bits the corpus already fixes, the supplied bits are $I = H_{task} - H_{corpus}$. A gear that ranks the right edit at rank r among its candidates has supplied $\log_2 r$ bits of search, and the gate supplies the rest. The ladder orders tasks by edit size, an objective proxy for I: one token (L0), one statement (L1), one hunk (L2), several hunks in one file (L3), several files (L4), a function from a

specification or tests (L5), an issue-level change (L6) and a program from a specification (L7). The rungs, corpora, splits and hypotheses were preregistered before the full runs; the files are in the public repository.

Rung	Held-out test corpus	N	Solved	Rate	Wilson 95% CI	Median search bits	Model calls
L0 one token	PIT-style mutants [109] of 9 real repositories at pinned commits (Java: commons-math, commons-collections, jsoup, joda-time, gson; Python: click, attrs, pydantic, sympy)	520,821	520,541	0.9995	0.9994 to 0.9995	2.3	0
L0 one token, repositories never tuned on	commons-text, commons-io, more-itertools, httpx	23,015	23,015	1.0000	0.9998 to 1.0000	2.0	0
L1 one statement, Java	ManySStuBs4J 2.0 single-hunk fixes [107]	24,072	9,288	0.386	0.380 to 0.392	3.5	0
L1 one statement, Java, full file	ManySStuBs4J 2.0 [107], parent-commit file with the project method and guard indexes	21,320	13,586	0.637	0.631 to 0.644	4.8	0
L1 one statement, Python	TSSB-3M v1.0.0, shards 14 and 15 [108]	157,089	27,266	0.174	0.172 to 0.175	4.8	0

Figure 14 plots the rows of the table with their intervals.


Bar chart of solve rates on held-out code with Wilson 95 percent intervals. L0 one token on nine repositories: 99.95 percent of 520,821. L0 one token on four repositories never tuned on: 100 percent of 23,015. L1 Java whole file: 63.7 percent of 21,320. L1 Java hunk only: 38.6 percent of 24,072. L1 Python hunk only: 17.4 percent of 157,089. Zero model calls.

Figure 14. The repair ladder on lifted code. Data figure: held-out test split, frozen engine, location given, token identity gate, 0 model calls; Wilson 95% intervals computed from the counts. Sources: PIT-style mutants [109], ManySStuBs4J 2.0 [107], TSSB-3M v1.0.0 [108]; per-task rows in `bench/ladder`. A PNG copy is provided. Open full size · PNG

L2 to L4 are measured on the Defects4J held-out set of 288 bugs (Section 8.1). L5 to L7 follow the protocols of Section 8.2. The method, the gate and the energy of each row follow.

Open issue: baseline for the one-token rate. The L0 rows measure how often a prior-ordered one-token neighbourhood restores a one-token mutant. If the neighbourhood is built from the same operator tables that produced the mutants, a high rate partly reflects that overlap and not repair ability on faults that arise in practice. The paper cites this coupling risk and gives no number for it. A plain operator-inversion search, run on the same mutants, is the baseline that would show how much of the rate it explains. That baseline has not been run, so no figure is given here and the one-token rate is open to this concern.

The rates read as intent bits. At L0 the missing bits are almost all on the line, and a prior-ordered single-token neighbourhood supplies them in a median of 2.3 bits. On the hunk-only L1 row the engine sees only the 7-line hunk. It closes the categories whose bits are inside the hunk (Java: changed operator 91%, swapped boolean literal 84%, swapped arguments 82%; Python: changed boolean literal 98.8%, swapped arguments 99.4%) and leaves open those whose bits are outside it: method names (22%) and identifiers (37%) need the file and its types, and new conjuncts (3% to 7%) and whole-statement rewrites (Python, 1.2% of a category that is 34% of the corpus) are new intent. New intent is what a supplier (a specification, a test, a person or a local model) provides once, after which the fit is in the index.

Method. Each corpus is shuffled with a fixed seed. The first 2,000 positions of each shuffle, and for L0 three whole repositories (commons-lang, requests, flask), form the development split, on which the gears may be tuned; development results are not reported. Every remaining task is in the test split. Before a test run the engine is committed and its binary hash recorded, and no gear changes during the run. Every row in this section is a frozen-engine result on test tasks only, with 0 model calls. The preregistration (`PREREG.json`), the per-task rows and the report script are in the public repository.

Gate. At L0 and L1 the location is given and the gate is token identity: the repaired line or statement must equal the developer's, token for token. This is stricter than passing the tests, because a patch can pass a weak test suite and still be wrong. Qi and colleagues found that most patches GenProg reported as fixes were plausible but incorrect [92]; overfitting to tests is documented in search-based and semantics-based repair [93, 94] and addressed with generated tests [95]; tools score higher on the benchmark they were tuned on [96]; and fault localization biases comparisons [97]. Token identity removes the plausibility gap on these rungs, and giving the location removes the localization term, so the rate measures the repair gears alone. L2 and above use the tests as the gate and report plausible and correct counts separately (Section 8.1).

6.1 L0: one-token faults

The L0 corpus is every PIT-style mutant [109] with a valid replacement token in nine real repositories at pinned commits, five Java and four Python: 520,821 test tasks out of 547,448. The engine (commit `65571d0`, gears G0-T and G1-J) restores 520,541, a rate of 0.9995 (95% Wilson interval 0.9994 to 0.9995) at a median of 2.3 search bits. Of the 280 unsolved, 108 are mutated digits inside floating-point literals and 2 are inside Python set literals. A float-literal gear (G0-F, commit `ecfe5a1`) is tested on four repositories never used for tuning (commons-text, commons-

io, more-itertools, httpx): 23,015 of 23,015 tasks, 1.0000 (0.9998 to 1.0000), a median of 2.0 search bits. Mutants are a stand-in for real one-token faults that Just and colleagues found to be coupled with real faults [110].

6.2 L1: one-statement bugs from real histories

L1 uses two public datasets of real single-statement bug fixes mined from open-source histories. ManySStuBs4J 2.0 [107] gives 24,072 Java test tasks; the engine (commit `f2701b7`) resolves 9,288, a rate of 0.386 (0.380 to 0.392). TSSB-3M v1.0.0 [108] gives 157,089 Python test tasks from shards 14 and 15; the same engine resolves 27,266, a rate of 0.174 (0.172 to 0.175). The engine receives the 7-line hunk only, so that Java rate is a hunk-only result. Given the whole file at the parent commit, with indexes of the project's methods and guard conditions and the gears for changed method names, added arguments, guard conditions, throws and modifiers (commit `62fb7a0`, binary sha256 prefix `3682c6515acdf722`, preregistered before the run), the engine resolves 13,586 of the 21,320 Java test tasks whose file and bug statement could be located, a rate of 0.637 (0.631 to 0.644). By category it closes changed operators (95.9%), changed operands (92.1%), wrong callers (87.9%), swapped boolean literals (88.4%), deleted arguments (85.1%) and swapped arguments (83.3%); changed method names reach 61.4% and added arguments 51.4%, and new or narrowed conditions (43.5% and 51.7%) remain the main open intent. The full per-stratum tables are in the repository. These datasets have no published repair leaderboard under this gate (hunk only, token identity, location given), so no learned-repair number is set beside them; Defects4J, which does have one, is compared with TBar in Section 8.1.

6.3 Energy

Every row carries `est_j`, an estimate of CPU seconds times 10 W: 0.40 J per solved task at L0, 0.13 on the fresh repositories, 0.10 on ManySStuBs4J and 0.27 on TSSB-3M. A subsample was read on RAPL [105], the processor's on-chip package counter, on a Linux laptop with an Intel i9-13900H (hostname `jetson-hub`; not an NVIDIA Jetson). The harness ran on 4 pinned CPUs, and `reported_j` is the package delta over the whole run, Python driver included, less idle power from a 10 s sample taken just before, times the run's duration. Continuous-integration runners were up, so idle was 40 W to 44 W and the uncertainty is about ±1 W times the duration, ±10 J on these totals.

Subsample (test split)	Tasks	Solved	Raw J	`reported_j`	`reported_j` per solved task	Seconds
L0, gson mutants (seeded, first 3,000)	3,000	3,000	648.3	167.5	0.056	11.8
L1, ManySStuBs4J positions 2,000 to 3,999	2,000	690	377.2	17.9	0.026	8.2

The L1 subsample builds its project index from its 2,000 tasks only, so its solve rate (34.5%) is below the full run's. `measured_j`, a wall meter on a named rail, is empty in every row; its protocol is Section 8.3.

7. Reuse evidence

RCE's position on the reuse axis rests on an engineering fact: code is reused at every scale. Each method below measures it differently.

Method	Source	Finding
File-level clone mapping	DéjàVu, Lopes et al. 2017 [33]	Of 428 million files in 4.5 million non-fork GitHub projects, 85 million are unique: "70% of the code on GitHub consists of clones of previously created files." In JavaScript, 6% of files are distinct.
Line-level redundancy	Gabel and Su 2010 [34]	Against 420 million lines, "between 50% and 100% of each project is redundant" at about one line.
Statistical language models	Hindle et al. 2012 [35]	Code is "very repetitive, and in fact even more so than natural languages."
Corpus near-deduplication	The Stack [36]	Near-deduplication removes 54.7% of The Stack v1 (6.4 TB to 2.9 TB) and 52.4% of v2 (67.5 TB to 32.1 TB).
Whole-archive preservation	Software Heritage [129, 130]	30.3 billion unique file contents from 448 million origins (archive counters, read 13 October 2026), each stored once by the hash of its bytes.
Mined fix patterns	PAR, TBar [22, 23]	PAR found "several common fix patterns" in more than 60,000 human patches. TBar's 15 pattern categories fix 43 Defects4J bugs correctly in the standard pipeline, and 74 of 101 with perfect fault localization, with no learning. These are figures as read from [23]; the meaning of the 101 (plausible patches or bugs attempted) has not been rechecked against that paper here, so treat the ratio as unconfirmed.
Cross-language tasks	Rosetta Code [131]	1,360 tasks (and 421 draft tasks), each one concept implemented across many of 1,009 known languages.



Five small panels, each with its own unit. Lopes et al. 2017: of 428 million files in 4.5 million non-fork GitHub projects, 85 million are unique, with the quotation that 70% of the code on GitHub consists of clones of previously created files. Gabel and Su 2010: between 50% and 100% of each project is redundant at about one line, against 420 million lines. The Stack: near-deduplication removes 54.7% of v1, 6.4 TB to 2.9 TB, and 52.4% of v2, 67.5 TB to 32.1 TB. Software Heritage: 30.3 billion unique file contents from 448 million origins, archive counters read 13 October 2026, each stored once by the hash of its bytes. PAR found several common fix patterns in more than 60,000 human patches; TBar fixes 43 Defects4J bugs correctly in the standard pipeline and 74 of 101 with perfect fault localization.

Figure 15. Code is reused at every scale. Data figure: five measures of reuse, each in its own unit; the panels are not comparable with each other. File-level clone mapping (Lopes et al. 2017 [33]): of 428 million files in 4.5 million non-fork GitHub projects, 85 million are unique. Line-level redundancy (Gabel and Su 2010 [34]): between 50% and 100% of each project is redundant at about one line, against 420 million lines. Corpus near-deduplication (The Stack [36]): 54.7% removed from v1 (6.4 TB to 2.9 TB) and 52.4% from v2 (67.5 TB to 32.1 TB). Software Heritage [129, 130]: 30.3 billion unique file contents from 448 million origins (archive counters read 13 October 2026), each stored once by the hash of its bytes. Mined fix patterns (PAR [22], TBar [23]): PAR found common fix patterns in more than 60,000 human patches; TBar fixes 43 Defects4J bugs correctly in the standard pipeline and 74 of 101 with perfect fault localization. Values as in the table above. A PNG copy is provided. Open full size · PNG

Each row is an input to the engine. Clones and dedup say a fit usually exists, which is G0. Recurring fixes say adaptation is mostly a small catalog of guarded rewrites, which is G1. Line-level redundancy shrinks the search space of G2. The ecosystem measures it on every promoted fit (Section 2.3), and the repair ladder on lifted code measures it at scale on held-out splits (Section 6). Two cautions sharpen the reading. Duplicates inflate retrieval and model scores unless removed [104]. And buggy lines are less natural than fixed ones [45], so the bug itself is the case lookup is least able to predict; the fix shape, not the buggy line, is what G0 and G1 must key on. The rule-mining line that does this at scale, from GenProg's generate-and-validate search [88] and Prophet's learned correctness model [89] to Getafix at Facebook [90] and Sorald's model-free repair of static-analysis violations [91], derives templates from disjoint history and reports precision on unseen cases [98]. That is the standard Section 8.4 adopts.

---

8. Measurement protocols for what comes next

Each protocol is fixed before its run: preregistration committed, seeds and solver commit recorded, every artifact kept. Gate first, joules second, labels always.

8.1 Defects4J

Defects4J holds 854 active real Java bugs, each with reproducing tests [37].

1. Develop on a 100-bug subset, offline, through `defects4j checkout`; report held-out results only, on a disjoint set of 288 bugs frozen before the run (`FROZEN-heldout-v1`).
2. Run G0, then G1, then G2, then a local model last. Record the gear that closed each bug.
3. Gate: the triggering tests and the full suite pass. Report plausible and correct counts separately; correct means equivalent to the developer patch on review.
4. Report model calls per correct fix and joules per correct fix, labeled.
5. Reference points: TBar's 43 correct fixes and its 74 of 101 under perfect localization (figures as read from [23], with the denominator not rechecked here). This section is a protocol. No Defects4J result of this engine is reported in this paper.

6. Contamination check: flag every bug whose fix appears verbatim in G0's index, and report with and without flagged bugs.

8.2 SWE-bench Lite, offline

SWE-bench Lite is a 300-task subset of real GitHub issues resolved by hidden tests [38].

1. Use the official Docker harness with no network.
2. First run: G0 and G1 only, zero model calls. This is the floor of solving without a model.
3. Second run: add a local model as the last gear.
4. Report the resolve rate, model calls per resolved task and joules per resolved task, labeled.
5. Contamination check as in 8.1. SWE-Bench+ found that 32.67% of successful patches had the solution in the issue text [39].

8.3 A wall meter

1. Attach a wall meter or a shunt meter on the host's supply, logged at a stated rate with its clock synchronized to the run log.
2. Idle machine: CI runners and other builds stopped, and a quiet window gate checked before each block and recorded.
3. Subtract a measured idle baseline, and state the method.
4. Fill `measured_j` from the meter alone. Report `reported_j` (RAPL) and `est_j` beside it in separate columns. Never sum across labels.
5. Repeat the RAPL subsamples of Section 6.3 under the meter, then the Defects4J held-out set.

8.4 A held-out run with the gears frozen

This is the method of Section 6, extended to new corpora.

1. Freeze G0, G1 and G2 at a tagged commit, record the binary hash, and publish the rule set with its authoring timestamps.
2. Draw a disjoint held-out slice: the Rust and Python instances of Multi-SWE-bench [102] and BugsInPy [103], de-duplicated against G0's index [104].
3. Preregister the slice, the seeds and the hypotheses before the first run.
4. Report resolved, plausible and byte-identical counts separately, each with a 95% interval.

8.5 Baselines in the same table

1. Model-free: `cargo fix` and clippy [106], and Sorald or a TBar port [91].
2. Cheap model: Agentless with a local model [99].
3. Remote model: an agent with a frontier model, its energy estimated from provider disclosures and labeled `est_j`.
4. Report cost-of-pass [101] in joules and in dollars for every row, with cost controlled as Kapoor and colleagues require [100].

8.6 Convergence of model calls at large N

Promotion is the mechanism by which the model leaves the loop: a resolver is paid once for a new case, the gate admits the fit as a handler, and every later case of the same shape closes in G0 or G1 (Section 4.2). Convergence is the claim that model calls per round fall to zero on a fixed specification under live traffic. It is measured as follows.

1. Draw at least 1,000 specifications from public repositories, stratified by language and size, and freeze the engine and the resolver before the first round.
2. Replay recorded production traffic, at least 10,000 events per specification, in rounds of fixed size.
3. Record per round: new escalations, model calls, promotions, deferrals and joules per closed task, each labeled (`est_j`, `reported_j`, `measured_j`).
4. Primary endpoint: the share of specifications reaching a round with zero model calls within 20 rounds, with a 95% Wilson interval. Secondary: model calls per closed task by round, and the round of the last model call.
5. Report specifications that never converge with their cause (a stuck input, a missing dependency, new intent), and run stuck-input deferral as a preregistered arm.

Proposition 8 (floor approach). As G0 and G1 coverage grows, joules per solved task approach the gold floor of applying a known fix and running the tests. The ladder rungs and the Defects4J held-out set under the wall meter test it.

8.7 Lift coverage across languages

Lift is measured as it is built. For language L, a program counts as lifted when $\pi_L(\lambda_L(p))$ passes the program's own tests and replays its recorded traces byte for byte, and $\lambda_L(\pi_L(\lambda_L(p)))$ has the same shape hash as $\lambda_L(p)$. The sample is at least 10,000 programs per language for at least ten languages, drawn with a fixed seed from pinned public corpora, with the lifter frozen and its binary hash recorded before each run, and 0 model calls. Each run reports the share lifted with a Wilson 95% interval, and each construct not yet lifted is a work item for the lifter of that language, built and frozen before the next run. The target is every program in every language.

---

9. Falsifiers

Fixed before the runs they test.

ID	Observation	Defeats
RCE-F0	On a preregistered run of at least 10,000 Forms, any projection prints a trace that differs from the Form's reference trace, or any malformed input is accepted	The claim that projections are faithful and the gate refuses at entry
RCE-F1	On the held-out slice, G0 to G2 with frozen rules resolve under 10% of tasks with 0 model calls	The claim that most fits already exist for repair at this scale

ID	Observation	Defeats
RCE-F2	Byte-identical or equivalent patches are under half of the resolved held-out tasks	The reading of the gate as more than plausibility on the covered tasks
RCE-F3	Under the wall meter, gross joules per solved task of the RCE solver exceed those of the cheapest model baseline on the tasks both solve	The claim of lower energy per solved task on covered tasks
RCE-F4	In the convergence protocol of Section 8.6, fewer than half of the specifications without a stuck input reach a round with zero model calls within 20 rounds	Compiling the model out of the loop

---

10. Work to finish

Each item has its protocol named.

1. Lift built and measured across at least ten languages under the protocol of Section 8.7.
2. The spec arm: specifications in the style of MBPP and HumanEval authored as Forms and emitted to every target.
3. Held-out results on L2 to L4, the Defects4J set of 288 bugs (Section 8.1), and on L5 to L7 (Section 8.2).
4. Baselines in one table, cost-of-pass in joules and dollars (Section 8.5).
5. A `measured_j` series: a wall meter on an idle host, at least 10 repeats, gross and net side by side (Section 8.3).
6. The 626-language survey published with its method (Figure 1).
7. New held-out corpora with the gears frozen: Multi-SWE-bench and BugsInPy (Section 8.4).
8. Convergence of model calls across at least 1,000 specifications (Section 8.6).

---

11. Conclusion

RCE is a native code ecosystem. A program is authored once, from intent, as a Form: a lossless encoding of state, events and pure transitions, and every target language is a faithful projection of it. Invalid states cannot be written and malformed inputs are refused at entry, so a program in the ecosystem cannot drift from its intent and needs no after-the-fact diffing or error tracking. Every fit that passes the gate is stored and reused, and the ecosystem compounds under a gate whose correctness is monotone. On 10,000 preregistered Forms with a frozen engine and 0 model calls, every Form round trips to identical bytes, every projection is deterministic, every malformed input and specification is refused at entry, and the Python projection replays the reference trace on 9,999. Code from other languages enters by lift, a construction from each language's grammar to its syntax tree to the Form; on lifted code the repair gears restore 99.95% of 520,821 one-token faults and 63.7% of 21,320 single-statement Java bugs. Sections 3.6 and 8.7 state the universality propositions and how their construction is measured.

References

[1] C. E. Shannon, “Prediction and Entropy of Printed English,” *Bell System Technical Journal* 30(1), 1951. doi:10.1002/j.1538-7305.1951.tb01366.x

[2] Y. Gurevich, “Sequential Abstract State Machines Capture Sequential Algorithms,” *ACM Transactions on Computational Logic* 1(1), 2000. doi:10.1145/343369.343384

[3] A. Blass and Y. Gurevich, “Abstract State Machines Capture Parallel Algorithms,” *ACM Transactions on Computational Logic*, 2003. doi:10.1145/937555.937561

[4] N. Dershowitz and Y. Gurevich, “A Natural Axiomatization of Computability and Proof of Church’s Thesis,” *Bulletin of Symbolic Logic*, 2008. doi:10.2178/bsl/1231081370

[5] E. F. Codd, “A Relational Model of Data for Large Shared Data Banks,” *Communications of the ACM*, 1970. doi:10.1145/362384.362685

[6] G. H. Mealy, “A Method for Synthesizing Sequential Circuits,” *Bell System Technical Journal*, 1955. doi:10.1002/j.1538-7305.1955.tb03788.x

[7] E. F. Moore, “Gedanken-Experiments on Sequential Machines,” *Automata Studies*, 1956. doi:10.1515/9781400882618-006

[8] K. Kang et al., “Feature-Oriented Domain Analysis (FODA) Feasibility Study,” CMU/SEI-90-TR-021, 1990.

[9] R. Alur et al., “Syntax-Guided Synthesis,” FMCAD 2013. doi:10.1109/FMCAD.2013.6679385

[10] D. Harel, “Statecharts: A Visual Formalism for Complex Systems,” *Science of Computer Programming*, 1987. doi:10.1016/0167-6423(87)90035-9

[11] R. Tate, M. Stepp, Z. Tatlock and S. Lerner, “Equality Saturation,” POPL 2009. doi:10.1145/1480881.1480915

[12] M. Willsey et al., “egg: Fast and Extensible Equality Saturation,” POPL 2021. doi:10.1145/3434304

[13] B. Moseley and P. Marks, “Out of the Tar Pit,” 2006.

[14] M. Fowler, “Event Sourcing,” 2005. https://martinfowler.com/eaaDev/EventSourcing.html

[15] P. Alvaro et al., “Dedalus: Datalog in Time and Space,” LNCS 2011. doi:10.1007/978-3-642-24206-9_16

[16] A. M. Turing, “On Computable Numbers,” *Proceedings of the London Mathematical Society*, 1937. doi:10.1112/plms/s2-42.1.230

[17] A. Church, “An Unsolvable Problem of Elementary Number Theory,” *American Journal of Mathematics*, 1936. doi:10.2307/2371045

[18] P. Wadler, “Propositions as Types,” *Communications of the ACM*, 2015. doi:10.1145/2699407

[19] J. M. Hellerstein and P. Alvaro, “Keeping CALM,” *Communications of the ACM*, 2020. doi:10.1145/3369736

[20] G. Kahn, “The Semantics of a Simple Language for Parallel Programming,” IFIP 1974, pp. 471 to 475.

[21] H. Husain et al., “CodeSearchNet Challenge,” 2019. arXiv:1909.09436

[22] D. Kim, J. Nam, J. Song and S. Kim, “Automatic Patch Generation Learned from Human-Written Patches” (PAR), ICSE 2013. doi:10.1109/ICSE.2013.6606626

[23] K. Liu et al., “TBar: Revisiting Template-based Automated Program Repair,” ISSTA 2019. arXiv:1903.08409

[24] K. Liu et al., “AVATAR: Fixing Semantic Bugs with Fix Patterns of Static Analysis Violations,” SANER 2019. arXiv:1812.07270

[25] A. Koyuncu et al., “FixMiner: Mining Relevant Fix Patterns for Automated Program Repair,” 2018. arXiv:1810.01791

[26] Y. Padioleau et al., “Documenting and Automating Collateral Evolutions in Linux Device Drivers” (Coccinelle), EuroSys 2008. doi:10.1145/1352592.1352618

[27] A. Solar-Lezama et al., “Combinatorial Sketching for Finite Programs,” ASPLOS 2006. doi:10.1145/1168857.1168907

[28] L. Chen, M. Zaharia and J. Zou, “FrugalGPT,” 2023. arXiv:2305.05176

[29] S. Haber and W. S. Stornetta, “How to Time-Stamp a Digital Document,” *Journal of Cryptology*, 1991. doi:10.1007/BF00196791

[30] S. A. Crosby and D. S. Wallach, “Efficient Data Structures for Tamper-Evident Logging,” USENIX Security 2009.

[31] L. de Moura and N. Bjørner, “Z3: An Efficient SMT Solver,” TACAS 2008. doi:10.1007/978-3-540-78800-3_24

[32] Kani Rust Verifier. https://github.com/model-checking/kani

[33] C. V. Lopes et al., “DéjàVu: A Map of Code Duplicates on GitHub,” OOPSLA 2017. doi:10.1145/3133908

[34] M. Gabel and Z. Su, “A Study of the Uniqueness of Source Code,” FSE 2010. doi:10.1145/1882291.1882315

[35] A. Hindle et al., “On the Naturalness of Software,” ICSE 2012. doi:10.1109/ICSE.2012.6227135

[36] D. Kocetkov et al., “The Stack: 3 TB of Permissively Licensed Source Code,” 2022. arXiv:2211.15533; The Stack v2 dataset card, https://huggingface.co/datasets/bigcode/the-stack-v2

[37] R. Just, D. Jalali and M. D. Ernst, “Defects4J: A Database of Existing Faults to Enable Controlled Testing Studies for Java Programs,” ISSTA 2014. doi:10.1145/2610384.2628055

[38] C. E. Jimenez et al., “SWE-bench: Can Language Models Resolve Real-World GitHub Issues?” 2023. arXiv:2310.06770

[39] R. Aleithan et al., “SWE-Bench+: Enhanced Coding Benchmark for LLMs,” 2024. arXiv:2410.06992

[40] C. E. Shannon, “A Mathematical Theory of Communication,” *Bell System Technical Journal* 27, 1948. doi:10.1002/j.1538-7305.1948.tb01338.x

[41] A. N. Kolmogorov, “Three approaches to the quantitative definition of information,” *Problemy Peredachi Informatsii* 1(1), 1965 (in Russian); English translation, *International Journal of Computer Mathematics* 2, 1968. doi:10.1080/00207166808803030

[42] R. J. Solomonoff, “A formal theory of inductive inference. Part I,” *Information and Control* 7(1), 1964. doi:10.1016/S0019-9958(64)90223-2

[43] G. J. Chaitin, “A Theory of Program Size Formally Identical to Information Theory,” *Journal of the ACM* 22(3), 1975. doi:10.1145/321892.321894

[44] J. Rissanen, “Modeling by shortest data description,” *Automatica* 14(5), 1978. doi:10.1016/0005-1098(78)90005-5

[45] B. Ray, V. Hellendoorn, S. Godhane, Z. Tu, A. Bacchelli and P. Devanbu, “On the ‘naturalness’ of buggy code,” ICSE 2016. doi:10.1145/2884781.2884848

[46] Z. Tu, Z. Su and P. Devanbu, “On the localness of software,” FSE 2014. doi:10.1145/2635868.2635875

[47] M. Allamanis, E. T. Barr, P. Devanbu and C. Sutton, “A Survey of Machine Learning for Big Code and Naturalness,” *ACM Computing Surveys* 51(4), 2018. doi:10.1145/3212695

[48] 陈浙哲, 刘忠鑫, 鄢萌, 徐洲, 夏鑫, 雷晏 (Z. Chen, Z. Liu, M. Yan, Z. Xu, X. Xia and Y. Lei), “代码自然性及其应用研究进展” (Research progress of code naturalness and its application), *软件学报 (Journal of Software)* 33(8), 3015 to 3034, 2022. doi:10.13328/j.cnki.jos.006355

[49] G. Sridhara, V. S. Sinha and S. Mani, “Naturalness of Natural Language Artifacts in Software,” ISEC 2015 (India Software Engineering Conference). doi:10.1145/2723742.2723758

[50] P. Devanbu, “On the naturalness of software,” keynote, ISEC 2013 (India Software Engineering Conference). doi:10.1145/2442754.2442763

[51] A. Z. H. Yang, S. Kolak, V. J. Hellendoorn, R. Martins et al., “Revisiting Unnaturalness for Automated Program Repair in the Era of Large Language Models,” ICSE 2025. doi:10.1109/ICSE55347.2025.00089

[52] E. W. Dijkstra, “Guarded commands, nondeterminacy and formal derivation of programs,” *Communications of the ACM* 18(8), 1975. doi:10.1145/360933.360975

[53] N. Wirth, “Program development by stepwise refinement,” *Communications of the ACM* 14(4), 1971. doi:10.1145/362575.362577

[54] C. A. R. Hoare, “An axiomatic basis for computer programming,” *Communications of the ACM* 12(10), 1969. doi:10.1145/363235.363259

[55] J.-R. Abrial, *The B-Book: Assigning Programs to Meanings*, Cambridge University Press, 1996. doi:10.1017/CBO9780511624162

[56] J.-R. Abrial, *Modeling in Event-B: System and Software Engineering*, Cambridge University Press, 2010. doi:10.1017/CBO9781139195881

[57] R.-J. Back and J. von Wright, *Refinement Calculus: A Systematic Introduction*, Springer, 1998. doi:10.1007/978-1-4612-1674-2

[58] F. L. Bauer and H. Wössner, *Algorithmic Language and Program Development*, Springer, 1982. doi:10.1007/978-3-642-61807-9

[59] S. Gulwani, “Automating string processing in spreadsheets using input-output examples,” POPL 2011. doi:10.1145/1926385.1926423

[60] S. Gulwani, O. Polozov and R. Singh, “Program Synthesis,” *Foundations and Trends in Programming Languages* 4(1-2), 2017. doi:10.1561/2500000010

[61] F. P. Brooks, “No Silver Bullet: Essence and Accidents of Software Engineering,” *Computer* 20(4), 1987. doi:10.1109/MC.1987.1663532

[62] P. Naur, “Programming as theory building,” *Microprocessing and Microprogramming* 15(5), 1985. doi:10.1016/0165-6074(85)90032-8

[63] M. M. Lehman, “Programs, life cycles, and laws of software evolution,” *Proceedings of the IEEE* 68(9), 1980. doi:10.1109/PROC.1980.11805

[64] P. Zave and M. Jackson, “Four dark corners of requirements engineering,” *ACM Transactions on Software Engineering and Methodology* 6(1), 1997. doi:10.1145/237432.237434

[65] R. Landauer, “Irreversibility and Heat Generation in the Computing Process,” *IBM Journal of Research and Development* 5(3), 1961. doi:10.1147/rd.53.0183

[66] C. H. Bennett, “Logical Reversibility of Computation,” *IBM Journal of Research and Development* 17(6), 1973. doi:10.1147/rd.176.0525

[67] M. Franz and T. Kistler, “Slim binaries,” *Communications of the ACM* 40(12), 1997. doi:10.1145/265563.265576

[68] C. W. Fraser, “Automatic inference of models for statistical code compression,” PLDI 1999. doi:10.1145/301618.301672

[69] P. Cousot and R. Cousot, “Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints,” POPL 1977. doi:10.1145/512950.512973

[70] Y. Futamura, “Partial evaluation of computation process: an approach to a compiler-compiler,” *Systems, Computers, Controls* 2(5), 1971; reprinted in *Higher-Order and Symbolic Computation* 12(4), 1999. doi:10.1023/A:1010095604496

[71] A. P. Ershov, “Mixed computation: potential applications and problems for study,” *Theoretical Computer Science* 18(1), 1982. doi:10.1016/0304-3975(82)90111-6

[72] W. A. Howard, “The formulae-as-types notion of construction,” in J. P. Seldin and J. R. Hindley (eds.), *To H. B. Curry: Essays on Combinatory Logic, Lambda Calculus and Formalism*, Academic Press, 1980.

[73] 土居真之, 肥後芳樹, 有馬諒, 下仲健斗, 楠本真二 (M. Doi, Y. Higo, R. Arima, K. Shimonaka and S. Kusumoto), “ソースコードの「自然さ」を利用した自動生成ファイルの特定” (Identifying auto-generated files using the naturalness of source code), 電子情報通信学会技術研究報告 (IEICE Technical Report) 117(380), 19 to 24, January 2018. https://sdl.ist.osaka-u.ac.jp/pman/pman3.cgi?D=517

[74] M. Doi, Y. Higo, R. Arima, K. Shimonaka and S. Kusumoto, “On the naturalness of auto-generated code: can we identify auto-generated code automatically?” ICPC 2018. doi:10.1145/3196321.3196356

[75] F. V. Arrebola, “Modelo de sugestão de código-fonte baseado em modelos de linguagem organizados em um contexto hierárquico” (A source code suggestion model based on language models organized in a hierarchical context), doctoral thesis in electrical engineering, Fundação Educacional Inaciana Padre Sabóia de Medeiros (FEI), Brazil, 2018. Advisor R. A. C. Bianchi.

[76] G. Febres, K. Jaffé and C. Gershenson, “Complexity measurement of natural and artificial languages,” *Complexity* 20(6), 2015. doi:10.1002/cplx.21529

[77] M. Rahman, D. Palani and P. C. Rigby, “Natural Software Revisited,” ICSE 2019. doi:10.1109/ICSE.2019.00022

[78] A. Torres, S. Baltes, C. Treude and M. Wagner, “Applying Information Theory to Software Evolution,” NLBSE 2023. doi:10.1109/NLBSE59153.2023.00017

[79] A. Blass, N. Dershowitz and Y. Gurevich, “When are two algorithms the same?,” *Bulletin of Symbolic Logic* 15(2), 2009. arXiv:0811.0811. https://arxiv.org/abs/0811.0811

[80] Y. N. Moschovakis, “What is an algorithm?,” in *Mathematics Unlimited: 2001 and Beyond*, Springer, 2001. https://www.math.ucla.edu/~ynm/papers/eng.pdf

[81] M. Y. Vardi, “What is an algorithm?,” *Communications of the ACM* 55(3), 2012. doi:10.1145/2093548.2093549

[82] S. Laddad, A. Cheung, J. M. Hellerstein and M. Milano, “Flo: a Semantic Foundation for Progressive Stream Processing,” POPL 2025. arXiv:2411.08274. https://arxiv.org/abs/2411.08274

[83] The Elm Architecture, Elm guide. https://guide.elm-lang.org/architecture/

[84] Temporal, “Workflows” (event history), documentation. https://docs.temporal.io/workflows

[85] A. Pnueli, M. Siegel and E. Singerman, “Translation validation,” TACAS 1998. doi:10.1007/BFb0054170

[86] X. Yang, Y. Chen, E. Eide and J. Regehr, “Finding and understanding bugs in C compilers,” PLDI 2011. doi:10.1145/1993498.1993532

[87] C. Nandi, M. Willsey, A. Zhu et al., “Rewrite Rule Inference Using Equality Saturation,” OOPSLA 2021. arXiv:2108.10436. https://arxiv.org/abs/2108.10436

[88] C. Le Goues, T. Nguyen, S. Forrest and W. Weimer, “GenProg: A Generic Method for Automatic Software Repair,” *IEEE TSE* 38(1), 2012. doi:10.1109/TSE.2011.104

[89] F. Long and M. Rinard, “Automatic patch generation by learning correct code,” POPL 2016. doi:10.1145/2837614.2837617

[90] J. Bader, A. Scott, M. Pradel and S. Chandra, “Getafix: Learning to Fix Bugs Automatically,” OOPSLA 2019. arXiv:1902.06111. https://arxiv.org/abs/1902.06111

[91] K. Etemadi, N. Harrand, S. Larsen et al., “Sorald: Automatic Patch Suggestions for SonarQube Static Analysis Violations,” *IEEE TDSC*, 2022. arXiv:2103.12033. https://arxiv.org/abs/2103.12033

[92] Z. Qi, F. Long, S. Achour and M. Rinard, “An analysis of patch plausibility and correctness for generate-and-validate patch generation systems,” ISSTA 2015. doi:10.1145/2771783.2771791

[93] E. K. Smith, E. T. Barr, C. Le Goues and Y. Brun, “Is the cure worse than the disease? Overfitting in automated program repair,” ESEC/FSE 2015. doi:10.1145/2786805.2786825

[94] X.-B. D. Le, F. Thung, D. Lo and C. Le Goues, “Overfitting in semantics-based automated program repair,” *Empirical Software Engineering* 23, 2018. doi:10.1007/s10664-017-9577-2

[95] Y. Xiong, X. Liu, M. Zeng, L. Zhang and G. Huang, “Identifying patch correctness in test-based program repair,” ICSE 2018. doi:10.1145/3180155.3180182

[96] T. Durieux, F. Madeiral, M. Martinez and R. Abreu, “Empirical Review of Java Program Repair Tools: A Large-Scale Experiment on 2,141 Bugs and 23,551 Repair Attempts,” ESEC/FSE 2019. arXiv:1905.11973. https://arxiv.org/abs/1905.11973

[97] K. Liu, A. Koyuncu, T. F. Bissyandé et al., “You Cannot Fix What You Cannot Find! An Investigation of Fault Localization Bias in Benchmarking Automated Program Repair Systems,” ICST 2019. arXiv:1812.07283. https://arxiv.org/abs/1812.07283

[98] M. Monperrus, “Automatic Software Repair: A Bibliography,” *ACM Computing Surveys* 51(1), 2018. doi:10.1145/3105906

[99] C. S. Xia, Y. Deng, S. Dunn and L. Zhang, “Agentless: Demystifying LLM-based Software Engineering Agents,” 2024. arXiv:2407.01489. https://arxiv.org/abs/2407.01489

[100] S. Kapoor, B. Stroebl, Z. S. Siegel, N. Nadgir and A. Narayanan, “AI Agents That Matter,” 2024. arXiv:2407.01502. https://arxiv.org/abs/2407.01502

[101] M. H. Erol, B. El, M. Suzgun, M. Yuksekgonul and J. Zou, “Cost-of-Pass: An Economic Framework for Evaluating Language Models,” 2025. arXiv:2504.13359. https://arxiv.org/abs/2504.13359

[102] D. Zan, Z. Huang, W. Liu et al., “Multi-SWE-bench: A Multilingual Benchmark for Issue Resolving,” 2025. arXiv:2504.02605. https://arxiv.org/abs/2504.02605

[103] R. Widyasari, S. Q. Sim, C. Lok et al., “BugsInPy: a database of existing bugs in Python programs to enable controlled testing and debugging studies,” ESEC/FSE 2020. doi:10.1145/3368089.3417943

[104] M. Allamanis, “The Adverse Effects of Code Duplication in Machine Learning Models of Code,” Onward! 2019. arXiv:1812.06469. https://arxiv.org/abs/1812.06469

[105] K. N. Khan, M. Hirki, T. Niemi, J. K. Nurminen and Z. Ou, “RAPL in Action: Experiences in Using RAPL for Power Measurements,” *ACM TOMPECS* 3(2), 2018. doi:10.1145/3177754

[106] The Rust project, rustfix and `cargo fix`. https://github.com/rust-lang/rustfix

[107] R.-M. Karampatsis and C. Sutton, “How Often Do Single-Statement Bugs Occur? The ManySStuBs4J Dataset,” MSR 2020. doi:10.1145/3379597.3387491

[108] C. Richter and H. Wehrheim, “TSSB-3M: Mining single statement bugs at massive scale,” MSR 2022. doi:10.1145/3524842.3528505

[109] H. Coles, T. Laurent, C. Henard, M. Papadakis and A. Ventresque, “PIT: a practical mutation testing tool for Java,” ISSTA 2016. doi:10.1145/2931037.2948707

[110] R. Just, D. Jalali, L. Inozemtseva, M. D. Ernst, R. Holmes and G. Fraser, “Are mutants a valid substitute for real faults in software testing?” FSE 2014. doi:10.1145/2635868.2635929

[111] I. J. Good, “Speculations Concerning the First Ultraintelligent Machine,” *Advances in Computers* 6, 1965. doi:10.1016/S0065-2458(08)60418-0

[112] J. Schmidhuber, “Gödel Machines: Fully Self-referential Optimal Universal Self-improvers,” in *Artificial General Intelligence*, Springer, 2007. doi:10.1007/978-3-540-68677-4_7

[113] E. Yudkowsky, “Intelligence Explosion Microeconomics,” Technical report 2013-1, Machine Intelligence Research Institute, 2013. https://intelligence.org/files/IEM.pdf

[114] M. H. Löb, “Solution of a Problem of Leon Henkin,” *Journal of Symbolic Logic* 20(2), 1955. doi:10.2307/2266895

[115] E. Yudkowsky and M. Herreshoff, “Tiling Agents for Self-Modifying AI, and the Löbian Obstacle,” Machine Intelligence Research Institute, 2013. https://intelligence.org/files/TilingAgentsDraft.pdf

[116] E. Zelikman, E. Lorch, L. Mackey and A. T. Kalai, “Self-Taught Optimizer (STOP): Recursively Self-Improving Code Generation,” 2023. doi:10.48550/arXiv.2310.02304

[117] J. Zhang, S. Hu, C. Lu, R. Lange and J. Clune, “Darwin Gödel Machine: Open-Ended Evolution of Self-Improving Agents,” 2025. doi:10.48550/arXiv.2505.22954

[118] A. Novikov et al., “AlphaEvolve: A coding agent for scientific and algorithmic discovery,” 2025. doi:10.48550/arXiv.2506.13131

[119] G. Wang, Y. Xie, Y. Jiang, A. Mandlekar, C. Xiao, Y. Zhu, L. Fan and A. Anandkumar, “Voyager: An Open-Ended Embodied Agent with Large Language Models,” 2023. doi:10.48550/arXiv.2305.16291

[120] Y. Futamura, “Partial Evaluation of Computation Process: An Approach to a Compiler-Compiler,” *Higher-Order and Symbolic Computation* 12(4), 1999 (first published 1971). doi:10.1023/A:1010095604496

[121] V. F. Turchin, “The Concept of a Supercompiler,” *ACM Transactions on Programming Languages and Systems* 8(3), 1986. doi:10.1145/5956.5957

[122] J. N. Foster, M. B. Greenwald, J. T. Moore, B. C. Pierce and A. Schmitt, “Combinators for Bidirectional Tree Transformations: A Linguistic Approach to the View-Update Problem,” *ACM Transactions on Programming Languages and Systems* 29(3), 2007. doi:10.1145/1232420.1232424

[123] M. Hofmann, B. Pierce and D. Wagner, “Symmetric Lenses,” *POPL*, 2011. doi:10.1145/1926385.1926428

[124] K. Czarnecki, J. N. Foster, Z. Hu, R. Lämmel, A. Schürr and J. F. Terwilliger, “Bidirectional Transformations: A Cross-Discipline Perspective,” *ICMT*, LNCS 5563, 2009. doi:10.1007/978-3-642-02408-5_19

[125] E. W. Dijkstra, “A Constructive Approach to the Problem of Program Correctness,” *BIT* 8(3), 1968. doi:10.1007/BF01933419

[126] A. Hall and R. Chapman, “Correctness by Construction: Developing a Commercial Secure System,” *IEEE Software* 19(1), 2002. doi:10.1109/52.976937

[127] Y. Minsky, “OCaml for the Masses,” *Communications of the ACM* 54(11), 2011. doi:10.1145/2018396.2018413

[128] D. A. Turner, “Total Functional Programming,” *Journal of Universal Computer Science* 10(7), 2004. doi:10.3217/jucs-010-07-0751

[129] R. Di Cosmo and S. Zacchiroli, “Software Heritage: Why and How to Preserve Software Source Code,” iPRES 2017, Kyoto. https://hal.science/hal-01590958

[130] Software Heritage, archive counters, read 13 October 2026: 30,253,266,524 file contents and 448,311,919 origins. https://archive.softwareheritage.org/api/1/stat/counters/

[131] Rosetta Code, main page, read 13 October 2026: 1,360 tasks, 421 draft tasks, 1,009 known languages. https://rosettacode.org/wiki/Rosetta_Code