

浙江東明不锈钢制品股份有限公司检测实验室
TONG MING ENTERPRISE (ZHEJIANG) CO.,LTD. TEST LABORATORY

质量保证书
(CERTIFICATE OF INSPECTION)

客户名称:	订单号码:	报告编号:
PURCHASER	PO#NO	Report Code
客户地址:	短项目号: 262514	实发数量:
ADDRESS	ITEM NO	SHIP QTY
项目号: D0912134CCOW02000800	标准: DIN912-1983	材质: A2(304)
CUST P/N	COMMODITY	MATERIAL TYPE
制造日期: 2024-09-14	品名: 内六角圆柱头螺钉(滚花)	批号: 20240920W514
MFR. DATE	Product Name Hex Socket Screw(Knurled)	LOT NO
抽样日期: 2024-09-20	印记: 光面	炉号: S240610AA23
Sampling Date	MARKING	HEAT NO
检测日期: 2024-09-20	规格: M2-0.4 X 8	表面处理:
Test Date	SIZE	Surface
制造商: 浙江東明不锈钢制品股份有限公司	抽样计划: ASME B18.18-2017	
MFR	Sample Plan spec	

尺寸检验 DIMENSIONAL INSPECTIONS 单位(mm)		测试方法(SAMPLE STANDARD):DIN912-1983			
测试项目 (CHARACTERISTICS)	标准值 (SPECIFICATION)	实测值 (ACTUAL RESULT)	测试判定 (SAMPLE DETERMINANT)		
圆头径 Head Diameter	3.62 <---> 3.98	3.72 <---> 3.74	合格(Qualified)		
头部厚度 Head Height	1.86 <---> 2	1.9 <---> 1.94	合格(Qualified)		
长度 Nominal Length	7.71 <---> 8.29	8 <---> 8.02	合格(Qualified)		
深度 Drive Depth	1min	1.02 <---> 1.1	合格(Qualified)		
内对边宽 Drive Width	1.52 <---> 1.56	1.56 <---> 1.56	合格(Qualified)		
螺纹最大径 Major Diameter	1.886 <---> 1.981	1.91 <---> 1.93	合格(Qualified)		
螺纹有效径 Pitch Diameter(GO/NOGO)	1.654 <---> 1.721	检验合格(PASSED)	合格(Qualified)		

机械性能 MECHANICAL PROPERTIES		测试方法(SAMPLE STANDARD):ISO3506-1 :2020			
测试项目 (CHARACTERISTICS)	标准值 (SPECIFICATION)	实测值 (ACTUAL RESULT)	测试判定 (SAMPLE DETERMINANT)		
破坏扭矩(N.m) Breaking Torque(N.m)	0.4min	0.67 <---> 0.7	合格(Qualified)		

化学成分 CHEMICAL COMPOSITION% (除标明范围外, 其余均为最大值. Maximum Value Or Range.)								测试判定
炉号HeatNumber	C	Si	Mn	P	S	Ni	Cr	(SAMPLE DETERMINANT)
标准值Specification	0.08	1	2	0.045	0.03	8--10.5	18--20	
S240610AA23	0.012	0.5	0.76	0.032	0.001	8.03	18.2	合格(Qualified)

Jiaminshen

Authorization

Xiaochunchen

Verification

QC48

Sample:

2024-06-16

Date

This Lot fit the demands of EN10204 3.1

声明: 该报告除非获得实验室书面同意, 证书或报告不得摘录、复制, 但全部复制除外

INSPECTION RESULT: SAMPLES TESTED CONFORM TO ALL OF SPECIFICATION AS ABOVE THIS REPORT MUST NOT BE REPRODUCED EXCEPT IN FULL.
WHENEVER TESTING DISCREPANCIES ARE DETECTED OR DEPARTURES FROM DOCUMENTED POLICIES AND PROCEDURE ABOUT, THEY WILL BE SHOWN
备注 IN REMARK.

1、测试半牙螺丝的单位是HRC, 测试全牙螺丝、螺帽和牙条的单位是HRB(S).

HRC for Screw Bolt with partial thread;HRB(S) for Nut、Thread rod and Bolt Screw with full thread.

Tel: +86-573-82203125

Fax: +86-573-82207588

Web: www.tongming.com.cn

E-mail:export@tongming.com.cn

ADD:88 ChangSheng RD, E. D. Zone, JiaXing, ZheJiang, China

Zip:314000