



OPEN

Compute Project

Bunch of Wires (BoW) PHY Specification

The Open Domain-Specific Architecture BoW Workstream

DRAFT Version 1.1b
September 30th, 2022

Contents

Glossary of Terms	4
Language	5
1. License Agreement	5
1.1. Open Web Foundation (OWF) CLA	5
2. OCP Tenets Compliance	6
2.1. Openness	6
2.2. Efficiency	6
2.3. Scale	7
2.4. Impact	7
3. Revision Table	7
4. Scope	7
5. BoW Overview	8
5.1. Key Features and Conformance	8
5.2. BoW Slice	8
5.3. BoW Wires	10
5.4. BoW Modes	10
5.5. Logic Interface	10
6. Signal Definitions	12

6.1. Directionality	12
6.2. Die-to-die Signals (Wires)	12
6.2.1. DBI on the AUX wire	12
6.3. Slice Logic (Link Layer) Interface for a Unidirectional PHY	13
6.3.1. Slice Logic Interface: Clock and Data Signals	13
6.4. Slice Logic (Link Layer) Interface for a Bidirectional PHY	13
6.4.1. Slice Logic Interface: Clock and Data Signals	13
6.5. Slice Logic (Link Layer) Interface aspects common to unidirectional and bidirectional PHYs	15
6.5.1. Slice Logic Interface: Control Signals	15
6.5.2. Programming	16
6.5.3. Link Controller	16
7. BoW Modes and Reach	16
8. BoW Physical Configuration	17
8.1. Dead-Bug Views	17
8.2. BoW Components	17
8.3. Example Link	17
8.4. BoW Half-Link Components	19
8.4.1. Minimal Half-Link	19
8.4.2. Half-Link to Regular Link Interoperability	19
8.5. Die-to-Die Signals	21
8.6. Signal Ordering	22
8.7. Bump Arrangements	22
8.7.1. Alternate Bump Arrangements	22
8.8. Cross Section	23
8.9. Staggered Slices	24
8.10. Slice Numbering	24
8.11. Slice Stacking Pattern for Symmetric Links	24
8.12. Connecting Bidirectional Slices	24
9. BoW PHY Electrical Specifications	27
9.1. Voltages and Termination Resistance	27
9.2. PHY protection	28
9.3. ESD	29
9.4. Return Loss and Parasitic Capacitance	29
9.5. Receiver Bandwidth	29
10. BoW PHY Timing Specifications	31
10.1. Bit Ordering	31
10.2. Clocking	31
10.3. Clock and Data Specifications	33
10.3.1. Transmitter Maximum Rise-Time	33
10.3.2. Transmitter Differential Clock Timing Mismatch	34
10.3.3. Transmitter Correlated Jitter Filtering	34
10.3.4. Transmitter Deterministic Timing Error	34
10.3.5. Transmitter Total Timing Error	35
10.3.6. CLK Receiver Sensitivity to Common-Mode Variations	35
10.3.7. Receiver Clock versus Data Path Delay	35

10.3.8. Receiver Sensitivity and Timing Margin	35
10.3.9. Voltage Overshoot	36
10.3.10. Slice-to-Clice CLK Skew	37
11. Power Management	37
11.1. Data Idle State	37
11.2. Clock Gated State	37
11.2.1. Signal Levels During Clock Gated State	37
11.2.2. Minimum Preamble, Postamble, and Payload Durations	38
11.2.3. PHY_Idle Timing and Parallel Data During Preamble / Postamble	38
11.2.4. Maximum Duration of Occupancy Within Clock Gated State	38
12. Chip-to-Chip Channel Specifications	39
12.1. Channel-Induced CLK Edge to D Transition Skew at RX	39
12.2. Channel Impedance	39
12.3. Example BoW Channel for Doubly-Terminated Links	39
12.3.1. Channel Loss	40
12.3.2. Crosstalk	40
13. Redundancy	40
14. Sideband Slices	40
15. Reset and Initialization	40
15.1. External Facilities	40
15.2. Initialization Sequence	41
15.2.1. A TX-RX Link should be brought up as follows:	41
15.3. Bidirectional slice turnaround	42
15.4. Unspecified Items	42
16. Configuration	42
16.1. Link Training	43
17. Control Register Mapping	43
18. Testability	43
18.1. Test Patterns	43
18.2. Loopback Test	43
19. BoW in an ODSA Design	46
19.1. BoW for Common Transaction Protocols	46
Appendix A - Requirements for IC Approval (to be completed Contributor(s) of this Spec)	48
Appendix B	48

Glossary of Terms

This section provides glossary used in this specification.

Term	Abbreviation	Definition
Bunch of Wires	BoW	The name for the PHY specification defined in this document
Die-to-die	D2D	Generic term used to refer to on-package interconnect
BoW Mode	N/A	A specific defined mode of operation for a BoW interface
picojoules per bit	pJ/bit	Energy required to transport a bit of data over a D2D interface
PHY		The set of circuitry physically communicating bits from one die to another
Core Logic		Digital logic transmitting data to/from the PHY
Control Logic		Logic used to manage the operation of the PHY
Tera/Giga bits per second	Tbps/Gbps	Measures of the speed of data transmission on the PHY
Beachfront		The length of die edge required by a PHY implementation
Clock		A signal that regulates the speed of data transmission
Bump		Solder balls grown on a die to allow connection to off-die wires
Channel		A term for the physical connection between a transmitter and a receiver
Test		The process of verifying functional correctness of a circuit
Initialization		The process of preparing an interface for data transmission

Table 1. Glossary of Terms

Language

This document uses the following terms as defined below.

- “Shall” or “must” indicates a requirement. Failure to meet the requirement results in non-conformance
- “Should” indicates a recommendation, but not a requirement. Failure to implement the recommendation does not result in non-conformance.
- “May” indicates an implementation option.
- The lack of one of the above verbs indicates the material is informative.
- “Reference” indicates a reference design that is provided as example for explanation, but is not a requirement.

1. License Agreement

1.1. Open Web Foundation (OWF) CLA

Contributions to this Specification are made under the terms and conditions set forth in the modified Open Web Foundation Contributor License Agreement (“OWF CLA 1.0”) (“Contribution License”) by:

ANALOG PORT, BLUE CHEETAH ANALOG DESIGN, D-MATRIX, IBM, KEYSIGHT, TESSOLVE, VENTANA MICRO

You can review the signed copies of the applicable Contributor License(s) for this Specification on the OCP website at <http://www.opencompute.org/products/specsanddesign>

Usage of this Specification is governed by the terms and conditions set forth in the modified Open Web Foundation Final Specification Agreement (“OWFa 1.0”) (“Specification License”).

Notes:

1. The above license does not apply to the Appendix or Appendices. The information in the Appendix or Appendices is for reference only and non-normative in nature.

NOTWITHSTANDING THE FOREGOING LICENSES, THIS SPECIFICATION IS PROVIDED BY OCP “AS IS” AND OCP EXPRESSLY DISCLAIMS ANY WARRANTIES (EXPRESS, IMPLIED, OR OTHERWISE), INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR A PARTICULAR PURPOSE, OR TITLE, RELATED TO THE SPECIFICATION. NOTICE IS HEREBY GIVEN, THAT OTHER RIGHTS NOT GRANTED AS SET FORTH ABOVE, INCLUDING WITHOUT LIMITATION, RIGHTS OF THIRD PARTIES WHO DID NOT EXECUTE THE ABOVE LICENSES, MAY BE IMPLICATED BY THE IMPLEMENTATION OF OR COMPLIANCE WITH THIS SPECIFICATION. OCP IS NOT RESPONSIBLE FOR IDENTIFYING RIGHTS FOR WHICH A LICENSE MAY BE REQUIRED IN ORDER TO IMPLEMENT THIS SPECIFICATION. THE ENTIRE RISK AS TO IMPLEMENTING OR OTHERWISE USING THE SPECIFICATION IS ASSUMED BY YOU. IN NO EVENT WILL OCP BE LIABLE TO YOU FOR ANY MONETARY DAMAGES WITH RESPECT TO ANY CLAIMS RELATED TO, OR ARISING OUT OF YOUR USE OF THIS SPECIFICATION, INCLUDING BUT NOT LIMITED TO ANY LIABILITY FOR LOST PROFITS OR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT, SPECIAL OR PUNITIVE DAMAGES OF ANY CHARACTER FROM ANY CAUSES OF ACTION OF ANY KIND WITH RESPECT TO THIS SPECIFICATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), OR OTHERWISE, AND EVEN IF OCP HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

2. OCP Tenets Compliance

The Bunch of Wires (BoW) specification defines a versatile, open and interoperable physical interface between two chiplets or chip-scale-packages (CSP) in a common package, and is fully backwards compatible with the Bunch of Wires specification. This document specifies the BoW interface PHY layer, and defines a set of die-to-die parallel interfaces that implementers / adopters have the flexibility to trade off throughput/chip-edge for design complexity, cost, and packaging technology. The use of BoW is expected to be confined to connect die placed close to one another within the same package. In this environment, signal attenuation is small and the interface can be simple. The definition of the BoWx interface aims to meet the following OCP tenets as follows:

2.1. Openness

- Unencumbered by technology license costs

2.2. Efficiency

- Very low peak power (< 0.5 - 1 pJ/bit for doubly terminated modes, <0.25 - 0.5 pJ/bit for unterminated)
- Energy proportional down to ~10% activity
- Very low latency (<2-4 ns without FEC, <15 ns with FEC from logic interface to logic interface)
- High throughput density (up to 2 - 12+ Tbps/mm-chip-edge)

- Support for key features such as redundancy, sideband signaling, and configurable directionality
- Fully backwards compatible with BoW 1.0

2.3. Scale

- Flexible to support both laminate and advancing packaging technologies
- Portable across multiple bump pitches
- Portable across IC process nodes ranging from 65 nm to 5 nm and beyond

2.4. Impact

The BoW specification provides several key advantages for chiplet-based systems:

- Can be implemented in legacy as well as state-of-the-art technologies (process nodes)
- Can be implemented in any packaging technology while retaining a single logical definition
- Provides design/implementation flexibility while retaining interoperability, allowing chiplet interfaces to be optimized for a given product/application

Compared to SerDes, BoW uses a lower data rate/wire so it requires more wires. However the lower data rates allow use of single-ended signaling and denser wire packing. In addition, in laminates, BoW can take advantage of multiple wiring layers and in advanced packaging it can take advantage of the much-increased wire density.

3. Revision Table

Date	Revision	Author	Description
07/26/22	Draft 1.1a	Elad Alon	Initial updates from 1.0 to 1.1
09/30/22	Draft 1.1b	Marek Hempel, Elad Alon	Half-slice and power management added

4. Scope

The scope of this document has several levels.

1. The specification of the BoW interface includes these requirements:
 - a. Operating modes
 - b. Chip-to-chip wire signals
 - c. Wire ordering
 - d. Timing and electrical specifications on the chip-to-chip interface
 - e. Signals at the logic (Link Layer) interface
 - f. Configuration, initialization, calibration
 - g. Functions that must be supported at the Link Layer or above
2. The specification includes recommendations for these elements:
 - a. Bump patterns

- b. Arrangement of multiple slices in a link
 - c. Arrangement of wires in laminate and advanced packaging
 - d. signal integrity of the wire channel
 - e. Configuration and management programming
 - f. Design for test and test methods
 - g. Performance estimates
 - h. Conformance verification
3. The following activities are outside the scope of this document:
- a. Specific implementations of the interface
 - b. Integration of the interface with system-level data flow
 - c. The use of this interface outside of a package or entirely inside a chip
 - d. Definition of protocols for logical data transfer
4. The following aspects may be addressed in subsequent versions of this specification:
- a. Simultaneous bidirectional data (full duplex on each wire)
 - b. Security

5. BoW Overview

This section provides an overview of the BoW physical interface (PHY) and its use in a multi-chiplet design.

5.1. Key Features and Conformance

The specifications must be met over process variation, supply voltage range and temperature range (PVT). Each implementation must document its supported I/O voltage range, supply voltage range and temperature range.

Table 2 summarize the conformance points that shall be met in order to comply with the BoW specification. Each of the conformance points is discussed in the specification.

5.2. BoW Slice

BoW is an energy-efficient, easy-to-use PHY interface between a pair of die inside a single package as shown in Figure 1. The BoW PHY is defined as a single unidirectional slice. Multiple slices are combined to create links of the desired throughput. A link may be symmetric, asymmetric or unidirectional. The BoW PHYs between two die are physically connected through wires on a substrate or interposer. A BoW PHY does not have enough drive strength for off-package interfaces, nor is it designed for buses that are entirely on die.

This document specifies the protocol for a BoW PHY slice. The aggregation of multiple PHYs into a link is beyond the scope of this document.

A BoW PHY slice either transmits or receives 16 bits of data between die. The BoW is a source-synchronous PHY and each transmitting PHY slice transmits a complementary clock signal CLK+ and CLK- with the data. A BoW PHY optionally has two additional wires designated FEC

Description	Section	Detail
BoW Modes	5.4	
Die-to-die Signals (Wires)	6.2	
Slice Logic Interface	[#sec-slice-logic-interface]	
BoWx Modes and Reach	7	Table 8
Wire and Slice Ordering	8	
Voltages and Termination Resistance	9.1	
PHY Protection	[#sec-phy-protection]	
ESD	9.3	
Return Loss and Parasitic Capacitance	9.4	
Clocking	10.2	
Clock and Data Specs	7.2	
Channel Skew	8.1	
External Facilities	15.1	
Initialization	15.2	
Control Register Mapping	17	

Table 2. BoW Conformance Summary **TO BE UPDATED**




Figure 1. BoW Overview

BoW Mode	Slice Data Rate Gbps	Wire Bit Rate Gbps/wire	TxClock GHz
BoW-32	32	2	1
BoW-64	64	4	2
BoW-128	128	8	4
BoW-256	256	16	8
BoW-384	384	24	12
BoW-512	512	32	16

Table 3. BoW Modes

(for Forward Error Correction) and AUX, for other optional functions such as Data Bus Inversion (DBI).

5.3. BoW Wires

Within the package, the BoW datapath is transported on physical passive wires between the pair of connected die. The specifics of the wires, such as their density, maximum length, impedance characteristics and how they are realized vary with the packaging technology. In order to minimize power, unterminated and source-terminated links will have short reaches requiring chips to be adjacent.

5.4. BoW Modes

A BoW PHY must be operable in one of the BoW Modes listed in ascending order in Table 3. A BoW Mode defines the speed of clock and data of the PHY on the die-to-die wires. In all modes, the data must be clocked DDR: the chip-to-chip data wire bit rate is double the clock wire frequency. All BoW interfaces faster than BoW-64 should also be able to support BoW-64. Supporting rates other than the defined modes is an implementation choice. There is more detail on BoW Modes in section 7.

Figure 2 shows the tradeoff between package, data rate, termination, and reach. Source-terminated BoW on laminate allows a longer reach than advanced packaging, but the wider design rules in laminate means that both of these cases are barely able to reach 8 Gbps/wire. A doubly-terminated link offers longer distances and higher rates, but requires a more complicated receiver design.

5.5. Logic Interface

Figure 3 shows the logic interface between a BoW slice and the digital Link Layer logic in a chip. The speed at the logic interface (Figure 1) is implementation-dependent. Typically, PCLK will be the TxClock frequency divided by a power of 2, so 250, 500 and 1000 MHz are common rates. The data at the logic interface is SDR (bit rate equal to PCLK frequency).




Figure 2. BoW Data Rate vs. Reach tradeoff **TO BE UPDATED**




Figure 3. BoW slice logic interface

Function	# Wires	Signal Name	Notes
Clock	2	CLK+, CLK-	Differential
Data	16	D0-15	
Forward Error Correction	0/1	FEC	Optional
Auxiliary	0/1	AUX	Optional

Table 4. BoW Signals at the Die To Die Interface

6. Signal Definitions

This section specifies the control data signals into and out of device logic and package for BoW RX and TX slices.

6.1. Directionality

- A BoW **link** may be bidirectional (each side contains both RX and TX slices) or unidirectional (each chiplet's side contains only TX or only RX slices)
- Each BoW **PHY slice** is unidirectional when in operation
- A BoW **PHY slice** is said to be bidirectional if it can be configured to operate in TX or in RX
- This spec does not include full-duplex operation (simultaneous TX and RX over the same wires)

6.2. Die-to-die Signals (Wires)

As shown in Figure 1, each BoW slice consists of a differential clock pair, 16 single-ended data wires, and an optional pair of wires FEC and AUX.

FEC (Forward Error Correction) is an optional signal that allows using FEC to improve the bit error rate (BER), or may be used for redundancy for defect repair. By using an additional wire when FEC is enabled, the payload data rate is not affected and the wire data rate is unaffected. This allows $F(PCLK) = F(TxClk) / 2^n$ with FEC off or on, which simplifies the clock generation and serialization functions. If used, FEC is implemented in the Link Layer, and the PHY treats the FEC bit the same as the other data bits.

AUX is an optional signal that may be used for purposes such as Data Bus Inversion (DBI), flow control, redundancy for defect repair, etc.

The Link Layers of Chiplets A and B will need to agree on the details on FEC and AUX usage. An implementation may choose to support the FEC and AUX wires, or to omit both of them. If FEC and AUX are included in a PHY implementation, the PHY carries them in the same way as the data bits without acting on the content.

Table 4 summarizes these signals.

6.2.1. DBI on the AUX wire

Data Bus Inversion (DBI) may be used to mitigate simultaneous switching output (SSO) noise or to optimize energy of a BoW PHY by reducing the number of BoW data wires that switch between adjacent data transfer cycles. DBI functionality is optional; it one of several possible uses of the

Signal	# Bits	TX Slice	RX Slice	Description
PD	16*N	In	Out	Data
PFEC	N or 0	In	Out	Forward Error Correction (optional)
PAUX	N or 0	In	Out	Auxiliary uses (optional)
PCLK	1	Out	Out	
TxClk	1	In	NA	Comes from a PLL or other clock source, not the Link Layer. The TxClk source is usually shared among many TX slices. May be differential
RxClk	1 or 0	NA	Out	May be differential

Table 5. Logic Interface Signals

AUX wire. If implemented, DBI is in the Link Layer and must be implemented on both RX and TX.

6.3. Slice Logic (Link Layer) Interface for a Unidirectional PHY

Figure 3 shows the data and control signals in the interfaces to the logic in the die in each BoW transmit and receive slice. The data at the slice logic interface must be SDR (Single Data Rate - bit rate equal to the PCLK frequency).

6.3.1. Slice Logic Interface: Clock and Data Signals

The signals in Table 6 shall constitute the data and clocks in the logic interface of the PHY. N is the ratio of the chip-to-chip per-wire data rate to the logic interface per-wire data rate.

6.4. Slice Logic (Link Layer) Interface for a Bidirectional PHY

Figure 4 shows the block diagram of a bidirectional slice. A bidirectional slice shall have one set of 18 or 20 signal bumps and wires and two sets of signals connecting to the chiplet's core logic (or Link Layer).

In mission mode, each slice must have only the PHY TX or the PHY RX enabled. For loopback test, both may be enabled. For loopback, it is recommended to enable testing one slice at a time to avoid drawing both RX and TX power of all the slices in the whole link at the same time.

The data at the slice logic interface must be SDR (Single Data Rate - bit rate equal to the TXPCLK/RXPCLK frequency).

6.4.1. Slice Logic Interface: Clock and Data Signals

The signals in Table 6 shall constitute the data and clocks in the logic interface of a bidirectional PHY. N is the ratio of the chip-to-chip per-wire data rate to the logic interface per-wire data rate. End of BIDI section




Figure 4. BoW Bidirectional slice block diagram

Signal	# Bits	Direction	Description
TXD	16*N	In	TX Data
TXFEC	N or 0	In	Forward Error Correction (optional)
TXAUX	N or 0	In	Auxiliary uses (optional)
TXPCLK	1	Out	SDR clock for the TXD, TXFEC, TXAUX bits
TXCLK	1	In	Comes from a PLL or other clock source, not the Link Layer. The TXCLK source is usually shared among many TX slices. May be differential
RXD	16*N	Out	RX Data
RXFEC	N or 0	Out	Forward Error Correction (optional)
RXAUX	N or 0	Out	Auxiliary uses (optional)
RXPCLK	1	Out	SDR clock for the RXD, RXFEC, RXAUX bits
RXCLK	1 or 0	Out	May be differential

Table 6. Bidirectional Logic Interface Signals

6.5. Slice Logic (Link Layer) Interface aspects common to unidirectional and bidirectional PHYs

6.5.1. Slice Logic Interface: Control Signals

A BoW interface slice must provide the control and status signals shown in Table 7.

6.5.1.1. PHYResetB TX and RX The PHYResetB pin shall be asserted by the link controller to initialize the PHY. While the PHYResetB signal is asserted, the PHY shall stay in its reset state. When the PHYResetB signal is de-asserted, the PHY shall perform any necessary self-alignment. The reset states are otherwise implementation-dependent and shall be documented in the datasheet of a particular implementation.

Signal	# Bits	TX Slice	RX Slice	Description
PHYResetB	1	In	In	Resets the BoW slice. 0 causes a reset
PHYReady	1	Out	Out	Indicates that the PHY is ready to transmit/receive mission mode data. 1 indicates ready
PHYIdle	1 or 0	In	N/A	Optional signal Active high indicates to the TX slice that it should enter the clock gated state on the next parallel word aligned clock edge

Table 7. Logic Interface Control Signals

6.5.1.2. PHYReady TX On a TX slice, the PHY shall assert PHYReady to indicate it is transmitting appropriate CLK and PCLK signals, and that it is ready to transmit data.

6.5.1.3. PHYReady RX On an RX slice, when PHYResetB is deasserted, the PHY assumes that the corresponding TX slice is sending CLK and that the TX Link Layer is sending training data on the data wires.

After the RX slice clock self-alignments are complete, each RX PHY slice shall assert its PHYReady pin. How an RX PHY slice determines completion of the self-alignment is implementation-dependent. For instance, it may be determined by observing the settling of the DLL or by a simple timer. PHYReady asserted indicates that any data received will be captured correctly.

Further description of this optional signal and its functionality are provided in Section
TO BE UPDATED.

6.5.1.4. PHYIdle TX

6.5.2. Programming

There shall be an AMBA APB programming interface to control internal registers for control and status readout of the PHY.

The internal registers are implementation-dependent. The internal registers shall be fully documented in the PHY datasheet.

6.5.3. Link Controller

There shall be a Link Controller (LC) outside the PHY. This will manage initialization of the Link. It may reside on one of the chiplets of the link, in a third chiplet in the package or outside the package.

Communication from the Link Controller across chiplets shall be by a transport mechanism outside the BoW link. This could be a serial link like SPI or I2C, but this is not specified at this time.

Link initialization is described in Section 15. Clocks are described in 10.2.

7. BoW Modes and Reach

A BoW PHY slice must conform to at least one of the BoW Modes seen in Table 3. The recommended maximum wire reach for different packaging types and terminations is seen in Table 8. Exceeding these reach values may degrade the voltage margins at the receiver. See section 12 for how TX, RX and channels are qualified.

“Laminate” is intended to include organic laminate packages (a.k.a. “buildup”) and similar technologies with approximately $25\ \mu m$ line and space rules. The minimum wire length for closely spaced chips in these technologies is around 3 mm for the slice closest to the chip edge.

“Advanced” is intended to include silicon interposer and similar technologies. These have much finer line and space dimensions, but traces are usually much more resistive than in organic laminate packages and will be limited to much shorter trace lengths. Due to these short traces, termination is not expected to be useful for implementations targeting Advanced packaging. The minimum wire length in these technologies may be less than 1 mm.

Adding termination increases the speed and/or reach, at the expense of greater design complexity and power.

Package			Laminate	Laminate	Laminate	Advanced
Termination			None	Source	Double	None
BoW Mode	Wire Bit Rate	TxClock	Reach	Reach	Reach	Reach
	(Gbps/wire)	(GHz)	(mm)	(mm)	(mm)	(mm)
BoW-32	2	1	10	20	25+	4
BoW-64	4	2	NA	10	25+	2
BoW-128	8	4	NA	5	25+	2
BoW-256	16	8	NA	NA	25+	2
BoW-384	24	12	NA	NA	25+	2
BoW-512	32	16	NA	NA	25+	2

Table 8. Recommended BoW Wire Reaches

8. BoW Physical Configuration

8.1. Dead-Bug Views

The physical diagrams and descriptions in this document must be interpreted as looking down at the top layer of the unpackaged chiplets. Since these are flip-chip packages, these views are equivalent to looking through the bottom of the package with the balls up (dead bug view). For the view as seen looking down on a package as mounted on a PCB (live bug view), these views must be mirrored.

8.2. BoW Components

A BoW link between two chiplets is made up of wires, slices, and stacks as seen in Figure 5.

- The signal traces in the package between chiplets are called **wires**.
- A **slice** is the basic unit of a BoW PHY. It must have 18 or 20 signal bumps. It must have 2 bumps for the differential clock and 16 single-ended data bumps. It may also have the optional single-ended signals AUX and FEC. The long edge of a slice must be parallel to the chip edge.
- A **stack** is composed of one or more slices stacked from the chip edge towards the center. The slice positions are designated A, B, C, etc, starting with the slice closest to the edge of the chip.
- A **link** from one chiplet to another is composed of one or more stacks placed along the chip edge. A link may be configured with equal numbers of RX and TX slices, or it may be asymmetric or one-way.

8.3. Example Link

The minimal bidirectional reference link is shown in Figure 6.

In this example, each chiplet has one TX slice and one RX slice, arranged in two one-slice stacks on each chiplet. This is a dead-bug view.




Figure 5. BoW Link Components




Figure 6. BoW Minimal Bidirectional Reference Link

8.4. BoW Half-Link Components

For low-bandwidth or constrained die-edge applications a half-link or 8-bit link consisting of 8 data wires per half-slice is defined as shown in Figure 7.

- A **half-slice** is a smaller version of a slice with 10 or 12 signal bumps. It must have 10 or 12 signal bumps. It must have 2 bumps for the differential clock and 8 single-ended data bumps. It may also have the optional single-ended signals AUX and FEC.
- A **half-stack** is composed of one or more half-slices stacked from the chip edge towards the center. It may not contain a mix of half-width and regular-width slices. The slice positions are designated A, B, C, etc, starting with the slice closest to the edge of the chip.
- A **half-link** from one chiplet to another is composed of one or two half-stacks placed along the chip edge. A half-link may not contain more than two half-stacks at which point the use of regular-width slices is recommended. A half-link may be configured with equal numbers of RX and TX slices, or it may be asymmetric or one-way.

8.4.1. Minimal Half-Link

The minimal bidirectional reference half-link is shown in Figure 8 .

In this example, each chiplet has one TX half-slice and one RX half-slice, arranged in two half-slice stacks on each chiplet. This is a dead-bug view.

8.4.2. Half-Link to Regular Link Interoperability

A half-link shall be compatible with a regular-width link by fanning out the signal wires D0-D7, the differential clock pins and optionally AUX and FEC, see Figure 9 . Each half-slice shall be




Figure 7. BoW Half-Link Components




Figure 8. BoW Minimal Bidirectional Reference Half-Link

Function	# Signals	Signal Name	Notes
Clock	2	CLK+, CLK-	Differential
Data	16	D[15:0]	
Forward Error Correction	0/1	FEC	Optional
Auxiliary	0/1	AUX	Optional

Table 9. BoW Die-to-Die Signals

connected to a unique regular-width slice on the other chiplet. Connecting two half-slices on one chiplet to a regular slice on another chiplet is not permitted.

To accommodate this compatibility, the intended configuration (8-bit or 16-bit slices) shall be programmed into the PHY at startup via APB. Unused transmit pins should be open-circuited to save power, and unused receive pins should be disabled or make use of a weak pulldown (as discussed in Section 9.2).

8.5. Die-to-Die Signals

Each BoW slice consists of a differential clock pair, 16 single-ended data wires, and optional wires FEC and AUX. Each BoW slice is unidirectional when in operation. A PHY may be designed as RX-only and TX-only slices, or each slice may have both TX and RX capability, one of which is selected at configuration time. A bidirectional link is composed of some whole number of slices configured for RX and some whole number of slices for TX.

FEC (Forward Error Correction) is an optional signal that allows using error correction to improve the bit error rate (BER). AUX is an optional signal that may be used for purposes such




Figure 9. Reference Example of Half-Link to Regular Link Compatibility

as DBI, flow control, redundancy, etc. Chiplets A and B will need to agree on the details on FEC and AUX usage, which is defined in the Link Layer.

8.6. Signal Ordering

A BoW interface must conform to these wire order rules at the edge of the chip:

- The signals for a TX slice or a bidirectional slice are in the following order at the chip edge, going clockwise around the chiplet in a dead-bug view: AUX, D0, D1, D2, D3, D4, D5, D6, D7, CLK+, CLK-, D8, D9, D10, D11, D12, D13, D14, D15, FEC
- The signals for an RX slice are in the reversed order (ascending goes counter-clockwise)
- The same clockwise/counter-clockwise ordering is used on all four sides of a chiplet
- The AUX and FEC signals may be omitted
- For a half-slice D8, D9, D10, D11, D12, D13, D14, D15 shall be omitted

8.7. Bump Arrangements

Note that bump patterns are not specified by BoW; only the signal *ordering* at the chip edge is specified for interoperability.

The reference example in Figure 6 uses hexagonal closest packing for the bumps: two rows for signal bumps and one row for power and ground bumps. In this pattern, the wire pitch is half the bump pitch.

8.7.1. Alternate Bump Arrangements

Alternate bump arrangements may include:




Figure 10. Cross section of a BoW Link in an Organic Laminate Package

- 90-degree rotation of the hexagonal packing direction (to decrease the wire pitch 14%)
- square bump arrays instead of hexagonal (for regularity of layout)
- more than two rows of signal bumps (to decrease the wire pitch without changing the bump pitch)
- different ordering of power and ground bumps
- multiple power and ground rows

Somewhat different wire pitches between two chiplets may be accommodated with fan-out in the chip-to-chip wires. This is limited by the maximum skew due to different wire lengths - see section 12.1.

8.8. Cross Section

An example cross section for an organic laminate (a.k.a. “buildup”) package is shown in Figure 10.

In an organic laminate package, signal layers should be alternated with ground layers in order to maintain a controlled impedance of 50Ω . Each slice position (A, B, C, D) should be associated with one signal layer and there should be no mixing of signals from multiple slices.

In any technology, the position-A slice on chiplet A must be connected to the position-A slice on chiplet B (one must be configured for TX and one for RX). The position-B slices are connected together, and so on.

There is no specified limit to the number of slices in a stack. In organic laminate, the practical limit in 2020 is an 8-2-8 laminate which supports 4 slices as shown in Figure 10. A 7-2-7 laminate may support 4 slices by omitting the top GND layer, but with reduced signal integrity. Layers on the bottom side of the package typically cannot be used for BoW signals due to low via density passing through the thick central core layer.

In advanced packaging technologies, the shorter wire lengths and higher wire resistance suggests the use of non-controlled-impedance wires and unterminated transmitters and receivers. The smaller wire and space dimensions may allow the wires for multiple slices to be interleaved on a single wiring layer. The wire order within each slice must be maintained, even if interleaving with

other slices is used.

8.9. Staggered Slices

To optimize the density of hexagonal bump arrays, slices in positions B and D may be offset horizontally by one half the bump pitch as seen in Figure 11. This necessitates a one-bump-pitch horizontal jog in the wires for slices B and D. The practical effect of this 130-um jog across a 2.5+ mm wire between chiplets is very small.

An alternative arrangement is to keep the slices aligned vertically. This requires adding a small extra vertical space between the slices, for an overall increase of 4% of the slice area.

8.10. Slice Numbering

A BoW interface composed of unidirectional slices must conform to these slice numbering rules:

- The TX slices in a link are numbered from 0 at the upper left edge of the link (facing from the chip center to the edge in a dead-bug view) and ascending through the TX slices in a stack, then from stack to stack clockwise.
- The RX slices in a link are numbered from 0 at the upper right, through the RX slices in a stack, then stack to stack counterclockwise.

An example of this numbering is shown in Figure 12.

The signal ordering and slice numbering rules allow BoW chiplets to be connected without signal reordering regardless of chiplet rotations.

8.11. Slice Stacking Pattern for Symmetric Links

For bidirectional links, a pattern of alternating TX and RX stacks should be used. Figure 12 shows an example bidirectional link with 4 stacks of 4 slices each, for 8 TX and 8 RX slices on each chiplet. The first TX stack should be at the left edge of the link.

Asymmetric and unidirectional links may use any slice pattern, but the slice numbering rules must be observed.

In BoW-256 at 16 Gbps/wire, the link in Figure 12 provides a total of 2.0 Tb/s in each direction. In an organic substrate using the hexagonal bump pattern of Figure 6 with a bump pitch is 130 um, the total edge width is 5.2 mm (4.16 mm without AUX and FEC); the depth from the edge is 1.35 mm. In an interposer, if the bump pitch is 40 um, the edge width is 1.60 mm (or 1.28 mm) and the depth is 0.42 mm.

8.12. Connecting Bidirectional Slices

A bidirectional BoW PHY slice is designed to operate as RX or TX, to be configured upon powerup. This allows complete flexibility in link configuration and interoperability and also provides an opportunity for wafer-level loopback testing before package assembly (known good die).

In bidirectional slices, the wires and slices must be numbered as if they are all TX slices.

Bidirectional slices are connected from chiplet to chiplet as in Figure 13: AUX to FEC, D0 to D15, D1 to D14... FEC to AUX.




Figure 11. Staggered slices for the densest bump packing




Figure 12. Alternating-Stacks Pattern of TX and RX Slices in a Link

- The Link Layer interface has a complete set of Tx wires and a complete set of Rx wires; only one set is in use for a particular slice
- Configure for A->B or B->A:
- A->B (red): Chiplet A configured for TX, chiplet B for RX
- B->A (green): Chiplet B configured for TX , chiplet A for RX
- This diagram ignores the larger number of wires at the link layer due to the serialization factor




Figure 13. Alternating-Stacks Pattern of TX and RX Slices in a Link

9. BoW PHY Electrical Specifications

In order to ensure interoperability between differing BoW PHY implementations, this chapter provides a set of electrical specifications that all such BoW PHY implementations must meet.

9.1. Voltages and Termination Resistance

All BoW implementations must support signaling based on a 0.75 V “I/O voltage”. BoW PHYs may also support higher or lower signaling voltages, but must support 0.75 V based signaling for interoperability.

Note that the simplest implementation is to provide a 0.75 supply voltage to the BoW VDD bumps, but the supply voltage may be different from the I/O voltage as long as the signal voltages meet the specification.

In doubly terminated modes of operation, the RX termination resistance must be connected to 0V, the I/O voltage, or mid-rail of the I/O voltage (e.g., 375 mV with a 0.75 V I/O voltage). The selection of termination voltage is expected to be static (hardwired) in the RX, and must be specified in the receiver’s datasheet. It is expected that Source-Series-Terminated (SST) Transmitters will be largely agnostic to the choice of termination voltage on the receiver. Note that BoW receivers which support the optional data idle state described in Section 11.1 must terminate to 0V, and must not terminate to the I/O voltage or mid-rail.

Regardless of the value selected for the I/O supply voltage, BoW transmitters and receivers must meet the DC termination resistance requirements defined in Table 10. Note that TX/RX termination (output/input) resistance values are skewed low/high compared to the channel impedance in order to ensure that the DC single-ended voltage swing at the RX is never reduced to less than half of the I/O voltage (i.e., 375 mV for a 0.75 V I/O voltage). Note that these termination resistance values must be met with all combinations of data inputs (logical 1 and logical 0), termination

	Unterminated	Source-Terminated (BoW-256 or lower)	Doubly Terminated (BoW-256 or lower)	Doubly T (BoW-384)
TX DC Term.	As required to meet TX risetime	36 Ω - 50 Ω (0.72 - 1.0 Z_{chan})	36 Ω - 50 Ω (0.72 - 1.0 Z_{chan})	36 Ω - 43 Ω (0.72 - 0.88 Z_{chan})
RX DC Term.	-	-	50 Ω - 69 Ω (1.0 - 1.38 Z_{chan})	59 Ω - 69 Ω (1.18 - 1.38 Z_{chan})
Within-Slice DC Term. Matching	-	$\sigma = 1.333\%$ (8% over 6 σ)	$\sigma = 0.667\%$ (4% over 6 σ)	$\sigma = 0.667\%$ (4% over 6 σ)

Table 10. TX and RX Termination Resistance Requirements vs. Mode

voltage selections (ground terminated, supply terminated, or mid-rail terminated), and termination resistance values. For example, a BoW TX must achieve between 36Ω and 50Ω resistance when driving a load resistance (modeling the RX termination) of $50\text{-}69 \Omega$ with any of the three termination options.

Especially in doubly terminated modes, within-slice variations of termination resistance would directly result in varying swing levels at each pin. Thus, in order to reduce or eliminate the need for per-pin voltage reference adjustment at the RX, Table 10 also specifies requirements on DC termination resistance matching across all I/O's within a given BoW slice. The σ for this variation in the table must be interpreted as capturing within-slice manufacturing variability across worst-case voltage/temperature operating conditions, and is expected to be primarily influenced by some combination of transistor and explicit resistor matching (with the mix depending on the circuit implementation).

9.2. PHY protection

A BoW PHY should not draw excessive current nor be damaged under the following conditions:

- The bumps are open-circuited, e.g., at wafer test, or if not connected in a package assembly.
- In the un-powered state when connected to a BoW PHY which may be powered or un-powered.
- In the reset state when connected to a BoW PHY which may be powered or un-powered.
- In a properly-configured operational state.

Should the above conditions be “musts”?

A BoW PHY implementation must document how long it can withstand without damage an accidental incorrect state with TX configured and enabled on both ends of a wire.

A bidirectional PHY slice shall have the TX circuits disabled (high impedance) upon assertion of PHYResetB and require an APB command to be turn them on.

A unidirectional PHY TX slice need not be disabled at reset.

All RX slices must avoid “crowbar” states where a floating or mid-range input voltage can cause a large DC current to flow in the RX circuit. Therefore a PHY must either:

- Turn off the RX circuits upon assertion of PHYResetB and require an APB command to be turn them on, or

	BoW-32 or BoW-64	BoW-128	BoW-256	BoW-384 or BoW-512 Source Term.	BoW
Maximum Equivalent Capacitance (TX or RX)	800 fF	400 fF	200 fF	200 fF	

Table 11. Maximum Parasitic Capacitance at a BoW I/O vs. Mode

- Include pulldown resistors on all bumps, including CLK+ and CLK- and ensure that all the RX circuits be in a low current state including the CLK RX circuit with both CLK+ and CLK- low.

9.3. ESD

BoW I/O shall be designed to withstand **50 V CDM** (Charged Device Model) and **250 V HBM** (Human Body Model) at the bumps. This requirement is deemed sufficient for intra-package signaling, similar to other die-to-die interface standards.

Note that for CDM, the ESD current corresponding to 50 V depends on the package size. (E.g., 50 V CDM on a 65 x 65 mm package is 1.3 A.) A BoW PHY shall document the package size assumed for CDM.

9.4. Return Loss and Parasitic Capacitance

Since BoW PHYs are targeted for relatively dense and simple realizations, it is expected that the primary frequency-dependent parasitics seen at a PHY's I/Os will be capacitive in nature. Table 11 provides limits on the maximum “equivalent” capacitance allowed on each side of each BoW I/O pin. (E.g., a BoW-128 TX is allowed to have up to 500 fF of equivalent capacitance.) Note that while the maximum capacitance specification does increase at lower data-rates, it is recommended that BoW PHY implementations retain as low of a capacitance as practical in order to reduce power consumption and improve signal integrity.

Since the actual frequency-dependent impedance profile of any given implementation may be comprised of a complex electrical network, conformance with the “equivalent” capacitance metric is formally defined by requiring that the magnitude of the return loss of any BoW I/O must be lower than the maximum limits shown in Figures 14 and 15 below. (Note that the return loss requirements are different for TX and RX because of the differences in DC termination between the two sides.) Similarly to DC termination resistance, the maximum s_{11} magnitude in the figure must be met with all combinations of data inputs (logical 1 and logical 0), termination voltage selections (ground terminated, supply terminated, or mid-rail terminated), and termination resistance values.

9.5. Receiver Bandwidth

While this specification does not place a direct requirement on the bandwidth of a BoW receiver implementation, such receivers should maintain an effective 3 dB bandwidth of at least (**0.667/T_{bit}**) Hz. For example, for a BoW-256 PHY, the receiver 3 dB bandwidth is recommended to be at least 10.667 GHz.




Figure 14. BoW TX Termination Maximum Return Loss (TO BE UPDATED)




Figure 15. BoW RX Termination Maximum Return Loss (TO BE UPDATED)




Figure 16. BoW Clock and Data Block Diagram - One TX Slice, One RX Slice

10. BoW PHY Timing Specifications

10.1. Bit Ordering

The PHY TX serializer shall order data this way (referring to Figure 16):

- On the first CLK edge (CLK+ rising) bits P_D[0:15] are sent on wires D[0:15]
- On the second CLK edge (CLK+ falling) bits P_D[16:31] are sent on wires D[0:15]
- and so on to bits P_D[M*16-16:M*16-1].
- Then the cycle repeats.

The RX PHY shall order bits in the same fashion. However, the bits at the RX PHY logic interface P_D[*] may be offset by a multiple of 16 bits from the TX order if the TX and RX PCLK dividers are not aligned. A PHY implementation may provide a way to align the TX and RX dividers, or it may rely on the Link Layer to rotate the RX P_D[*] bits to provide that alignment as part of the training of the Link Layer.

10.2. Clocking

Figure 16 shows the clock and data flow for a single TX slice and a single RX slice. On the TX side, data bits (and optional FEC and AUX bits) come in a wide word from the Link Layer, and are serialized to the line rate. At the RX side, they are sampled with a common slicer clock in most BoW implementations. BoW PHYs may optionally implement per-bit delay adjust or per-bit slicer clock adjust.

BoW PHYs shall be DDR (Double Data Rate) at the chip-to-chip interface: the data bit rate is twice the clock frequency, so data is clocked in on both edges of the clock in the RX slice. BoW PHYs shall be SDR (Single Data Rate) at the logic interface.

Mode	Data Rate (Gbps)	PCLK (MHz)	Mux Ratio M	Logic Data Width
BoW-32	2	250	8	8x18
		500	4	4x18
		1000	2	2x18
BoW-64	4	250	16	16x18
		500	8	8x18
		1000	4	4x18
		2000	2	2x18
BoW-128	8	500	16	16x18
		1000	8	8x18
		2000	4	4x18
BoW-256	16	500	32	32x18
		1000	16	16x18
		2000	8	8x18
BoW-384	24	750	32	32x18
		1500	16	16x18
BoW-512	32	1000	32	32x18
		2000	16	16x18

Table 12. Recommended PCLK and Logic Data Rates for Figure 16

Table 12 provides recommended clock and data rates for each BoW mode. The ratio M should be limited to integers, preferably powers of two, and any other ratios should be implemented outside the PHY.

Note that higher PCLK rates (and lower M ratios) help reduce gate count and Link Layer latency, but lower rates are often more power efficient. The best PCLK rate(s) to implement for a particular chiplet will tend to be a function of its process node. For implementations in process nodes at 16 nm and below, supporting 1000 MHz is recommended.

Table 13 provides clock and data rates for an example with 4 Gbps wire data rate and M=4 to support a 1 Gbps data rate at the Link-PHY interface.

The DDR clock TxClk is provided to the TX PHY from elsewhere on Chiplet-A. This may come for example from an on-chip PLL (typically shared across multiple slices) or routed from the RxClk

Signal	Rate	SDR/DDR
TxClk	2 GHz	
CLK+,CLK-, D[15:0],AUX,FEC	2 GHz 4 Gbps	DDR
PCLK P_D[63:0],P_AUX[3:0],P_FEC[3:0]	1 GHz 1 Gbps	SDR

Table 13. Example Clock and Data Rates for Figure 16 with 4 Gbps, M=4

of an RX slice on Chiplet-A. In order to meet duty cycle requirements, a Duty Cycle Corrector (DCC) may be needed in the TX slice. TxClk is used to drive the serializers and provide the output CLK+, CLK- to Chiplet-B.

On the RX side, the PHY must align the slicer clock to sample the data correctly. This may be done with a DLL, adjustable delays, or other methods. If the PHY includes control logic to self-align the slicer clock for correct sampling of the data, the PHYReady signal must be asserted after the logic has determined that such alignment is complete. The RX PHY may output the received CLK as RxClk to the logic interface.

All BoW interfaces shall be source synchronous at the die-to-die interface within a slice. No modes of BoW require per-wire or per-slicer delay adjustments, but such capability may be optionally included.

Clock skew between the slices in each direction of a link likely depends on the implementation of the TxClk distribution to all the TX slices. That is, for the data flow from Chiplet A to Chiplet B, the TxClk distribution on Chiplet A probably dominates the the clock skew of the TX slices on Chiplet A and the clock skew of the RX slices on Chiplet B, and vice versa for flow from B to A. The skew between TX CLK signals within one direction of a link should be no more than 150 ps/stack along the chip edge. There is no specification of the skew between TxClk on Chiplet A vs. TxClk on Chiplet B nor between different links.

Note that the dividers creating PCLK in each PHY slice are not required to be aligned. This implies that they will tend to have random starting states, leading to additional PCLK misalignment between slices of up to one PCLK period. PHY implementations may optionally include methods to align these dividers.

On both the TX and RX sides, the Link Layer will usually need to include a Clock Domain Crossing (CDC) to align the data between CoreClk and PCLK. The Link Layer must be able to absorb the slice-to-slice clock skew and core clock distribution skew across a whole BoW link. Word alignment across a link need not be supported by the PHY; if required, it should be done in the Link Layer.

10.3. Clock and Data Specifications

In order to not introduce excess pessimism into the link budgets implied by the BoW specification and avoid unnecessary over-design of BoW PHY circuitry, note that both the TX and RX voltage and timing error component requirements account for deterministic (bounded) terms separately from random (unbounded) terms. However, in order to retain some degree of design flexibility on each of the TX and RX, a bound is always placed on the maximum deterministic error and on the maximum total error budget at the target error rate of 1e-15. Thus, if a given BoW PHY design achieves deterministic error performance better than that requirement set by the deterministic component, the random errors introduced by that design may be increased as long as the total error requirement at 1e-15 probability is still met.

Note that the error rate of 1e-15 is at the level of any individual wire within a slice. In other words, in a conformant BoW interface, no individual wire within the interface would have an error-rate exceeding 1e-15.

10.3.1. Transmitter Maximum Rise-Time

The maximum 20% - 80% rise-time at the output of BoW TX shall not exceed **23% of a UI**. For example, for a BoW-128 transmitter, the 20% - 80% rise-time shall not exceed 28.75 ps. This

rise-time shall be simulated with the TX (including all of its parasitics) driving an ideal load of 50 Ω (Z_{chan}).

10.3.2. Transmitter Differential Clock Timing Mismatch

The maximum timing mismatch between CLK+ and CLK- outputs at the TX shall not exceed **2.5% of a UI**. For example, for a BoW-128 TX, the timing mismatch shall not exceed 3.125 ps.

10.3.3. Transmitter Correlated Jitter Filtering

For timing-error specifications provided in the following sections that are impacted by transmitter jitter, this jitter must be evaluated for CLK edges that are up to N_{clk-d} UI earlier than the CLK edge that launched the data bit being captured at the receiver. This is due to the fact that even though jitter on the data edges may be correlated with the CLK jitter, the slicer in the RX side is likely to use a different CLK edge due to delays in the RX-side clock alignment circuit (usually a DLL and clock distribution). See Section 10.3.7 for the receiver's requirements. For **BoW-256 mode and lower rates**, $N_{clk-d} = 3$ UI. For **BoW-384 mode and higher rates**, $N_{clk-d} = 6$ UI.

In order to properly account for the jitter filtering/peaking that will occur due to the difference in delay between the data launching edge at the TX and the data capturing edge at the RX, when evaluating the transmitter's jitter (and whether it meets the requirements described in this document), the jitter at the TX output that is **correlated** between the CLK and D lines shall be filtered by the following frequency-dependent transfer function:

$$H_{tx_jit}(j\omega) = 1 - e^{(-j\omega t_{clk-d})}$$

where t_{clk-d} is the delay between the CLK edge that launched the data bit and the CLK edge used to capture it. Note that jitter that is not correlated between the CLK and D signals shall **not** be filtered by this transfer function. (I.e., if the CLK signal and a given D signal have completely independent sources of jitter added to them such as non-shared portions of the clock distribution network, those jitter sources shall not be filtered by $H_{tx_jit}(j\omega)$). Since the total TX jitter after filtering by this transfer function might not be monotonic with t_{clk-d} , and since receiver implementations may realize varying values of t_{clk-d} , a transmitter must meet all related specifications for $t_{clk-d} = N_d * T_{bit}$, with N_d taking all integer values between 1 and $N_{clk-d} + 1$.

10.3.4. Transmitter Deterministic Timing Error

The total deterministic (bounded) timing errors introduced by the TX shall not exceed **14% of a UI peak-to-peak**. The evaluation of these timing errors must include all possible deterministic contributors, such as reference clock, clock distribution networks, duty cycle error (i.e., deviation from 50% duty cycle), skew between CLK and any D line, and power supply variation induced jitter or skew. Note that any such time-dependent error terms (i.e., jitter) that are correlated between the CLK and D lines must be filtered as described in Section 10.3.3.

This specification is a peak-to-peak requirement, so if a given design has e.g. +/-5% UI of duty cycle error, this would imply that it can achieve a TX deterministic timing error of no better than 10% UI.

10.3.5. Transmitter Total Timing Error

The total timing error introduced between the CLK and any data (D) line at the output of the TX shall not exceed **25% of a UI peak-to-peak at an error rate of 1e-15**. The evaluation of errors must encompass all possible deterministic as well as random timing error contributors, including all sources of random jitter in addition to the representative deterministic error sources described in Section 10.3.4.

Assuming a Gaussian distribution for the random jitter, then in order to account for the 1e-15 error rate and peak-to-peak requirement, the total timing error $t_{err,tot}$ may be computed as:

$$t_{err,tot} = t_{err,deterministic} + 15.9 \sigma_{tj,random}$$

10.3.6. CLK Receiver Sensitivity to Common-Mode Variations

The differential receiver for the CLK signal within a BoW receiver must achieve an input-referred common-mode to differential conversion gain of less than **0.2 V / V**. This requirement must be met across any common-mode input frequency less than or equal to $1/T_{bit}$. For example, with a conformant BoW RX, 20mV of common-mode variation on the CLK+/CLK- lines must impact the effective differential input by less than 4mV.

Note that common-mode variations on the CLK+/CLK- lines of ~10-15% of the signal swing may be expected on typical in BoW channels.

10.3.7. Receiver Clock versus Data Path Delay

In order to be compatible with the TX jitter requirements provided in Section 10.3.3, for BoW-256 and low rate modes, a BoW receiver must capture data using clock edges that were launched by the TX no more than **3UI** earlier than the data being captured. For BoW-384 or BoW-512 receivers, data must be captured using clock edges that were launched by the TX no more than **6UI** earlier than the data being captured.

10.3.8. Receiver Sensitivity and Timing Margin

A BoW receiver must meet a set of requirements on the following sets of timing and voltage error components:

- **Maximum RX Deterministic Voltage Error:** This term ($V_{err,det,RX}$) must include all deterministic voltage errors that would shift the receiver's voltage threshold relative to its ideal position in the middle of the signal swing. For example, any deterministic voltage errors due to residual offset, reference level error, and supply noise must be included. This specification accounts for the double-sided loss in margin, so if a given design has e.g. a residual threshold error of 0mV to +10mV, this would imply that the design can achieve a $V_{err,det,RX}$ of no better than 20 mV.
- **Maximum Total Required RX Voltage Margin:** This term must include all possible voltage errors at the RX at a probability of 1e-15 or higher. In addition to the deterministic RX voltage error sources mentioned above, error sources such as receiver thermal/flicker noise must therefore be included in this term. For Gaussian random voltage noise, the total required voltage margin ($V_{err,tot,RX}$) may be computed as:

$$V_{err,tot,RX} = V_{err,det,RX} + 15.9 \sigma_{Verr,random,RX}$$

	BoW-256	BoW-128	BoW-128	BoW-64 or BoW-32
	Any Termination	Doubly Terminated	Source- or Unterminated	Doubly Terminated
$V_{err,det,RX}$	40 mV	40 mV	100 mV	65 mV
$V_{err,tot,RX}$	75 mV	75 mV	150 mV	100 mV
$t_{err,det,RX}$	32% T_{bit}	32% T_{bit}	32% T_{bit}	28% T_{bit}
$t_{err,tot,RX}$	40.5% T_{bit}	40.5% T_{bit}	40.5% T_{bit}	36.5% T_{bit}

Table 14. Receiver Voltage and Timing Requirements for BoW-256 and Below

	BoW-512 or BoW-384
	Any Termination
$V_{err,det,RX}$	40 mV
$V_{err,tot,RX}$	75 mV
$t_{err,det,RX}$	25% T_{bit}
$t_{err,tot,RX}$	33.5% T_{bit}

Table 15. Receiver Voltage and Timing Requirements for BoW-384 and Above

- **Maximum RX Deterministic Timing Error:** This term ($t_{err,det,RX}$) must include all deterministic timing errors that would shift the receiver's sampling timing relative to its ideal position for any data line. This term must therefore include errors due to e.g. residual sample timing position error, DLL dither, and power supply induced jitter. This specification accounts for the double-sided loss in margin, so if a given design has a mismatch-induced shift of the sampling position (relative to the ideal) of 0% to 5%, this would imply that the design can achieve a $t_{err,det,RX}$ of no better than 10% UI.
- **Maximum Total RX Timing Error:** This term must include all possible timing errors at the RX at a probability of 1e-15 or higher. In addition to the deterministic RX timing error sources mention above, error sources such as RX clock receiver or clock distribution random jitter must be included in the total timing error. For Gaussian random jitter, the maximum total required timing error ($t_{err,tot,RX}$) may be computed as:

$$t_{err,tot,RX} = t_{err,det,RX} + 15.9 \sigma_{terr,random,RX}$$

Since swing and signal integrity are expected to vary with termination as well as data-rate, the RX voltage and timing requirements are termination- and rate-dependent, as outlined in Table 14 and Table 15

10.3.9. Voltage Overshoot

This specification does not place a specific requirement on the overshoot observed by the RX, but it is expected that the overshoot should have magnitude of less than 300 mV for 750 mV I/O supply. Since overshoot is most likely to create potential reliability and other issues in unterminated operating modes, BoW RX's are allowed to turn on termination resistors to reduce the overshoot they observe. The value of the RX termination resistance in this case must be larger than 50 Ω, but is otherwise unconstrained as long as the receiver is able to meet its timing margin requirements with the resulting swing/channel.

BoW TX's therefore shall be designed to achieve their lifetime, reliability, and other requirements regardless of whether the BoW RX selects to operate with or without termination.

10.3.10. Slice-to-Clice CLK Skew

The slice to slice clock skew t_{skew} across the width of a BoW transmit link (along the chip edge) **must** be less than 150 ps/stack. (E.g., for a 4-stack interface, the skew from end to end must be less than 600 ps.) This skew includes only analog delays and specifically does not include any clock-related timing skew due to flip-flops/latches or varying reset states.

The slice to slice clock skew within a stack (orthogonal to the chip edge) for slices that are used within the same link must be less than **50ps/slice**.

This skew is expected to be dominated by the TxClk distribution network.

11. Power Management

BoW PHYs may optionally implement the features/states described in this section in order to reduce average power consumption.

11.1. Data Idle State

The data idle state is defined by having the link layer set the value of all parallel data lines (including the optional AUX and FEC signals) fed into the PHY to logical 0 (0V at the output of the TX). In doubly terminated modes, a BoW PHY supporting this feature must connect the receiver's termination to 0V (ground). I.e., the selection of termination voltage is more restricted than as described in Section 9.

For the remainder of this section, a UI where all of the data lines are at logic 0 (0V) will be referred to as an "IDLE". Note that real data with values of all 0's can still be transmitted/received by BoW PHY's supporting this feature.

11.2. Clock Gated State

While in the clock gated state, a BoW PHY TX ceases toggling the forwarded differential clocks CLK+/CLK-. In order to ensure proper operation of the PHY upon entry and exit from the clock gated state, a preamble and a postamble are appended to the payload data; these and further detailed requirements for entry, exit, and occupancy in this state are defined in the subsections below.

11.2.1. Signal Levels During Clock Gated State

During the clock gated state, a BoW PHY TX must drive differential low on the CLK+/CLK-signals. Similarly, while the PHY is in the clock gated state, the data signals must be IDLE (i.e., set to the data idle state).

Note that the use of static clock gated and data idle levels might result in aging of the TX/RX circuits within the PHY. PHY implementations may hence need to budget for the impact of this aging and/or include mechanisms to compensate for the errors introduced by such aging.




Figure 17. PHY_Idle timing for entry/exit from clock gated state with $M_{ser} = 4$ and $N_{par}=1$

11.2.2. Minimum Preamble, Postamble, and Payload Durations

In order to avoid the need to adjust the time alignment of parallel data words at the input/output of the PHYs due to entry/exit from the clock gated states, all durations of preamble, postamble, and payload must be set such that they are an integer multiple of the largest (between TX and RX) number of UI contained within a parallel input/output. For example, if a BoW TX with 4:1 serialization is communicating with a BoW RX using 8:1 deserialization, the preamble, postamble, and payload must all have durations of $N_{par} * 8$ UI, where N is an integer greater than 1.

Since arbitrary serialization/deserialization ratios could result in very large minimum UI durations (due to the need to find the lowest common multiple), PHYs that support the clock gating mode must use only powers of 2 for the “Mux Ratio M” from Table 12.

BoW PHYs must publish as part of their datasheet the preamble, postamble, and payload lengths they support. It is strongly recommended that BoW interfaces support a configurable set of preamble, postamble, and payload length - particularly 4, 8, 16, and 32 UI.

11.2.3. PHY_Idle Timing and Parallel Data During Preamble / Postamble

As shown in Fig. 17, the PHY_Idle signal must be asserted (set to logic high) one TX parallel clock cycle earlier than the forwarded clocks enter the gated state. Similarly, the PHY_Idle signal must be deasserted (set to logic low) one TX parallel clock cycle earlier than the forwarded clock restarts.

The data driven into the PHY must be IDLE for all TX parallel clock cycles contained within the preamble, the postamble, or the clock gated states. Note that as shown in Fig. 18, if the pre or postamble lengths extend beyond a single TX parallel clock cycle, the pre/postamble duration must be extended by the link layer by padding the payload with additional IDLE data.

11.2.4. Maximum Duration of Occupancy Within Clock Gated State

To mitigate potential issues with drifts in various circuitry and/or control loops that depend on the clocks actively toggling (e.g., the receiver’s DLL), BoW interfaces must not leave the forwarded clock gated for more than 1024 UI or 128 largest (between TX and RX) parallel words, whichever is smaller.




Figure 18. PHY_Idle timing with $M_{ser,TX} = 4$ and postamble $N_{par}=2$

12. Chip-to-Chip Channel Specifications

BoW does not place any direct requirements on characteristics such as channel loss or crosstalk. Instead, BoW channels are considered conforming if they are able to achieve the required error rate of 1e-15 in conjunction with reference transmitters and receivers that meet all of the requirements provided in Section 9 and Section 10.3.

To assist with evaluating conformance of a given channel, open-source software evaluating signal integrity and the overall link budgets with the reference transmitters and receivers will be provided at a future date.

12.1. Channel-Induced CLK Edge to D Transition Skew at RX

Within each slice, a BoW channel should not introduce more than **2% UI** of skew between any D lines and the CLK lines. For BoW-256, this corresponds to $\sim 187.5 \mu\text{m}$ of length mismatch on a substrate with an ϵ_r of 4.

Note that the skew recommendation above is based on achieving sufficient timing margin on representative channels; channels with better signal integrity may allow for larger skew between the D and CLK lines as they meet the overall timing margin requirements.

Note further that if the BoW PHYs used on a given channel include per-bit delay adjustment, channels with larger skew can be supported. Note however that all of the timing requirements described in Section 10.3 must then be met with the residual skew and its variation over time taken into account.

12.2. Channel Impedance

In laminate packages, the channel characteristic impedance should be between 45 and 55 Ω .

12.3. Example BoW Channel for Doubly-Terminated Links

To provide guidance on the types of channels that are expected to meet the requirements for conformance with the BoW reference receiver and transmitter, this section provides examples of typical loss and crosstalk profiles for doubly-terminated channels supporting 16 Gbps operation




Figure 19. BoW Doubly-Terminated Wire Channel Loss Limit

(which are most sensitive to channel signal integrity). Note that when operating at lower rates, the frequency axes in the figures below should be scaled with the data-rate relative to 16 Gbps.

12.3.1. Channel Loss

To avoid the need for equalization, a BoW-256 channel should typically have lower loss than shown in Figure 19.

12.3.2. Crosstalk

The total crosstalk observed on an individual signal within a BoW-256 channel should typically be less than ~35% of the signal swing.

13. Redundancy

14. Sideband Slices

15. Reset and Initialization

TO BE UPDATED

Sideband slices must function immediately out of reset with no training or calibration. Data slices use the remainder of the text below.

15.1. External Facilities

These facilities must be provided outside the PHY:

- A Link Controller (LC) which will manage initialization of the Link. It may reside on one of the chiplets of the Link, in a third chiplet in the package or outside the package.




Figure 20. Example BoW System Configuration

- A communication path from the Link Controller to the PHY slices outside the BoW link. This could be a serial link like SPI or I2C, but this is not specified at this time.
- A source of training pattern data outside the PHY, assumed to be the Link Layer here. This must be able to repetitively transmit an arbitrary 16 bit per wire pattern (256 or 288 bits pattern depending on inclusion of FEC+AUX) required by the RX slice for clock alignment as specified in the datasheet for the RX PHY.
- The PHYResetB input to each PHY shall be asserted upon powerup. It may also be asserted by commands from the LC.

An example topology is shown in Figure 20. The BoW interface communicates to interface and core logic (I&C) blocks.

[Replace this with a figure with the LC embedded rather than external.](#)

15.2. Initialization Sequence

15.2.1. A TX-RX Link should be brought up as follows:

1. The Link Controller (LC) asserts PHYResetB to the PHY slices on both ends of the link.
2. The Link Controller (LC) **de-asserts PHYResetB to the TX PHY** slices including bidirectional slices which will be used as TX slices
3. The LC performs any needed configuration of the TX PHY slices via the APB interface. This is implementation dependent.
4. The LC enables the TX slices if necessary (see section 9.2)
5. Once its outgoing CLK and PCLK stabilize, each TX PHY slice asserts PHYReady to the LC
6. When all TX PHY slices are ready, the LC signals the TX Link Layer to send the training pattern (repeating) specified by the RX PHY
7. The Link Controller (LC) **de-asserts PHYResetB to the RX PHY** slices including bidi-

- rectional slices which will be used as RX slices
8. The LC performs any needed configuration of the RX PHY slices via the APB interface. This is implementation dependent.
 9. The LC enables the RX slices if necessary (see section [9.2](#))
 10. Each RX PHY slice performs clock and data alignment and signals PHYReady to the LC when done
 11. When all RX PHY slices are ready, the LC signals the TX and RX Link Layers to proceed with channel bonding

Note that BoW PHY implementations that do not adopt the order recommended above are not be guaranteed to interoperate with other BoW PHY implementations.

Implementation dependent:

- Whether the up and down links are initialized one at a time or in parallel
- How the signals from the the LC get to and from the PHYResetB and PHYReady pins of the PHY
- How the Link Layer performs channel bonding or start of data transmission
- Any PHY registers required to implement this process

15.3. Bidirectional slice turnaround

To reverse direction on a link with bidirectional slices on both ends, perform a full reset, reconfiguration and initialization. This will likely take 10-500 us, probably limited by DLL settling time.

15.4. Unspecified Items

- Whether the APB registers are separate for each slice or shared among slices in a link
- There is no low-power standby mode defined.
- There is no specification for when a PHY should de-assert its PHYReady pin. PLL or DLL losing lock are possible causes.
- There is no definition of what occurs if the PHY does de-assert PHYReady
- There is no definition of what should be done with unused PHYs (that are on the chip but have no partner on another chiplet)
- There is no definition of logical addressing of chiplets, Links or slices
- Possible use of PRBS patterns for training
- Fast turnaround of bidirectional slices.

16. Configuration

PHY configuration is implementation dependent. It may include:

- TX vs RX for configurable slices
- PLL, DLL, DCC or similar circuit configuration

PHY configuration may be hardwired in the chiplet implementation, or it may be programmable.




Figure 21. Stress Test Pattern

16.1. Link Training

Link training will be addressed in a future revision of the specification.

17. Control Register Mapping

The interface control registers are implementation dependent. The registers shall be fully documented in the PHY datasheet.

18. Testability

18.1. Test Patterns

In order to support die-to-die (in package) testing, within a BoW implementation, either the link layer, the PHY, or both must be able to support the generation (on the TX side) or checking (on the RX side) of repeating data patterns.

Users of BoW systems should check that one or more of the test patterns supported on the TX is also supported on the RX. Such pattern generators / checkers should therefore support the following patterns:

- PRBS-9 Pattern, defined by polynomial of $X^9 + X^5 + 1$
- PRBS-31 Pattern, defined by polynomial of $X^{31} + X^{28} + 1$
- Isolated 1 and 0 pattern to test DC wander and single bit response:
 - [‘0’] X 10 + ‘1’ + [‘0’] X 10 + [‘1’] X 10 + ‘0’ + [‘1’] X 10 + [‘0’] X 10
 - This may be prepended to a PRBS pattern as seen in Figure 21

18.2. Loopback Test

A BoW interface may implement loopback testing for several use cases: at chiplet wafer-sort test, post-assembly package test, and debug/validation.

Wafer sort tests are currently only practical for the BoW interface with regular bump pitches ($\sim 130 \mu\text{m}$), where ATE (automatic testing equipment) probe boards with matching pin pitches are available. Microbump probes will require additional effort.

Unidirectional links should support open-loop testing. In TX open loop testing, shown in Figure 22, Chiplet-A transmits a known test pattern (PRBS9 or PRBS31) to a golden reference




Figure 22. Open loop TX wafer test




Figure 23. Open loop RX wafer test

receiver through the ATE load board. The received pattern should be verified in the ATE load board.

RX open loop testing, shown in Figure 23, is used for a link where the DUT is only a receiver. A golden reference TX transmits a known pattern (PRBS9 or PRBS31) through the channel to the chiplet. The received pattern should be analyzed for quality and functional tests.

The logic for generating and testing the PRBS sequences is outside the PHY, e.g., in the Link Layer.

In bidirectional links, loopback tests may be implemented in several modes:

- Slice-to-slice short loopback
 - Data is looped back within the chip from a TX slice to an RX slice using on-chip switching (shown in Figure 24). The short loopback path is configured by the ATE using implementation-dependent registers.
 - Loopback may be implemented before the PHY serializer, between the serializer and the output buffer, and/or at the bumps.
- Intra-slice short loopback
 - A single slice containing both RX and TX paths sharing the same bumps may perform




Figure 24. Short loopback testing




Figure 25. Long loopback testing

on-chip loopback testing simply by turning on both the RX and TX paths at once. This has more on-chip circuitry, but allows loopback testing with no switches or extra lines connected to the bumps other than the TX driver tristate switches. Figure 24 applies, except there is only one shared set of bumps for a TX/RX slice.

- Long loopback
 - The PRBS pattern is generated by chiplet-A, sent over the replica channel on the ATE load board which loops it back (shown in Figure 25). The received pattern should be passed to a bit error rate tester (BERT) to analyze the performance of the link with off-chip data and clock wires.

Both loopback modes may potentially be used for in-field validation bring-up and test. Cooperation across chiplets will be required to execute these tests in the field. Open-loop testing requires the use of a fixed test pattern recognized by both ends and is the only option for unidirectional links. Long loopback mode can be implemented on interposer or organic laminate for validation/verification purposes.




Figure 26. Chiplet-to-chiplet long loopback

Figure 26 shows how a long loopback mode is executed across two chiplets for in-field validation and test where TX and RX are in different chiplets. Furthermore, this configuration may be expanded to loop back the data from the transmitter of chiplet-A to the receiver of chiplet-A.

19. BoW in an ODSA Design

Chiplet-based designs require logical connectivity between the die in a single package, in addition to physical connectivity. This section provides an overview of how the Open Domain-Specific Architecture stack may be used as an underlay for popular transaction protocols.

19.1. BoW for Common Transaction Protocols

Two connected die in a multi-chiplet device need to exchange logical information. The ODSA aims to define an open physical and logical interface for chiplets, as shown in Figure 27 to enable chiplets from multiple vendors to interoperate and be integrated in a multi-die package. The Bunch of Wires is an open D2D PHY option in the interface. The logical component of the ODSA interface aims to support protocols used for the two most common chiplet use cases, package aggregation and die disaggregation across a wide range of open and proprietary D2D PHYs such as PCIe, CXL, CCIX, AXI and proprietary streaming protocols.

The ODSA stack abstracts the PHY layer from the logical interface by using the well-defined abstraction interfaces PIPE and LPIF. Any logic transaction controller, such as a PCIe controller, that supports a PIPE or LPIF interface may use any D2D PHY that also supports that interface as its physical layer. As shown in Figure 27, the BoW interface may receive data through either the PIPE or LPIF interfaces to support common transaction protocols. For this use case, some BoW-specific adapter logic will be needed to support the requirements of PIPE or LPIF. The specifications for these adapters are outside the scope of this document. Figure 28 shows how the BoW with an PIPE adapter may be interfaced to a PCIe controller.




Figure 27. The BoW PHY in the ODSA Stack




Figure 28. BoW with a PIPE adapter for PCIe transactions

Appendix A - Requirements for IC Approval (to be completed Contributor(s) of this Spec)

List all the requirements in one summary table with links from the sections.

Requirements	Details
Contribution License Agreement	OWF CLA 1.0 (modified)
Are All Contributors listed in Sec 1: License?	Yes
Did All the Contributors sign the appropriate license for this spec? Final Spec Agreement/HW License?	Yes
Which 3 of the 4 OCP Tenets are supported by this Spec?	All four
Is there a Supplier(s) that is building a product based on this Spec? (Supplier must be an OCP Solution Provider)	
Will Supplier(s) have the product available for GENERAL AVAILABILITY within 120 days?	Seeking exception to have extended period for silicon availability. Test chips expected in 2H'2022 by multiple

Appendix B

Created with [Madoko.net](#).