Summary - AD9361 ADC

Name	ad9361_adc
Worker Type	Device
Version	v1.4
Release Date	October 2018
Component Library	ocpi.assets.devices
Workers	ad9361_adc.hdl
Tested Platforms	• Agilent Zedboard/Analog Devices FMCOMMS2 (Vivado only) • Agilent Zedboard/Analog Devices FMCOMMS3 (Vivado only) • x86/Xilinx ML605/Analog Devices FMCOMMS2 • x86/Xilinx ML605/Analog Devices FMCOMMS3 • Ettus E310 (Vivado only, application for testing exists in e310 project)

Functionality

The AD9361 ADC device worker outputs a single RX channel's data from the AD9361 IC[1] via an iqstream output port. Up to two instances of this worker can be used to provide each AD9361 RX channel data stream in an independent, non-phase-coherent fashion.

Worker Implementation Details

ad9361_adc.hdl

The ad9361_adc_sub.hdl subdevice worker supports the ad9361_adc.hdl device worker. The ad9361_adc_sub.hdl subdevice sends a data bus containing 24-bit parallel I/Q data in the AD9361's DATA_CLK_P pin clock domain via the `dev_adc` dev signal port. Either of data streams from the two AD9361 RX channels may be sent to an instance of ad9361_adc.hdl. Which RX channel data stream is sent is determined within the ad9361_adc_sub.hdl subdevice worker. The Q0.15 I/Q values on the ad9361_adc.hdl output port are sign extended from the AD9361's 12-bit I/Q ADC bus. For more information see [3].
The ad9361_adc.hdl worker passes data from the `dev_adc` dev signal bus through an asynchronous First-In-First-Out (FIFO) buffer to achieve clock domain crossing. The FIFO's output side is in the HDL container's control clock domain. Note that the HDL container's control clock rate is platform-specific. The FIFO's depth in number of samples is determined at build-time by the `fifo_depth` parameter property. An `overrun` property indicates when samples have been dropped due to the FIFO being full, which is possible when backpressure overcomes the ADC sample rate for long enough to fill up the FIFO. The output data port generates messages whose length in bytes is determined at runtime by the messageSize property.

Block Diagrams

Top level



Source Dependencies

ad9361_adc.hdl

- assets/hdl/devices/ad9361_adc.hdl/ad9361_adc.vhd
- core/hdl/primitives/util/adc_fifo.vhd
- core/hdl/primitives/util/sync_status.vhd
- core/hdl/primitives/util/util_pkg.vhd
- core/hdl/primitives/bsv/imports/SyncFIFO.v
- core/hdl/primitives/bsv/imports/SyncResetA.v
- core/hdl/primitives/bsv/imports/SyncHandshake.v
- core/hdl/primitives/bsv/bsv_pkg.vhd

Component Spec Properties

Name	Type	SequenceLength	ArrayDimensions	Accessibility	Valid Range	Default	Usage
`messageSize`	Long	-	-	Initial, Readable	Standard	-	Number of bytes in output message
`overrun`	Bool	-	-	Writable, Volatile	Standard	-	Flag set when ADC tries to load a sample and the ADC FIFO is full. Once high, this flag is not cleared (i.e. set low) until the property is written to again (the flag clears regardless of write value, i.e. writing true or false both result in a value of false, also note that a property write happens on reset).

Worker Properties

ad9361_adc.hdl

Scope	Name	Type	SequenceLength	ArrayDimensions	Accessibility	Valid Range	Default	Usage
SpecProperty	`messageSize`	Long	-	-	Initial,Readable	Standard	8192	Number of bytes in output message
SpecProperty	`overrun`	Bool	-	-	Writable,Volatile	Standard	0	Flag set when ADC tries to load a sample and the ADC FIFO is full. Once high, this flag is not cleared (i.e. set low) until the property is written to again (the flag clears regardless of write value, i.e. writing true or false both result in a value of false, also note that a property write happens on reset).
Property	`fifo_depth`	ULong	-	-	Parameter	Standard	0	Depth in number of samples of the ADC-to-control clock domain crossing FIFO.

Component Ports

Name	Producer	Protocol	Optional	Advanced	Usage
out	true	iqstream_protocol	true	-	Complex signed samples (Q0.15 I, Q0.15 Q).

Worker Interfaces

ad9361_adc.hdl

Type	Name	DataWidth	Advanced	Usage
StreamInterface	out	32	-	Complex signed samples (Q0.15 I, Q0.15 Q). This port generates data and obeys backpressure. Because both backpressure from the `out` port and forward pressure from the `dev_adc` data bus exists, it is possible for samples to be dropped in the clock domain-crossing FIFO, i.e. seen on the `dev_adc` data bus but never make it to the output port. This event is monitored via the `overrun` property.

Type	Name	Count	Optional	Master	Signal	Direction	Width	Description
DevSignal	dev_adc	1	False	True	present	Output	1	Value is 1 if a worker is connected to this devsignal port.
					adc_data_I	Input	12	Signed Q0.11 I value of ADC sample corresponding to RX channel 1.
					adc_data_Q	Input	12	Signed Q0.11 Q value of ADC sample corresponding to RX channel 1.
					adc_clk	Input	1	Clock for adc_data_I, adc_data_Q, and adc_give.
					adc_give	Input	1	Indicates that the adc_data_I and adc_data_Q are valid and should be latched on the next rising edge of adc_clk.

Control Timing and Signals

The ad9361_adc.hdl device worker contains two clock domains: the clock from the Control Plane, and the adc_clk clock from the dev signal.

The latency from the dev signal data bus to the output port is non-deterministic due to data flowing through an asynchronous FIFO with each side in a different clock domain. This non-determinism exists even in the absense of backpressure. In the presence of backpressure, the latency increases in an amount directly proportional to the degree to which the FIFO is full.

Worker Configuration Parameters

ad9361_adc.hdl

Table 1: Table of Worker Configurations for worker: ad9361_adc

Configuration	fifo_depth	ocpi_endian	ocpi_debug
0	64	little	false

Performance and Resource Utilization

ad9361_adc.hdl

The FPGA resource utilization and Fmax are included for this worker. Fmax refers to the maximum allowable clock rate for any registered signal paths within a given clock domain for an FPGA design. Fmax in the table below is specific only to this worker and represents the maximum possible Fmax for any OpenCPI bitstream built with this worker included. Note that the Fmax value for a given clock domain for the final bitstream is often worse than the Fmax specific to this worker, even if this worker is the only one included in the bitstream. Note also that the DATA_CLK_P devsignal's rate will only ever go as high as 245.76 MHz[2].

Table 2: Resource Utilization Table for worker: ad9361_adc

Configuration	OCPI Target	Tool	Version	Device	Registers (Typ)	LUTs (Typ)	Fmax (MHz) (Typ)		Memory/Special Functions
							control plane clock	dev_adc.adc_clk clock	
0	zynq	Vivado	2017.1	xc7z020clg484-1	188	133	202 [1]	339 [1]	RAMB18: 1
0	stratix4	Quartus	17.1.0	EP4SGX230KF40C2	187	185	N/A	N/A	N/A
0	virtex6	ISE	14.7	6vlx240tff1156-1	208	258	335.373	369	RAM64M: 8

[1] These measurements were the result of a Vivado timing analysis which was different from the Vivado analysis performed by default for OpenCPI worker builds. For more info see Appendix 2

Test and Verification

No unit test for this component exists. However, a hardware-in-the-loop application (which is NOT a unit test) exists for testing purposes (see assets/applications/ad9361_adc_test).

References

[1] AD9361 Datasheet and Product Info
`http://www.analog.com/en/products/rf-microwave/integrated-transceivers-transmitters-receivers/wideband-transceivers-ic/ad9361.html`

[2] AD9361 Reference Manual UG-570
AD9361_Reference_Manual_UG-570.pdf

[3] AD361 ADC Sub Component Data Sheet
`https://opencpi.github.io/assets/AD9361_ADC_Sub.pdf`

1 Appendix 1 - AD9361 ADC Data Fidelity / Delay Setting Verification

1.1 FMCOMMS3 on ML605 FMC-LPC slot

A custom script was run to report bit error rate vs. on-AD9361 RX data-clock delay settings. The following confirms both the ability of the ML605/FMCOMMS3 to have 100% data fidelity up to the maximum data rate and the experimental range of valid delay settings. Each entry in the table below represents bit error rate in percent.

```
FIR enabled      : 0
Data port config : 1R1T
sample rate      : 2.083334e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       11.1165 32.5526 38.0768 38.888  38.739  38.7141 38.7461 38.9165 error   38.7726 38.6963 38.887  38.8316 38.8514 38.8423 38.8295
1       0.175476
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      0
FIR enabled      : 0
Data port config : 1R1T
sample rate      : 25e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       10.0082 32.0424 37.6495 38.6719 38.5193 38.267  38.6541 39.18   38.913  39.1368 38.7884 37.9674 37.9908 38.7934 38.827  37.885
1       0.0223796
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      0
FIR enabled      : 0
Data port config : 1R1T
sample rate      : 40e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       10.0683 32.1218 37.4532 39.2014 39.1764 38.8275 37.9369 38.6688 38.5096 38.9964 38.5442 37.9761 38.4176 37.973  37.9934 38.9781
1       0.00101725
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      0
FIR enabled      : 0
Data port config : 1R1T
sample rate      : 61.44e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
```

```
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       8.7087  31.222  36.0377 39.0559 38.7578 38.8687 38.5117 39.0518 38.8646 38.6719 38.3362 39.0422 38.4893 37.7355 39.0508 39.0106
1       0.161743
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      0
FIR enabled      : 0
Data port config : 2R2T
sample rate      : 2.083334e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       error   31.9356 error   38.8067 38.7568 error   error   38.6948 38.6612 38.8941 38.6012 38.7405 38.7589 38.9399 38.7741 38.8087
1       0
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      error
FIR enabled      : 0
Data port config : 2R2T
sample rate      : 25e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       10.2153 31.5826 37.1175 38.8011 38.7777 38.7955 38.9638 39.1596 38.6841 39.1734 38.7619 38.6576 38.6983 38.9506 38.5905 38.9964
1       0
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      0
13      0
14      0
15      0
FIR enabled      : 0
Data port config : 2R2T
sample rate      : 40e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       19.9519 34.5505 38.4109 38.6759 38.8428 39.123  39.1123 38.7451 38.8947 37.7131 38.6642 38.6897 38.415  36.411  26.7649 11.1231
1       3.42967
2       0
3       0
4       0
5       0
6       0
7       0
8       0
9       0
10      0
11      0
12      3.35541
13      15.3783
```

```
14      34.4991
15      37.8092
FIR enabled      : 0
Data port config : 2R2T
sample rate      : 61.44e6 sps
 rx_data_clock_delay    rx_data_delay->
  |
  v
        0       1       2       3       4       5       6       7       8       9       10      11      12      13      14      15
0       9.56268 30.2144 37.0743 39.0889 38.6958 38.6719 39.1861 38.9008 37.7182 34.2031 20.5037 5.95449 0       0       0       0
1       0.54067
2       0
3       0
4       0
5       0
6       0.18158
7       7.34151
8       23.8927
9       36.7589
10      38.9262
11      39.0381
12      38.886
13      38.8255
14      39.1647
15      38.3784
```

2 Appendix 2 - Vivado Timing Analysis

The Vivado timing report that OpenCPI runs for device workers may erroneously report a max delay for a clocking path which should have been ignored. Custom Vivado tcl commands had to be run for this device worker to extract pertinent information from Vivado timing analysis. After building the worker, the following commands were run from the assets project directory (after the Vivado settings64.sh was sourced):

```
cd hdl/devices/
vivado -mode tcl
```

Then the following commands were run inside the Vivado tcl terminal:

```
open_project ad9361_adc.hdl/target-zynq/ad9361_adc_rv.xpr
synth_design -part xc7z020clg484-1 -top ad9361_adc_rv -mode out_of_context
create_clock -name clk1 -period 0.001 [get_nets {ctl_in[Clk]}]
create_clock -name clk2 -period 0.001 [get_nets {dev_adc_in[adc_clk]}]
set_clock_groups -asynchronous -group [get_clocks clk1] -group [get_clocks clk2]
report_timing -delay_type min_max -sort_by slack -input_pins -group clk1
report_timing -delay_type min_max -sort_by slack -input_pins -group clk2
```

The following is the output of the timing reports. The Fmax for the control plane clock for this worker is computed as the maximum magnitude slack with a control plane clock of 1 ps plus 2 times the assumed 1 ps control plane clock period (4.933 ns + 0.002 ns = 4.935 ns, 1/4.935 ns = 202.63 MHz). The Fmax for the adc_clk clock from the devsignal is computed as the maximum magnitude slack with adc_clk of 1 ps plus 2 times the assumed 1 ps adc_clk period (2.947 ns + 0.002 ns = 2.949 ns, 1/2.949 ns = 339.10 MHz).

```
Vivado% report_timing -delay_type min_max -sort_by slack -input_pins -group clk1


Timing Report


Slack (VIOLATED) :     -4.933ns (required time - arrival time)
 Source:               wci/messageSize_property/value_reg[7]/C
                         (rising edge-triggered cell FDRE clocked by clk1 {rise@0.000ns fall@0.001ns period=0.001ns})
 Destination:          worker/fifo/samplesInMessage_r_reg[0]/S
                         (rising edge-triggered cell FDSE clocked by clk1 {rise@0.000ns fall@0.001ns period=0.001ns})
 Path Group:           clk1
 Path Type:            Setup (Max at Slow Process Corner)
 Requirement:          0.002ns (clk1 rise@0.002ns - clk1 rise@0.000ns)
 Data Path Delay:      4.327ns (logic 2.025ns (46.799%) route 2.302ns (53.201%))
 Logic Levels:         5  (CARRY4=3 LUT5=1 LUT6=1)
 Clock Path Skew:      -0.049ns (DCD - SCD + CPR)
   Destination Clock Delay (DCD): 0.924ns = ( 0.926 - 0.002 )
   Source Clock Delay    (SCD):   0.973ns
   Clock Pessimism Removal (CPR): 0.000ns
 Clock Uncertainty:    0.035ns ((TSJ^2 + TIJ^2)^1/2 + DJ) / 2 + PE
   Total System Jitter  (TSJ):   0.071ns
   Total Input Jitter   (TIJ):   0.000ns
   Discrete Jitter       (DJ):   0.000ns
   Phase Error           (PE):   0.000ns

   Location           Delay type             Incr(ns) Path(ns)   Netlist Resource(s)
 ------------------------------------------------------------------- -------------------
                     (clock clk1 rise edge)    0.000    0.000 r
                                               0.000    0.000 r ctl_in[Clk] (IN)
                     net (fo=155, unset)       0.973    0.973   wci/messageSize_property/ctl_in[Clk]
                     FDRE                                   r  wci/messageSize_property/value_reg[7]/C
 ------------------------------------------------------------------- -------------------
```

```
                    FDRE (Prop_fdre_C_Q)      0.518    1.491 r wci/messageSize_property/value_reg[7]/Q
                    net (fo=2, unplaced)      0.976    2.467   wci/messageSize_property/Q[6]
                                                        r  wci/messageSize_property/b_carry_i_3/I0
                    LUT6 (Prop_lut6_I0_O)     0.295    2.762 r wci/messageSize_property/b_carry_i_3/O
                    net (fo=1, unplaced)      0.000    2.762   worker/fifo/S[1]
                                                        r  worker/fifo/b_carry/S[1]
                    CARRY4 (Prop_carry4_S[1]_CO[3])
                                              0.533    3.295 r worker/fifo/b_carry/CO[3]
                    net (fo=1, unplaced)      0.009    3.304   worker/fifo/b_carry_n_0
                                                        r  worker/fifo/b_carry__0/CI
                    CARRY4 (Prop_carry4_CI_CO[3])
                                              0.117    3.421 r worker/fifo/b_carry__0/CO[3]
                    net (fo=1, unplaced)      0.000    3.421   worker/fifo/b_carry__0_n_0
                                                        r  worker/fifo/b_carry__1/CI
                    CARRY4 (Prop_carry4_CI_CO[2])
                                              0.252    3.673 r worker/fifo/b_carry__1/CO[2]
                    net (fo=3, unplaced)      0.470    4.143   wci/wci_decode/CO[0]
                                                        r  wci/wci_decode/samplesInMessage_r[0]_i_1/I3
                    LUT5 (Prop_lut5_I3_O)     0.310    4.453 r wci/wci_decode/samplesInMessage_r[0]_i_1/O
                    net (fo=32, unplaced)     0.847    5.300   worker/fifo/or
                    FDSE                                 r  worker/fifo/samplesInMessage_r_reg[0]/S
  ------------------------------------------------------------------- -------------------

                    (clock clk1 rise edge)    0.002    0.002 r
                                              0.000    0.002 r ctl_in[Clk] (IN)
                    net (fo=155, unset)       0.924    0.926   worker/fifo/ctl_in[Clk]
                    FDSE                                 r  worker/fifo/samplesInMessage_r_reg[0]/C
                    clock pessimism           0.000    0.926
                    clock uncertainty        -0.035    0.891
                    FDSE (Setup_fdse_C_S)    -0.524    0.367   worker/fifo/samplesInMessage_r_reg[0]
  -------------------------------------------------------------------
                    required time                       0.367
                    arrival time                       -5.300
  -------------------------------------------------------------------
                    slack                              -4.933

Vivado% report_timing -delay_type min_max -sort_by slack -input_pins -group clk2

Timing Report

Slack (VIOLATED) :      -2.947ns (required time - arrival time)
  Source:               worker/fifo/fifo/sGEnqPtr_reg[1]/C
                          (rising edge-triggered cell FDCE clocked by clk2 {rise@0.000ns fall@0.001ns period=0.001ns})
  Destination:          worker/fifo/fifo/sNotFullReg_reg/D
                          (rising edge-triggered cell FDCE clocked by clk2 {rise@0.000ns fall@0.001ns period=0.001ns})
  Path Group:           clk2
  Path Type:            Setup (Max at Slow Process Corner)
  Requirement:          0.002ns (clk2 rise@0.002ns - clk2 rise@0.000ns)
  Data Path Delay:      2.942ns (logic 1.061ns (36.064%) route 1.881ns (63.936%))
  Logic Levels:         3  (LUT4=1 LUT6=2)
  Clock Path Skew:      -0.049ns (DCD - SCD + CPR)
    Destination Clock Delay (DCD): 0.924ns = ( 0.926 - 0.002 )
    Source Clock Delay    (SCD):   0.973ns
    Clock Pessimism Removal (CPR): 0.000ns
  Clock Uncertainty:    0.035ns ((TSJ^2 + TIJ^2)^1/2 + DJ) / 2 + PE
    Total System Jitter   (TSJ):   0.071ns
    Total Input Jitter    (TIJ):   0.000ns
```

```
  Discrete Jitter       (DJ):   0.000ns
  Phase Error           (PE):   0.000ns

  Location          Delay type             Incr(ns) Path(ns)   Netlist Resource(s)
-------------------------------------------------------------------- -------------------
                    (clock clk2 rise edge)    0.000    0.000 r
                                              0.000    0.000 r dev_adc_in[adc_clk] (IN)
                    net (fo=33, unset)        0.973    0.973   worker/fifo/fifo/dev_adc_in[adc_clk]
                    FDCE                                   r  worker/fifo/fifo/sGEnqPtr_reg[1]/C
-------------------------------------------------------------------- -------------------
                    FDCE (Prop_fdce_C_Q)      0.518    1.491 r worker/fifo/fifo/sGEnqPtr_reg[1]/Q
                    net (fo=3, unplaced)      0.983    2.474   worker/fifo/fifo/p_0_in[0]
                                                       r  worker/fifo/fifo/sNotFullReg_i_6/I0
                    LUT6 (Prop_lut6_I0_O)     0.295    2.769 r worker/fifo/fifo/sNotFullReg_i_6/O
                    net (fo=1, unplaced)      0.449    3.218   worker/fifo/fifo/sNotFullReg_i_6_n_0
                                                       r  worker/fifo/fifo/sNotFullReg_i_4/I3
                    LUT4 (Prop_lut4_I3_O)     0.124    3.342 r worker/fifo/fifo/sNotFullReg_i_4/O
                    net (fo=1, unplaced)      0.449    3.791   worker/fifo/fifo/sNextNotFull__12
                                                       r  worker/fifo/fifo/sNotFullReg_i_1/I5
                    LUT6 (Prop_lut6_I5_O)     0.124    3.915 r worker/fifo/fifo/sNotFullReg_i_1/O
                    net (fo=1, unplaced)      0.000    3.915   worker/fifo/fifo/sNotFullReg_i_1_n_0
                    FDCE                                   r  worker/fifo/fifo/sNotFullReg_reg/D
-------------------------------------------------------------------- -------------------

                    (clock clk2 rise edge)    0.002    0.002 r
                                              0.000    0.002 r dev_adc_in[adc_clk] (IN)
                    net (fo=33, unset)        0.924    0.926   worker/fifo/fifo/dev_adc_in[adc_clk]
                    FDCE                                   r  worker/fifo/fifo/sNotFullReg_reg/C
                    clock pessimism           0.000    0.926
                    clock uncertainty        -0.035    0.891
                    FDCE (Setup_fdce_C_D)     0.077    0.968   worker/fifo/fifo/sNotFullReg_reg
-------------------------------------------------------------------
                    required time                      0.968
                    arrival time                      -3.915
-------------------------------------------------------------------
                    slack                             -2.947
```

These calculations can be verified by replacing the `create_clock` lines above with the following values and rerunning the `report_timing` commands and observing a value of 0.000 ns for the slacks:

```
create_clock -name clk1 -period 4.935 [get_nets {ctl_in[Clk]}]
create_clock -name clk2 -period 2.949 [get_nets {dev_adc_in[adc_clk]}]
report_timing -delay_type min_max -sort_by slack -input_pins -group clk1
report_timing -delay_type min_max -sort_by slack -input_pins -group clk2
```

```
Vivado% report_timing -delay_type min_max -sort_by slack -input_pins -group clk1

Timing Report

Slack (MET) :          0.000ns (required time - arrival time)
  Source:              wci/messageSize_property/value_reg[7]/C
                         (rising edge-triggered cell FDRE clocked by clk1 {rise@0.000ns fall@2.467ns period=4.935ns})
  Destination:         worker/fifo/samplesInMessage_r_reg[0]/S
                         (rising edge-triggered cell FDSE clocked by clk1 {rise@0.000ns fall@2.467ns period=4.935ns})
  Path Group:          clk1
  Path Type:           Setup (Max at Slow Process Corner)
```

```
Requirement:          4.935ns (clk1 rise@4.935ns - clk1 rise@0.000ns)
Data Path Delay:      4.327ns (logic 2.025ns (46.799%) route 2.302ns (53.201%))
Logic Levels:         5  (CARRY4=3 LUT5=1 LUT6=1)
Clock Path Skew:      -0.049ns (DCD - SCD + CPR)
  Destination Clock Delay (DCD): 0.924ns = ( 5.859 - 4.935 )
  Source Clock Delay    (SCD):   0.973ns
  Clock Pessimism Removal (CPR): 0.000ns
Clock Uncertainty:    0.035ns ((TSJ^2 + TIJ^2)^1/2 + DJ) / 2 + PE
  Total System Jitter   (TSJ):   0.071ns
  Total Input Jitter    (TIJ):   0.000ns
  Discrete Jitter        (DJ):   0.000ns
  Phase Error            (PE):   0.000ns

  Location           Delay type              Incr(ns) Path(ns)   Netlist Resource(s)
------------------------------------------------------------------- -------------------
                     (clock clk1 rise edge)    0.000    0.000 r
                                               0.000    0.000 r ctl_in[Clk] (IN)
                     net (fo=155, unset)       0.973    0.973   wci/messageSize_property/ctl_in[Clk]
                     FDRE                                   r  wci/messageSize_property/value_reg[7]/C
------------------------------------------------------------------- -------------------
                     FDRE (Prop_fdre_C_Q)      0.518    1.491 r wci/messageSize_property/value_reg[7]/Q
                     net (fo=2, unplaced)      0.976    2.467   wci/messageSize_property/Q[6]
                                                        r  wci/messageSize_property/b_carry_i_3/I0
                     LUT6 (Prop_lut6_I0_O)     0.295    2.762 r wci/messageSize_property/b_carry_i_3/O
                     net (fo=1, unplaced)      0.000    2.762   worker/fifo/S[1]
                                                        r  worker/fifo/b_carry/S[1]
                     CARRY4 (Prop_carry4_S[1]_CO[3])
                                               0.533    3.295 r worker/fifo/b_carry/CO[3]
                     net (fo=1, unplaced)      0.009    3.304   worker/fifo/b_carry_n_0
                                                        r  worker/fifo/b_carry__0/CI
                     CARRY4 (Prop_carry4_CI_CO[3])
                                               0.117    3.421 r worker/fifo/b_carry__0/CO[3]
                     net (fo=1, unplaced)      0.000    3.421   worker/fifo/b_carry__0_n_0
                                                        r  worker/fifo/b_carry__1/CI
                     CARRY4 (Prop_carry4_CI_CO[2])
                                               0.252    3.673 r worker/fifo/b_carry__1/CO[2]
                     net (fo=3, unplaced)      0.470    4.143   wci/wci_decode/CO[0]
                                                        r  wci/wci_decode/samplesInMessage_r[0]_i_1/I3
                     LUT5 (Prop_lut5_I3_O)     0.310    4.453 r wci/wci_decode/samplesInMessage_r[0]_i_1/O
                     net (fo=32, unplaced)     0.847    5.300   worker/fifo/or
                     FDSE                                   r  worker/fifo/samplesInMessage_r_reg[0]/S
------------------------------------------------------------------- -------------------

                     (clock clk1 rise edge)    4.935    4.935 r
                                               0.000    4.935 r ctl_in[Clk] (IN)
                     net (fo=155, unset)       0.924    5.859   worker/fifo/ctl_in[Clk]
                     FDSE                                   r  worker/fifo/samplesInMessage_r_reg[0]/C
                     clock pessimism           0.000    5.859
                     clock uncertainty        -0.035    5.824
                     FDSE (Setup_fdse_C_S)    -0.524    5.300   worker/fifo/samplesInMessage_r_reg[0]
-------------------------------------------------------------------
                     required time                      5.300
                     arrival time                      -5.300
-------------------------------------------------------------------
                     slack                              0.000
```

```
Vivado% report_timing -delay_type min_max -sort_by slack -input_pins -group clk2

Timing Report

Slack (MET) :           0.000ns (required time - arrival time)
  Source:               worker/fifo/fifo/sGEnqPtr_reg[1]/C
                          (rising edge-triggered cell FDCE clocked by clk2 {rise@0.000ns fall@1.474ns period=2.949ns})
  Destination:          worker/fifo/fifo/sNotFullReg_reg/D
                          (rising edge-triggered cell FDCE clocked by clk2 {rise@0.000ns fall@1.474ns period=2.949ns})
  Path Group:           clk2
  Path Type:            Setup (Max at Slow Process Corner)
  Requirement:          2.949ns (clk2 rise@2.949ns - clk2 rise@0.000ns)
  Data Path Delay:      2.942ns (logic 1.061ns (36.064%) route 1.881ns (63.936%))
  Logic Levels:         3  (LUT4=1 LUT6=2)
  Clock Path Skew:      -0.049ns (DCD - SCD + CPR)
    Destination Clock Delay (DCD): 0.924ns = ( 3.873 - 2.949 )
    Source Clock Delay    (SCD):   0.973ns
    Clock Pessimism Removal (CPR): 0.000ns
  Clock Uncertainty:    0.035ns ((TSJ^2 + TIJ^2)^1/2 + DJ) / 2 + PE
    Total System Jitter   (TSJ):   0.071ns
    Total Input Jitter    (TIJ):   0.000ns
    Discrete Jitter        (DJ):   0.000ns
    Phase Error            (PE):   0.000ns

    Location           Delay type             Incr(ns) Path(ns)   Netlist Resource(s)
  ------------------------------------------------------------------- -------------------
                       (clock clk2 rise edge)    0.000    0.000 r
                                                 0.000    0.000 r dev_adc_in[adc_clk] (IN)
                       net (fo=33, unset)        0.973    0.973   worker/fifo/fifo/dev_adc_in[adc_clk]
                       FDCE                                   r  worker/fifo/fifo/sGEnqPtr_reg[1]/C
  ------------------------------------------------------------------- -------------------
                       FDCE (Prop_fdce_C_Q)      0.518    1.491 r worker/fifo/fifo/sGEnqPtr_reg[1]/Q
                       net (fo=3, unplaced)      0.983    2.474   worker/fifo/fifo/p_0_in[0]
                                                                  r  worker/fifo/fifo/sNotFullReg_i_6/I0
                       LUT6 (Prop_lut6_I0_O)     0.295    2.769 r worker/fifo/fifo/sNotFullReg_i_6/O
                       net (fo=1, unplaced)      0.449    3.218   worker/fifo/fifo/sNotFullReg_i_6_n_0
                                                                  r  worker/fifo/fifo/sNotFullReg_i_4/I3
                       LUT4 (Prop_lut4_I3_O)     0.124    3.342 r worker/fifo/fifo/sNotFullReg_i_4/O
                       net (fo=1, unplaced)      0.449    3.791   worker/fifo/fifo/sNextNotFull__12
                                                                  r  worker/fifo/fifo/sNotFullReg_i_1/I5
                       LUT6 (Prop_lut6_I5_O)     0.124    3.915 r worker/fifo/fifo/sNotFullReg_i_1/O
                       net (fo=1, unplaced)      0.000    3.915   worker/fifo/fifo/sNotFullReg_i_1_n_0
                       FDCE                                   r  worker/fifo/fifo/sNotFullReg_reg/D
  ------------------------------------------------------------------- -------------------

                       (clock clk2 rise edge)    2.949    2.949 r
                                                 0.000    2.949 r dev_adc_in[adc_clk] (IN)
                       net (fo=33, unset)        0.924    3.873   worker/fifo/fifo/dev_adc_in[adc_clk]
                       FDCE                                   r  worker/fifo/fifo/sNotFullReg_reg/C
                       clock pessimism           0.000    3.873
                       clock uncertainty        -0.035    3.838
                       FDCE (Setup_fdce_C_D)     0.077    3.915   worker/fifo/fifo/sNotFullReg_reg
  -------------------------------------------------------------------
                       required time                      3.915
                       arrival time                      -3.915
```

```
--------------------------------------------------------------------
                    slack                           0.000
```