OpenCPI
E3xx MIMO RCVR Filter Proxy Test App Guide

Version 1.4

Revision History

Revision	Description of Change	Date
v1.4	Initial release.	9/2018

1 Description

This application is intended to perform a hardware-in-the-loop test of the e3xx_mimo_xcvr_filter_proxy.rcc device proxy. The application is meant to exercise the properties of the proxy worker dynamically while the application is running. The different modes of the frontend are cycled through for various different frequency/filter bank settings to visually verify the LEDs are responding appropriately. The following steps are taken in the application:

1. Set the frequency of the RX and TX LOs

2. Set the mode for Frontend A to TX,RX i.e. full duplex

3. Set the mode for Frontend B to TX,RX i.e. full duplex

4. Request user input for validation

5. Set the mode for Frontend A to RX,off

6. Set the mode for Frontend B to TX,RX i.e. full duplex

7. Request user input for validation

8. Set the mode for Frontend A to RX,off

9. Set the mode for Frontend B to RX,off

10. Request user input for validation

11. Set the mode for Frontend A to TX,RX i.e. full duplex

12. Set the mode for Frontend B to RX,off

13. Request user input for validation

14. Set the mode for Frontend A to TX,RX i.e. full duplex

15. Set the mode for Frontend B to off,off

16. Request user input for validation

17. Set the mode for Frontend A to off,off

18. Set the mode for Frontend B to TX,RX i.e. full duplex

19. Request user input for validation

20. Set the mode for Frontend A to off,off

21. Set the mode for Frontend B to off,off

22. Request user input for validation

23. Repeat steps 1 through 22 for each frequency being tested

2   Hardware Portability

This application is intended to test e3xx_mimo_filter_proxy.rcc, which is by design specific to the `e3xx` platform.

3   Execution

3.1   Prerequisites

The following must be true before application execution:

- The following assets are built and their build artifacts (FPGA bitstream file/shared object file) are contained within the directory list of the OCPI_LIBRARY_PATH environment variable.

  - for `e3xx/xilinx13_4` HDL/RCC platforms:
    * `empty/cnt_e3xx_mimo_xcvr_filter` assembly/container
    * `e3xx_mimo_xcvr_filter_proxy.rcc`

- The current directory is the applications/e3xx_mimo_xcvr_filter_proxy_test directory.

3.2   Command(s)

```
./<target-dir>/e3xx_mimo_xcvr_filter_proxy_test
```

4   Verification

Verification is performed by running the application and visually verifying that the LEDs on the E3xx match the values printed to stdout. An application exit status which is non-zero indicates that the test could not complete.