

fn make_privacy_filter

Michael Shoemate

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of fn make_privacy_filter.

1 Hoare Triple

Precondition

Compiler-verified

- Argument odometer of type Odometer<DI, MI, MO, Q, A>.
- Argument d_out of type MO_Distance, the associated distance type of MO.
- Generic DI implements **Domain**.
- Generic MI implements **Metric**.
- Generic MO implements **Measure**.
- MI_Distance implements **ProductOrd**.
- MO_Distance implements **ProductOrd**.
- (DI, MI) implements **MetricSpace**.

User-verified

None

Pseudocode

```
1 def make_privacy_filter(  
2     odometer: Odometer[DI, MI, MO, Q, A],  
3     d_in: MI_Distance,  
4     d_out: MO_Distance,  
5 ) -> Measurement[DI, OdometerQueryable[MI, MO, Q, A], MI, MO]:  
6     odo_function = odometer.function  
7  
8     def function(arg: DI_Carrier) -> OdometerQueryable[MI, MO, Q, A]:  
9         #  
10        continuation_rule = new_continuation_rule(d_in, d_out, MI, MO)  
11        return wrap(continuation_rule, lambda: odo_function.eval(arg)) #  
12  
13    def privacy_map(d_in_p: MI_Distance) -> MO_Distance:  
14        if d_in_p.total_gt(d_in):  
15            raise "input distance must not be greater than d_in"
```

```

16
17     return d_out
18
19     return Measurement.new(
20         odometer.input_domain,
21         Function.new_interactive(function),
22         odometer.input_metric,
23         odometer.output_measure,
24         PrivacyMap.new_fallible(privacy_map),
25     )

```

Postcondition

For every setting of the input parameters (`odometer`, `d_out`, `DI`, `MI`, `MO`, `Q`, `A`) to `make_privacy_filter` such that the given preconditions hold, `make_privacy_filter` raises an error (at compile time or run time) or returns a valid odometer. A valid odometer has the following properties:

1. (Data-independent runtime errors). For every pair of members x and x' in `input_domain`, `invoke(x)` and `invoke(x')` either both return the same error or neither return an error.
2. (Valid odometer queryable). For every member x in `input_domain`, where `function(x)` does not raise an error, `function(x)` returns a valid odometer queryable.

Proof of data-independent errors. `Function.eval` on line 11 has data-independent exceptions, because the function is from `odometer`, which is a valid odometer. Since this is the only location where an exception can be raised, the data-independent errors property holds. \square

Proof of privacy guarantee. By the definition of a valid odometer queryable, the output of `make_privacy_filter` upholds the privacy guarantee. \square