

fn check_candidates

Michael Shoemate

May 16, 2025

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of `check_candidates` in `mod.rs` at commit `f5bb719` (outdated¹). `check_candidates` raises an error if the discrete quantile candidate set is invalid.

1 Hoare Triple

Precondition

None

Function

```
1 def validate_candidates(candidates: list[T]):  
2     if not candidates: #  
3         raise ValueError("candidates must not be empty")  
4  
5     i1 = iter(candidates)  
6     i2 = iter(candidates)  
7     next(i1)  
8  
9     for c1, c2 in zip(i1, i2): #  
10         cmp = c1.partial_cmp(c2)  
11         if cmp is None or cmp != Ordering.Less:  
12             raise ValueError("candidates must be non-null and strictly increasing")
```

Postcondition

Theorem 1.1. Candidates must be:

1. non-empty
2. strictly increasing
3. totally ordered

Otherwise the function errors.

Proof. The postconditions can be directly checked:

1. `candidates` is non-empty, by the check on line 2
2. `candidates` is strictly increasing, because there is no window where the left candidate is not less than the right candidate

¹See new changes with `git diff f5bb719..11c2f7f rust/src/transformations/quantile_score_candidates/mod.rs`

3. `candidates` is totally ordered, because no comparisons may fail
Therefore the postcondition holds. □