

fn then_saturating_cast

Michael Shoemate

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of the implementation of `then_saturating_cast` in `mod.rs` at commit `f5bb719` (outdated¹).

1 Hoare Triple

Precondition

Compiler-Verified

- Generic T0 implements trait `SaturatingCast<IBig>`

User-Verified

None

Pseudocode

```
1 def then_saturating_cast() -> Function[Vec[IBig], Vec[T0]]:  
2   return Function.new(lambda x: [T0.saturating_cast(x_i) for x_i in x])
```

Postcondition

Theorem 1.1. For every setting of the input parameters (T0) to `then_saturating_cast` such that the given preconditions hold, `then_saturating_cast` raises an exception (at compile time or run time) or returns a valid postprocessor. A valid postprocessor has the following property:

1. (Data-independent errors). For every pair of elements x, x' in `input_domain`, `function(x)`, `function(x')` either neither or both raise an error. If both raise an error, then they both raise the same error.

Proof. Since `T0.saturating_cast` is infallible, the function is infallible, meaning that the function cannot raise data-dependent errors. Therefore the function is a valid postprocessor. \square

¹See new changes with `git diff f5bb719..a58e34b rust/src/measurements/noise/nature/integer/mod.rs`