CompositionMeasure for PureDP

Michael Shoemate (@Shoeboxam)

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of the implementation of `CompositionMeasure` for `PureDP` in `mod.rs` at commit f5bb719 (outdated[1]).

1 Hoare Triple

Precondition

Compiler-verified

Types matching pseudocode.

Caller-verified

None

Pseudocode

```
1  class CompositionMeasure(PureDP):
2      def composability(  #
3          self, adaptivity: Adaptivity
4      ) -> Composability:
5          return Composability.Concurrent
6
7      def compose(self, d_mids: Vec[Self_Distance]) -> Self_Distance:
8          d_out = 0.0
9          for d_mid in d_mids:
10             d_out = d_out.inf_add(d_mid)
11         return d_out
```

Postcondition

Theorem 1.1. `composability` returns `Ok(out)` if the composition of a vector of privacy parameters `d_mids` is bounded above by `self.compose(d_mids)` under `adaptivity` adaptivity and `out`-composability. Otherwise returns an error.

Proof. By the postcondition of `InfAdd` we have that $\sum_i \texttt{d_mids}_i \leq \texttt{compose(d_mids)}$.

Adaptivity	Sequential	Concurrent
Non-Adaptive	Theorem 1[DMNS06]	Theorem 1.8[VW21]
Adaptive	Theorem 1[DMNS06]	Theorem 1.8[VW21]
Fully-Adaptive	None	None

This table is reflected in the implementation of `composability` on line 2.

[1] See new changes with `git diff f5bb719..5f7c632a rust/src/combinators/sequential_composition/mod.rs`

□

References

[DMNS06] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In Shai Halevi and Tal Rabin, editors, *Theory of Cryptography*, pages 265–284, Berlin, Heidelberg, 2006. Springer Berlin Heidelberg.

[VW21] Salil Vadhan and Tianhao Wang. Concurrent composition of differential privacy, 2021.