fn make_count

Sílvia Casacuberta, Grace Tian, Connor Wagaman

Proves soundness of `make_count` in `mod.rs` at commit f5bb719 (outdated[1]).

`make_count` returns a Transformation that computes a count of the number of records in a vector. The length of the vector, of type `usize`, is exactly casted to a user specified output type `TO`. If the length is too large to be represented exactly by `TO`, the cast saturates at the maximum value of type `TO`.

1 Hoare Triple

Precondition

Compiler-verified

- Generic `TIA` (atomic input type) is a type with trait `Primitive`.
- Generic `TO` (output type) is a type with trait `Number`.
- Argument `input_domain` is of type `VectorDomain<AtomDomain<TIA>>`.
- Argument `input_metric` is of type `SymmetricDistance`.

Caller-verified

None

Pseudocode

```
def make_count(
    input_domain: VectorDomain[AtomDomain[TIA]],
    input_metric: SymmetricDistance
):
    output_domain = AtomDomain.default(TO) #

    def function(arg: Vec[TIA]) -> TO: #
        size = arg.len() #
        try: #
            return TO.exact_int_cast(size) #
        except FailedCast:
            return TO.MAX_CONSECUTIVE #

    output_metric = AbsoluteDistance(TO)

    stability_map = StabilityMap.new_from_constant(TO.one()) #

    return Transformation(
        input_domain, output_domain, function,
        input_metric, output_metric, stability_map)
```

[1] See new changes with `git diff f5bb719..315312c rust/src/transformations/count/mod.rs`

Postcondition

Theorem 1.1. For every setting of the input parameters `(input_domain, input_metric, TIA, TO)` to `make_count` such that the given preconditions hold, `make_count` raises an error (at compile time or run time) or returns a valid transformation. A valid transformation has the following properties:

1. (Data-independent runtime errors). For every pair of members x and x' in `input_domain`, `invoke`(x) and `invoke`(x') either both return the same error or neither return an error.

2. (Appropriate output domain). For every member x in `input_domain`, `function`(x) is in `output_domain` or raises a data-independent runtime error.

3. (Stability guarantee). For every pair of members x and x' in `input_domain` and for every pair (`d_in`, `d_out`), where `d_in` has the associated type for `input_metric` and `d_out` has the associated type for
`output_metric`, if x, x' are `d_in`-close under `input_metric`, `stability_map(d_in)` does not raise an error, and `stability_map(d_in)` = `d_out`, then `function`(x), `function`(x') are `d_out`-close under `output_metric`.

2 Proofs

Proof. **(Part 1 – appropriate output domain).** The `output_domain` is `AtomDomain(TO)`, so it is sufficient to show that `function` always returns non-null values of type `TO`. By the definition of the `ExactIntCast` trait, `TO.exact_int_cast` always returns a non-null value of type `TO` or raises an exception. If an exception is raised, the function returns `TO.MAXIMUM_CONSECUTIVE`, which is also a non-null value of type `TO`. Thus, in all cases, the function (from line 9) returns a non-null value of type `TO`. □

Before proceeding with proving the validity of the stability map, we provide a couple lemmas.

Lemma 2.1. $|\texttt{function}(x) - \texttt{function}(x')| \leq |\texttt{len(x)} - \texttt{len(x')}|$, where `len` is an alias for `input_domain.size`.

Proof. As `arg` has type `Vec<TIA>`, it supports the Rust standard library function `len` that returns the number of elements in the `arg` as type `usize` on line 8. By the definition of `ExactIntCast`, the invocation of `TO.exact_int_cast` on line 10 can only fail if the argument is greater than `TO.MAX_CONSECUTIVE`. In this case, the value is replaced with `TO.MAX_CONSECUTIVE`. Therefore, `function`$(x) = \min(\texttt{len(x)}, c)$, where $c =$ `TO.MAX_CONSECUTIVE`. We use this equality to prove the lemma:

$$
\begin{aligned}
|\texttt{function}(x) - \texttt{function}(x')| &= |\min(\texttt{len(x)}, c) - \min(\texttt{len(x')}, c)| \\
&\leq |\texttt{len(x)} - \texttt{len(x')}| && \text{since clamping is stable}
\end{aligned}
$$

□

Lemma 2.2. For vector x with each element $\ell \in x$ drawn from domain $\mathcal{X}$, $\texttt{len(x)} = \sum_{z \in \mathcal{X}} h_x(z)$.

Proof. Every element $\ell \in x$ is drawn from domain $\mathcal{X}$, so summing over all $z \in \mathcal{X}$ will sum over every element $\ell \in x$. Recall that the definition of `SymmetricDistance` states that $h_x(z)$ will return the number of occurrences of value z in vector x. Therefore, $\sum_{z \in \mathcal{X}} h_x(z)$ is the sum of the number of occurrences of each unique value; this is equivalent to the total number of items in the vector.

By the postcondition of `Vec.len` in the Rust standard library, the variable `size` is of type `usize` containing the number of elements in `arg`. Therefore, $\sum_{z \in \mathcal{X}} h_x(z)$ is equivalent to `size`. □

Proof. **(Part 2 – stability map).** Take any two elements x, x' in the `input_domain` and any pair $(\texttt{d_in}, \texttt{d_out})$, where `d_in` has the associated type for `input_metric` and `d_out` has the associated type for `output_metric`. Assume x, x' are `d_in`-close under `input_metric` and that $\texttt{stability_map}(\texttt{d_in}) \leq \texttt{d_out}$. These assumptions are used to establish the following inequality:

$$
\begin{aligned}
|\texttt{function}(x) - \texttt{function}(x')| &\leq |\texttt{len(x)} - \texttt{len(x')}| && \text{by 2.1} \\
&= |\sum_{z \in \mathcal{X}} h_{\texttt{x}}(z) - \sum_{z \in \mathcal{X}} h_{\texttt{x'}}(z)| && \text{by 2.2} \\
&= |\sum_{z \in \mathcal{X}} (h_{\texttt{x}}(z) - h_{\texttt{x'}}(z))| && \text{by algebra} \\
&\leq \sum_{z \in \mathcal{X}} |h_{\texttt{x}}(z) - h_{\texttt{x'}}(z)| && \text{by triangle inequality} \\
&= d_{Sym}(x, x') && \text{by } \texttt{SymmetricDistance} \\
&\leq \texttt{d_in} && \text{by the first assumption} \\
&\leq \texttt{TO.inf_cast(d_in)} && \text{by } \texttt{InfCast} \\
&\leq \texttt{TO.one().inf_mul(TO.inf_cast(d_in))} && \text{by } \texttt{InfMul} \\
&= \texttt{stability_map(d_in)} && \text{by line 16, see } \texttt{StabilityMap} \\
&\leq \texttt{d_out} && \text{by the second assumption}
\end{aligned}
$$

It is shown that `function`(x), `function`(x') are `d_out`-close under `output_metric`. □