`fn x_mul_2k`

Michael Shoemate (@Shoeboxam)

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of the implementation of `x_mul_2k` in `mod.rs` at commit a65f7f1ab (outdated[1]).

1 Hoare Triple

Precondition

Compiler-verified

None

Caller-verified

$k \neq$ `i32.MIN`

Pseudocode

```
def x_mul_2k(x: RBig, k: i32) -> RBig:
    num, den = x.into_parts()  #
    if k < 0:
        den <<= cast(-k, usize)
    else:
        num <<= cast(k, usize)

    return RBig.from_parts(num, den)
```

Postcondition

Theorem 1.1. Return $x \cdot 2^k$.

Proof. Since x is a fraction, line 2 splits x into its numerator and denominator.
Consider two cases:

- If $k < 0$, then multiplying the denominator by 2^-k is equivalent to multiplying by 2^k. Since k is negative, then $-k$ is positive, meaning the cast to `usize` is valid. Shifting $-k$ zeros to the left is equivalent to multipying the denominator by 2^k. Negation of k is well-defined for all values of `i32`, except for `i32.MIN`, which is not allowed by the precondition. Therefore, the result is $x \cdot 2^k$.
- If $k \geq 0$, then we multiply the numerator by 2^k. Since k is positive, the cast to `usize` is valid. Shifting k zeros to the left is equivalent to multipying the numerator by 2^k. Therefore, the result is $x \cdot 2^k$.

In both cases, the result is $x \cdot 2^k$. □

[1] See new changes with `git diff a65f7f1ab..286ce37c rust/src/measurements/noise/nature/float/utilities/mod.rs`