

fn new_fully_adaptive_composition_queryable

Michael Shoemate (@Shoeboxam)

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of fn new_fully_adaptive_composition_queryable.

1 Hoare Triple

Precondition

Compiler-verified

Types matching those in the pseudocode.

- Generic DI implements **Domain**.
- Generic MI implements **Metric**.
- Generic MO implements **CompositionMeasure**.
- (DI, MI) implements **MetricSpace**.

Caller-verified

data is a member of input_domain.

Pseudocode

```
1 def new_fully_adaptive_composition_queryable(  
2     input_domain: DI,  
3     input_metric: MI,  
4     output_measure: MO,  
5     data: DI_Carrier,  
6 ) -> OdometerQueryable[Measurement[DI, MI, MO, TO], TO, MO_Distance]:  
7  
8     require_sequentiality = matches(  
9         output_measure.composability(Adaptivity.FullyAdaptive), Composability.Sequential  
10    )  
11  
12    privacy_maps = OrderedCounts() #  
13    num_queries = 0  
14  
15    def transition( #  
16        self_: OdometerQueryable[Measurement[DI, MI, MO, TO], TO, MO_Distance],  
17        query: Query[OdometerQuery[Measurement[DI, MI, MO, TO]]],  
18    ):  
19        # this queryable and wrapped children communicate via an AskPermission query  
20        # defined here, where no-one else can access the type  
21        @dataclass
```

```

22     class AskPermission:
23         id: usize
24
25     match query:
26         # evaluate external invoke query
27         case Query.External(
28             OdometerQuery.Invoke(meas)
29         ): #
30             assert_elements_match( #
31                 DomainMismatch, input_domain, meas.input_domain
32             )
33
34             assert_elements_match( #
35                 MetricMismatch, input_metric, meas.input_metric
36             )
37
38             assert_elements_match( #
39                 MeasureMismatch, output_measure, meas.output_measure
40             )
41
42             # check the bookkeeping before spending privacy
43             num_queries.alerting_add(1)
44             privacy_maps.check_add(meas.privacy_map, 1)
45
46             enforce_sequentiality = False
47
48             if require_sequentiality:
49                 # when the output measure doesn't allow concurrent composition,
50                 # wrap any interactive queryables spawned.
51                 # This way, when the child gets a query it sends an AskPermission query
52                 # to this parent queryable, giving this sequential odometer queryable
53                 # a chance to deny the child permission to execute
54                 child_id = num_queries
55
56                 def callback():
57                     if enforce_sequentiality:
58                         return self.eval_internal(AskPermission(child_id))
59                     else:
60                         return ()
61
62                 seq_wrapper = Wrapper.new_recursive_pre_hook( #
63                     callback
64                 )
65             else:
66                 seq_wrapper = None
67
68             answer = meas.invoke_wrap(data, seq_wrapper) #
69
70             enforce_sequentiality = True
71
72             # We've now increased our privacy spend.
73             # This is our only state modification
74             num_queries = num_queries.alerting_add(1)
75             privacy_maps.add(meas.privacy_map, 1) #
76
77             return Answer.External(OdometerAnswer.Invoke(answer))
78
79     # evaluate external privacy loss query
80     case Query.External(OdometerQuery.PrivacyLoss(d_in)):
81         d_mids = [(m.eval(d_in), k) for m, k in privacy_maps]
82         d_out = output_measure.compose(d_mids)
83         return Answer.External(OdometerAnswer.Map(d_out))
84
85     case Query.Internal(query):

```

```

86         # Check if the query is from a child queryable
87         # who is asking for permission to execute
88         if isinstance(query, AskPermission): #
89             # deny permission if the sequential odometer has moved on
90             if query.id + 1 != num_queries:
91                 raise ValueError("sequential odometer has received a new query")
92
93             # otherwise, return 0k to approve the change
94             return Answer.internal(())
95
96         raise ValueError("query not recognized")
97
98     return Queryable.new(transition) #

```

Postcondition

Theorem 1.1. For every setting of the input parameters (`input_domain`, `input_metric`, `output_measure`, `data`, `DI`, `MI`, `MO`, `T0`) to `new_fully_adaptive_composition_queryable` such that the given preconditions hold, `new_fully_adaptive_composition_queryable` raises a data-independent error or returns a valid odometer queryable (queryable). A valid odometer queryable is an `OdometerQueryable` with the following properties:

1. (Data-independent errors). For every pair of members x and x' in `input_domain`, and every query q , `queryable.invokex(q)` and `queryable.invokex'(q)` either both return the same error or neither return an error.
2. (Privacy Guarantee). For every pair of members x and x' in `input_domain`, every adversary $\mathcal{A}$, and for every pair (d_in, d_out) , where d_in has the associated type for `input_metric` and d_out has the associated type for `output_measure`, if x and x' are d_in -close under `input_metric`, `queryable.eval(privacy_loss)` does not return an error, and `queryable.eval(privacy_loss) = d_out`, then $\text{View}(\mathcal{A} \leftrightarrow \text{queryable}_x), \text{View}(\mathcal{A} \leftrightarrow \text{queryable}_{x'})$ are d_out -close under `output_measure`, where `queryablex` denotes all messages received by $\mathcal{A}$ under x .

Proof of data-independent errors. The only interaction with the data is on line 68. By the postcondition of a valid measurement, errors are data-independent. $\square$

Proof of privacy guarantee. The transition function follows the $\mathcal{G}$ -OdomCon(IM) procedure described in Algorithm 6 of [HST⁺23], with some adjustments that do not materially affect the privacy analysis.

- When an odometer invokes $\mathcal{M}_{k+1}$, the OpenDP Library implementation eagerly accounts for all future privacy loss of the child mechanism immediately (on line 75), even if the analyst never interacts with the spawned interactive mechanism.
- The OpenDP Library represents interactive mechanisms via queryables, where the state s is hidden from the adversary. When invoking $\mathcal{M}_k$, no initial state λ is passed, and the response is a queryable with hidden state. By the definition of a valid interactive measurement, the view an adversary gains from this queryable has privacy loss d_k for some choice of d_in .
- The queryable for child k can be viewed as $\mathcal{M}_k$ together with s_k . Since the queryable itself satisfies d_k -DP, the queryable can be returned to the user to provide query access, child queryables ($\mathcal{M}_k$ and s_k) can be removed from the odometer state, and the handling of child update queries $m = (j, q)$ can be removed while preserving equivalency with Algorithm 6. This equivalently reduces the odometer state to $(s, [d_1, \dots, d_k])$.
- In addition to storing the dataset x , the state also contains the input domain, input metric and privacy measure. Each incoming mechanism must share these same supporting elements. This is an implicit requirement of the paper made explicit in the implementation.

We now discuss how the pseudocode implements this equivalent algorithm. The input domain, input metric, privacy measure and data are moved into the transition function, as well as a mutable list of privacy maps and the number of times each is charged, from line 12, to form the state.

First consider the case where the privacy measure satisfies concurrent composition. Lines 34 and 38 are necessary to guarantee that the constructed odometer queryable gives valid privacy loss guarantees with respect to `input_metric` and `output_measure`. On line 68, the user-verified preconditions for invoking the measurement are met, by the precondition that the `data` is a member of `input_domain` and the check that the measurement’s input domain matches `input_domain` on line 30. Therefore by the definition of a valid measurement, `answer` satisfies `measurement.privacy_map(d_in)`-DP, with respect to `output_measure`, for some choice of `d_in`.

Now consider the case where the privacy measure does not satisfy concurrent composition. Then `seq_wrapper` on line 62 is a wrapper that will cause wrapped queryables to send an `AskPermission` query with their self-reported id to this queryable before answering any query. By line 88, permission is only granted if the most recently spawned child is asking for permission to execute a query. This ensures that an adversary may only interact with the most recently spawned child mechanism.

Now that we’ve shown a correspondence between the pseudocode and Algorithm 6 of [HST⁺23], the proof from Appendix B.1 shows that the pseudocode implements a valid $\mathcal{D}$ DP privacy loss accumulator for interactive mechanisms.

The transition function is then used to construct a queryable on line 98. □

References

- [HST⁺23] Samuel Haney, Michael Shoemate, Grace Tian, Salil Vadhan, Andrew Vyrros, Vicki Xu, and Wanrong Zhang. Concurrent composition for interactive differential privacy with adaptive privacy-loss parameters, 2023.