fn then_deintegerize_hashmap

Michael Shoemate (@Shoeboxam)

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of the implementation of then_deintegerize_hashmap in mod.rs at commit 286ce37ce (outdated[1]).

1 Hoare Triple

Precondition

Compiler-verified

- Generic TV implements trait CastInternalRational

Caller-verified

None

Pseudocode

```
def then_deintegerize_hashmap(k: i32) -> Function[HashMap[TK, IBig], HashMap[TK, TV]]:
    if k == i32.MIN:  #
        raise ValueError("k must not be i32.MIN")

    def value_function(v_i):
        return TV.from_rational(x_mul_2k(RBig.from_(v_i), k))

    return Function.new(lambda x: {k_i: value_function(v_i) for k_i, v_i in x.items()})
```

Postcondition

Theorem 1.1. For every setting of the input parameters (k, TK, TV) to then_deintegerize_hashmap such that the given preconditions hold, then_deintegerize_hashmap raises an error (at compile time or run time) or returns a valid postprocessor. A valid postprocessor has the following property:

1. (Data-independent errors). For every pair of members x and x' in input_domain, function(x), function(x') either both raise the same error, or neither raise an error.

Proof. By the postcondition of TV.from_rational, the outcome of the function is the nearest representable float, and may saturate to positive or negative infinity. The precondition of x_mul_2k that k is not i32.MIN is satisfied on line 2. Since TV.from_rational and x_mul_2k are both infallible, the function is infallible, meaning that the function cannot raise data-dependent errors. Therefore the function is a valid postprocessor. □

[1] See new changes with git diff 286ce37ce..c6ec4181 rust/src/measurements/noise_threshold/nature/float/mod.rs