fn match_truncations

Michael Shoemate (@Shoeboxam)

October 19, 2026

> This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of `match_truncations` in `mod.rs` at commit 86bfbd898 (outdated[1]).

1 Hoare Triple

Precondition

Compiler-verified

Types matching pseudocode.

Caller-verified

None

Pseudocode

```
def match_truncations(
    plan: DslPlan, identifier: Expr
) -> tuple[DslPlan, Vec[Truncation], Vec[Bound]]:
    truncations = []
    bounds = []

    allowed_keys = match_group_by_truncation(
        plan, identifier
    )  #
    if allowed_keys:
        input, truncate, new_bound = allowed_keys
        plan = input  #
        truncations.append(truncate)
        bounds.append(new_bound)  #
        allowed_keys = new_bound.by  #

    # match until not a filter truncation
    while isinstance(plan, Truncation.Filter):  #
        input, predicate = plan.input, plan.predicate
        new_bounds = match_truncation_predicate(
            predicate, identifier
        )  #
        if new_bounds is None:
            break
```

[1] See new changes with `git diff 86bfbd898..d682c5d9 rust/src/transformations/make_stable_lazyframe/truncate/matching/mod.rs`

```
25
26          # When filter truncation is behind a groupby truncation,
27          # if the groupby group keys don't cover the filter truncation keys,
28          # then the groupby aggs can overwrite the filter truncation keys,
29          # invalidating the filter truncation bounds.
30          if allowed_keys is not None:  #
31              for bound in new_bounds:
32                  if not bound.by.is_subset(allowed_keys):
33                      raise f"Filter truncation keys ({bound.by}) must be a subset of groupby
    truncation keys ({allowed_keys})."
34
35          plan = input  #
36          truncations.append(Truncation.Filter(predicate))
37          bounds.extend(new_bounds)  #
38
39      # just for better error messages, no privacy implications
40      if (
41          match_group_by_truncation(plan, identifier) is not None
42      ):  #
43          raise Exception("groupby truncation must be the last truncation in the plan.")
44
45      # since the parse descends to the source,
46      # truncations and bounds are in reverse order
47      truncations.reverse()  #
48      bounds.reverse()  #
49
50      return plan, truncations, bounds
```

Postcondition

Theorem 1.1 (Postcondition)**.** For any choice of LazyFrame plan, returns the plan with the truncations removed, the truncations that were removed in the order they are applied, and per-id bounds on row and/or group contributions.

Proof. The algorithm maintains three invariants:

- `input` is the LazyFrame plan with truncations removed
- `truncations` is a list of truncations in reverse-order
- `bounds` is a list of per-id bounds on row and/or group contributions

In order to ensure that all per-id bounds remain valid after successive truncations, the group-by truncation may only be applied last in the truncation pipeline, as the group-by truncation rewrites all columns in the data, and potentially overwrites user identifiers.

Since parsing the query plan happens in reverse order, the algorithm starts by attempting to parse a group-by truncation on line 9. By the postcondition of `match_group_by_truncation`, if the group-by truncation is present, it will be returned as a tuple of `input`, (the execution plan with the group-by truncation removed), `truncation`, (the group-by truncation) and `per_id_bounds` (the per-id bounds on row contributions). The state of the algorithm is then updated on lines 12-14, maintaining the invariants on `input`, `truncations` and `bounds`.

Another limitation of the group-by truncation is that bounds on row contributions when grouped by a given set of columns are no longer valid if those columns are changed in the group-by truncation. Therefore, `allowed_keys` on line 15 contains columns that are preserved through the group-by truncation, by virtue of being part of the grouping columns. This limitation does not hinder expected use-cases, but is necessary to ensure that per-id bounds on contributions remain valid after the group-by truncation.

If a group-by truncation is not present, no update is made to the state.

The algorithm then attempts to repeatedly parse filter truncations on line 18. By the postcondition of `match_truncation_predicate` on line 22, the return is a list of per-id contribution bounds if the predicate

consists solely of truncations, otherwise none. This ensures that the algorithm rejects predicates that contain conditions that are not truncations.

Line 30 checks that the truncation predicate is valid, by ensuring that the truncation predicate is a subset of the allowed keys. The algorithm then updates the state on lines 35-37, maintaining the invariants on `input`, `truncations` and `bounds`. Finally, since the descent through the query plan is in reverse order, line 47 ensures that the truncation order is correct. Neither the check on line 42 nor the reversal on line 48 are necessary to match the postcondition, but both are included to improve usability.

Since the invariants on `input`, `truncations` and `bounds` are maintained, and the algorithm only matches through truncations, the postcondition is satisfied. □