# `fn x_mul_2k`

Michael Shoemate (@Shoeboxam)

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of the implementation of `x_mul_2k` in `mod.rs` at commit f5bb719 (outdated[1]).

## 1 Hoare Triple

### Precondition

#### Compiler-verified

None

#### Caller-verified

$k \neq$ `i32.MIN`

### Pseudocode

```
def x_mul_2k(x: RBig, k: i32) -> RBig:
    num, den = x.into_parts()  #
    if k < 0:
        den <<= cast(-k, usize)
    else:
        num <<= cast(k, usize)

    return RBig.from_parts(num, den)
```

### Postcondition

**Theorem 1.1.** Return $x \cdot 2^k$.

*Proof.* Since $x$ is a fraction, line 2 splits $x$ into its numerator and denominator.
Consider two cases:

- If $k < 0$, then multiplying the denominator by $2^-k$ is equivalent to multiplying by $2^k$. Since $k$ is negative, then $-k$ is positive, meaning the cast to `usize` is valid. Shifting $-k$ zeros to the left is equivalent to multipying the denominator by $2^k$. Negation of $k$ is well-defined for all values of `i32`, except for `i32.MIN`, which is not allowed by the precondition. Therefore, the result is $x \cdot 2^k$.
- If $k \geq 0$, then we multiply the numerator by $2^k$. Since $k$ is positive, the cast to `usize` is valid. Shifting $k$ zeros to the left is equivalent to multipying the numerator by $2^k$. Therefore, the result is $x \cdot 2^k$.

In both cases, the result is $x \cdot 2^k$. □

[1] See new changes with `git diff f5bb719..5c6c303 rust/src/measurements/noise/nature/float/utilities/mod.rs`